



12. Radio Frequency Exposure

12.1 Applicable Standards

The measurements shown in this test report were made in accordance with the procedures given in FCC Part 2 (Section 2.1091)

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

12.2 EUT Specification

| | |
|--|--|
| Frequency band (Operating) | <input checked="" type="checkbox"/> 2400MHz -2483.5MHz |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Evaluation applied | <input type="checkbox"/> Blanket 1 mW Blanket Exemption <input checked="" type="checkbox"/> MPE-based Exemption <input type="checkbox"/> SAR-based Exemption |
| Remark: The maximum conducted output power is <u>3.65 dBm (2.317 mW)</u> at <u>2403.35MHz</u> (with <u>2.12dBi antenna gain.</u>) | |

12.3 Result

| Channel Frequency (MHz) | Max. Conducted output power (dBm) | Max. Tune up power (dBm) | Antenna Gain(dBi) | Max.Tune up e.r.p. Power (dBm) | Max. Tune up e.r.p power (mW) | Limit (mW) |
|-------------------------|-----------------------------------|--------------------------|-------------------|--------------------------------|-------------------------------|------------|
| 2403.35 | 3.65 | 4.15 | 2.12 | 4.12 | 2.58 | 3060 |

No non-compliance noted.

-----THE END OF REPORT-----