

TEST REPORT

Applicant: Shenzhen Jimi IoT Co., Ltd.
Address: 3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China
Equipment Type: 4G AI Dashcam
Model Name: JC371 (refer to section 2.3)
Brand Name: JimiIoT
FCC ID: 2AMLF-JC371
Test Standard: 47 CFR Part 15 Subpart B
ANSI C63.4-2014
Sample Arrival Date: Aug. 22, 2024
Test Date: Aug. 26, 2024
Date of Issue: Nov. 14, 2024

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Li JunFeng**Checked by:** Liu Zhenxiang**Approved by:** Tolan Tu
(Testing Director)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Nov. 14, 2024</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1 GENERAL INFORMATION	4
1.1 Test Laboratory	4
1.2 Test Location	4
2 PRODUCT INFORMATION	5
2.1 Applicant Information	5
2.2 Manufacturer Information	5
2.3 General Description for Equipment under Test (EUT)	5
2.4 Ancillary Equipment	5
2.5 Technical Information	6
3 SUMMARY OF TEST RESULTS	7
3.1 Test Standards	7
3.1 Verdict	7
3.2 Test Uncertainty	7
4 GENERAL TEST CONFIGURATIONS	8
4.1 Test Enclosure List	8
4.2 Test Configurations	8
4.3 Test Setups	9
5 TEST ITEMS	11
5.1 Emission Tests	11
ANNEX A TEST RESULTS	16
A.1 Radiated Emission	16
A.2 Conducted Emission, AC Ports	29
ANNEX B TEST SETUP PHOTOS	30
ANNEX C EUT EXTERNAL PHOTOS	30

ANNEX D EUT INTERNAL PHOTOS	30
-----------------------------------	----

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.2 Manufacturer Information

Manufacturer	Shenzhen Jimi IoT Co., Ltd.
Address	3-4/F, Block A, Building #7, Shenzhen International Innovation Valley, Dashi 1st Road, Nanshan District, Shenzhen, Guangdong, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	4G AI Dashcam
Model Name Under Test	JC371
Series Model Name	C371, JC371-LA, JC371S, JC371C, JC371S-LA, JC371C-LA, JC371LA
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Hardware Version	C371_MB_V1.2
Software Version	C371_0_0_STD_JM_JC371_V1.2.2a_241108.1110
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Note: Not applicable.

2.5 Technical Information

Network and Wireless connectivity	2G Network GSM 850/1900 MHz 3G Network WCDMA/HSDPA/HSUPA Band 2/4/5 4G Network FDD LTE Band2/4/5/7/66 WIFI 802.11b, 802.11g, 802.11n(HT20) GPS, BDS, AGPS
Classification of equipment	Class B
The highest internal frequency of EUT	2472 MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.1 Verdict

No.	Description	FCC Rule	Test Verdict	Remark
1	Radiated Emission	15.109	Pass	--
2	Conducted Emission, AC Ports	15.107	N/A	Note 1
Note 1: The EUT has no AC Port, so this test item is not applicable.				

3.2 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Radiated emissions (30 MHz-1 GHz)-966#2	4.4 dB
Radiated emissions (1 GHz-18 GHz)-966#2	5.0 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
Camera	N/A	N/A	N/A	N/A	N/A	☒
Vehicle battery	CAMEL	6-QWLZ-4 5(370)	N/A	N/A	N/A	☒
TF Card	Samsung	N/A	N/A	N/A	256G	☒
Laptop	Lenovo	N/A	N/A	N/A	N/A	☒
USB Cable	N/A	N/A	N/A	N/A	N/A	☒

4.2 Test Configurations

All test modes of EUT are listed in the table below.


Test Mode Configuration	Description
Mode 1	<u>The Standby Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 2	<u>The Camera Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 3	<u>The SOS key Work Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 4	<u>The Speaker Work Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card
Mode 5	<u>The USB Test Mode</u> Power supply line + Vehicle battery + SOS key + Camera + TF Card + Laptop + USB Cable

Test Case	Test Mode Configuration	Worst Mode
Radiated Emission	Mode 1~Mode 5	4, 5


Note: All operation modes were tested, but only test data of the worst mode was presented in this report.

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted Emissions, AC Ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated Emission

5.1.1.1 Limit

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

NOTE:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) For 30 MHz to 1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$$

Where:

L_{3m} is Average Class A limit at 3m;

L_{10m} is Average Class A limit at 10m;

d_{10m} is Measurement distance in 10m;

d_{3m} is Measurement distance in 3m.

For this case: $L_{3m} = 49.5 + 20 \cdot \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

5.1.1.2 Test Setup

Refer to 4.3 section (test setup 1) for radiated emission test, the photo of test setup please refer to ANNEX B.

5.1.1.3 Test Procedure

All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.

The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$

VBW $\geq$ RBW

Sweep = auto

Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$

Trace = max hold

5.1.1.4 Test Result and Test Equipment List

Please refer to ANNEX A.1.

NOTE:

1. Results (dB μ V/m) = Reading (dB μ V) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)

3. Margin = Limit - Results

5.1.2 Conducted Emission, AC Ports

5.1.2.1 Test Limit

Frequency range (MHz)	Class A	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66
0.50 - 30	73	60

Frequency range (MHz)	Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.

5.1.2.2 Test Setup

Refer to 4.3 section test (test setup 2) for conducted emission, the photo of test setup please refer to ANNEX B.

5.1.2.3 Test Procedure

The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

Use the following spectrum analyzer settings:

RBW = 9 kHz

VBW $\geq$ RBW

Sweep = 10ms

Detector function = peak & Average

Trace = max hold

5.1.2.4 Test Result and Test Equipment List

Please refer to ANNEX A.2.

NOTE:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit - Results

ANNEX A TEST RESULTS

A.1 Radiated Emission

Note 1: The symbol of “--” in the table which means not application.


Note 2: For the test data above 1 GHz, according the ANSI C63.4-2014, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The Radiated Emission is required to be investigated to the upper frequency of 5th harmonic of the highest internal frequency of EUT or 40 GHz, whichever is lower. The test results above 18GHz are only noise and are not recorded in the report.

Sample No.	S10	Temperature	22.1 – 22.4℃
Humidity	42 - 46%RH	Pressure	101kPa
Test Engineer	He Shichang	Test Date	2024.08.26


Test Mode 4

1) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	30.000	27.50	-28.82	40.0	12.50	Peak	313.00	100	Vertical	Pass
2	45.084	32.70	-25.53	40.0	7.30	Peak	228.00	100	Vertical	Pass
3	83.689	36.69	-30.25	40.0	3.31	Peak	293.00	100	Vertical	Pass
4	127.097	30.66	-29.54	43.5	12.84	Peak	54.00	100	Vertical	Pass
5	544.537	29.62	-17.66	46.0	16.38	Peak	132.00	100	Vertical	Pass
6	900.478	30.62	-9.81	46.0	15.38	Peak	139.00	200	Vertical	Pass

2) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	44.307	22.63	-25.73	40.0	17.37	Peak	214.00	100	Horizontal	Pass
2	80.828	21.04	-30.94	40.0	18.96	Peak	339.00	200	Horizontal	Pass
3	130.007	21.24	-29.73	43.5	22.26	Peak	186.00	200	Horizontal	Pass
4	328.517	26.89	-22.78	46.0	19.11	Peak	214.00	100	Horizontal	Pass
5	460.050	30.49	-19.67	46.0	15.51	Peak	207.00	200	Horizontal	Pass
6	742.562	31.01	-13.04	46.0	14.99	Peak	175.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2023.09.05	2024.09.04	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2023.12.05	2024.12.04	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00867	2022.04.12	2025.04.11	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

3) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1052.200	38.24	-16.27	74.0	35.76	Peak	132.00	100	Vertical	Pass
1**	1052.200	28.28	-16.27	54.0	25.72	AV	132.00	100	Vertical	Pass
2	1484.800	40.47	-15.93	74.0	33.53	Peak	84.00	100	Vertical	Pass
2**	1484.800	30.13	-15.93	54.0	23.87	AV	84.00	100	Vertical	Pass
3	4991.750	54.64	2.16	74.0	19.36	Peak	335.00	100	Vertical	Pass
3**	4991.750	45.06	2.16	54.0	8.94	AV	335.00	100	Vertical	Pass
4	9340.000	53.86	2.15	74.0	20.14	Peak	360.00	100	Vertical	Pass
4**	9340.000	44.70	2.15	54.0	9.30	AV	360.00	100	Vertical	Pass
5	14052.500	56.55	5.38	74.0	17.45	Peak	103.00	100	Vertical	Pass
5**	14052.500	46.49	5.38	54.0	7.51	AV	103.00	100	Vertical	Pass
6	17099.500	54.01	3.73	74.0	19.99	Peak	262.00	100	Vertical	Pass
6**	17099.500	45.47	3.73	54.0	8.53	AV	262.00	100	Vertical	Pass

4) Test Antenna Horizontal, 1 GHz – 18 GHz




No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1025.700	38.54	-16.17	74.0	35.46	Peak	191.00	100	Horizontal	Pass
1**	1025.700	29.94	-16.17	54.0	24.06	AV	191.00	100	Horizontal	Pass
2	1367.900	39.54	-16.17	74.0	34.46	Peak	67.00	100	Horizontal	Pass
2**	1367.900	29.86	-16.17	54.0	24.14	AV	67.00	100	Horizontal	Pass
3	1748.600	40.67	-15.56	74.0	33.33	Peak	63.00	100	Horizontal	Pass
3**	1748.600	29.99	-15.56	54.0	24.01	AV	63.00	100	Horizontal	Pass
4	5865.000	55.74	3.85	74.0	18.26	Peak	324.00	100	Horizontal	Pass
4**	5865.000	46.05	3.85	54.0	7.95	AV	324.00	100	Horizontal	Pass
5	9269.500	53.35	1.74	74.0	20.65	Peak	90.00	100	Horizontal	Pass
5**	9269.500	44.53	1.74	54.0	9.47	AV	90.00	100	Horizontal	Pass
6	13805.000	56.33	5.75	74.0	17.67	Peak	37.00	100	Horizontal	Pass
6**	13805.000	46.89	5.75	54.0	7.11	AV	37.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2023.09.05	2024.09.04	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2023.12.05	2024.12.04	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2023.12.05	2024.12.04	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒


Test Mode 5

5) Test Antenna Vertical, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	35.820	28.04	-28.10	40.0	11.96	Peak	138.00	100	Vertical	Pass
2	72.074	37.60	-30.24	40.0	2.40	Peak	79.00	111	Vertical	N/A
2*	72.074	29.46	-30.24	40.0	10.54	QP	79.00	111	Vertical	Pass
3	82.719	32.29	-30.52	40.0	7.71	Peak	64.00	100	Vertical	Pass
4	126.806	35.35	-29.50	43.5	8.15	Peak	100.00	100	Vertical	Pass
5	499.626	35.89	-18.63	46.0	10.11	Peak	306.00	100	Vertical	Pass
6	789.073	38.82	-12.22	46.0	7.18	Peak	222.00	200	Vertical	Pass

6) Test Antenna Horizontal, 30 MHz – 1 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	71.904	27.08	-30.16	40.0	12.92	Peak	116.00	100	Horizontal	Pass
2	82.865	25.58	-30.48	40.0	14.42	Peak	149.00	200	Horizontal	Pass
3	126.272	27.96	-29.44	43.5	15.54	Peak	86.00	200	Horizontal	Pass
4	296.992	33.63	-23.83	46.0	12.37	Peak	145.00	100	Horizontal	Pass
5	789.704	38.14	-12.23	46.0	7.86	Peak	118.00	100	Horizontal	Pass
6	959.987	37.00	-9.29	46.0	9.00	Peak	195.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Below 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2023.09.05	2024.09.04	☒
Amplifier (30-1GHz)	COM-MV	ZT30-1000M	B2017119081	2023.12.05	2024.12.04	☒
Test Antenna- Bi-Log	SCHWARZB ECK	VULB 9168	9168-00867	2022.04.12	2025.04.11	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

7) Test Antenna Vertical, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1064.100	39.47	-16.42	74.0	34.53	Peak	310.00	100	Vertical	Pass
1**	1064.100	29.76	-16.42	54.0	24.24	AV	310.00	100	Vertical	Pass
2	1196.800	40.68	-16.32	74.0	33.32	Peak	21.00	100	Vertical	Pass
2**	1196.800	29.98	-16.32	54.0	24.02	AV	21.00	100	Vertical	Pass
3	1328.900	44.43	-16.03	74.0	29.57	Peak	21.00	100	Vertical	Pass
3**	1328.900	30.10	-16.03	54.0	23.90	AV	21.00	100	Vertical	Pass
4	1596.600	40.68	-16.16	74.0	33.32	Peak	140.00	100	Vertical	Pass
4**	1596.600	30.26	-16.16	54.0	23.74	AV	140.00	100	Vertical	Pass
5	5903.000	56.20	3.74	74.0	17.80	Peak	34.00	100	Vertical	Pass
5**	5903.000	46.35	3.74	54.0	7.65	AV	34.00	100	Vertical	Pass
6	13811.500	56.35	5.66	74.0	17.65	Peak	258.00	100	Vertical	Pass
6**	13811.500	46.85	5.66	54.0	7.15	AV	258.00	100	Vertical	Pass

8) Test Antenna Horizontal, 1 GHz – 18 GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1162.600	44.05	-16.06	74.0	29.95	Peak	86.00	100	Horizontal	Pass
1**	1162.600	29.85	-16.06	54.0	24.15	AV	86.00	100	Horizontal	Pass
2	1198.800	42.72	-16.25	74.0	31.28	Peak	99.00	100	Horizontal	Pass
2**	1198.800	33.31	-16.25	54.0	20.69	AV	99.00	100	Horizontal	Pass
3	1331.200	42.59	-16.14	74.0	31.41	Peak	73.00	100	Horizontal	Pass
3**	1331.200	31.04	-16.14	54.0	22.96	AV	73.00	100	Horizontal	Pass
4	5930.000	55.98	3.04	74.0	18.02	Peak	336.00	100	Horizontal	Pass
4**	5930.000	46.79	3.04	54.0	7.21	AV	336.00	100	Horizontal	Pass
5	7923.250	56.01	2.98	74.0	17.99	Peak	345.00	100	Horizontal	Pass
5**	7923.250	46.58	2.98	54.0	7.42	AV	345.00	100	Horizontal	Pass
6	13328.000	55.99	4.46	74.0	18.01	Peak	181.00	100	Horizontal	Pass
6**	13328.000	46.07	4.46	54.0	7.93	AV	181.00	100	Horizontal	Pass

Equipment Information						
Equipment Name	Supplier	Model	Serial No.	Cal. Date	Cal. Due	Use
Frequency Above 1 GHz						
EMI Receiver	Keysight	N9038A	MY55330120	2023.09.05	2024.09.04	☒
Amplifier (1-12GHz)	Advanced Microwave	WLA652A	1740103	2023.12.05	2024.12.04	☒
Amplifier (0.8-21GHz)	Mini-Circuits	ZVA-213-S+	225321316	2023.12.05	2024.12.04	☒
Test Antenna- Horn	SCHWARZB ECK	BBHA 9120D	01917	2022.06.09	2025.06.08	☒
Anechoic Chamber (#2)	YiHeng	9m*6m*6m	142	2024.07.21	2027.07.20	☒
Description	Supplier	Name	Version	/		Use
Test Software	BALUN	BL410-E	V22.930	/		☒

A.2 Conducted Emission, AC Ports

Note: Not applicable.

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ2470920-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SZ2470920-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SZ2470920-AI.PDF”.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--