

# **User Manual**

**of the**

**Continental Automotive**

**Tire Pressure Sensor (Wheel Unit)  
TIS-23 / TIS-24**

# Continental Automotive

1. TECHNICAL DESCRIPTION FOR UHF	3
2. TECHNICAL DESCRIPTION FOR BLUETOOTH LOW ENERGY	3
3. TYPICAL USAGE PATTERN	3
3.1. AVERAGE FACTOR CALCULATION (Standard 47 CFR Part 15C (periodic intentional transmitter))	3
4. PRODUCT INFORMATION	4
4.1. General information	4
4.2. PICTURES	4
5. LABELS AND USER MANUAL STATEMENTS	5
5.1. Europe (TIS-23)	5
5.2. USA & Canada (TIS-23 & TIS-24)	5
5.3. Great Britain (TIS-23)	6

## 1. TECHNICAL DESCRIPTION FOR UHF

Carrier frequency:	433.92MHz for TIS-23 (EU) 433.92MHz for TIS-23 (US) 315MHz for TIS-24 (US)
Frequency FSK deviation:	± 40 kHz
Number of channels:	1
Type of modulation:	Frequency Shift Keying (FSK) and Amplitude Shift Keying (ASK)
Baud rate:	9600kbps/19200bds -> for 433MHz 9600kbps/19200bds, 4200kbps/8400bds, 4096kbps/8191bds and 1820kbps/3640bds -> for 315MHz
Rated Output Power:	< 10mW
Antenna:	Internal
Voltage supply:	1 Lithium battery 3V (CR2450)
Voltage supply range:	2.1 up to 3.6V

## 2. TECHNICAL DESCRIPTION FOR BLUETOOTH LOW ENERGY

Bandwidth frequency:	2.4GHz – 2.48GHz (for all frequencies)
Frequency GFSK deviation:	± 250 kHz
Number of channels:	40
Type of modulation:	Gaussian Frequency Shift Keying (GFSK)
Baud rate:	1Mb/s/, 1Msym/s
Rated Output Power:	< 10mW
Antenna:	Internal
Voltage supply:	1 Lithium battery 3V (CR2450)
Voltage supply range:	2.1 up to 3.6V

## 3. TYPICAL USAGE PATTERN

### 3.1. AVERAGE FACTOR CALCULATION (STANDARD 47 CFR PART 15C (PERIODIC INTENTIONAL TRANSMITTER))

#### For TIS-23 433MHz:

RF frames maximum duration = 41,66ms

Averaging factor =  $20 \times \log(41,66/100) = -7.6\text{dB}$

Calculation is based on the identified worst-case protocol described in chapter:  
Fehler! Verweisquelle konnte nicht gefunden werden.

#### For TIS-24 315MHz:

RF frames maximum duration = 23.44ms

Averaging factor =  $20 \times \log((8.33+30.22/2)/100) = -12.51\text{dB}$

Calculation is based on the identified worst-case protocol

## 4. PRODUCT INFORMATION

### 4.1. GENERAL INFORMATION

- Manufacturer: Continental Automotive GmbH  
Address: Vahrenwalder Straße  
930165 Hannover  
Germany
- Production plant: Toulouse (FR)  
Address: 1 Avenue Paul Ourliac  
31100 Toulouse  
France

### 4.2. PICTURES



Exploded view



External view – housing + valve

## 5. LABELS AND USER MANUAL STATEMENTS

### 5.1. EUROPE (TIS-23)



### 5.2. USA & CANADA (TIS-23 & TIS-24)

FCC ID: KR5TIS-23  
FCC ID: KR5TIS-24

IC: 7812D-TIS23  
IC: 7812D-TIS24

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation

*Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.*

This device complies with FCC/ISED radiation exposure limits set forth for an uncontrolled environment and meets the FCC radio frequency (RF) Exposure Guidelines and RSS-102 of the ISED radio frequency (RF) Exposure rules. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. The antenna should be installed and operated with minimum distance of 20 cm between the radiator and your body.

*Le présent appareil est conforme à l'exposition aux radiations FCC / ISED définies pour un environnement non contrôlé et répond aux directives d'exposition de la fréquence de la FCC radiofréquence (RF) et RSS-102 de la fréquence radio (RF) ISED règles d'exposition. L'émetteur ne doit pas être colocalisé ni fonctionner conjointement avec à autre antenne ou autre émetteur. L'antenne doit être installée de façon à garder une distance minimale de 20 centimètres entre la source de rayonnements et votre corps.*

### 5.3. GREAT BRITAIN (TIS-23)

