

PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



HEARING AID COMPATIBILITY

Applicant Name:

LG Electronics U.S.A, Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 United States Date of Testing: 9/28/2018 - 10/04/2018
Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.: 1M1809240182-02.ZNF

FCC ID: ZNFX220PM

APPLICANT: LG ELECTRONICS U.S.A, INC.

Scope of Test: Audio Band Magnetic Testing (T-Coil)

Application Type: Certification
FCC Rule Part(s): CFR §20.19(b)
HAC Standard: ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

DUT Type: Portable Handset **Model:** LM-X220PM

Additional Model(s): LMX220PM, X220PM

Test Device Serial No.: Pre-Production Sample [S/N: 05455]

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.







FCC ID: ZNFX220PM	PETEST:	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 1 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 10101

TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	6
4.	METHOD OF MEASUREMENT	8
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	. 18
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	. 22
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	. 25
8.	FCC 3G MEASUREMENTS	. 28
9.	T-COIL TEST SUMMARY	. 30
10.	MEASUREMENT UNCERTAINTY	. 40
11.	EQUIPMENT LIST	. 41
12.	TEST DATA	. 42
13.	CALIBRATION CERTIFICATES	. 69
14.	CONCLUSION	. 76
15.	REFERENCES	. 77
16.	TEST SETUP PHOTOGRAPHS	. 79

FCC ID: ZNFX220PM	POTEST VECTOR LAND BETORY, INC.	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 2 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 2 01 61

1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 3 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		raye 3 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

DUT DESCRIPTION 2.



FCC ID: ZNFX220PM

Applicant: LG Electronics U.S.A, Inc.

1000 Sylvan Avenue

Englewood Cliffs, NJ 07632

United States

Model: LM-X220PM

Additional Model(s): LMX220PM, X220PM

Serial Number: 05455 HW Version: Rev.B

SW Version: X220PM0Ca Antenna: Internal Antenna DUT Type: Portable Handset

Table 2-1 7NEX220PM HAC Air Interfaces

Air-Interface	Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service	Audio Codec Evaluated
	835	VO	Yes	Yes: WIFI or BT	CMRS Voice ¹	EVRC
CDMA	1900					
	EvDO	VD	Yes	Yes: WIFI or BT	Google Duo ²	OPUS
-	850	vo	Yes	Yes: WIFI or BT	CMRS Voice ¹	EFR
GSM	1900	_				
	GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo ²	OPUS
	850				CMRS Voice ¹	NB AMR
UMTS 1700 1900	VD	Yes	Yes: WIFI or BT			
	700 (B12)					
	780 (B13)					
	850 (B5)				Vol TE' Google Duo ²	
LTE (FDD)	850 (B26)	VD	Yes	Yes: WIFI or BT		VoLTE: NB AMR, WB AMR Google Duo: OPUS
	1700 (B4)					
	1900 (B2)					
•	1900 (B25)	1				
LTE (TDD)	2600 (B41)	VD	Yes	Yes: WIFI or BT	VoLTE ¹ , Google Duo ²	VoLTE: NB AMR, WB AMR Google Duo: OPUS
WIFI	2450	VD	Yes	Yes: CDMA, GSM, UMTS, or LTE	VoWIFI², Google Duo²	VoWIFI: NB AMR, WB AMR Google Duo: OPUS
BT	2450	DT	No	Yes: CDMA, GSM, UMTS, or LTE	N/A	N/A

Type Transport

VO = Voice Only

DT = Digital Data - Not intended for CMRS Service

VD = CMRS and IP Voice over Data Transport

Reference level in accordance with 7.4.2.1 of ANSI C63.19-2011 and July 2012 C63 VoLTE Interpretation.

Reference level is -20dBm0 in accordance with FCC KDB 285076 D02

FCC ID: ZNFX220PM	PETEST:	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 4 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 4 01 61

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

I. LTE Band Selection

This device supports the following pairs of LTE bands with similar frequencies: LTE B26 & B5, and LTE B25 & B2. These pairs of LTE bands share the same transmission path and the larger band's target power is greater than or equal to the smaller band's target power. Since the supported frequency span for the smaller LTE bands are completely covered by the larger LTE bands, only the larger LTE bands (LTE B26 & B25) were evaluated for hearing-aid compliance.

FCC ID: ZNFX220PM	POTEST VECENTIAL LADDETON, INC.	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 5 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 3 01 01

3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

I. MAGNETIC COUPLING

Axial and Radial Field Intensity

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be \geq -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz




Figure 3-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds
-15 dB(A/m) at 1 kHz

FCC ID: ZNFX220PM	INCINETAINE LABORATORS, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 6 of 91
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 6 of 81

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

Signal Quality

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Category	Telephone RF Parameters			
Category	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]			
T1	0 to 10 dB			
T2	10 to 20 dB			
Т3	20 to 30 dB			
T4	> 30 dB			
Table 3-1 Magnetic Coupling Parameters				

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFX220PM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 7 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage / 0101

4. METHOD OF MEASUREMENT

I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 4-1
Validation Setup with Helmholtz Coil




Figure 4-2 T-Coil Test Setup

FCC ID: ZNFX220PM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 8 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 0 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size: 0.1 mm

Maximum speed 6.1 cm/sec
Line Voltage: 115 VAC
Line Frequency: 60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T

Active Frequency 100 Hz – 8 kHz

Range:
Stimulus Type:
Male and Female, no spaces

Single Sample

Duration: 20.96 seconds

Activity Level: 100%




Figure 4-4
Spectral Characteristic of full P.50





Figure 4-5
Temporal Characteristic of full P.50

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 9 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 3 01 01



ABM2 Measurement Block Diagram:



Figure 4-6 Magnetic Measurement Processing Steps

IV. Test Procedure

- 1. Ambient Noise Check per C63.19 §7.3.1
 - Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
 - b. "A-weighting" and Half-Band Integration was applied to the measurements.
 - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation(See Figure 4-1)
 - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
 - b. ABM1 Validation

The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where H_c = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.08m; R=10.2Ω and using V=18mV:

$$H_c = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of $-10 \, dB(A/m)$ in the center of the Helmholtz coil which was used to validate the probe measurement at $-10 \, dB(A/m)$. This was verified to be within $\pm 0.5 \, dB$ of the $-10 \, dB(A/m)$ value (see Page 38).

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 10 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 10 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

Frequency Response Validation
 The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:



Figure 4-7 Frequency Response Validation

d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 11 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		raye 110101







Figure 4-8
ABM2 Frequency Response Validation

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and A-weighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2
ABM2 Power Sum Validation

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFX220PM	PCTEST INCIDENT LABORATORY, 14C.	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 12 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 12 01 61

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M




Figure 4-10
ABM2 Power Sum Validation

3. Measurement Test Setup

- a. Fine scan above the WD (TEM)
 - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):




Figure 4-11 Measurement Distance




Figure 4-12 Measurement Grid

- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-15 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator
 - i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN TM	TDMA (22 and 11 Hz)	-18

FCC ID: ZNFX220PM	PETEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 13 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 13 01 61

© 2018 PCTEST Engineering Laboratory, Inc.

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- iii. See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.

c. Real-Time Analyzer (RTA)

i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.

d. WD Radio Configuration Selection

i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 8 for more information regarding worst-case configurations for CDMA and UMTS. LTE configuration information can be found in Section 5. WIFI configuration information can be found in Section 6 and 7.):




Figure 4-13 Vocoder Analysis for ABM Noise for GSM

4. Signal Quality Data Analysis

- a. Narrow-band Magnetic Intensity
 - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.

b. Frequency Response

- i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
- ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
- iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.

c. Signal Quality Index

i. Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no

FCC ID: ZNFX220PM	POTEST VECENTIAL LADDETON, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 14 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 14 01 6 1

- audio signal through the vocoder, the WD was measured over at least 100 Hz 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
- ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
- This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

V. Test Setup




Figure 4-14
Audio Magnetic Field Test Setup

VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to inaccessible RF ports.

VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil unless otherwise noted. See Table 2-1 for more details regarding which modes were tested.

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 15 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 13 01 01

VIII. Wireless Device Channels and Frequencies

1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes.

Table 4-3
Center Channels and Frequencies

Ochter Onamicis and Frequencies				
Test frequencies & associated channels				
Channel	Frequency (MHz)			
Secondary Cellular 8	20			
564 (CDMA)	820.10			
Cellular 850				
384 (CDMA)	836.52			
190 (GSM)	836.60			
4183 (UMTS)	836.60			
AWS 1750				
1412 (UMTS)	1730.40			
PCS 1900				
600 (CDMA)	1880			
661 (GSM)	1880			
9400 (UMTS)	1880			

2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. Low-mid and mid-high channels are additionally tested for LTE TDD. The middle channel and supported bandwidths from the worst-case band according to Table 7-6, and 7-7 were additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-5 to 9-11, and Tables 9-16 to 9-17 for LTE bandwidths and channels.

3. WIFI

The middle channel for each 802.11 standard was tested for each probe orientation. The 2.4GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. The 5GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested on higher U-NII bands as well as applicable low and high channels. See Tables 9-12 and 9-18 for WIFI standards and channels.

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 16 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 10 01 61

IX. Test Flow

The flow diagram below was followed (From C63.19):




Figure 4-15 C63.19 T-Coil Signal Test Process

FCC ID: ZNFX220PM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 17 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		raye 17 0101

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoLTE over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1
Test Setup for VoLTE over IMS T-Coil Measurements

2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

* http://c63.org/documents/misc/posting/new_interpretations.htm

FCC ID: ZNFX220PM	PCTEST'	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 18 of 81
1M1809240182-02 7NF	9/28/2018 - 10/04/2018	Portable Handset		rage 10 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. **DUT Configuration for VoLTE over IMS T-coil Testing**

1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. 16QAM, 1RB, 99RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

> Table 5-1 Vol TE over IMS SNNR by Radio Configuration

	VOLTE OVER IMS SINKE BY RAUIO CONTINUITATION													
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]						
1732.5	20175	20	QPSK	1	0	3.09	-34.12	37.21						
1732.5	20175	20	QPSK	1	50	3.17	-34.33	37.50						
1732.5	20175	20	QPSK	1	99	3.17	-33.62	36.79						
1732.5	20175	20	QPSK	50	0	3.21	-34.81	38.02						
1732.5	20175	20	QPSK	50	25	3.17	-34.85	38.02						
1732.5	20175	20	QPSK	50	50	2.52	-35.12	37.64						
1732.5	20175	20	QPSK	100	0	2.74	-34.74	37.48						
1732.5	20175	20	16QAM	1	0	2.86	-30.52	33.38						
1732.5	20175	20	16QAM	1	50	2.46	-30.68	33.14						
1732.5	20175	20	16QAM	1	99	2.60	-29.62	32.22						
1732.5	20175	20	16QAM	50	0	2.66	-33.98	36.64						
1732.5	20175	20	16QAM	50	25	2.99	-34.27	37.26						
1732.5	20175	20	16QAM	50	50	2.91	-35.11	38.02						
1732.5	20175	20	16QAM	100	0	3.14	-34.32	37.46						


2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.60kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 5-2 AMR Codec Investigation - VoLTE over IMS

			0 0 0 3 0 0 0 0				
Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	3.71	2.62	11.73	11.37			
ABM2 (dBA/m)	-31.26	-31.16	-30.79	-30.63	— Axial	Band 4 20MHz BW	20175
Frequency Response	Pass	Pass	Pass	Pass			
S+N/N (dB)	34.97	33.78	42.52	42.00			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFX220PM	PETEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 19 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 19 01 01

3. LTE TDD Uplink-Downlink Configuration Investigation for VoLTE over IMS

An investigation was performed to determine the worst-case Uplink-Downlink configuration for VoLTE over IMS T-Coil testing.

Per 3GPP TS 36.211, the total frame length for each TDD radio frame of length $T_f = 307200 \cdot T_s$ = 10 ms, where T_s is a number of time units equal to $1/(15000 \times 2048)$ seconds. Additionally, each radio frame consists of 10 subframes, each of length $30720 \cdot T_s = 1$ ms, and subframes can be designated as uplink (U), downlink (D), or special subframe (S), depending on the Uplink-Downlink configuration as indicated in Table 4.2-2 of 3GPP TS 36.211. In the transmission duty factor calculation, the special subframe configuration with the shortest UpPTS duration within the special subframe is used and will be applied for measurement. From 3GPP TS 36.211 Table 4.2-1, the shortest UpPTS is 2192 · Ts which occurs in the normal cyclic prefix and special subframe configuration 4.

See table below outlining the calculated transmission duty cycles for each Uplink-Downlink configuration:

> Table 5-3 **Uplink-Downlink Configurations for Type 2 Frame Structures**

Uplink-downlink	Downlink-to-Uplink	Subframe number								Calculated Transmission		
configuration	Switch-point periodicity	0	1	2	3	4	5	6	7	8	9	Duty Cycle (%)
0	5 ms	D	S	U	U	U	D	S	U	U	U	61.4%
1	5 ms	D	S	U	U	D	D	S	U	U	D	41.4%
2	5 ms	D	S	U	D	D	D	S	U	D	D	21.4%
3	10 ms	D	S	U	U	U	D	D	D	D	D	30.7%
4	10 ms	D	S	U	U	D	D	D	D	D	D	20.7%
5	10 ms	D	S	U	D	D	D	D	D	D	D	10.7%
6	5 ms	D	S	U	U	U	D	S	U	U	D	51.4%

a. Power Class 3 Uplink-Downlink Configuration Investigation

Power class 3 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 99RB Offset. For Power Class 3, all configurations (0-6) are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 6 was used as the worst-case configuration for Power Class 3 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-4 Power Class 3 VoLTE over IMS SNNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	16QAM	1	99	0	2.72	-27.06	29.78
2593.0	40620	20	16QAM	1	99	1	2.91	-26.25	29.16
2593.0	40620	20	16QAM	1	99	2	2.78	-26.19	28.97
2593.0	40620	20	16QAM	1	99	3	2.87	-28.38	31.25
2593.0	40620	20	16QAM	1	99	4	2.53	-29.23	31.76
2593.0	40620	20	16QAM	1	99	5	2.85	-28.87	31.72
2593.0	40620	20	16QAM	1	99	6	2.64	-25.73	28.37

FCC ID: ZNFX220PM	TENTINE LANGEAUDA, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 20 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 20 01 01	

b. Power Class 2 Uplink-Downlink Configuration Investigation

Power Class 2 was evaluated with the following radio configuration: channel 40620, 20MHz BW, 16QAM, 1RB, 99RB Offset. For Power Class 2, configurations 1-5 are supported. The configuration which resulted in the worst SNNR was used for full testing. Uplink-Downlink configuration 1 was used as the worst-case configuration for Power Class 2 VoLTE over IMS T-Coil testing. See table below for the SNNR comparison between each Uplink-Downlink configuration:

Table 5-5
Power Class 2 VoLTE over IMS SNNR by UL-DL Configuration

Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	UL-DL Configuration	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2593.0	40620	20	16QAM	1	99	1	2.64	-24.02	26.66
2593.0	40620	20	16QAM	1	99	2	2.26	-25.61	27.87
2593.0	40620	20	16QAM	1	99	3	2.44	-27.70	30.14
2593.0	40620	20	16QAM	1	99	4	2.24	-28.01	30.25
2593.0	40620	20	16QAM	1	99	5	2.27	-27.17	29.44

Note: LTE TDD B41 Power Class 2 only supports UL-DL configurations 1-5, not 0 or 6.

c. Conclusion

Per the investigations above, UL-DL Configuration 6 was used to evaluate Power Class 3 VoLTE over IMS and UL-DL Configuration 1 was used to evaluate Power Class 2 VoLTE over IMS.

FCC ID: ZNFX220PM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 21 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 210101

VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION 6.

I. Test System Setup for VoWIFI over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1 Test Setup for VoWIFI over IMS T-Coil Measurements

2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level2. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

² FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFX220PM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 22 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 22 01 0 1

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

DUT Configuration for VoWIFI over IMS T-coil Testing II.

1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each 802.11 standard:

> Table 6-1 802.11b SNNR by Radio Configuration

		002.115 01	TITIL Dy ITAG	o oomingarador	•	
Mode	Channel	Modulation	Data Rate	ABM1	ABM2	SNNR
			[Mbps]	[dB(A/m)]	[dB(A/m)]	[dB]
802.11b	6	DSSS	1	-0.23	-27.08	26.85
802.11b	6	DSSS	2	-0.24	-27.19	26.95
802.11b	6	CCK	5.5	-0.16	-26.50	26.34
802.11b	6	CCK	11	-0.20	-26.91	26.71

Table 6-2 802.11g SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11g	6	BPSK	6	0.36	-30.11	30.47
802.11g	6	BPSK	9	0.22	-31.19	31.41
802.11g	6	QPSK	12	0.60	-29.77	30.37
802.11g	6	QPSK	18	0.22	-30.80	31.02
802.11g	6	16-QAM	24	0.14	-31.83	31.97
802.11g	6	16-QAM	36	0.27	-32.93	33.20
802.11g	6	64-QAM	48	0.24	-31.95	32.19
802.11g	6	64-QAM	54	0.02	-33.23	33.25

Table 6-3 802.11n SNNR by Radio Configuration

	over the control of t								
Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]			
802.11n	6	BPSK	6.5	0.69	-31.88	32.57			
802.11n	6	QPSK	13	0.45	-26.44	26.89			
802.11n	6	QPSK	19.5	0.63	-27.57	28.20			
802.11n	6	16-QAM	26	0.62	-29.37	29.99			
802.11n	6	16-QAM	39	0.46	-29.90	30.36			
802.11n	6	64-QAM	52	0.55	-30.16	30.71			
802.11n	6	64-QAM	58.5	0.46	-30.64	31.10			
802.11n	6	64-QAM	65	0.52	-28.81	29.33			

FCC ID: ZNFX220PM	PCTEST INCIDENT LABORATORY, 14C.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 23 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 23 01 6 1


2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The WB AMR 6.6kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 6-4
AMR Codec Investigation – VoWIFI over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel		
ABM1 (dBA/m)	0.80	0.11	11.67	11.47						
ABM2 (dBA/m)	-27.00	-27.27	-27.24	-27.19	Axial	2.4GHz	IEEE 802.11b	6		
Frequency Response	Pass	Pass	Pass	Pass	Axiai	2.4GHz				
S+N/N (dB)	27.80	27.38	38.91	38.66						

Mute on; Backlight off; Max Volume; Max Contrast



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 24 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 24 01 6 1

OTT VOIP TEST SYSTEM AND DUT CONFIGURATION 7.

I. Test System Setup for OTT VolP T-Coil Testing

1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 64kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

3. Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation3. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

II. **DUT Configuration for OTT VolP T-Coil Testing**

1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 6kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

> Table 7-1 Codec Investigation - OTT VoIP (EvDO)

Codec Setting:	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	11.48	10.97		
ABM2 (dBA/m)	-30.61	-30.77	Axial	384
Frequency Response	Pass	Pass	Axiai	304
S+N/N (dB)	42.09	41.74		

³ FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFX220PM	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 25 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 23 01 6 1

Table 7-2 Codec Investigation – OTT VoIP (EDGE)

	irroongan	<u>,,, </u>	••• \==•	
Codec Setting:	64kbps	6kbps	Orientation	Channel
ABM1 (dBA/m)	10.76	10.35		
ABM2 (dBA/m)	-16.99	-15.84	Axial	661
Frequency Response	Pass	Pass	AAlai	
S+N/N (dB)	27.75	26.19		

Table 7-3 Codec Investigation - OTT VolP (HSPA)

	nvestigatio	,,, O,, v	011 (1101 /	•/	
Codec Setting:	64kbps	6kbps	Orientation	Channel	
ABM1 (dBA/m)	9.95	9.78			
ABM2 (dBA/m)	-34.43	-34.16	Axial	0.400	
Frequency Response	Pass	Pass	Axiai	9400	
S+N/N (dB)	44.38	43.94			

Table 7-4 Codec Investigation - OTT VolP (LTE)

	Odec ilives	ruganon	<u> </u>	(-		
Codec Setting:	64kbps	6kbps	Orientation	Band / BW	Channel	
ABM1 (dBA/m)	11.10	10.45				
ABM2 (dBA/m)	-27.39	-26.68	Avial	Band 4	20175	
Frequency Response	Pass	Pass	- Axial	20MHz BW		
S+N/N (dB)	38.49	37.13				

Table 7-5 Codec Investigation - OTT VoIP (WIFI)

		voongan	•••	1011 (1111	,	
Codec Setting:	64kbps	6kbps	Orientation	Band	Standard	Channel
ABM1 (dBA/m)	9.99	9.33				6
ABM2 (dBA/m)	-23.51	-23.67	Axial	2.4GHz	802.11b	
Frequency Response	Pass	Pass	Axiai	2.40112	002.110	
S+N/N (dB)	33.50	33.00				

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.H




Figure 7-1 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFX220PM	PETEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 26 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 20 01 6 1

2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE FDD band to be used for OTT VoIP testing. LTE Band 4 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE FDD bands:

Table 7-6
OTT VoIP (LTE) SNNR by LTE FDD Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
12	707.5	23095	10	16QAM	1	49	10.70	-29.58	40.28
13	782.0	23230	10	16QAM	1	49	10.76	-27.33	38.09
26	831.5	26865	15	16QAM	1	74	10.75	-27.51	38.26
4	1732.5	20175	20	16QAM	1	99	10.26	-26.97	37.23
25	1882.5	26365	20	16QAM	1	99	10.53	-26.90	37.43

An investigation was performed to determine the worst-case LTE TDD band to be used for OTT VoIP testing. LTE Band 41 Power Class 2 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE TDD bands:

Table 7-7
OTT VoIP (LTE) SNNR by LTE TDD Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
41 (PC3)	2593.0	40620	20	16QAM	1	99	10.15	-21.19	31.34
41 (PC2)	2593.0	40620	20	16QAM	1	99	10.62	-17.93	28.55

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 27 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 27 01 61

8. FCC 3G MEASUREMENTS

I. CDMA Test Configurations

Radio Configuration 1, Service Option 3 (thick, green data curve) was used for the testing as the worst-case configuration for the handset due to vocoder gating from the EVRC logic. See below plot for ABM noise comparison between operational field service options and radio configurations for a CDMA2000 handset:





Figure 8-1
CDMA Audio Band Magnetic Noise

Table 8-1 FCC 3G ABM Measurements for ZNFX220PM (CDMA)

Configuration:	RC1/SO3	RC3/SO3	RC4/SO3	Orientation	Channel	
ABM1 (dBA/m)	13.84	13.65	13.58			
ABM2 (dBA/m)	-27.66	-41.18	-41.12	Axial	384	
Frequency Response	Pass	Pass	Pass	AAIai	304	
S+N/N (dB)	41.50	54.83	54.70			

- Mute on; Backlight off; Max Volume; Max Contrast
- Power Control Bits = "All Up"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 28 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 20 01 0 1

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. UMTS Test Configurations

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:





Figure 8-3
UMTS Audio Band Magnetic Noise

Table 8-2 Codec Investigation - UMTS

Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel	
ABM1 (dBA/m)	12.82	12.73	12.35			
ABM2 (dBA/m)	-40.74	-41.28	-41.51	Axial	9400	
Frequency Response	Pass	Pass	Pass	Axiai	3400	
S+N/N (dB)	53.56	54.01	53.86			

- Mute on; Backlight off; Max Volume; Max Contrast
- · TPC="All 1s"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 29 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 29 01 0 1

9. T-COIL TEST SUMMARY

Table 9-1 Consolidated Tabled Results

Consolidated Tabled Results											
		-	esponse rgin	_	netic / Verdict		SNNR dict	Margin from FCC Limit	C63.19-2011		
C62 1	9 Section	8.3.2		8.3.1		8.3.4		(dB)	Rating		
C03. 13	9 Section	Axial	Radial	Axial	Radial	Axial	Radial				
	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS				
CDMA	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-17.56	T4		
	PCS	PASS	NA	PASS	PASS	PASS	PASS				
	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS				
EvDO (OTT VoIP)	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-20.10	T4		
,	PCS	PASS	NA	PASS	PASS	PASS	PASS				
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-2.00	Т3		
GSIVI	PCS	PASS	NA	PASS	PASS	PASS	PASS	-2.00	13		
EDGE	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-4.03	Т3		
(OTT VoIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS	-4.03	13		
	Cellular	PASS	NA	PASS	PASS	PASS	PASS				
UMTS	AWS	PASS	NA	PASS	PASS	PASS	PASS	-33.64	T4		
	PCS	PASS	NA	PASS	PASS	PASS	PASS				
	Cellular	PASS	NA	PASS	PASS	PASS	PASS				
HSPA (OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS	-24.11	T4		
	PCS	PASS	NA	PASS	PASS	PASS	PASS				
	B12	PASS	NA	PASS	PASS	PASS	PASS				
	B13	PASS	NA	PASS	PASS	PASS	PASS				
LTE FDD	B26	PASS	NA	PASS	PASS	PASS	PASS	-9.85	Т3		
	B4	PASS	NA	PASS	PASS	PASS	PASS				
	B25	PASS	NA	PASS	PASS	PASS	PASS				
LTE FDD (OTT VoIP)	B4	PASS	NA	PASS	PASS	PASS	PASS	-17.02	T4		
LTE TDD	B41	PASS	NA	PASS	PASS	PASS	PASS	-2.08	Т3		
LTE TDD (OTT VoIP)	B41	PASS	NA	PASS	PASS	PASS	PASS	-8.25	Т3		
	802.11b	PASS	NA	PASS	PASS	PASS	PASS				
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-4.59	Т3		
	802.11n	PASS	NA	PASS	PASS	PASS	PASS				
	802.11b	PASS	NA	PASS	PASS	PASS	PASS				
WLAN (OTT VoIP)	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-10.07	T4		
(570)	802.11n	PASS	NA	PASS	PASS	PASS	PASS				

FCC ID: ZNFX220PM	POTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 30 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 30 01 6 1

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

I. **Raw Handset Data**

Table 9-2 **Raw Data Results for CDMA**

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		476	13.30	-26.20		1.97	39.50	20.00	-19.50	T4		
	Axial	564	13.29	-27.09	-60.45	1.99	40.38	20.00	-20.38	T4	2.4, 3.4	
Cellular Radial	684	13.61	-26.56		1.75	40.17	20.00	-20.17	T4			
	476	6.94	-36.95			43.89	20.00	-23.89	T4			
	564	7.17	-37.99	-60.54 N/A	45.16	20.00	-25.16	T4	2.8, 3.2			
	684	7.16	-37.27			44.43	20.00	-24.43	T4			
	1013	13.57	-26.16		1.63	39.73	20.00	-19.73	T4			
	Axial	384	13.60	-27.01	-60.45	1.84	40.61	20.00	-20.61	T4	2.4, 3.4	
Cellular		777	13.42	-26.21		1.77	39.63	20.00	-19.63	T4		
Celiulai		1013	7.10	-36.79	-60.54	-60.54 N/A		43.89	20.00	-23.89	T4	
	Radial	384	7.15	-38.20			45.35	20.00	-25.35	T4	2.8, 3.2	
		777	7.18	-36.68			43.86	20.00	-23.86	T4		
		25	13.26	-24.96		1.99	38.22	20.00	-18.22	T4		
	Axial	600	13.41	-25.88	-60.45	1.97	39.29	20.00	-19.29	T4	2.4, 3.4	
PCS		1175	13.40	-24.16		2.00	37.56	20.00	-17.56	T4	1	
PCS		25	7.09	-38.79			45.88	20.00	-25.88	T4		
	Radial	600	7.11	-38.18	-60.54	N/A	45.29	20.00	-25.29	T4	2.8, 3.2	
		1175	7.21	-35.26			42.47	20.00	-22.47	T4	1	

Table 9-3 Raw Data Results for GSM

	Naw Data Nesults for Com												
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates		
		128	12.82	-10.16		2.00	22.98	20.00	-2.98	T3			
	Axial	190	12.93	-9.88	-60.45	2.00	22.81	20.00	-2.81	T3	2.4, 3.4		
GSM850		251	12.80	-9.20		2.00	22.00	20.00	-2.00	Т3			
GSINIOSU		128	6.83	-22.21			29.04	20.00	-9.04	T3			
	Radial	190	6.73	-21.83	-60.54	-60.54 N/A	28.56	20.00	-8.56	T3	2.8, 3.2		
		251	6.71	-21.16				27.87	20.00	-7.87	T3		
		512	12.71	-15.66		2.00	28.37	20.00	-8.37	Т3			
	Axial	661	12.54	-15.37	-60.45	2.00	27.91	20.00	-7.91	T3	2.4, 3.4		
CCM4000		810	12.67	-15.42		2.00	28.09	20.00	-8.09	T3			
G3W1900	SSM1900	512	6.69	-27.00			33.69	20.00	-13.69	T4			
	Radial	661	6.59	-26.73	-60.54	N/A	33.32	20.00	-13.32	T4	2.8, 3.2		
		810	6.76	-27.13			33.89	20.00	-13.89	T4			

Table 9-4 **Raw Data Results for UMTS**

Train Bata Robalto for Gill C												
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
		4132	12.67	-41.42		1.98	54.09	20.00	-34.09	T4		
	Axial	4183	12.68	-41.60	-60.45	1.94	54.28	20.00	-34.28	T4	2.4, 3.4	
UMTS V		4233	12.70	-41.22		2.00	53.92	20.00	-33.92	T4		
OWISV		4132	6.91	-49.98			56.89	20.00	-36.89	T4		
	Radial	4183	6.95	-50.04	-60.54	N/A	56.99	20.00	-36.99	T4	2.8, 3.2	
		4233	6.90	-49.95			56.85	20.00	-36.85	T4		
		1312	12.77	-41.16		1.96	53.93	20.00	-33.93	T4		
	Axial	1412	12.70	-41.07	-60.45	1.96	53.77	20.00	-33.77	T4	2.4, 3.4	
UMTS IV		1513	12.64	-41.00		1.99	53.64	20.00	-33.64	T4		
OWITSTV		1312	6.86	-50.83			57.69	20.00	-37.69	T4		
	Radial	1412	6.87	-50.93	-60.54	N/A	57.80	20.00	-37.80	T4	2.8, 3.2	
		1513	6.87	-51.08			57.95	20.00	-37.95	T4		
		9262	12.69	-41.07		1.93	53.76	20.00	-33.76	T4		
	Axial	9400	12.70	-40.96	-60.45	1.94	53.66	20.00	-33.66	T4	2.4, 3.4	
UMTSII		9538	12.68	-41.06		1.96	53.74	20.00	-33.74	T4		
OWISII		9262	6.84	-51.33			58.17	20.00	-38.17	T4		
	Radial	9400	6.78	-50.97	-60.54	N/A	57.75	20.00	-37.75	T4	2.8, 3.2	
		9538	6.83	-50.73			57.56	20.00	-37.56	T4		

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 31 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 31 01 61

Table 9-5 **Raw Data Results for LTE B12**

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		10MHz	23095	2.31	-28.82		2.00	31.13	20.00	-11.13	T4	
	Axial	5MHz	23095	2.26	-28.94	-60.45	2.00	31.20	20.00	-11.20	T4	2.0. 3.4
	AXIAI	3MHz	23095	2.32	-28.72	-00.43	2.00	31.04	20.00	-11.04	T4	2.0, 3.4
LTE Band		1.4MHz	23095	2.21	-30.41		2.00	32.62	20.00	-12.62	T4	
12		10MHz	23095	-0.95	-42.57	-60.54		41.62	20.00	-21.62	T4	
	Radial	5MHz	23095	-0.88	-40.15		-60.54 N/A	39.27	20.00	-19.27	T4	2.8. 3.2
	Naulai	3MHz	23095	-1.55	-40.27		INA	38.72	20.00	-18.72	T4	2.0, 3.2
		1.4MHz	23095	-1.48	-39.87			38.39	20.00	-18.39	T4	

Table 9-6 **Raw Data Results for LTE B13**

	Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)		Test Coordinates
ı		Axial	10MHz	23230	2.40	-29.37	-60.45	2.00	31.77	20.00	-11.77	T4	2.0. 3.4
	LTE Band	Axiai	5MHz	23230	2.13	-29.20	-00.45	2.00	31.33	20.00	-11.33	T4	2.0, 3.4
	13 Radial	Destin	10MHz	23230	-0.98	-38.42	-60.54	N/A	37.44	20.00	-17.44	T4	2.8. 3.2
		Radiai	5MHz	23230	-0.89	-39.05	-00.54	N/A	38.16	20.00	-18.16	T4	2.0, 3.2

Table 9-7 Raw Data Results for LTE B26

						•	OI								
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates			
		15MHz	26965	2.16	-29.27		2.00	31.43	20.00	-11.43	T4				
		15MHz	26865	2.36	-27.49		2.00	29.85	20.00	-9.85	T3				
		15MHz	26765	2.13	-29.13		2.00	31.26	20.00	-11.26	T4				
	Axial	10MHz	26865	2.32	-30.12	-60.45	2.00	32.44	20.00	-12.44	T4	2.0, 3.4			
		5MHz	26865	2.38	-29.07		2.00	31.45	20.00	-11.45	T4				
LTE Band		3MHz	26865	2.24	-31.09		2.00	33.33	20.00	-13.33	T4				
26		1.4MHz	26865	2.48	-30.10		2.00	32.58	20.00	-12.58	T4				
		15MHz	26865	-1.01	-40.56			39.55	20.00	-19.55	T4				
		10MHz	26865	-0.98	-40.92	7 -60.54	02 07 -60.54 N	-60.54		39.94	20.00	-19.94	T4		
	Radial	5MHz	26865	-0.89	-41.07				-60.54	-60.54	N/A	40.18	20.00	-20.18	T4
		3MHz	26865	-0.84	-42.01				41.17	20.00	-21.17	T4			
		1.4MHz	26865	-0.75	-42.05			41.30	20.00	-21.30	T4				

Table 9-8 Raw Data Results for LTE B4

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	20175	2.17	-31.10		2.00	33.27	20.00	-13.27	T4	
		15MHz	20175	2.19	-29.22		2.00	31.41	20.00	-11.41	T4	
	A	10MHz	20175	2.17	-29.30	-60.45	2.00	31.47	20.00	-11.47	T4	2.0. 3.4
Axial	5MHz	20175	2.35	-29.06	-00.45	2.00	31.41	20.00	-11.41	T4	2.0, 3.4	
		3MHz	20175	2.12	-29.97		2.00	32.09	20.00	-12.09	T4	
LTE Band 4	LTE Don't 4	1.4MHz	20175	2.27	-29.73		2.00	32.00	20.00	-12.00	T4	
LIE Ballu 4		20MHz	20175	-0.82	-39.10			38.28	20.00	-18.28	T4	
		15MHz	20175	-1.03	-40.29			39.26	20.00	-19.26	T4	
	Radial	10MHz	20175	-1.01	-41.49	60.54	N/A	40.48	20.00	-20.48	T4	2.8. 3.2
	Naulai	5MHz	20175	-0.91	-40.54	-60.54	N/A	39.63	20.00	-19.63	T4	2.0, 3.2
		3MHz	20175	-0.99	-41.91			40.92	20.00	-20.92	T4	
		1.4MHz	20175	-0.59	-41.20			40.61	20.00	-20.61	T4	

Table 9-9 Raw Data Results for LTF B25

				aw D	ita ixo	SuitS i	O.	. DZU				
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	26365	2.22	-28.77		2.00	30.99	20.00	-10.99	T4	
		15MHz	26365	2.51	-29.35		2.00	31.86	20.00	-11.86	T4	
	Axial	10MHz	26365	2.27	-29.61	-60.45	2.00	31.88	20.00	-11.88	T4	2.0, 3.4
	Andi	5MHz	26365	2.62	-30.33	-00.45	2.00	32.95	20.00	-12.95	T4	2.0, 3.4
		3MHz	26365	2.37	-31.03		2.00	33.40	20.00	-13.40	T4	
		1.4MHz	26365	2.33	-31.04		2.00	33.37	20.00	-13.37	T4	
LTE Band		20MHz	26590	-0.58	-40.45			39.87	20.00	-19.87	T4	
25		20MHz	26365	-1.11	-38.47			37.36	20.00	-17.36	T4	j
		20MHz	26140	-0.58	-37.98			37.40	20.00	-17.40	T4	
	Radial	15MHz	26365	-1.02	-39.12	-60.54	N/A	38.10	20.00	-18.10	T4	2.8, 3.2
	radial	10MHz	26365	-0.88	-40.19	-00.54	IWA	39.31	20.00	-19.31	T4	2.0, 3.2
		5MHz	26365	-0.83	-40.99	9		40.16	20.00	-20.16	T4	
		3MHz	26365	-0.88	-40.06			39.18	20.00	-19.18	T4	
		1.4MHz	26365	-0.53	-41.34			40.81	20.00	-20.81	T4	

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 32 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 32 01 0 1

Table 9-10 Raw Data Results for LTE B41 Power Class 3

			~		a					•		
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	40620	2.63	-26.08		2.00	28.71	20.00	-8.71	T3	
	Axial	15MHz	40620	2.45	-26.92	-60.45	2.00	29.37	20.00	-9.37	T3	2.0. 3.4
	Axiai	10MHz	40620	2.36	-26.55		2.00	28.91	20.00	-8.91	T3	2.0, 3.4
LTE Band		5MHz	40620	2.35	-26.69		2.00	29.04	20.00	-9.04	T3	
41		20MHz	40620	-1.98	-32.26			30.28	20.00	-10.28	T4	
	Radial	15MHz	40620	-1.96	-31.79	-60.54	-60.54 N/A	29.83	20.00	-9.83	T3	2.8. 3.2
	Naulai	10MHz	40620	-2.11	-31.17		INA	29.06	20.00	-9.06	T3	2.0, 3.2
		5MHz	40620	-2.23	-29.99			27.76	20.00	-7.76	T3	

Table 9-11 Raw Data Results for LTE B41 Power Class 2

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	41490	2.20	-25.84		2.00	28.04	20.00	-8.04	T3	
		20MHz	41055	2.23	-26.43		2.00	28.66	20.00	-8.66	T3	
		20MHz	40620	2.67	-23.54		2.00	26.21	20.00	-6.21	T3	
	Axial	20MHz	40185	2.33	-26.25	-60.45	2.00	28.58	20.00	-8.58	T3	2.0, 3.4
	Axiai	20MHz	39750	2.29	-25.09	-00.45	2.00	27.38	20.00	-7.38	T3	2.0, 3.4
		15MHz	40620	2.35	-25.62		2.00	27.97	20.00	-7.97	T3	
		10MHz	40620	2.41	-26.25		2.00	28.66	20.00	-8.66	T3	
LTE Band		5MHz	40620	2.27	-25.35		2.00	27.62	20.00	-7.62	T3	
41		20MHz	40620	-1.45	-25.14			23.69	20.00	-3.69	T3	
		15MHz	40620	-1.38	-25.04			23.66	20.00	-3.66	T3	
		10MHz	41490	-1.77	-24.28			22.51	20.00	-2.51	T3	
	Radial	10MHz	41055	-2.02	-26.22	-60.54	N/A	24.20	20.00	-4.20	T3	20.22
	Radiai	10MHz	40620	-1.68	-25.27	-00.54	N/A	23.59	20.00	-3.59	T3	2.8, 3.2
		10MHz	40185	-1.92	-24.99	9		23.07	20.00	-3.07	T3	
		10MHz	39750	-2.21	-24.29			22.08	20.00	-2.08	T3	
		5MHz	40620	-1.44	-25.79			24.35	20.00	-4.35	T3	

Table 9-12 Raw Data Results for 2.4GHz WIFI

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	0.46	-27.15		2.00	27.61	20.00	-7.61	T3	
WLAN	Axial	6	0.07	-26.75	-60.45	2.00	26.82	20.00	-6.82	Т3	2.4, 3.4
802.11b		11	0.38	-27.89		2.00	28.27	20.00	-8.27	Т3	
	Radial	6	-5.20	-30.20	-60.54	N/A	25.00	20.00	-5.00	T3	2.8, 3.2
WLAN	Axial	6	0.23	-28.79	-60.45	2.00	29.02	20.00	-9.02	T3	2.4, 3.4
802.11g	Radial	6	-4.89	-36.65	-60.54	N/A	31.76	20.00	-11.76	T4	2.8, 3.2
	Axial	6	0.50	-26.53	-60.45	2.00	27.03	20.00	-7.03	T3	2.4, 3.4
WLAN		1	-5.14	-30.33			25.19	20.00	-5.19	T3	
802.11n	Radial	6	-4.85	-29.44	-60.54	N/A	24.59	20.00	-4.59	T3	2.8, 3.2
		11	-5.16	-30.96			25.80	20.00	-5.80	T3	

Table 9-13 Raw Data Results for EvDO (OTT VoIP)

	Trave Data (County) Margin from											
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
Secondary Cellular	Axial	564	10.51	-29.70	-60.45	1.77	40.21	20.00	-20.21	T4	2.4, 3.4	
EvDO	Radial	564	5.77	-41.94	-60.54	N/A	47.71	20.00	-27.71	T4	2.8, 3.2	
Cellular	Axial	384	10.45	-29.65	-60.45	1.89	40.10	20.00	-20.10	T4	2.4, 3.4	
EvDO	Radial	384	5.72	-43.51	-60.54	N/A	49.23	20.00	-29.23	T4	2.8, 3.2	
PCS	Axial	600	10.76	-30.02	-60.45	1.91	40.78	20.00	-20.78	T4	2.4, 3.4	
EvDO	Radial	600	5.50	-43.81	-60.54	N/A	49.31	20.00	-29.31	T4	2.8, 3.2	

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 33 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 33 01 6 1

Table 9-14 Raw Data Results for EDGE (OTT VoIP)

	Num Bata Nesatto for EBGE (GTT Voll)												
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates		
EDGE850	Axial	190	10.69	-13.34	-60.45	1.45	24.03	20.00	-4.03	Т3	2.4, 3.4		
EDGE000	Radial	190	4.92	-22.94	-60.54	N/A	27.86	20.00	-7.86	Т3	2.8, 3.2		
EDGE1900	Axial	661	10.45	-16.65	-60.45	1.65	27.10	20.00	-7.10	Т3	2.4, 3.4		
EDGE 1900	Radial	661	5.01	-26.92	-60.54	N/A	31.93	20.00	-11.93	T4	2.8, 3.2		

Table 9-15 Raw Data Results for HSPA (OTT VoIP)

	Train Bata Resource for Field 77 (STE Voil)										
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
HSPA V	Axial	4183	10.21	-34.37	-60.45	1.77	44.58	20.00	-24.58	T4	2.4, 3.4
nora v	Radial	4183	4.78	-43.91	-60.54	N/A	48.69	20.00	-28.69	T4	2.8, 3.2
HSPA IV	Axial	1412	9.97	-34.24	-60.45	1.87	44.21	20.00	-24.21	T4	2.4, 3.4
порату	Radial	1412	4.94	-45.55	-60.54	N/A	50.49	20.00	-30.49	T4	2.8, 3.2
HSPAII	Axial	9400	10.08	-34.03	-60.45	1.85	44.11	20.00	-24.11	T4	2.4, 3.4
HOPAII	Radial	9400	4.97	-44.94	-60.54	N/A	49.91	20.00	-29.91	T4	2.8, 3.2

Table 9-16 Raw Data Results for LTE B4 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	20175	10.38	-26.82		1.68	37.20	20.00	-17.20	T4	2.4, 3.4
		15MHz	20325	10.61	-27.78		1.59	38.39	20.00	-18.39	T4	
		15MHz	20175	10.50	-26.52		1.68	37.02	20.00	-17.02	T4	
	Axial	15MHz	20025	10.25	-28.23	-60.45	1.84	38.48	20.00	-18.48	T4	
		10MHz	20175	10.42	-28.07	-00.45	1.86	38.49	20.00	-18.49	T4	
		5MHz	20175	10.28	-28.14		1.76	38.42	20.00	-18.42	T4	
		3MHz	20175	10.36	-27.98		1.52	38.34	20.00	-18.34	T4	
LTE Band 4		1.4MHz	20175	10.18	-28.46		1.91	38.64	20.00	-18.64	T4	
LIE Ballu 4		20MHz	20175	4.76	-36.76			41.52	20.00	-21.52	T4	
		15MHz	20325	4.77	-37.06			41.83	20.00	-21.83	T4	
		15MHz	20175	4.68	-36.80			41.48	20.00	-21.48	T4	
	Radial	15MHz	20025	4.65	-39.37	60.54	N/A	44.02	20.00	-24.02	T4	2.8, 3.2
	radial	10MHz	20175	4.91	-37.11	-60.54	N/A	42.02	20.00	-22.02	T4	
		5MHz	20175	4.96	-37.47			42.43	20.00	-22.43	T4	
		3MHz	20175	4.67	-38.66			43.33	20.00	-23.33	T4	
		1.4MHz	20175	4.62	-38.48			43.10	20.00	-23.10	T4	

Table 9-17 Raw Data Results for LTE B41 Power Class 2 (OTT VoIP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	41490	10.52	-19.96		1.80	30.48	20.00	-10.48	T4	2.4, 3.4
		20MHz	41055	10.65	-19.95		1.73	30.60	20.00	-10.60	T4	
		20MHz	40620	10.14	-18.11		1.81	28.25	20.00	-8.25	Т3	
	Axial	20MHz	40185	10.29	-19.92	-60.45	1.73	30.21	20.00	-10.21	T4	
	Axiai	20MHz	39750	10.47	-19.75		1.87	30.22	20.00	-10.22	T4	
		15MHz	40620	10.43	-19.98		1.81	30.41	20.00	-10.41	T4	
		10MHz	40620	10.58	-20.12		1.69	30.70	20.00	-10.70	T4	
LTE Band		5MHz	40620	10.28	-19.99		1.83	30.27	20.00	-10.27	T4	
41		20MHz	40620	4.83	-25.08			29.91	20.00	-9.91	Т3	
		15MHz	40620	4.62	-24.89			29.51	20.00	-9.51	Т3	
		10MHz	40620	4.83	-24.85			29.68	20.00	-9.68	Т3	
	Radial	5MHz	41490	4.96	-23.84	-60.54	N/A	28.80	20.00	-8.80	Т3	2.8, 3.2
	Naulai	5MHz	41055	4.57	-24.63	-00.54	INA	29.20	20.00	-9.20	Т3	2.0, 3.2
		5MHz	40620	4.82	-24.62			29.44	20.00	-9.44	T3	1
		5MHz	40185	4.63	-23.68			28.31	20.00	-8.31	Т3	1
		5MHz	39750	5.08	-24.60			29.68	20.00	-9.68	Т3	1

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 34 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 34 01 01	

Table 9-18 Raw Data Results for 2.4GHz WIFI (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	9.81	-24.28		1.64	34.09	20.00	-14.09	T4	
	Axial	6	9.69	-23.65	-60.45	1.71	33.34	20.00	-13.34	T4	2.4, 3.4
WLAN		11	10.20	-25.27		1.59	35.47	20.00	-15.47	T4	
802.11b		1	2.76	-27.89			30.65	20.00	-10.65	T4	
	Radial	6	3.34	-26.73	-60.54	N/A	30.07	20.00	-10.07	T4	2.8, 3.2
		11	2.81	-27.92			30.73	20.00	-10.73	T4	
WLAN	Axial	6	9.52	-27.98	-60.45	1.72	37.50	20.00	-17.50	T4	2.4, 3.4
802.11g	Radial	6	2.83	-31.42	-60.54	N/A	34.25	20.00	-14.25	T4	2.8, 3.2
WLAN	Axial	6	9.75	-24.77	-60.45	1.69	34.52	20.00	-14.52	T4	2.4, 3.4
802.11n	Radial	6	2.86	-27.84	-60.54	N/A	30.70	20.00	-10.70	T4	2.8, 3.2

II. **Test Notes**

A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- 3. Hearing Aid Mode (Phone→Call Settings→Additional Settings→Hearing aids) was set to ON for Frequency Response compliance
- 4. Speech Signal: ITU-T P.50 Artificial Voice
- 5. Bluetooth and WIFI were disabled for 2G/3G/4G modes while testing.
- 6. Licensed data modes and Bluetooth were disabled for WIFI modes while testing.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

B. CDMA

- 1. Power Configuration: Power Control Bits = "All Up"
- 2. Vocoder Configuration: RC1/SO3 (CDMA EVRC)

C. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

D. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

E. LTE FDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 99RB offset
- 3. Vocoder Configuration: WB AMR 6.60kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 26 at 15MHz is the worst-case for the Axial probe orientation. LTE Band 25 at 20MHz bandwidth is the worst-case for the Radial probe orientation.

FCC ID: ZNFX220PM	PETEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 35 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 33 01 6 1	

F. LTE TDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 99RB offset
- 3. Power Class 3 Uplink-Downlink configuration: 6
- 4. Power Class 2 Uplink-Downlink configuration: 1
- 5. Vocoder Configuration: WB AMR 6.60kbps
- 6. Speech Signal: ITU-T P.50 Artificial Voice
- 7. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, mid-high and high channels for those combinations. LTE Band 41 (Power class 2) at 20MHz is the worst-case for the Axial probe orientation. LTE Band 41 (Power class 2) at 10MHz bandwidth is the worst-case for the Radial probe orientation.

G. WIFI

- 1. Radio Configuration
 - a. 802.11b: CCK, 5.5Mbps
 - b. 802.11g: QPSK, 12Mbps
 - c. 802.11n: QPSK, 13Mbps
- 2. Vocoder Configuration: WB AMR 6.6kbps
- 3. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for the Axial probe orientation. 802.11n is the worst-case for the Radial probe orientation.

H. OTT VolP


- 1. Vocoder Configuration: 6kbps
- 2. EvDO Configuration
 - a. Revision: A
- 3. EDGE Configuration
 - a. MCS Index: 7
 - b. Number of TX slots: 2
- 4. HSPA Configuration:
 - a. Release: 6
 - b. 3GPP 34.121 Subtest 1
- 5. LTE FDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 99RB offset
 - c. LTE Band 4 was the worst-case band from Table 7-6 and was used to test both Axial and Radial probe orientations.
 - d. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 4 at 15MHz is the worst-case for both the Axial and Radial probe orientations.
- 6. LTE TDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 99RB offset
 - c. Power Class 2 Uplink-Downlink configuration: 1
 - d. LTE Band 41 (Power Class 2) was the worst-case band from Table 7-7 and was used to test both Axial and Radial probe orientations.
 - e. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low, low-mid, high-mid, and high channels for those combinations. LTE Band 41 (Powers Class 2) at 20MHz is the worst-case for the Axial

FCC ID: ZNFX220PM	PETEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 36 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 30 01 6 1	


probe orientation and LTE Band 41 (Power Class 2) at 5MHz is the Radial probe orientation.

- 7. WIFI Configuration:
 - a. Radio Configuration
 - i. 802.11b: CCK, 5.5Mbps
 - ii. 802.11g: QPSK, 12Mbps
 - iii. 802.11n: QPSK, 13Mbps
 - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both the Axial and Radial probe orientations.


III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -18 dBm0 for CDMA. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 37 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 37 01 61

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018


IV. T-Coil Validation Test Results

Table 9-19
Helmholtz Coil Validation Table of Results

Item	Target	Result	Verdict
Axial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.166	PASS
Environmental Noise	< -58 dBA/m	-60.45	PASS
Frequency Response, from limits	> 0 dB 0.60		PASS
Radial			
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.286	PASS
Environmental Noise	< -58 dBA/m	-60.54	PASS
Frequency Response, from limits	> 0 dB	0.70	PASS

FCC ID: ZNFX220PM	POTEST VECENTIAL LADDETON, INC.	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 38 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 30 01 6 1

V. ABM1 Magnetic Field Distribution Scan Overlays



Axial Radial (Transverse)

Figure 9-1

T-Coil Scan Overlay Magnetic Field Distributions

Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots. The VoLTE over IMS Axial measurement location is indicated by a blue cursor.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 39 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 39 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

10. MEASUREMENT UNCERTAINTY

Table 10-1
Uncertainty Estimation Table

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1)						17.7%	0.71
Expanded uncertainty (k=2), 95% confidence level						35.3%	1.31

Notes:

- 1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 40 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 40 01 01

11. EQUIPMENT LIST

Table 11-1 Equipment List

		Equipment Elot				
Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Dell	Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/11/2017	Biennial	4/11/2019	7BFNM32
Listen	SoundConnect	Microphone Power Supply	12/2/2016	Biennial	12/2/2018	PS2612
RME	Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/11/2017	Biennial	4/11/2019	23528889
Rohde & Schwarz	CMW500	Wideband Radio Communication Tester	1/19/2018	Annual	1/19/2019	162125
Rohde & Schwarz	CMW500	Radio Communication Tester	4/20/2018	Annual	4/20/2019	128635
Seekonk	NC-100	Torque Wrench (8" lb)	5/10/2018	Biennial	5/10/2020	21053
TEM	C63.19	Helmholtz Coil	12/7/2016	Biennial	12/7/2018	925
TEM	Radial T-Coil Probe	Radial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1130
TEM	Axial T-Coil Probe	Axial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1124
TEM		HAC System Controller with Software	N/A		N/A	N/A
TEM		HAC Positioner	N/A		N/A	N/A

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 41 01 61

12. TEST DATA

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 42 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 42 01 6 1



DUT: HH Coil - SN:925


Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Axial T-Coil Probe SN: TEM-1124; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.166	dB	\checkmark	Max/Min	-9.5/-10.5
Verification ABM2	-60.45	dB	•	Maximum	-58.0
Frequency Response Margin	600m	dB	•	Tolerance curves	Aligned Data

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 43 01 6 1



DUT: HH Coil - SN:925


Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.286 dE	•	Max/Min	-9.5/-10.5
Verification ABM2	-60.54 dE	€	Maximum	-58.0
Frequency Response Margin	700m dE	•	Tolerance curves	Aligned Data

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 44 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 44 01 6 1



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- . Mode: CDMA Secondary Cell.
- Channel: 476
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 45 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 45 01 61



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: CDMA Cell.Channel: 777

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 46 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 40 01 01



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: CDMA PCSChannel: 1175

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 47 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Faye 47 0101



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM 850Channel: 251

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 48 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 46 01 6 1



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM 1900Channel: 661

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 40 of 91
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 49 of 81



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

. Mode: UMTS Band V

Channel: 4233

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 50 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 50 01 61



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

. Mode: UMTS Band IV

Channel: 1513

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 51 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 310101



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS Band II

Channel: 9400

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST:	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 52 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 52 of 81



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE FDD Band 26Bandwidth: 15MHz

Channel: 26865

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 53 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 33 01 6 1



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016


Test Configuration:

Mode: LTE TDD Band 41 (PC2)

Bandwidth: 20MHz

Channel: 40620

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 54 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 54 01 6 1



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

Channel: 6

· Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 55 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 33 01 0 1



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- VolP Application: Google Duo
- Mode: EDGE 850
- Channel: 190
- · Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 56 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		raye 30 01 01



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: CDMA Secondary Cell.

· Channel: 476



FCC ID: ZNFX220PM	POTEST VECENTIAL LADDETON, INC.	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 57 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 37 01 61



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: CDMA Cell.Channel: 777



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 58 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 56 01 6 1



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: CDMA PCS
Channel: 1175



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 59 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 39 01 6 1



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM 850Channel: 251



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 60 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 60 01 61



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM 1900Channel: 661



FCC ID: ZNFX220PM	PCTEST INCIDENT LABORATORY, 14C.	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 61 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 01 01 01



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

• Probe: Radial T-Coil Probe - SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS Band VChannel: 4233



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 62 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 02 01 0 1



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011

Equipment:

SNNR

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS Band IVChannel: 1312



57.69 dB

Minimum

20.0

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 63 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 03 01 6 1



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS Band II
Channel: 9538



FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 64 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 04 01 6 1



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

• Probe: Radial T-Coil Probe - SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE FDD Band 25Bandwidth: 20MHzChannel: 26365



FCC ID: ZNFX220PM	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 03 01 61



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011


Equipment:

• Probe: Radial T-Coil Probe - SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

. Mode: LTE TDD Band 41 (PC2)

Bandwidth: 10MHzChannel: 39750



FCC ID: ZNFX220PM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 66 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		raye 00 01 01



Type: Portable Handset Serial: 05455


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

- Mode: 2.4GHz WIFI
- Standard: IEEE 802.11n
- Channel: 6



FCC ID: ZNFX220PM	POTEST VECENTIAL LADDETON, INC.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 67 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 07 0101



Type: Portable Handset Serial: 05455

Measurement Standard: ANSI C63.19-2011


Equipment:

• Probe: Radial T-Coil Probe - SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

· VoIP Application: Google Duo


Mode: EDGE 850Channel: 190



FCC ID: ZNFX220PM	PCTEST:	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 68 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 00 01 01

13. CALIBRATION CERTIFICATES

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 69 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage 09 01 01



FCC ID: ZNFX220PM	POTEST.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 70 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 70 01 61

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

HCATEMC_TEM 1124_Dec-07-2016



ISO/IEC 17025: 2005

1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01

REPORT OF CALIBRATION

TEM Consulting LP Axial T Coil Probe Model No.: Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab. I. D. No: 80578

Probe Sensitivity measured wit	h Helmholt	z Call			
Helmholtz Coil;			Bofore & ofte	r data same	: X
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environ	ment:	
the current in the coils, in amperes.;	0.09	Α	Ambient Temperature:	20.2	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	31.4	% RH
Helmholtz Coil magnetic field;	5.98	A/m	Ambient Pressure:	99.1	kPa
			Calibration Date:	7-D••-16	
Probe Sensitivity at	1000	H≥.			
Was	-60.23	a BV/A/m	Report Number:	27068	-3
	0.974	m V/A/m	Control Number:	27068	
Proberesistance	904	Ohm.			
The above listed instrument meets or o	exceeds th	ne tested manufact	urer's specifications.		
his Calibration is traceable through NIST test number		683/284413-14			
he expanded uncertainty of calibration: 0.30dB at 95% c	onfidence leve	el with a coverage factor of k	c=2.		

Graph represents Probas Fraquency Response.

Axial Probe Response Measured Probe Resp. 20 15 10 Magnitude (dB) 5 0 -5 -10 -15 -20 10000 Freq. (Hz)

The above listed instrument was checked using calibration procedure documented in West Caldwell Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC Calibration Laboratories Inc. procedure :

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intanded to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016 Felix Christopher Calibrated on WCCL system type 9700

Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC This doou ment shall not be reproduced, except in full, without the written approval from West Caldwell Col. Labe. Inc.

Page 1 of 2

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Dogo 71 of 91
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 71 of 81

© 2018 PCTEST Engineering Laboratory, Inc.

HCATEMC_TEM 1124_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Axial T Coil Probe

Model No.: Axial T Coil Probe

Serial No.: TEM 1124

Company: PCTEST Engineering Lab.

Test	Function	Tolera	nce	Me	easured valu	ies
				Bafora	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz.	a BV/A/m	-60.23		
2.0	Probe Level Linearity	Rof. (0 c B)	а В 6 0 -6 -12	6.03 0.00 -6.03 -12.05		
3.0	Probe Frequency Response	Rer. (0 a B)	H ₂ 100 126 158 200 251 316 398 501 631 794 1000 1259 1585 1995 2512 3162 3981 5012 6310 7943 10000	-19.8 -18.0 -16.0 -13.9 -12.0 -9.9 -8.0 -6.0 -4.0 -2.0 0.0 2.0 4.0 6.0 7.9 9.9 11.9 13.9 15.9 18.0 20.2		

Instruments used for calibration	on:		Date of Cal.	Traceability No.	Due Dete
HP	34401A	S/N 36064102	1-Oat-2016	,287708	1-Oat-2017
HP	34401A	S/N 36102471	1-Oct-2016	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oet-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oot-2016	683/284413-14	1-Oot-2017


Cat. Date: 7-Dec-2016 Callbrated on WCCL system type 9700

Tested by: Felix Christopher

Rev. 7.0 Jan. 24, 2014 Dec. # 1038 HCATEMC

Page 2 of 2

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 72 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 72 01 6 1



FCC ID: ZNFX220PM	TENTINE LADRACON, INC.	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 73 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage /3 01 01

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

HCRTEMC_TEM-1130_Dec-07-2016



ISO/IEC 17025: 2005


1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01


REPORT OF CALIBRATION

TEM Consulting LP Radial T Coil Probe Model No.: Radial T Coil Probe Serial No.: TEM-1130

I. D. No: 80579 Company: PCTEST Engineering Lab.



Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements of ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016 Calibrated on WCCL system type 9700 Felix Christopher Rev. 7.0 Jan. 24, 2014 Dec. # 1038 HCRTEMC

Page 1 of 2

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 74 of 81
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Page 74 01 6 1

© 2018 PCTEST Engineering Laboratory, Inc.

HCRTEMC_TEM-1130_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tel. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Radial T Coil Probe

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

Company: PCTEST Engineering Lab.

Test	Function	Tolera	Tolerance			Measured values		
				Bafora	Out	Remarks		
1.0	Probe Sensitivity at	1000 Hz.	d BV/A/m	-60.27				
2.0	Proba Lavel Linearity	Ref. (0 eB)	⊌B 6 0 -6 -12	6.03 0.00 -6.03 -12.06				
3.0	Proba Frequency Response	Rar. (0 dB)	H ₂ 100 126 158 200 251 316 398 501 631 794 1000 1259 1585 1995 2512 3162 3981 5012 6310 7943 10000	-19.9 -18.0 -16.0 -13.9 -12.0 -10.0 -8.0 -6.0 -4.0 -2.0 0.0 2.0 4.0 6.0 7.9 9.9 11.9 13.9 15.9 18.0 20.2				

Instruments used for calibrat	ion:		Date of Cal.	Traceability No.	Duo Doto
HP	34401A	S/N 36064102	1-Oat-2016	,287708	1-Oct-2017
HP	34401A	S/N 36102471	1-Oct-2016	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oct-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oot-2016	683/284413-14	1-Oot-2017

Cat. Date: 7-Dec-2016

Tested by: Felix Christopher

Callbrated on WCCL system type 9700

Rev. 7.0 Jan. 24, 2014 Dec. # 1038 HCRTEMC

Page 2 of 2

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 75 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 73 01 01	

14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFX220PM	PCTEST INCIDENT LABORATORY, 14C.	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 76 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 70 01 01	

15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017 2.
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017 3.
- FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 5 FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 6.
- Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, "IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, " U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- 12. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1013, July 1981,
- EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
- 14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- 15. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- 16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
- 17. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 77 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		rage // or or	

- 22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- 24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 25. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- 26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
- 29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFX220PM	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 78 of 81	
1M1809240182-02.ZNF	9/28/2018 - 10/04/2018	Portable Handset		Fage 70 01 01	