

# ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR SUPERREGENERATIVE RECEIVER

Test report file number : E048R-009

Applicant	: SEOBY ELECTRONICS CO., LTD.
Address	: 38-2 Anyang 2-Dong, Manan-Gu, Anayang City Gyeunggi-Do Korea
Manufacturer	: SEOBY ELECTRONICS CO., LTD.
Address	: 38-2 Anyang 2-Dong, Manan-Gu, Anayang City Gyeunggi-Do Korea
Type of Equipment	: Remote Control Extender
FCC ID	: SCBRCV01
Basic Model Name	: UFO-1000
Multiple Model Name	: RCV-1000
Serial number	: N/A
Total page of Report	: 11 pages (including this page)
Date of Incoming	: June 09, 2004
Date of issuing	: August 03, 2004

# **SUMMARY**

The equipment complies with the regulation; FCC PART 15 SUBPART B §15.101 This test report contains only the result of a single test of the sample supplied for the examination.

It is not a general valid assessment of the features of the respective products of the mass-production.

Prepared by:

G. W. Lee/ Chief Engineer EMC Div. ONETECH Corp.

Reviewed by Y. K. Kwon/ Director

EMC Div. ONETECH Corp.

FCC-004 (Rev.0)

This report shall not be reproduced except in full without our written approval.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)



# CONTENTS

1. VERIFICATION OF COMPLIANCE	
2. GENERAL INFORMATION	4
2.1 Product Description	4
2.2 RELATED SUBMITTAL(S) / GRANT(S)	4
2.3 TEST SYSTEM DETAILS	5
2.4 Test Methodology	5
2.5 TEST FACILITY	5
3. SYSTEM TEST CONFIGURATION	5
3.1 JUSTIFICATION	5
3.2 EUT EXERCISE SOFTWARE	5
<b>3.3</b> Equipment Modifications	5
3.4 CONFIGURATION OF TEST SYSTEM	
4. PRELIMINARY TEST	6
4.1 AC Power line Conducted Emissions Tests	
4.2 RADIATED EMISSIONS TESTS	
5. FINAL RESULT OF MEASURMENT	7
5.1 Conducted Emission Test	7
5.2 RADIATED EMISSION TEST	9
6. FIELD STRENGTH CALCULATION	
7. LIST OF TEST EOUIPMENT	

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)



Page 3 of 11 FCC ID. : SCBRCV01 File No. : E048R-009

# **1. VERIFICATION OF COMPLIANCE**

APPLICANT	: SEOBY ELECTRONICS CO., LTD.
ADDRESS	: 38-2 Anyang 2-Dong, Manan-Gu, Anayang City Gyeunggi-Do Korea
CONTACT PERSON	: Gab-Ju Jung / General Manager
TELEPHONE NO	: 82-31-474-8001
FCC ID	: SCBRCV01
MODEL NO/NAME	: UFO-1000
SERIAL NUMBER	: N/A
DATE	: August 03, 2004

DEVICE TYPE	UNINTENTIONAL RADIATOR
E.U.T. DESCRIPTION	Remote Control Extender
	-SUPERREGENERATIVE RECEIVER
THIS REPORT CONCERNS	ORIGINAL GRANT
MEASUREMENT PROCEDURES	ANSI C63.4/2001
TYPE OF EQUIPMENT TESTED	PRE-PRODUCTION
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	CERTIFICATION
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 \$15.101
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	No
FINAL TEST WAS CONDUCTED ON	3 METER OPEN AREA TEST SITE

-. This device has shown compliance with the conducted emissions limits in 15.107 adopted under FCC 02-107 (ET Docket 98-80). The device may be marketed after July 11, 2005 and is not affected by the 15.37(j) transition provisions.

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)



# 2. GENERAL INFORMATION

#### **2.1 Product Description**

The Seoby Electronics Co., Ltd., Model UFO-1000 (referred to as the EUT in this report) is a receiver that is built-in Telescopic antenna. The EUT catch RF signal from a RF remote controller and decode IR signal from RF signal and then transmit IR signal through LED to home appliance. The product specification described herein was obtained from product data sheet or user's manual.

CHASSIS TYPE	Plastic
RECEIVING FREQUENCY	433.92 MHz
SENSITIVITY	Min-107dBm
IR TRANSMITTING FREQUENCY	38kHz / 56kHz
REFERENCE DATA PROTOCOL	NEC
DATA RATES	2500 kbps (Max.)
LIST OF EACH OSC. OR CRY. FREQ.(FREQ.>=1MHz)	433.92 MHz Resonator
NUMBER OF LAYERS	2 LAYERS
EXTERNAL CONNECTOR	DC Input Jack
RATED SUPPLY VOLTAGE	DC 12V, 200mA

Model Differences:

-. No other model differences have been mentioned.

## 2.2 Related Submittal(s) / Grant(s)

Original submittal only.

This report shall not be reproduced except in full without our written approval.



## 2.3 Test System Details

The EUT was tested with the following all equipment used in the tested systems are:

Model	Manufacturer	FCC ID	Description	Connected to
UFO-1000	SEOBY ELECTRONICS CO., LTD.	SCBRCV01	RECEIVER	AC/DC Adapter
Thomas	ICX International	O5JUSE000001	Remote Controller	N/A
YU120020DI	YEE FU Electronic Enterprise	N/A	AC/DC Adapter	EUT
8657A	НР	N/A	Signal Generator	N/A

#### 2.4 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.4/2001. Radiated testing was performed at a distance of 3 meters from EUT to the antenna.

#### 2.5 Test Facility

The open area test site and conducted measurement facilities are located on at 426-1 Daessangryung-Ri, Chowol-Myun, Kwangju-Kun, Kyunggi-Do 464-080 Korea. Description details of test facilities were submitted to the Commission on October 02, 2002. (Registration Number: 529838)

## **3. SYSTEM TEST CONFIGURATION**

#### **3.1 Justification**

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
MAIN BOARD	SEOBY ELECTRONICS CO., LTD.	FR-4	N/A

#### **3.2 EUT exercise Software**

Set the signal generator to transmit at 433.92MHz and then the EUT receives the signal.

Used battery for the EUT was fully charged.

To get a maximum emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes.

#### **3.3 Equipment Modifications**

None

This report shall not be reproduced except in full without our written approval.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)



#### 3.4 Configuration of Test System

Line Conducted Emission Test:

The EUT was connected to USB port of PC and the power line of PC was connected to LISN. All supporting equipments were connected to another LISN. Using the procedure in ANSI C63.4/1992 7.2.3 to determine the worse operating conditions performed preliminary Power line Conducted Emission test.

Radiated Emission Test:

Preliminary radiated emissions tests were conducted using the procedure in ANSI C63.4/2001, 8.3.1.1 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 meters open area test site.

Coherent Test:

During Radiated Emission Tests, H.P. signal generator model no: 8657A was used to radiate an unmodulated CW signal to EUT at 433.92 MHz in order to cohere the individual components of the characteristic broadband emissions from EUT.

#### Antenna Power Conduction Test:

This equipment was only with a permanently attached antenna, so the radiated emission measurement was performed with the antenna attached.

## 4. PRELIMINARY TEST

#### 4.1 AC Power line Conducted Emissions Tests

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
RX Mode	Х

#### 4.2 Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)
RX mode	Х

This report shall not be reproduced except in full without our written approval.

HEAD OFFICE
 : #505
 SK
 APT.
 Factory
 223-28,
 Sangdaewon
 1
 Dong,
 Jungwon-Gu,
 Seongnam-City,
 Kyunggi-Do,
 462-121,
 Korea

 (TEL:
 82-31-746-8500
 FAX:
 82-31-746-8700)



# **5. FINAL RESULT OF MEASURMENT**

Preliminary test was done in normal operation mode. And the final measurement was selected for the maximized emission level.

### 5.1 Conducted Emission Test

Humidity Level	: <u>45 %</u>	Temperature: 23 °C
Limits apply to	: FCC CFR 47, PART 15, SUBPART B, SECTION 15.107	
Type of Test	: <u>CLASS B</u>	
Result	: PASSED BY -17.50 dB at 0.38 MHz at Peak mode	
EUT	: USB Multi Card Reader	Date: July 17, 2004

Operating Condition : Data were continuously read and written from the EUT to a personal computer.

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 9 kHz)

Frequency	Line	Quasi-Peak (dBuV)		Margin Average (dBuV)			Margin	
(MHz)		Emission Level	Detector Mode	Limits	(dB)	Emission level	Limits	(dB)
0.16	Ν	38.35	Р	65.73	-27.38	-	-	-
0.22	N	37.66	Р	62.82	-25.16	-	-	-
0.36	Ν	40.80	Р	58.73	-17.93	-	-	-
0.38	Ν	40.78	Р	58.28	-17.50	-	-	-
0.76	Ν	28.15	Р	56.00	-27.85	-	-	-

Line Conducted Emission Tabulated Data

Remark : "H": Hot Line, "N": Neutral line, "P": Peak detector

Average data was not recorded, because Peak values were under the average limit.

公川喜

Tested by: Gi-Hong, Nam / Test Engineer

FCC-004 (Rev.0)

This report shall not be reproduced except in full without our written approval.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)



Page 8 of 11 FCC ID. : SCBRCV01 File No. : E048R-009



This report shall not be reproduced except in full without our written approval.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)



#### 5.2 Radiated Emission Test

The following table shows the highest levels of radiated emission on both polarizations of horizontal and vertical.

Humidity Level	: <u>41 %</u>	Temperature : 27 °C
Limits apply to	: FCC CFR 47, PART 15, SUBPART B, SECTION 15.109	
Detector	: CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)	
Type of Test	: Unintentional Radiator	
Result	: PASSED BY -11.90 dB at 233.50 MHz	
_		

EUT	: Remote Control Extender	Date: August 02, 2004
Operating Condition	: RX mode	
Distance	: 3 Meter	

<b>Radiated Emission</b>		Ant	<b>Correction Factors</b>		Total	FCC LIMIT	
Freq.	Amp.		Antenna	Cable Loss	Amplitude	Limit	Margin
(MHz)	(dBuV)	Pol.	(dB/m)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
220.90	10.08	v	16.72	2.14	28.94	46.02	-17.08
233.50	14.90	Н	16.99	2.23	34.12	46.02	-11.90
270.32	13.00	Н	17.97	2.48	33.45	46.02	-12.57
348.81	14.60	Н	14.13	2.67	31.40	46.02	-14.62
440.87	12.90	Н	16.20	3.11	32.21	46.02	-13.81
501.92	10.91	Н	17.20	3.33	31.44	46.02	-14.58

Other frequencies are more than 30dB below the limit up to 2GHz.

Radiated Emission Tabulated Data

いいま

Tested by: Ki-Hong, Nam / Test Engineer

This report shall not be reproduced except in full without our written approval.



# 6. FIELD STRENGTH CALCULATION

Meter readings are compared to the specification limit correcting for antenna and cable losses

dB Relative to Spec

=

+	Meter reading	(dBuV)
+	Cable Loss	(dB)
+	Antenna Factor (Loss)	(dB/meter)
=	Corrected Reading	(dBuV/meter)
-	Specification Limit	(dBuV/meter)

(+/- dB)

This report shall not be reproduced except in full without our written approval.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)

Testing & Evaluation Lab.

**ONETECH** 

Page 11 of 11 FCC ID. : SCBRCV01 File No. : E048R-009

# 7. LIST OF TEST EQUIPMENT

No.	EQUIPMENTS	MFR.	MODEL	SER. NO.	LAST CAL	DUE CAL	USE
1.	Test receiver	R/S	ESVS 10	827864/005	NOV/03	12MONTH	
2.	Test receiver	R/S	ESHS10	834467/007	APR/04	12MONTH	
3.	Spectrum analyzer	HP	8567A	3021A00773	JUL/04	12MONTH	
4.	RF preselector	HP	85685A	3107A01268	JUL/04	12MONTH	
5.	Quasi-Peak Adapter	HP	85650A	3107A01550	JUL/04	12MONTH	
6.	Biconical antenna	EMCO	3104C	9109-4441	JUL/04	12MONTH	
				9109-4443			
				9109-4444			
7.	Log Periodic antenna	EMCO	3146	9109-3213	JUL/04	12MONTH	-
				9109-3214			
				9109-3217			
8.	Horn Antenna	SCHWARZBECK	BBHA9120D	BBHA9120D294	JUN/04	12MONTH	
9.	LISN	EMCO	3825/2	9109-1867	AUG/03	12MONTH	
				9109-1869			
10.	RF Amplifier	HP	8347F	3307A01354	JUN/04	N/A	
11	Spectrum Analyzer	HP	8564E	3650A00756	JUL/04	12MONTH	
12.	Spectrum Analyzer	HP	8566B	3407A08547	AUG/03	12MONTH	
13.	Plotter	HP	7475A	30052 22986	N/A	N/A	
14.	Position Controller	HD	HD100	100/788	N/A	N/A	
15.	Turn Table	HD	DS420S	N/A	N/A	N/A	
16.	Antenna Master	HD	HD240	N/A	N/A	N/A	
17.	Isolation Transformer	Digitek Power	DPT	DPF-22027	N/A	N/A	
18.	Isolation Transformer	Digitek Power	DPT	DPF-22028	N/A	N/A	
19.	Frequency Converter	Digitek Power	VFS/DEFC	N/A	N/A	N/A	

This report shall not be reproduced except in full without our written approval.

HEAD OFFICE : #505 SK APT. Factory 223-28, Sangdaewon 1 Dong, Jungwon-Gu, Seongnam-City, Kyunggi-Do, 462-121, Korea (TEL: 82-31-746-8500 FAX: 82-31-746-8700)