

Operating Frequency :	836520000	Hz
Channel :	384	
Reference Volage :	3.3	V
Deviation Limit :	+/- 0.00025/ 2.5	% / ppm

Voltage (%)	Voltage (Vdc)	Temp. (C)	Frequency (Hz)	Deviation (%)	Offset (Hz)
100%	3.3	-20	836520004.0	0.00000039	4.0
100%		-10	836519993.7	-0.00000084	-6.3
100%		0	836519995.5	-0.00000062	-4.5
100%		10	836519982.0	-0.00000224	-18.0
100%		25 (Ref)	836520000.7	0.00000000	0.7
100%		30	836520000.7	0.00000000	0.7
100%		40	836519995.0	-0.00000068	-5.0
100%		50	836520005.0	0.00000051	5.0
100%		60	836520029.0	0.00000338	29.0
90%	3.0	25	836519997.0	-0.00000044	-3.0
110%	3.6	25	836520008.7	0.00000096	8.7

Operating Frequency :		1880000000		Hz	
Channel :		600			
Reference Voltage :		3.3		V	
Deviation Limit :		+/- 0.00025/ 2.5		% / ppm	
Voltage	Voltage	Temp.	Frequency	Deviation	Offset
(%)	(Vdc)	(C)	(Hz)	(%)	(Hz)
100%	3.3	-20	1880000043.0	0.00000196	43
100%		-10	1879999992.0	-0.00000075	-8
100%		0	1879999978.0	-0.00000149	-22
100%		10	1880000012.4	0.00000034	12.4
100%		25 (Ref)	1880000006.1	0.00000000	6.1
100%		30	1879999960.0	-0.00000245	-40
100%		40	1880000004.3	-0.00000010	4.3
100%		50	1880000014.0	0.00000042	14
100%		60	1880000011.0	0.00000026	11
90%	3.0	25	1880000007.8	0.00000009	7.8
110%	3.6	25	1880000023.0	0.00000090	23