

PCTEST ENGINEERING LABORATORY, INC.

7185 Oakland Mills Road, Columbia, MD 21046 USA Tel. 410.290.6652 / Fax 410.290.6654 http://www.pctest.com



HEARING AID COMPATIBILITY

Applicant Name:

LG Electronics MobileComm U.S.A. Inc. 1000 Sylvan Avenue Englewood Cliffs, NJ 07632 United States Date of Testing: 05/24/2018 - 05/31/2018 Test Site/Location: PCTEST Lab, Columbia, MD, USA Test Report Serial No.: 1M1805030091-08-R1.ZNF

FCC ID: ZNFL414DL

APPLICANT: LG ELECTRONICS MOBILECOMM U.S.A. INC.

Scope of Test: Audio Band Magnetic Testing (T-Coil)

Application Type: Certification
FCC Rule Part(s): CFR §20.19(b)
HAC Standard: ANSI C63.19-2011

285076 D01 HAC Guidance v05

285076 D02 T-Coil testing for CMRS IP v03

DUT Type: Portable Handset

Model: LML414DL

Additional Model(s): LM-L414DL, L414DL

Test Device Serial No.: Pre-Production Sample [S/N: 00607]

C63.19-2011 HAC Category: T3 (SIGNAL TO NOISE CATEGORY)

Note: This revised Test Report (S/N: 1M1805030091-08-R1.ZNF) supersedes and replaces the previously issued test report on the same subject device for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

This wireless portable device has been shown to be hearing-aid compatible under the above rated category, specified in ANSI/IEEE Std. C63.19-2011 and has been tested in accordance with the specified measurement procedures. Test results reported herein relate only to the item(s) tested. Hearing-Aid Compatibility is based on the assumption that all production units will be designed electrically identical to the device tested in this report. North American Bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Randy Ortanez President





FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 1 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 10175

TABLE OF CONTENTS

1.	INTRODUCTION	3
2.	DUT DESCRIPTION	4
3.	ANSI C63.19-2011 PERFORMANCE CATEGORIES	6
4.	METHOD OF MEASUREMENT	8
5.	VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION	18
6.	VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION	20
7.	OTT VOIP TEST SYSTEM AND DUT CONFIGURATION	23
8.	FCC 3G MEASUREMENTS	26
9.	T-COIL TEST SUMMARY	28
10.	MEASUREMENT UNCERTAINTY	38
11.	EQUIPMENT LIST	39
12.	TEST DATA	40
13.	CALIBRATION CERTIFICATES	63
14.	CONCLUSION	70
15.	REFERENCES	71
16.	TEST SETUP PHOTOGRAPHS	73

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 2 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 2 01 75

1. INTRODUCTION

On July 10, 2003, the Federal Communications Commission (FCC) adopted new rules requiring wireless manufacturers and service providers to provide digital wireless phones that are compatible with hearing aids. The FCC has modified the exemption for wireless phones under the Hearing Aid Compatibility Act of 1998 (HAC Act) in WT Docket 01-309 RM-8658¹ to extend the benefits of wireless telecommunications to individuals with hearing disabilities. These benefits encompass business, social and emergency communications, which increase the value of the wireless network for everyone. An estimated more than 10% of the population in the United States show signs of hearing impairment and of that fraction, almost 80% use hearing aids. Approximately 500 million people worldwide and 30 million people in the United States suffer from hearing loss.

Compatibility Tests Involved:

The standard calls for wireless communications devices to be measured for:

- RF Electric-field emissions
- T-coil mode, magnetic-signal strength in the audio band
- T-coil mode, magnetic-signal frequency response through the audio band
- T-coil mode, magnetic-signal and noise articulation index

The hearing aid must be measured for:

- RF immunity in microphone mode
- RF immunity in T-coil mode

In the following tests and results, this report includes the evaluation for a wireless communications device.



Figure 1-1 Hearing Aid in-vitu

¹ FCC Rule & Order, WT Docket 01-309 RM-8658

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 3 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Faye 3 01 73

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

2. DUT DESCRIPTION



FCC ID: ZNFL414DL

Applicant: LG Electronics MobileComm U.S.A. Inc.

1000 Sylvan Avenue

Englewood Cliffs, NJ 07632

United States

Model: LML414DL

Additional Model(s): LM-L414DL, L414DL

Serial Number: 00607

HW Version: Rev.1.0

SW Version: L414DL06n

Antenna: Internal Antenna

DUT Type: Portable Handset

I. LTE Band Selection

This device supports the following pair of LTE bands with similar frequencies: LTE B4 & B66. This pair of LTE bands has the same target power and shares the same transmission path. Since the supported frequency span for the smaller LTE band is completely covered by the larger LTE band, only the larger LTE band (LTE B66) was evaluated for hearing-aid compliance.

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 4 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 4 0175

Table 2-1 **ZNFL414DL HAC Air Interfaces**

Band (MHz)	Type Transport	HAC Tested	Simultaneous But Not Tested	Name of Voice Service		
835	V/0	Vaa	Vee MIEL or DT	CMDC Vaina*		
1900	VO	res	tes. WIFI OF BT	CMRS Voice*		
EvDO	VD	Yes	Yes: WIFI or BT	Google Duo**		
850	VO	Vos	Voc. WIEL or DT	CMRS Voice*		
1900	VO	res	tes. Wiri of bi	CIVIK2 VOICE.		
GPRS/EDGE	VD	Yes	Yes: WIFI or BT	Google Duo**		
850						
1700	VD	Yes	Yes: WIFI or BT	Yes Yes: WIFI or BT	CMRS Voice*	
1900						
HSPA	VD	Yes	Yes: WIFI or BT	Google Duo**		
680 (B71)		Yes1				
700 (B12)		Yes: WIFI or BT				
780 (B13)						
850 (B5)	VD					VoLTE*, Google Duo**
1700 (B4)						
1700 (B66)						
1900 (B2)						
2450	VD	Yes	Yes: CDMA, GSM, UMTS, or LTE	VoWIFI**, Google Duo**		
2450	DT	No	Yes: CDMA, GSM, UMTS, or LTE	N/A		
, ta - Not intended for		Interpretation. ** Reference	level is -20dBm0 in accordance with FCC KDB 28	5076 D02		
	(MHz) 835 1900 EvDO 850 1900 GPRS/EDGE 850 1700 1900 HSPA 680 (B71) 700 (B12) 780 (B13) 850 (B5) 1700 (B4) 1700 (B66) 1900 (B2) 2450 2450 y ta - Not intended for	Type Transport	Type Transport HAC Tested	MHz Type Transport HAC Tested But Not Tested		

to the existing HAC procedures.

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 5 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 3 01 73

3. ANSI C63.19-2011 PERFORMANCE CATEGORIES

I. MAGNETIC COUPLING

Axial and Radial Field Intensity

All orientations of the magnetic field, in the axial and radial position along the measurement plane shall be \geq -18 dB(A/m) at 1 kHz in a 1/3 octave band filter per §8.3.1.

Frequency Response

The frequency response of the axial component of the magnetic field shall follow the response curve specified in EIA RS-504-1983, over the frequency range 300 Hz – 3000 Hz per §8.3.2.




Figure 3-1
Magnetic field frequency response for Wireless Devices with an axial field ≤-15 dB(A/m) at 1 kHz




Figure 3-2
Magnetic Field frequency response for wireless devices with an axial field that exceeds
-15 dB(A/m) at 1 kHz

FCC ID: ZNFL414DL	PCTEST TELEVISION OF THE	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 6 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 6 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

Signal Quality

The table below provides the signal quality requirement for the intended audio magnetic signal from a wireless device. Only the RF immunity of the hearing aid is measured in T-coil mode. It is assumed that a hearing aid can have no immunity to an interference signal in the audio band, which is the intended reception band for this mode. The only criterion that can be measured is the RF immunity in T-coil mode. This is measured using the same procedure as the audio coupling mode at the same levels.

The signal quality of the axial and radial components of the magnetic field was used to determine the T-coil mode category.

Catogory	Telephone RF Parameters		
Category	Wireless Device Signal Quality [(Signal + Noise)-to-noise ratio in dB]		
T1	0 to 10 dB		
T2	10 to 20 dB		
Т3	20 to 30 dB		
T4	> 30 dB		
Table 3-1 Magnetic Coupling Parameters			

Note: The FCC limit for SNNR is 20dB and the test data margins will indicate a margin from the FCC limit for compliance.

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 7 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage / 01/3

4. METHOD OF MEASUREMENT

I. Test Setup

The equipment was connected as shown in an acoustic/RF hemi-anechoic chamber:




Figure 4-1
Validation Setup with Helmholtz Coil




Figure 4-2 T-Coil Test Setup

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 8 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 0 01 75

II. Scanning Mechanism

Manufacturer: TEM

Accuracy: ± 0.83 cm/meter

Minimum Step Size: 0.1 mm

Maximum speed 6.1 cm/sec
Line Voltage: 115 VAC
Line Frequency: 60 Hz

Material Composite: Delrin (Acetal)

Data Control: Parallel Port

Dynamic Range (X-Y-Z): 45 x 31.75 x 47 cm

Dimensions: 36" x 25" x 38" Operating Area: 36" x 49" x 55"

Reflections: < -20 dB (in anechoic chamber)




Figure 4-3 RF Near-Field Scanner

III. ITU-T P.50 Artificial Voice

Manufacturer: ITU-T

Active Frequency 100 Hz – 8 kHz

Range:

Stimulus Type: Male and Female, no spaces

Single Sample Duration: 20.96 seconds

Activity Level: 100%




Figure 4-4 Spectral Characteristic of full P.50





Figure 4-5
Temporal Characteristic of full P.50

FCC ID: ZNFL414DL	PETEST'	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 9 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 9 01 75



ABM2 Measurement Block Diagram:



Figure 4-6 Magnetic Measurement Processing Steps

IV. Test Procedure

- 1. Ambient Noise Check per C63.19 §7.3.1
 - a. Ambient interference was monitored using a Real-Time Analyzer between 100-10,000 Hz with 1/3 octave filtering.
 - b. "A-weighting" and Half-Band Integration was applied to the measurements.
 - c. Since this measurement was measured in the same method as ABM2 measurements, this level was verified to be more than 10 dB below the lowest measurement signal (which is the highest ABM2 measurement for a T4 WD). Therefore the maximum noise level for a T4 WD with an ABM1 = -18 dBA/m is:

- 2. Measurement System Validation(See Figure 4-1)
 - a. The measurement system including the probe, pre-amplifier and acquisition system were validated as an entire system to ensure the reliability of test measurements.
 - b. ABM1 Validation

The magnetic field at the center of the Helmholtz coil is given by the equation (per C63.19 Annex D.10.1):

$$H_c = \frac{NI}{r\sqrt{1.25^3}} = \frac{N(\frac{V}{R})}{r\sqrt{1.25^3}}$$

Where H_c = magnetic field strength in amperes per meter N = number of turns per coil

For the Helmholtz Coil, N=20; r=0.08m; R=10.2Ω and using V=18mV:

$$H_c = \frac{20 \cdot (\frac{0.018}{10.2})}{0.08 \cdot \sqrt{1.25^3}} = 0.316A/m \approx -10dB(A/m)$$

Therefore a pure tone of 1kHz was applied into the coils such that 18mV was observed across the resistor. The voltmeter used for measurement was verified to be capable of measurements in the audio band range. This theoretically generates an expected field of $-10 \, dB(A/m)$ in the center of the Helmholtz coil which was used to validate the probe measurement at $-10 \, dB(A/m)$. This was verified to be within $\pm 0.5 \, dB$ of the $-10 \, dB(A/m)$ value (see Page 36).

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 10 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 10 0175

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

Frequency Response Validation
 The frequency response through the Helmholtz Coil was verified to be within 0.5 dB relative to 1kHz, between 300 – 3000 Hz using the P.50 signal as shown below:



Figure 4-7 Frequency Response Validation

d. ABM2 Measurement Validation

WD noise measurements are filtered with A-weighting and Half-Band Integration over a frequency range of 100Hz – 10kHz to process ABM2 measurements. Below is the verification of the system processing A-weighting and Half-Band integration between system input to output within 0.5 dB of the theoretical result:

Table 4-1
ABM2 Frequency Response Validation

	HBI, A -	HBI, A -	
f (Hz)	Measured	Theoretical	dB Var.
	(dB re 1kHz)	(dB re 1kHz)	
100	-16.180	-16.170	-0.010
125	-13.257	-13.250	-0.007
160	-10.347	-10.340	-0.007
200	-8.017	-8.010	-0.007
250	-5.925	-5.920	-0.005
315	-4.045	-4.040	-0.005
400	-2.405	-2.400	-0.005
500	-1.212	-1.210	-0.002
630	-0.349	-0.350	0.001
800	0.071	0.070	0.001
1000	0.000	0.000	0.000
1250	-0.503	-0.500	-0.003
1600	-1.513	-1.510	-0.003
2000	-2.778	-2.780	0.002
2500	-4.316	-4.320	0.004
3150	-6.166	-6.170	0.004
4000	-8.322	-8.330	0.008
5000	-10.573	-10.590	0.017
6300	-13.178	-13.200	0.022
8000	-16.241	-16.270	0.029
10000	-19.495	-19.520	0.025

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 11 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 110175







Figure 4-8 **ABM2 Frequency Response Validation**

The ABM2 result is a power sum from 100Hz to 10kHz with half-band integration and Aweighting. To verify the power sum measurement, a power sum over the full band was measured and verified to track with the source level (See Figure 4-9). Therefore the setup in this step was used to verify the power sum post-processing for ABM2 measurements. See below block diagram:



The power summed output results for a known input were compared to the multi-meter results to verify any deviation in the post-processing implemented with the power-sum.

Table 4-2 **ABM2 Power Sum Validation**

WN Input (dBV)	Power Sum (dBV)	Multimeter-Full (dBV)	Dev (dB)
-60	-60.36	-60.2	0.16
-50	-50.19	-50.13	0.06
-40	-40.14	-40.03	0.11
-30	-30.13	-30.01	0.12
-20	-20.12	-20	0.12
-10	-10.14	-10	0.14

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 12 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 12 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M






Figure 4-10
ABM2 Power Sum Validation

- 3. Measurement Test Setup
 - a. Fine scan above the WD (TEM)
 - i. A multitone signal was applied to the handset such that the phone acoustic output was stable within 1dB over the probe settling time and with the acoustic output level at the C63.19 specified levels (below). The measurement step size was in 2 mm increments at a distance of 10 mm between the surface of the wireless device as shown below (note that in Figure 4-12, the grid is not to scale but merely a graphical representation of the coordinate system in use):





- ii. After scanning, the planar field maximum point was determined. The position of the probe was moved to this location to setup the test using the SoundCheck system.
- iii. These steps were repeated for all T-coil orientations (axial and radial) per Figure 4-15 after a T-coil orientation was fully measured with the SoundCheck system.
- b. Speech Signal Setup to Base Station Simulator

Measurement Distance

i. C63.19 Table 7-1 states audio reference input levels for various technologies:

Standard	Technology	Input Level (dBm0)
TIA/EIA/IS-2000	CDMA	-18
J-STD-007	GSM (217)	-16
T1/T1P1/3GPP	UMTS (WCDMA)	-16
iDEN TM	TDMA (22 and 11 Hz)	-18

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 13 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 13 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

- ii. See Section 5 and 6 for more information regarding CMW500 audio level settings for Voice Over LTE (VoLTE), and Voice Over WIFI (VoWIFI) testing.
- See Section 7 for more information regarding audio level settings for Over-The-Top (OTT) Voice Over IP (VoIP) Testing.

c. Real-Time Analyzer (RTA)

i. The Real-Time Analyzer was configured to analyze measurements using 1/3 Octave band weighted filtering.

d. WD Radio Configuration Selection

i. The device was chosen to be tested in the worst-case ABM2 condition (see below for GSM, see Section 8 for more information regarding worst-case configurations for CDMA and UMTS. LTE configuration information can be found in Section 5. WIFI configuration information can be found in Section 6 and 7.):




Figure 4-13
Vocoder Analysis for ABM Noise for GSM

4. Signal Quality Data Analysis

- a. Narrow-band Magnetic Intensity
 - i. The standard specifies a 1kHz 1/3 octave band minimum field intensity for a sine tone. The ABM1 measurements were evaluated at 1kHz with 1/3 octave band filtering over an averaged period of 10 seconds.

b. Frequency Response

- i. The appropriate frequency response curve was measured to curves in Figure 3-1 or Figure 3-2 between 300 3000 Hz using digital linear averaging (limit lines chosen according to measurement found in step 4a). A linear average over 3x the length of the artificial voice signal (3x sampling) was performed. A 10 second delay was configured in the measurement process of the stimulus to ensure handset vocoder latency effects and echo cancellation devices (if any) were appropriately stabilized during measurements.
- ii. The appropriate post-processing was applied according to the system processing chain illustrated in Figure 4-7. All R10 frequencies were plotted with respect to 0dB at 1kHz value and aligned with respect to the EIA-504 mask.
- iii. The margin is represented by the closest measured data point on the curve to the EIA-504 limit lines, in dB.

c. Signal Quality Index

 Ensuring the WD was at maximum RF power, maximum volume, backlight off, display on, maximum contrast setting, keypad lights on (when possible) with no audio signal through the vocoder, the WD was measured over at least 100 Hz –

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 14 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 14 01 75

- 10,000 Hz, maximized over 5 seconds with a 50ms sample time for the ABM2 measurement (5 second time period is used in noise measurements under standards such as IEEE 269, etc.).
- ii. After applying half-band integration and A-weighting to the result, a power sum was applied over each 1/3 octave bandwidth frequency for an ABM2 value.
- iii. This result was subtracted from the ABM1 result in step a, to obtain the Signal Quality.

V. Test Setup




Figure 4-14
Audio Magnetic Field Test Setup

VI. Deviation from C63.19 Test Procedure

Non-conducted RF connection due to inaccessible RF ports.

VII. Air Interface Technologies Tested

All air interfaces which support voice capabilities over a managed CMRS or pre-installed OTT VoIP applications were tested for T-coil. See Table 2-1 for more details regarding which modes were tested.

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 15 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 15 01 75

VIII. Wireless Device Channels and Frequencies

1. 2G/3G Modes

The frequencies listed in the table below are those that lie in the center of the bands used for cellular telephony. Low, middle and high channels were tested in each band for FCC compliance evaluation to ensure the maximum emission is captured across the entire band. Only middle channels were evaluated for data modes since circuit-switched voice modes were worst-case.

Table 4-3
Center Channels and Frequencies

Test frequencies & associated channels				
Channel	Frequency (MHz)			
Cellular 850				
384 (CDMA)	836.52			
190 (GSM)	836.60			
4183 (UMTS)	836.60			
AWS 1750				
1412 (UMTS)	1730.40			
PCS 1900				
600 (CDMA)	1880			
661 (GSM)	1880			
9400 (UMTS)	1880			

2. 4G (LTE) Modes

The middle channel for every band and bandwidth combination was tested for each probe orientation. The band and bandwidth combination from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels for that band and bandwidth combination. The middle channel and supported bandwidths from the worst-case band according to Table 7-6 was additionally evaluated with OTT VoIP for each probe orientation. See Tables 9-5 to 9-10 and 9-15 for LTE bandwidths and channels.

3. WIFI

The middle channel for each 802.11 standard was tested for each probe orientation. The 2.4GHz 802.11 standard from each probe orientation resulting in the worst-case SNNR was additionally tested using low and high channels. See Tables 9-11 and 9-16 for WIFI standards and channels.

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 16 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 10 01 75

IX. **Test Flow**

The flow diagram below was followed (From C63.19):




Figure 4-15 C63.19 T-Coil Signal Test Process

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 17 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 17 0175

5. VOLTE TEST SYSTEM SETUP AND DUT CONFIGURATION

I. Test System Setup for VoLTE over IMS T-coil Testing

1. Equipment Setup

The general test setup used for VoLTE over IMS is shown below. The callbox used when performing VoLTE over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 5-1
Test Setup for VoLTE over IMS T-Coil Measurements

2. Audio Level Settings

According to the July 2012 interpretations by the C63 Committee regarding the appropriate audio levels to be used for VoLTE over IMS T-coil testing, -16dBm0 shall be used for the normal speech input level*. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -16dBm0 speech input level to the DUT for the VoLTE over IMS connection.

* http://c63.org/documents/misc/posting/new_interpretations.htm

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	டுடி	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 18 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Faye 10 01 /3

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. **DUT Configuration for VoLTE over IMS T-coil Testing**

1. Radio Configuration

An investigation was performed to determine the modulation and RB configuration to be used for testing. 16QAM, 1RB, 0RB offset was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different radio configurations:

> Table 5-1 Vol TE over IMS SNNR by Radio Configuration

	VOLIE OVER INIS SNIRE BY Radio Configuration									
Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]		
1880.0	18900	20	QPSK	1	0	1.39	-32.46	33.85		
1880.0	18900	20	QPSK	1	50	1.96	-31.98	33.94		
1880.0	18900	20	QPSK	1	99	1.56	-31.88	33.44		
1880.0	18900	20	QPSK	50	0	3.15	-34.87	38.02		
1880.0	18900	20	QPSK	50	25	3.16	-34.79	37.95		
1880.0	18900	20	QPSK	50	50	2.96	-34.73	37.69		
1880.0	18900	20	QPSK	100	0	3.01	-34.29	37.30		
1880.0	18900	20	16QAM	1	0	1.72	-29.01	30.73		
1880.0	18900	20	16QAM	1	50	1.78	-29.25	31.03		
1880.0	18900	20	16QAM	1	99	1.84	-28.90	30.74		
1880.0	18900	20	16QAM	50	0	2.88	-34.85	37.73		
1880.0	18900	20	16QAM	50	25	3.00	-34.66	37.66		
1880.0	18900	20	16QAM	50	50	2.57	-34.38	36.95		
1880.0	18900	20	16QAM	100	0	3.61	-34.74	38.35		

2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The NB AMR 4.75kbps setting was used for the audio codec on the CMW500 for VoLTE over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

> Table 5-2 AMR Codec Investigation - VoLTE over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	9.27	10.28	2.04	1.51		Axial Band 2 20MHz	18900
ABM2 (dBA/m)	-29.13	-29.10	-28.81	-29.05	Avial		
Frequency Response	Pass	Pass	Pass	Pass	Axiai		
S+N/N (dB)	38.40	39.38	30.85	30.56			

- Mute on; Backlight off; Max Volume; Max Contrast
- TPC = "Max Power"




Figure 5-2 **Audio Band Magnetic Curve Measurement Block Diagram**

FCC ID: ZNFL414DL	PETEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 19 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 19 01 75

VOWIFI TEST SYSTEM SETUP AND DUT CONFIGURATION 6.

I. Test System Setup for VoWIFI over IMS T-coil Testing

Equipment Setup

The general test setup used for VoWIFI over IMS, or CMRS WIFI Calling, is shown below. The callbox used when performing VoWIFI over IMS T-coil measurements is a CMW500. The Data Application Unit (DAU) of the CMW500 was used to simulate the IP Multimedia Subsystem (IMS) server.




Figure 6-1 Test Setup for VoWIFI over IMS T-Coil Measurements

2. Audio Level Settings

According to KDB 285076 D02 released by the FCC OET regarding the appropriate audio levels to be used for VoWIFI over IMS T-Coil testing, -20dBm0 shall be used for the normal speech input level2. The CMW500 base station simulator was manually configured to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the VoWIFI over IMS connection.

² FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	்டுட	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 20 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 20 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M

DUT Configuration for VoWIFI over IMS T-coil Testing II.

1. Radio Configuration

An investigation was performed on all applicable data rates and modulations to determine the radio configuration to be used for testing. See tables below for SNNR comparison between radio configurations in each 802.11 standard:

> Table 6-1 802.11b SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11b	6	DSSS	1	-2.92	-28.29	25.37
802.11b	6	DSSS	2	-3.01	-28.37	25.36
802.11b	6	CCK	5.5	-3.09	-29.53	26.44
802.11b	6	CCK	11	-3.03	-27.65	24.62

Table 6-2 802.11a SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR
			[Mbps]	[ub(A/III)]	[ub(A/III)]	[dB]
802.11g	6	BPSK	6	-3.04	-31.33	28.29
802.11g	6	BPSK	9	-3.03	-30.49	27.46
802.11g	6	QPSK	12	-3.19	-31.27	28.08
802.11g	6	QPSK	18	-2.99	-30.61	27.62
802.11g	6	16-QAM	24	-3.10	-32.20	29.10
802.11g	6	16-QAM	36	-2.95	-34.02	31.07
802.11g	6	64-QAM	48	-2.98	-34.08	31.10
802.11g	6	64-QAM	54	-3.04	-33.61	30.57

Table 6-3 802.11n SNNR by Radio Configuration

Mode	Channel	Modulation	Data Rate [Mbps]	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
802.11n	6	BPSK	6.5	-2.85	-26.76	23.91
802.11n	6	QPSK	13	-3.07	-27.17	24.10
802.11n	6	QPSK	19.5	-2.75	-27.62	24.87
802.11n	6	16-QAM	26	-2.98	-27.29	24.31
802.11n	6	16-QAM	39	-2.91	-27.62	24.71
802.11n	6	64-QAM	52	-3.30	-29.58	26.28
802.11n	6	64-QAM	58.5	-2.99	-28.19	25.20
802.11n	6	64-QAM	65	-2.96	-27.33	24.37

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 21 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 210175


2. Codec Configuration

An investigation was performed to determine the audio codec configuration to be used for testing. The NB AMR 4.75kbps setting was used for the audio codec on the CMW500 for VoWIFI over IMS T-coil testing. See below table for comparisons between different codecs and codec data rates:

Table 6-4
AMR Codec Investigation – VoWIFI over IMS

Codec Setting:	WB AMR 23.85kbps	WB AMR 6.60kbps	NB AMR 12.2kbps	NB AMR 4.75kbps	Orientation	Band	Standard	Channel	
ABM1 (dBA/m)	5.79	6.31	-2.33	-2.66					
ABM2 (dBA/m)	-28.47	-28.45	-28.06	-27.60	Axial	2.4GHz	IEEE 802.11b 6		
Frequency Response	Pass	Pass	Pass	Pass	Axiai	2.401/2 1222 002.118		O	
S+N/N (dB)	34.26	34.76	25.73	24.94					

Mute on; Backlight off; Max Volume; Max Contrast



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFL414DL	PETEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 22 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 22 01 75

7. OTT VOIP TEST SYSTEM AND DUT CONFIGURATION

I. Test System Setup for OTT VolP T-Coil Testing

1. OTT VoIP Application

Google Duo is a pre-installed application on the DUT which allows for VoIP calls in a held-to-ear scenario. Duo uses the OPUS audio codec and supports a bitrate range of 6kb/s to 64kb/s. All air interfaces capable of a data connection were evaluated with Google Duo.

2. Equipment Setup

A CMW500 callbox was used to perform OTT VoIP T-coil measurements. The Data Application Unit (DAU) of the CMW500 was connected to the internet and allowed for an IP data connection on the DUT. An auxiliary VoIP unit was used to initiate an OTT VoIP call to the DUT. The auxiliary VoIP unit allowed for the configuration and monitoring of the OTT VoIP codec bitrate during a call. Both high and low bitrate settings were evaluated in to determine the worst-case configuration.

Audio Level Settings

According to KDB 285076 D02, the average speech level of -20dBm0 shall be used for protocols not specifically listed in Table 7.1 of ANSI C63.19-2011 or the ANSI C63.19-2011 VoLTE interpretation3. The auxiliary VoIP unit allowed for monitoring the signal input level to ensure that the settings for speech input and full scale levels resulted in the -20dBm0 speech input level to the DUT for the OTT VoIP call.

II. **DUT Configuration for OTT VolP T-Coil Testing**

1. Codec Configuration

An investigation was performed for each applicable data mode to determine the audio codec configuration to be used for testing. The 64kbps codec setting was used for the audio codec on the auxiliary VoIP unit for OTT VoIP T-Coil testing. See below tables for comparisons between codec data rates on all applicable data modes:

> Table 7-1 Codec Investigation - OTT VolP (EvDO)

Codec investigation – OTT von (EVDO)							
Codec Setting:	64kbps	6kbps	Orientation	Channel			
ABM1 (dBA/m)	18.99	19.15					
ABM2 (dBA/m)	-33.32	-33.64	Avial	600			
Frequency Response	Pass	Pass	Axial				
S+N/N (dB)	52.31	52.79					

³ FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 23 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 23 01 75

Table 7-2
Codec Investigation – OTT VoIP (EDGE)

Couco invocagation CTT von (EDGE)							
Codec Setting:	64kbps	6kbps	Orientation	Channel			
ABM1 (dBA/m)	17.84	17.92					
ABM2 (dBA/m)	-17.53	-17.90	Axial	661			
Frequency Response	Pass	Pass	Axiai	001			
S+N/N (dB)	35.37	35.82					

Table 7-3
Codec Investigation – OTT VoIP (HSPA)

Codec investigation – OTT voil (Nor A)								
Codec Setting:	64kbps	6kbps	Orientation	Channel				
ABM1 (dBA/m)	17.86	17.99						
ABM2 (dBA/m)	-33.79	-34.03	Axial	9400				
Frequency Response	Pass	Pass	Avidi	5400				
S+N/N (dB)	51.65	52.02						

Table 7-4
Codec Investigation – OTT VoIP (LTE)

			• • • • • • • • • • • • • • • • • • • 	<u> </u>	
Codec Setting:	64kbps	6kbps	Orientation	Band / BW	Channel
ABM1 (dBA/m)	18.08	18.03		Band 2 20MHz	18900
ABM2 (dBA/m)	-28.25	-28.38	Axial		
Frequency Response	Pass	Pass	Axiai		
S+N/N (dB)	46.33	46.41			

Table 7-5
Codec Investigation – OTT VoIP (WIFI)

Codec investigation – OTT voiP (WIFT)									
Codec Setting:	64kbps	6kbps	Orientation	Band	Standard	Channel			
ABM1 (dBA/m)	19.26	19.36							
ABM2 (dBA/m)	-24.15	-24.67	Avial	2.4GHz	IEEE 802.11b	6			
Frequency Response	Pass	Pass	Axial			0			
S+N/N (dB)	43.41	44.03							

- Mute on; Backlight off; Max Volume; Max Contrast
- Radio Configurations can be found in Section 9.II.G




Figure 7-1
Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 24 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 24 01 75

2. Radio Configuration for OTT VoIP (LTE)

An investigation was performed to determine the worst-case LTE band to be used for OTT VoIP testing. LTE Band 66 was used for the testing as the worst-case configuration for the handset. See below table for SNNR comparison between different LTE bands:

Table 7-6
OTT VoIP (LTE) SNNR by LTE Band

Band	Frequency [MHz]	Channel	Bandwidth [MHz]	Modulation	RB Size	RB Offset	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	SNNR [dB]
2	1880.0	1890	20	16QAM	1	0	18.04	-28.49	46.53
5	836.5	20525	10	16QAM	1	0	18.22	-28.84	47.06
12	707.5	23095	10	16QAM	1	0	18.14	-30.36	48.50
13	782.0	23230	10	16QAM	1	0	17.70	-27.49	45.19
66	1745.0	132322	20	16QAM	1	0	17.98	-27.02	45.00
71	680.5	133297	20	16QAM	1	0	18.41	-26.96	45.37

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 25 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Faye 23 01 73

8. FCC 3G MEASUREMENTS

I. CDMA Test Configurations

Radio Configuration 1, Service Option 3 (thick, green data curve) was used for the testing as the worst-case configuration for the handset due to vocoder gating from the EVRC logic. See below plot for ABM noise comparison between operational field service options and radio configurations for a CDMA2000 handset:





Figure 8-1
CDMA Audio Band Magnetic Noise

Table 8-1 FCC 3G ABM Measurements for ZNFL414DL (CDMA)

Configuration:	RC1/SO3	RC3/SO3	RC4/SO3	Orientation	Channel
ABM1 (dBA/m)	2.57	2.91	2.66		600
ABM2 (dBA/m)	-27.09	-41.97	-41.14	Avial	
Frequency Response	Pass	Pass	Pass	– Axial	
S+N/N (dB)	29.66	44.88	43.80		

- Mute on; Backlight off; Max Volume; Max Contrast
- Power Control Bits = "All Up"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 26 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 20 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

II. UMTS Test Configurations

AMR at 12.2kbps, 13.6kbps SRB was used for the testing as the worst-case configuration for the handset. See below plot for ABM noise comparison between vocoder rates:





Figure 8-3
UMTS Audio Band Magnetic Noise

Table 8-2 Codec Investigation - UMTS

Oddec investigation - Oin 10							
Codec Setting:	AMR 12.2kbps	AMR 7.95kbps	AMR 4.75kbps	Orientation	Channel		
ABM1 (dBA/m)	1.80	2.56	3.50		9262		
ABM2 (dBA/m)	-39.59	-39.74	-39.96	Avial			
Frequency Response	Pass	Pass	Pass	- Axial			
S+N/N (dB)	41.39	42.30	43.46				

- Mute on; Backlight off; Max Volume; Max Contrast
- · TPC="All 1s"



Audio Band Magnetic Curve Measurement Block Diagram

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	① LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 27 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 27 0175

9. T-COIL TEST SUMMARY

Table 9-1 Consolidated Tabled Results

		F			abled Re		NIND.		
		•	esponse	•	netic / Verdict		SNNR dict	Margin from FCC Limit	C63.19-2011
C63 10	Section	8.3	3.2	8.3	3.1	8.3	3.4	(dB)	Rating
003.19	o Section	Axial	Radial	Axial	Radial	Axial	Radial		
	Secondary Cellular	PASS	NA	PASS	PASS	PASS	PASS		
CDMA	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-5.63	Т3
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
EvDO	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-22.59	T4
(OTT VoIP)	PCS	PASS	NA	PASS	PASS	PASS	PASS	-22.59	17
GSM	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-7.10	Т3
COM	PCS	PASS	NA	PASS	PASS	PASS	PASS	-7.10	13
EDGE	Cellular PCS Cellular AWS	PASS	NA	PASS	PASS	PASS	PASS	Q 75	Т3
(OTT VoIP)	PCS Cellular	PASS	NA	PASS	PASS	PASS	PASS	-6.75	13
	Cellular	PASS	NA	PASS	PASS	PASS	PASS	-8.75	
UMTS	AWS	PASS	NA	PASS	PASS	PASS	PASS	-10.33	T4
	PCS	PASS	NA	PASS	PASS	PASS	PASS		
	Cellular	PASS	NA	PASS	PASS	PASS	PASS		
HSPA (OTT VoIP)	AWS	PASS	NA	PASS	PASS	PASS	PASS		T4
,	PCS	PASS	NA	PASS	PASS	PASS	PASS		
	B71	PASS	NA	PASS	PASS	PASS	PASS		
	B12	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD	B13	PASS	NA	PASS	PASS	PASS	PASS	-6.61	Т3
LIEFDD	B5	PASS	NA	PASS	PASS	PASS	PASS	-0.01	13
	B66	PASS	NA	PASS	PASS	PASS	PASS		
	B2	PASS	NA	PASS	PASS	PASS	PASS		
LTE FDD (OTT VoIP)	B66	PASS	NA	PASS	PASS	PASS	PASS	-19.07	Т4
	802.11b	PASS	NA	PASS	PASS	PASS	PASS		
WLAN	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-3.11	Т3
	802.11n	PASS	NA	PASS	PASS	PASS	PASS		
	802.11b	PASS	NA	PASS	PASS	PASS	PASS		
WLAN (OTT VoIP)	802.11g	PASS	NA	PASS	PASS	PASS	PASS	-17.46	T4
(57.7.5)	802.11n	PASS	NA	PASS	PASS	PASS	PASS		

	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 28 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 20 01 73

I. Raw Handset Data

Table 9-2
Raw Data Results for CDMA

				- 10	ata ixesa						
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1013	3.09	-26.31		1.95	29.40	20.00	-9.40	Т3	
	Axial	384	3.41	-27.43	-63.05	1.98	30.84	20.00	-10.84	T4	2.8, 3.6
Callular		777	3.11	-26.35		1.96	29.46	20.00	-9.46	Т3	
Cellular		1013	-3.40	-29.03			25.63	20.00	-5.63	Т3	
	Radial	384	-3.66	-30.47	-63.61	N/A	26.81	20.00	-6.81	Т3	2.6, 4.2
		777	-3.33	-30.64			27.31	20.00	-7.31	Т3	
		25	3.79	-26.25		1.96	30.04	20.00	-10.04	T4	
	Axial	600	2.59	-26.94	-63.05	1.97	29.53	20.00	-9.53	Т3	2.8, 3.6
PCS		1175	3.73	-25.38		1.93	29.11	20.00	-9.11	Т3	
FCS		25	-3.27	-29.82			26.55	20.00	-6.55	T3	
	Radial	600	-3.31	-30.50	-63.61	N/A	27.19	20.00	-7.19	Т3	2.6, 4.2
		1175	-3.40	-29.12			25.72	20.00	-5.72	Т3	

Table 9-3
Raw Data Results for GSM

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		128	19.73	-7.37		1.03	27.10	20.00	-7.10	Т3	
	Axial	190	19.85	-8.21	-63.05	0.99	28.06	20.00	-8.06	Т3	2.8, 3.6
GSM850		251	20.16	-8.91		0.99	29.07	20.00	-9.07	Т3	
GSIVIOSU		128	12.43	-14.98			27.41	20.00	-7.41	Т3	
	Radial	190	12.53	-16.10	-63.61	N/A	28.63	20.00	-8.63	Т3	2.6, 4.2
		251	12.92	-16.26			29.18	20.00	-9.18	Т3	
		512	19.70	-13.45		1.00	33.15	20.00	-13.15	T4	
	Axial	661	19.93	-14.22	-63.05	1.05	34.15	20.00	-14.15	T4	2.8, 3.6
GSM1900		810	19.98	-13.76		1.10	33.74	20.00	-13.74	T4	
G3W1900		512	12.25	-20.42			32.67	20.00	-12.67	T4	_
	Radial	661	12.27	-21.07	-63.61	N/A	33.34	20.00	-13.34	T4	2.6, 4.2
		810	13.26	-20.91			34.17	20.00	-14.17	T4	

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 29 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 29 01 75

Table 9-4 Raw Data Results for UMTS

				I (att D	ala Nesu	100 101 01					
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		4132	1.72	-38.18		2.00	39.90	20.00	-19.90	T4	
	Axial	4183	1.92	-37.45	-63.05	2.00	39.37	20.00	-19.37	T4	2.8, 3.6
UMTS V		4233	2.05	-38.06		2.00	40.11	20.00	-20.11	T4	
UNITSV		4132	-5.60	-36.66			31.06	20.00	-11.06	T4	
	Radial	4183	-5.12	-36.93	-63.61	N/A	31.81	20.00	-11.81	T4	2.6, 4.2
		4233	-5.66	-36.95			31.29	20.00	-11.29	T4	
		1312	1.92	-37.33		2.00	39.25	20.00	-19.25	T4	
	Axial	1412	1.98	-36.69	-63.05	2.00	38.67	20.00	-18.67	T4	2.8, 3.6
UMTS IV		1513	1.70	-36.38		2.00	38.08	20.00	-18.08	T4	
OWITS IV		1312	-5.54	-36.83			31.29	20.00	-11.29	T4	
	Radial	1412	-5.16	-37.23	-63.61	N/A	32.07	20.00	-12.07	T4	2.6, 4.2
		1513	-5.63	-36.87			31.24	20.00	-11.24	T4	
		9262	1.75	-39.26		2.00	41.01	20.00	-21.01	T4	
	Axial	9400	1.89	-38.34	-63.05	2.00	40.23	20.00	-20.23	T4	2.8, 3.6
UMTS II		9538	1.92	-39.40	•	2.00	41.32	20.00	-21.32	T4	
OWISI		9262	-5.54	-38.09			32.55	20.00	-12.55	T4	
	Radial	9400	-5.73	-36.68	-63.61	N/A	30.95	20.00	-10.95	T4	2.6, 4.2
		9538	-5.60	-35.93			30.33	20.00	-10.33	T4	

Table 9-5 Raw Data Results for LTE B71

					Data it	counto 10		•																
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates												
		20MHz	133297	3.36	-27.20		2.00	30.56	20.00	-10.56	T4													
		15MHz	133397	2.95	-28.94		2.00	31.89	20.00	-11.89	T4													
	Axial	15MHz	133297	3.20	-25.54	-63.05	2.00	28.74	20.00	-8.74	Т3	2.8, 3.6												
	Axiai	15MHz	133197	3.01	-25.23	-03.03	2.00	28.24	20.00	-8.24	T3	2.0, 3.0												
LTE Band		10MHz	133297	3.16	-25.61		2.00	28.77	20.00	-8.77	Т3	i												
71		5MHz	133297	3.08	-25.87		2.00	28.95	20.00	-8.95	Т3													
		20MHz	133297	-4.84	-31.98	-63.61		27.14	20.00	-7.14	T3													
	Radial	15MHz	133297	-4.77	-31.75		-63.61 N/A	63.61	62.61	62.61	62.61	62.61	62.61	62.61	62.61	62.61	-63.61	5 63.61 N/A	N/Λ	26.98	20.00	-6.98	T3	2.6, 4.2
	Naulai	10MHz	133297	-4.63	-32.66			28.03	20.00	-8.03	Т3	2.0, 4.2												
		5MHz	133297	-4.87	-32.80			27.93	20.00	-7.93	Т3													

Table 9-6 Raw Data Results for LTE B12

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		10MHz	23095	3.11	-30.13		2.00	33.24	20.00	-13.24	T4	
	Axial	5MHz	23095	3.06	-29.91	-63.05	2.00	32.97	20.00	-12.97	T4	2.8, 3.6
	Axiai	3MHz	23095	2.91	-28.95	-03.03	2.00	31.86	20.00	-11.86	T4	2.0, 3.0
LTE Band		1.4MHz	23095	2.71	-28.62		2.00	31.33	20.00	-11.33	T4	
12		10MHz	23095	-4.75	-34.77			30.02	20.00	-10.02	T4	
	Radial	5MHz	23095	-4.78	-33.46	-63.61	N/A	28.68	20.00	-8.68	Т3	2.6, 4.2
	Naulai	3MHz	23095	-4.70	-33.82	-63.61	IN/A	29.12	20.00	-9.12	Т3	2.0, 4.2
		1.4MHz	23095	-4.89	-33.39			28.50	20.00	-8.50	Т3	

Table 9-7 Raw Data Results for LTE B13

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
	Axial	10MHz	23230	2.78	-26.76	-63.05	2.00	29.54	20.00	-9.54	T3	2.8, 3.6
LTE Band	Axiai	5MHz	23230	2.95	-29.97	-03.03	2.00	32.92	20.00	-12.92	T4	2.0, 3.0
13	Radial	10MHz	23230	-4.64	-33.18	-63.61	N/A	28.54	20.00	-8.54	Т3	2.6, 4.2
	Radiai	5MHz	23230	-4.65	-33.73	-03.01	IN/A	29.08	20.00	-9.08	T3	2.0, 4.2

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 30 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 30 01 73

Table 9-8 Raw Data Results for LTE B5

								-				
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		10MHz	20525	3.16	-28.53		2.00	31.69	20.00	-11.69	T4	
	Axial	5MHz	20525	3.05	-29.87	-63.05	2.00	32.92	20.00	-12.92	T4	2.8, 3.6
	Axiai	3MHz	20525	3.05	-30.27	-03.03	2.00	33.32	20.00	-13.32	T4	2.0, 3.0
LTE Band 5	1.4MHz	20525	3.00	-29.88		2.00	32.88	20.00	-12.88	T4		
LIE Ballu 5		10MHz	20525	-4.78	-33.01			28.23	20.00	-8.23	T3	
	Radial	5MHz	20525	-4.75	-33.35	-63.61 N/A	N/A	28.60	20.00	-8.60	Т3	2.6, 4.2
Radial	3MHz	20525	-4.63	-33.76	-03.01	IN/A	29.13	20.00	-9.13	T3	2.0, 4.2	
		1.4MHz	20525	-4.86	-33.56			28.70	20.00	-8.70	Т3	

Table 9-9 Raw Data Results for LTE B66

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		20MHz	132322	3.08	-26.46		2.00	29.54	20.00	-9.54	Т3	
		15MHz	132322	3.09	-27.37		2.00	30.46	20.00	-10.46	T4	
	Axial	10MHz	132322	2.88	-28.45	-63.05	2.00	31.33	20.00	-11.33	T4	2.8, 3.6
	Axiai	5MHz	132322	3.23	-28.41	-03.03	2.00	31.64	20.00	-11.64	T4	2.0, 3.0
		3MHz	132322	2.80	-28.75		2.00	31.55	20.00	-11.55	T4	
		1.4MHz	132322	2.45	-29.25		2.00	31.70	20.00	-11.70	T4	
LTE Band		20MHz	132572	-4.72	-31.44			26.72	20.00	-6.72	T3	
66		20MHz	132322	-4.61	-31.42	1		26.81	20.00	-6.81	Т3	
		20MHz	132072	-5.03	-31.64			26.61	20.00	-6.61	T3	
	Dediel	15MHz	132322	-5.04	-31.93	60.64	NIZA	26.89	20.00	-6.89	T3	00.40
	Radial	10MHz	132322	-4.97	-33.61	-63.61	N/A	28.64	20.00	-8.64	T3	2.6, 4.2
		5MHz	132322	-4.91	-33.16			28.25	20.00	-8.25	T3	
		3MHz	132322	-4.68	-33.33			28.65	20.00	-8.65	T3	
		1.4MHz	132322	-4.72	-33.44			28.72	20.00	-8.72	T3	

Table 9-10 Raw Data Results for LTE B2

	Naw Data Nesults for LTL B2												
Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates	
		20MHz	18900	3.12	-27.79		2.00	30.91	20.00	-10.91	T4		
		15MHz	18900	3.07	-28.23		2.00	31.30	20.00	-11.30	T4	1	
Axial	10MHz	18900	3.39	-28.81	-63.05	2.00	32.20	20.00	-12.20	T4	2026		
	Axiai	5MHz	18900	3.02	-28.55	-63.05	2.00	31.57	20.00	-11.57	T4	2.8, 3.6	
		3MHz	18900	3.21	-29.26		2.00	32.47	20.00	-12.47	T4		
LTE Band 2		1.4MHz	18900	3.18	-29.10		2.00	32.28	20.00	-12.28	T4		
LIE Ballu 2		20MHz	18900	-4.74	-32.07			27.33	20.00	-7.33	T3		
		15MHz	18900	-4.90	-31.83			26.93	20.00	-6.93	Т3		
	Radial	10MHz	18900	-4.63	-32.92	-63.61	N/A	28.29	20.00	-8.29	Т3	26.42	
	Radiai	5MHz	18900	-4.83	-33.26	-03.01	IWA	28.43	20.00	-8.43	T3	2.6, 4.2	
		3MHz	18900	-4.82	-33.07		1		28.25	20.00	-8.25	T3	
		1.4MHz	18900	-4.92	-33.12			28.20	20.00	-8.20	T3		

FCC ID: ZNFL414DL	PETEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 31 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 31 0173

Table 9-11 Raw Data Results for 2.4GHz WIFI

	That Bata Hoodito for Zing Ha										
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	-2.91	-28.61		2.00	25.70	20.00	-5.70	Т3	
	Axial	6	-2.83	-27.24	-63.05	2.00	24.41	20.00	-4.41	Т3	2.8, 3.6
WLAN		11	-2.52	-29.28		2.00	26.76	20.00	-6.76	Т3	
802.11b		1	-9.20	-33.31			24.11	20.00	-4.11	Т3	
	Radial	6	-10.37	-33.53	-63.61	N/A	23.16	20.00	-3.16	Т3	2.6, 4.2
		11	-10.77	-33.88			23.11	20.00	-3.11	Т3	
WLAN	Axial	6	-2.64	-30.60	-63.05	2.00	27.96	20.00	-7.96	Т3	2.8, 3.6
802.11g	Radial	6	-9.60	-32.84	-63.61	N/A	23.24	20.00	-3.24	Т3	2.6, 4.2
WLAN	Axial	6	-2.84	-33.29	-63.05	2.00	30.45	20.00	-10.45	T4	2.8, 3.6
802.11n	Radial	6	-9.30	-33.08	-63.61	N/A	23.78	20.00	-3.78	Т3	2.6, 4.2

Table 9-12 Raw Data Results for EvDO (OTT VoIP)

Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
Cellular	Axial	384	19.11	-31.93	-63.05	2.00	51.04	20.00	-31.04	T4	2.8, 3.6
EvDO	Radial	384	11.10	-31.49	-63.61	N/A	42.59	20.00	-22.59	T4	2.6, 4.2
PCS	Axial	600	19.06	-32.93	-63.05	2.00	51.99	20.00	-31.99	T4	2.8, 3.6
EvDO	Radial	600	11.30	-32.74	-63.61	N/A	44.04	20.00	-24.04	T4	2.6, 4.2

Table 9-13 Raw Data Results for EDGE (OTT VoIP)

	1141										
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
EDGE850	Axial	190	17.70	-14.59	-63.05	2.00	32.29	20.00	-12.29	T4	2.8, 3.6
EDGE650	Radial	190	10.65	-18.10	-63.61	N/A	28.75	20.00	-8.75	Т3	2.6, 4.2
EDGE1900	Axial	661	17.88	-17.02	-63.05	2.00	34.90	20.00	-14.90	T4	2.8, 3.6
EDGE1900	Radial	661	11.36	-22.94	-63.61	N/A	34.30	20.00	-14.30	T4	2.6, 4.2

Table 9-14 Raw Data Results for HSPA (OTT VolP)

	Raw Data Results for HSPA (OTT VOIP)											
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates	
HSPA V	Axial	4183	17.99	-34.08	-63.05	2.00	52.07	20.00	-32.07	T4	2.8, 3.6	
HOPA V	Radial	4183	10.87	-33.60	-63.61	N/A	44.47	20.00	-24.47	T4	2.6, 4.2	
HSPA IV	Axial	1412	17.94	-34.01	-63.05	2.00	51.95	20.00	-31.95	T4	2.8, 3.6	
порату	Radial	1412	10.88	-33.69	-63.61	N/A	44.57	20.00	-24.57	T4	2.6, 4.2	
HSPA II	Axial	9400	17.99	-33.64	-63.05	2.00	51.63	20.00	-31.63	T4	2.8, 3.6	
поган	Radial	9400	10.86	-34.53	-63.61	N/A	45.39	20.00	-25.39	T4	2.6, 4.2	

FCC ID: ZNFL414DL	PETEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 32 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 32 01 73

Table 9-15
Raw Data Results for LTE B66 (OTT VolP)

Mode	Orientation	Bandwidth	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011	Test Coordinates
		20MHz	132572	17.48	-26.26		2.00	43.74	20.00	-23.74	T4	
		20MHz	132322	17.81	-26.99		2.00	44.80	20.00	-24.80	T4	
		20MHz	132072	17.37	-26.48		2.00	43.85	20.00	-23.85	T4	
	Axial	15MHz	132322	17.45	-28.02	-63.05	2.00	45.47	20.00	-25.47	T4	2.8, 3.6
	Axiai	10MHz	132322	17.31	-28.63	-03.03	2.00	45.94	20.00	-25.94	T4	2.0, 3.0
		5MHz	132322	17.25	-28.77		2.00	46.02	20.00	-26.02	T4	
		3MHz	132322	17.64	-29.13		2.00	46.77	20.00	-26.77	T4	
LTE Band		1.4MHz	132322	17.35	-29.37		2.00	46.72	20.00	-26.72	T4	
66		20MHz	132572	9.79	-30.03			39.82	20.00	-19.82	T4	
		20MHz	132322	9.75	-30.01			39.76	20.00	-19.76	T4	
		20MHz	132072	9.57	-29.50			39.07	20.00	-19.07	T4	
	D-di-l	15MHz	132322	10.03	-30.53	60.64	NIZA	40.56	20.00	-20.56	T4	00.40
	Radial	10MHz	132322	9.99	-31.53	-63.61	N/A	41.52	20.00	-21.52	T4	2.6, 4.2
		5MHz	132322	10.08	-31.83	-		41.91	20.00	-21.91	T4	
		3MHz	132322	9.74	-31.95		1	7	41.69	20.00	-21.69	T4
		1.4MHz	132322	9.88	-32.09			41.97	20.00	-21.97	T4	1

Table 9-16
Raw Data Results for 2.4GHz WIFI (OTT VoIP)

Naw Data Results for 2.4GHz Will 1 (OTT VOIF)											
Mode	Orientation	Channel	ABM1 [dB(A/m)]	ABM2 [dB(A/m)]	Ambient Noise [dB(A/m)]	Frequency Response Margin (dB)	S+N/N (dB)	FCC Limit (dB)	Margin from FCC Limit (dB)	C63.19-2011 Rating	Test Coordinates
		1	19.17	-23.83		2.00	43.00	20.00	-23.00	T4	
	Axial	6	19.04	-24.02	-63.05	2.00	43.06	20.00	-23.06	T4	2.8, 3.6
WLAN		11	19.57	-24.95		2.00	44.52	20.00	-24.52	T4	1
802.11b		1	11.16	-27.18			38.34	20.00	-18.34	T4	
	Radial	6	11.34	-26.12	-63.61	N/A	37.46	20.00	-17.46	T4	2.6, 4.2
		11	11.29	-27.88			39.17	20.00	-19.17	T4	
WLAN	Axial	6	19.54	-26.91	-63.05	2.00	46.45	20.00	-26.45	T4	2.8, 3.6
802.11g	Radial	6	11.30	-28.13	-63.61	N/A	39.43	20.00	-19.43	T4	2.6, 4.2
WLAN	Axial	6	19.30	-26.40	-63.05	2.00	45.70	20.00	-25.70	T4	2.8, 3.6
802.11n	Radial	6	11.28	-28.22	-63.61	N/A	39.50	20.00	-19.50	T4	2.6, 4.2

II. Test Notes

A. General

- 1. Phone Condition: Mute on; Backlight off; Max Volume; Max Contrast
- 2. 'Radial' orientation refers to radial transverse.
- Hearing Aid Mode (Phone→Call Settings→Additional Settings→Hearing aids) was set to ON for Frequency Response compliance
- 4. Speech Signal: ITU-T P.50 Artificial Voice
- 5. Bluetooth and WIFI were disabled for 2G/3G/4G modes while testing.
- 6. Licensed data modes and Bluetooth were disabled for WIFI modes while testing.
- 7. The Margin from FCC limit column indicates a margin from the FCC limit for compliance (T3).

B. CDMA

- 1. Power Configuration: Power Control Bits = "All Up"
- 2. Vocoder Configuration: RC1/SO3 (CDMA EVRC)

C. GSM

- 1. Power Configuration: GSM850: PCL=5, GSM1900: PCL=0;
- 2. Vocoder Configuration: EFR (GSM);

FCC ID: ZNFL414DL	FCC ID: ZNFL414DL		(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 33 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 33 01 73

D. UMTS

- 1. Power Configuration: TPC= "All 1s";
- 2. Vocoder Configuration: AMR 12.2 kbps (UMTS);

E. LTE FDD

- 1. Power Configuration: TPC = "Max Power"
- 2. Radio Configuration: 16QAM, 1RB, 0RB offset
- 3. Vocoder Configuration: NB AMR 4.75kbps
- 4. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 71 at 15MHz is the worst-case for the Axial probe orientation. LTE Band 66 at 20MHz bandwidth is the worst-case for the Radial probe orientation.

F. WIFI


- 1. Radio Configuration
 - a. 802.11b: CCK, 11Mbps
 - b. 802.11g: BPSK, 9Mbps
 - c. 802.11n: BPSK, 6.5Mbps
- 2. Vocoder Configuration: NB AMR 4.75kbps
- 3. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both Axial and Radial probe orientations.

G. OTT VoIP


- 1. Vocoder Configuration: 64kbps
- 2. EvDO Configuration
 - a. Revision: A
- 3. EDGE Configuration
 - a. MCS Index: 7
 - b. Number of TX slots: 2
- 4. HSPA Configuration:
 - a. Release: 6
 - b. 3GPP 34.121 Subtest 1
- 5. LTE FDD Configuration:
 - a. Power Configuration: TPC = "Max Power"
 - b. Radio Configuration: 16QAM, 1RB, 0RB offset
 - c. LTE Band 66 was the worst-case band from Table 7-6 and was used to test both Axial and Radial probe orientations.
 - d. The worst-case band and bandwidth combination for each probe orientation is additionally tested on the low and high channels for those combinations. LTE Band 66 at 20MHz is the worst-case for both Axial and Radial probe orientations.
- 6. WIFI Configuration:
 - a. Radio Configuration
 - i. 802.11b: CCK, 11Mbps
 - ii. 802.11g: BPSK, 9Mbps
 - iii. 802.11n: BPSK, 6.5Mbps
 - b. The worst-case standard for 2.4GHz WIFI in each probe orientation is additionally tested on the low and high channels. 802.11b is the worst-case for both Axial and Radial probe orientations.

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	€ LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 34 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 34 01 73


III. 1 kHz Vocoder Application Check



This model was verified to be within the linear region for ABM1 measurements at -18 dBm0 for CDMA. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -16 dBm0 for GSM, UMTS, and VoLTE over IMS. This measurement was taken in the axial configuration above the maximum location.



This model was verified to be within the linear region for ABM1 measurements at -20 dBm0 for VoWIFI over IMS and OTT VoIP. This measurement was taken in the axial configuration above the maximum location.

FCC ID: ZNFL414DL	PETEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 35 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 33 01 73

IV. T-Coil Validation Test Results

Table 9-17
Helmholtz Coil Validation Table of Results

ltem	Target	Result	Verdict			
Axial						
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.178	PASS			
Environmental Noise	< -58 dBA/m	-63.05	PASS			
Frequency Response, from limits	> 0 dB	0.80	PASS			
Radial						
Magnetic Intensity, -10 dBA/m	-10 ± 0.5 dB	-10.270	PASS			
Environmental Noise	< -58 dBA/m	-63.61	PASS			
Frequency Response, from limits	> 0 dB	0.80	PASS			

FCC ID: ZNFL414DL	PETEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager	
Filename:	Test Dates:	DUT Type:		Page 36 of 75	
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset			

V. ABM1 Magnetic Field Distribution Scan Overlays




Figure 9-1
T-Coil Scan Overlay Magnetic Field Distributions

Notes:

- 1. Final measurement locations are indicated by a cursor on the contour plots.
- 2. See Test Setup Photographs for actual WD overlay.

FCC ID: ZNFL414DL	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 37 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 37 0175

© 2018 PCTEST Engineering Laboratory, Inc.

REV 3.2.M 04/17/2018

10. MEASUREMENT UNCERTAINTY

Table 10-1
Uncertainty Estimation Table

Contribution	Data +/- %	Data +/- dB	Data Type	Probability distribution	Divisor	Standard uncertainty	Standard Uncertainty (dB)
ABM Noise	7.0%	0.29	Std. Dev.	Normal k=1	1.00	7.0%	
RF Reflections	4.7%	0.20	Specification	Rectangular	1.73	2.7%	
Reference Signal Level	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Positioning Accuracy	10.0%	0.41	Uncertainty	Rectangular	1.73	5.8%	
Probe Coil Sensitivity	12.2%	0.50	Specification	Rectangular	1.73	7.0%	
Probe Linearity	2.4%	0.10	Std. Dev.	Normal k=1	1.00	2.4%	
Cable Loss	2.8%	0.12	Specification	Rectangular	1.73	1.6%	
Frequency Analyzer	5.0%	0.21	Specification	Rectangular	1.73	2.9%	
System Repeatability	5.0%	0.21	Std. Dev.	Normal k=1	1.00	5.0%	
WD Repeatability	9.0%	0.37	Std. Dev.	Normal k=1	1.00	9.0%	
Positioner Accuracy	1.0%	0.04	Specification	Rectangular	1.73	0.6%	
Combined standard uncertainty, uc (k=1)						17.7%	0.71
Expanded uncertainty (k=2), 95% confidence level					35.3%	1.31	

Notes:

- 1. Test equipments are calibrated according to techniques outlined in NIS81, NIS3003 and NIST Tech Note 1297.
- All equipments have traceability according to NIST. Measurement Uncertainties are defined in further detail in NIS 81 and NIST Tech Note 1297 and UKAS M3003.

Measurement uncertainty reflects the quality and accuracy of a measured result as compared to the true value. Such statements are generally required when stating results of measurements so that it is clear to the intended audience that the results may differ when reproduced by different facilities. Measurement results vary due to the measurement uncertainty of the instrumentation, measurement technique, and test engineer. Most uncertainties are calculated using the tolerances of the instrumentation used in the measurement, the measurement setup variability, and the technique used in performing the test. While not generally included, the variability of the equipment under test also figures into the overall measurement uncertainty. Another component of the overall uncertainty is based on the variability of repeated measurements (so-called Type A uncertainty). This may mean that the Hearing Aid compatibility tests may have to be repeated by taking down the test setup and resetting it up so that there are a statistically significant number of repeat measurements to identify the measurement uncertainty. By combining the repeat measurement results with that of the instrumentation chain using the technique contained in NIS 81 and NIS 3003, the overall measurement uncertainty was estimated.

FCC ID: ZNFL414DL	PETEST	HAC (1-CUIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 38 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 30 01 73

11. EQUIPMENT LIST

Table 11-1 Equipment List

Equipment List						
Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number	
Latitude E6540	SoundCheck Acoustic Analyzer Laptop	4/11/2017	Biennial	4/11/2019	7BFNM32	
SoundConnect	Microphone Power Supply	N/A		N/A	0899-PS150	
SoundConnect	Microphone Power Supply	12/2/2016	Biennial	12/2/2018	PS2612	
Fireface UC	Soundcheck Acoustic Analyzer External Audio Interface	4/11/2017	Biennial	4/11/2019	23528889	
CMW500	Wideband Radio Communication Tester	1/19/2018	Annual	1/19/2019	162125	
CMW500	Radio Communication Tester	7/14/2017	Annual	7/14/2018	140144	
CMW500	Radio Communication Tester	4/20/2018	Annual	4/20/2019	128635	
NC-100	Torque Wrench (8" lb)	9/1/2016	Biennial	9/1/2018	21053	
C63.19	Helmholtz Coil	12/7/2016	Biennial	12/7/2018	925	
Radial T-Coil Probe	Radial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1130	
Axial T-Coil Probe	Axial T-Coil Probe	12/7/2016	Biennial	12/7/2018	TEM-1124	
	HAC System Controller with Software	N/A		N/A	N/A	
	HAC Positioner	N/A		N/A	N/A	

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 39 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 39 01 73

12. TEST DATA

FCC ID: ZNFL414DL	PCTEST	HAC (I-CUIL) IEST REPURT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 40 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 40 01 75



DUT: HH Coil - SN: 925

Type: HH Coil Serial: 925


Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

• Helmholtz Coil - SN: 925; Calibrated: 12/07/2016

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.178 dB	\checkmark	Max/Min	-9.5/-10.5	
Verification ABM2	-63.05 dB	\checkmark	Maximum	-58.0	
Frequency Response Margin	800m dB	\checkmark	Tolerance curves	Aligned Data	

FCC ID: ZNFL414DL	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 41 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 410175



DUT: HH Coil - SN: 925


Type: HH Coil Serial: 925

Measurement Standard: ANSI C63.19-2011


Equipment:

- Probe: Radial T-Coil Probe SN: TEM-1130; Calibrated: 12/07/2016
- Helmholtz Coil SN: 925; Calibrated: 12/07/2016

Noise Spectrum



Frequency Response



Results

Verification 1kHz Intensity	-10.27 dB	Max/Min	-9.5/-10.5
Verification ABM2	-63.61 dB	Maximum	-58.0
Frequency Response Margin	800m dB	Tolerance curves	Aligned Data

FCC ID: ZNFL414DL	PETEST	HAC (I-COIL) IEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 42 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Faye 42 01 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: Cellular CDMA

Channel: 1013

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 43 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Faye 43 01 73



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: PCS CDMAChannel: 1175

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 44 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Faye 44 01 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM850Channel: 128

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 45 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Faye 43 01 73



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM1900Channel: 512

Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 46 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		rage 40 of 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS VChannel: 4183

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(†) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 47 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		rage 47 of 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IVChannel: 1513

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 48 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		rage 40 01 73



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IIChannel: 9400

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 49 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 49 01 73



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE FDD Band 71

Bandwidth: 15MHz Channel: 133197

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 50 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		rage 30 01 73



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

· Channel: 6

• Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 51 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 310173



Type: Portable Handset Serial: 00607


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Axial T-Coil Probe – SN: TEM-1124; Calibrated: 12/07/2016

Test Configuration:

- VolP Application: Google Duo
- Mode: EDGE850
- Channel: 190
- Speech Signal: ITU-T P.50 Artificial Voice



FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 52 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 32 01 73



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: Cellular CDMA
Channel: 1013

Noise Spectrum



Results

ABM1	-3.4	dB	\checkmark	Minimum	-18.0
ABM2	-29.03	dB	•	Maximum	0.0
SNNR	25.63	dB	\checkmark	Minimum	20.0

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 53 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 55 01 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

 Mode: PCS CDMA Channel: 1175

Noise Spectrum



Results

ABM1	-3.4	dB	\checkmark	Minimum	-18.0
ABM2	-29.12	dB	\checkmark	Maximum	0.0
SNNR	25.72	dB	\checkmark	Minimum	20.0

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 54 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 54 0175



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011


Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: GSM850Channel: 128





Results

ABM1	12.43 dB	•	Minimum	-18.0
ABM2	-14.98 dB	•	Maximum	0.0
SNNR	27.41 dB	✓	Minimum	20.0

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 55 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 55 01 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:


Noise Spectrum

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

 Mode: GSM1900 • Channel: 512

-10.0 --15.0 -20.0 -25.0 --30.0



Results

ABM1	12.25 dB	•	Minimum	-18.0
ABM2	-20.42 dB	•	Maximum	0.0
SNNR	32.67 dB	•	Minimum	20.0

FCC ID: ZNFL414DL	PCTEST*	HAC (I-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 56 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 30 01 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:

SNNR

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS VChannel: 4132



31.06 dB

Minimum

20.0

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 57 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 37 0173



Type: Portable Handset Serial: 00607


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IVChannel: 1513



ABM1	-5.63 dB	•	Minimum	-18.0
ABM2	-36.88 dB	•	Maximum	0.0
SNNR	31.24 dB	•	Minimum	20.0

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 58 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 30 01 75



Type: Portable Handset Serial: 00607


Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: UMTS IIChannel: 9538



Results

ABM1	-5.6 dB	•	Minimum	-18.0
ABM2	-35.93 dB	•	Maximum	0.0
SNNR	30.33 dB	₹	Minimum	20.0

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 59 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 39 01 73



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: LTE FDD Band 66Bandwidth: 20MHzChannel: 132072

Noise Spectrum



FCC ID: ZNFL414DL	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 60 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 00 01 75



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:


Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:

Mode: 2.4GHz WIFIStandard: IEEE 802.11b

Channel: 11





ABM1	-10.77 dB	Minimum	-18.0
ABM2	-33.88 dB	Maximum	0.0
SNNR	23.11 dB	Minimum	20.0

FCC ID: ZNFL414DL	HAC (T-COIL) TEST REPORT		(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 61 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 010175



Type: Portable Handset Serial: 00607

Measurement Standard: ANSI C63.19-2011

Equipment:

Probe: Radial T-Coil Probe – SN: TEM-1130; Calibrated: 12/07/2016

Test Configuration:


VolP Application: Google Duo

Mode: EDGE850Channel: 190

Noise Spectrum

ABM1

ABM2



SNNR 28.75 dB ✓ Minimum 20.0

10.65 dB

-18.1 dB

Minimum

Maximum


-18.0

0.0

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 62 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 02 01 75

13. CALIBRATION CERTIFICATES

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 63 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Page 63 01 75



FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(† LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 64 of 75
1M1805030001_08_R1 7NF	05/24/2018 - 05/31/2018	Portable Handset		Fage 04 01 73

© 2018 PCTEST Engineering Laboratory, Inc.

HCATEMC_TEM 1124_Dec-07-2016



ISO/IEC 17025: 2005

1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01


REPORT OF CALIBRATION

Model No.: Axial T Coil Probe TEM Consulting LP Axial T Coil Probe Serial No.: TEM 1124

Company: PCTEST Engineering Lab. I. D. No: 80578

Probe Sensitivity measured wit	h Helmholt	z Coll			
Helmholtz Coil;			Before & atte	er data same	: X
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environ	ment:	
the current in the coils, in amperes.;	0.09	A	Ambient Temperature:	20.2	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	31.4	% RH
Helmholtz Coil magnetic field;	5.98	A/m	Ambient Pressure:	99.1	кP«
			Calibration Date:	7-D••-16	
Probe Sensitivity at	1000	H₌.			
Was	-60.23	aBV/A/m	Report Number:	27068	-3
	0.974	m V/A/m	Control Number:	27068	
Proberesistance	904	Oh m .			
he above listed instrument meets or o	exceeds tl	ne tested manufact	turer's specifications.		
nis Celibration is traceable through NIST test number:	s:	683/284413-14			
he expanded uncertainty of calibration: 0.30dB at 95% c	onfidence leve	el with a coverage factor of l	k=2.		

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCATEMC Calibration Laboratories Inc. procedure :

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements or ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016 Measurements performed by: Felix Christopher Calibrated on WCCL system type 9700

Ray. 7.0 Jan. 24, 2014 Day. # 1038 HCATEMC

Page 1 of 2

FCC ID: ZNFL414DL	PETEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 65 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 03 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

HCATEMC_TEM 1124_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tol. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Axial T Coil Probe

Model No.: Axial T Coil Probe

Serial No.: TEM 1124

Company: PCTEST Engineering Lab.

Test	Function	Tolera	nce	Measured values		
				Before	Out	Remarks
1.0	Probe Sensitivity at	1000 Hz.	d BV/A/m	-60.23		
			aВ	2.22		
2.0	Probe Level Linearity	D (0 D)	6	6.03		
		R•f. (0 aB)	0	0.00		
			-6	-6.03		
			-12	-12.05		
			Hz			
3.0	Probe Frequency Response		100	-19.8		
			126	-18.0		
			158	-16.0		
			200	-13.9		
			251	-12.0		
			316	-9.9		
			398	-8.0		
			501	-6.0		
			631	-4.0		
			794	-2.0		
		Rer. (0 a B)	1000	0.0		
			1259	2.0		
			1585	4.0		
			1995	6.0		
			2512	7.9		
			3162	9.9		
			3981	11.9		
			5012	13.9		
			6310	15.9		
			7943	18.0		
			10000	20.2		

Instruments used for calibration	:		Date of Col.	Traceability No.	Dua Data
HP	34401A	S/N 36064102	1-Oct-2016	,287708	1-Oct-2017
HP	34401A	S/N 35102471	1-Oct-2016	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oct-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oat-2016	683/284413-14	1-Oat-2017

Cal. Date: 7-Dec-2016

Tested by: Felix Christopher


Calibrated on WCCL system type 9700

Rev. 7.0 Jan. 24, 2014 Dec. # 1038 HCATEMC

Page 2 of 2

FCC ID: ZNFL414DL	PETEST	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 66 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 00 01 75

© 2018 PCTEST Engineering Laboratory, Inc.



FCC ID: ZNFL414DL	PETEST:	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 67 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		raye or or 13



ISO/IEC 17025: 2005

1575 State Route 96, Victor NY 14564

Calibration Lab. Cert. # 1533.01


REPORT OF CALIBRATION

Model No.: Radial T Coil Probe **TEM Consulting LP Radial T Coil Probe** Serial No.: TEM-1130

Company: PCTEST Engineering Lab. I. D. No: 80579

Proba Sansitivity massured wit	h Helmholt	z Coll			
Helmholtz Coil;			Before & afte	r data same	: X
the number of turns on each coil;	10	No.			
the radius of each coil, in meters;	0.204	m	Laboratory Environ	ment:	
the current in the coils, in amperes.;	0.09	Α	Ambient Temperature:	20.2	°C
Helmholtz Coil Constant;	7.09	A/m/V	Ambient Humidity:	31.4	% RH
Helmholtz Coil magnetic field;	5.98	A/m	Ambiens Pressure:	99.1	ĸP∗
			Calibration Date:	7-D•e-16	
Probe Sensitivity at	1000	Hz.			
Was	-60.27	a BV/A/m	Report Number:	27068	-2
	0.969	m V/A/m	Control Number:	27068	
Proberesistance	902	Oh m •			
The above listed instrument meets or o	exceeds tl	ne tested manufact	urer's specifications.		
nis Calibration is traceable through NIST test number:	s:	683/284413-14	_		
he expanded uncertainty of calibration: 0.30dB at 95% c	onfidence levi	el with a coverage factor of k	=2.		

Graph represents Probes Frequency Response.



The above listed instrument was checked using calibration procedure documented in West Caldwell Calibration Laboratories Inc. procedure : Rev. 7.0 Jan. 24, 2014 Doc. # 1038 HCRTEMC

Calibration was performed by West Caldwell Calibration Laboratories Inc. under Operating Procedures intended to implement the requirements or ISO10012-1, IEC Guide 25, ANSI/NCSL Z540-1, (MIL-STD-45662A) and ISO 9001:2008, ISO 17025

Cal. Date: 7-Dec-2016 Measurements performed by: Felix Christopher Calibrated on WCCL system type 9700 Ray. 7.0 Jan. 24, 2014 Day. # 1038 HCRTEMC

Page 1 of 2

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 68 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 00 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

HCRTEMC_TEM-1130_Dec-07-2016

West Caldwell Calibration Laboratories Inc.

1575 State Route 96, Victor NY 14564 Tol. (585) 586-3900 FAX (585) 586-4327

Calibration Data Record

TEM Consulting LP Radial T Coil Probe

Model No.: Radial T Coil Probe

Serial No.: TEM-1130

Company: PCTEST Engineering Lab.

est	Function	Tolera	nce	Measured values		
				Before	Out	Remarks
0	Probe Sensitivity at	1000 Hz.	d BV/A/m	-60.27		
			вΒ			
0	Proba Lavel Linearity		6	6.03		
		R•r. (0 a B)	0	0.00		
			-6	-6.03		
			-12	-12.06		
			Hz			
0	Probe Frequency Response		100	-19.9		
			126	-18.0		
			158	-16.0		
			200	-13.9		
			251	-12.0		
			316	-10.0		
			398	-8.0		
			501	-6.0		
			631	-4.0		
			794	-2.0		
		Rer. (0 aB)	1000	0.0		
			1259	2.0		
			1585	4.0		
			1995	6.0		
			2512	7.9		
			3162	9.9		
			3981	11.9		
			5012	13.9		
			6310	15.9		
			7943	18.0		
			10000	20.2		
			6310 7943	15.9 18.0		

Instruments used for celibration:			Date of Cal.	Traceability No.	Dua Data
HP	34401A	S/N 36064102	1-Oct-2016	,287708	1-Oct-2017
HP	34401A	S/N 35102471	1-Oct-2016	,287708	1-Oct-2017
HP	33120A	S/N 36043716	1-Oct-2016	.287708	1-Oct-2017
B&K	2133	S/N 1583254	1-Oct-2016	683/284413-14	1-Oot-2017
B&K	2133	S/N 1583254	1-Oat-2016	683/284413-14	1-Oet-20

Cal. Date: 7-Dec-2016 Tested by: Felix Christopher

Calibrated on WCCL system type 9700

Rev. 7.0 Jan. 24, 2014 Dae. # 1038 HCRTEMC

Page 2 of 2

FCC ID: ZNFL414DL	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 69 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 09 01 75

© 2018 PCTEST Engineering Laboratory, Inc.

14. CONCLUSION

The measurements indicate that the wireless communications device complies with the HAC limits specified in accordance with the ANSI C63.19 Standard and FCC WT Docket No. 01-309 RM-8658. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters specific to the test. The test results and statements relate only to the item(s) tested.

The measurement system and techniques presented in this evaluation are proposed in the ANSI standard as a means of best approximating wireless device compatibility with a hearing-aid. The literature is under continual re-construction.

FCC ID: ZNFL414DL	PCTEST*	HAC (T-COIL) TEST REPORT	(LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 70 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		raye 10 01 13

15. REFERENCES

- ANSI C63.19-2011, American National Standard for Methods of Measurement of Compatibility between Wireless communication devices and Hearing Aids.", New York, NY, IEEE, May 2011
- FCC Office of Engineering and Technology KDB, "285076 D01 HAC Guidance v05," September 13, 2017
- FCC Office of Engineering and Technology KDB, "285076 D02 T-Coil Testing for CMRS IP v03," September 13, 2017 3.
- FCC Public Notice DA 06-1215, Wireless Telecommunications Bureau and Office of Engineering and Technology Clarify Use of Revised Wireless Phone Hearing Aid Compatibility Standard, June 6, 2006
- 5 FCC 3G Review Guidance, Laboratory Division OET FCC, May/June 2006
- Berger, H. S., "Compatibility Between Hearing Aids and Wireless Devices," Electronic Industries Forum, Boston, MA, May, 6.
- Berger, H. S., "Hearing Aid and Cellular Phone Compatibility: Working Toward Solutions," Wireless Telephones and Hearing Aids: New Challenges for Audiology, Gallaudet University, Washington, D.C., May, 1997 (To be reprinted in the American Journal of Audiology).
- Berger, H. S., "Hearing Aid Compatibility with Wireless Communications Devices, "IEEE International Symposium on Electromagnetic Compatibility, Austin, TX, August, 1997.
- Bronaugh, E. L., "Simplifying EMI Immunity (Susceptibility) Tests in TEM Cells," in the 1990 IEEE International Symposium on Electromagnetic Compatibility Symposium Record, Washington, D.C., August 1990, pp. 488-491
- 10. Byme, D. and Dillon, H., The National Acoustics Laboratory (NAL) New Procedure for Selecting the Gain and Frequency Response of a Hearing Aid, Ear and Hearing 7:257-265, 1986.
- 11. Crawford, M. L., "Measurement of Electromagnetic Radiation from Electronic Equipment using TEM Transmission Cells, " U.S. Department of Commerce, National Bureau of Standards, NBSIR 73-306, Feb. 1973.
- 12. Crawford, M. L., and Workman, J. L., "Using a TEM Cell for EMC Measurements of Electronic Equipment," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1013, July 1981,
- EHIMA GSM Project, Development phase, Project Report (1st part) Revision A. Technical-Audiological Laboratory and Telecom Denmark, October 1993.
- 14. EHIMA GSM Project, Development phase, Part II Project Report. Technical-Audiological Laboratory and Telecom Denmark, June 1994.
- 15. EHIMA GSM Project Final Report, Hearing Aids and GSM Mobile Telephones: Interference Problems, Methods of Measurement and Levels of Immunity. Technical-Audiological Laboratory and Telecom Denmark, 1995.
- 16. HAMPIS Report, Comparison of Mobile phone electromagnetic near field with an upscaled electromagnetic far field, using hearing aid as reference, 21 October 1999.
- 17. Hearing Aids/GSM, Report from OTWIDAM, Technical-Audiological Laboratory and Telecom Denmark, April 1993.
- 18. IEEE 100, The Authoritative Dictionary of IEEE Standards Terms, Seventh Edition.
- Joyner, K. H, et. al., Interference to Hearing Aids by the New Digital Mobile Telephone System, Global System for Mobile (GSM) Communication Standard, National Acoustic Laboratory, Australian Hearing Series, Sydney 1993.
- Joyner, K. H., et. al., Interference to Hearing Aids by the Digital Mobile Telephone System, Global System for Mobile Communications (GSM), NAL Report #131, National Acoustic Laboratory, Australian Hearing Series, Sydney, 1995.
- 21. Kecker, W. T., Crawford, M. L., and Wilson, W. A., "Contruction of a Transverse Electromagnetic Cell", U.S. Department of Commerce, National Bureau of Standards, Technical Note 1011, Nov. 1978.

FCC ID: ZNFL414DL	PCTEST*	HAC (1-COIL) TEST REPORT		Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 71 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage / 101/3

- 22. Konigstein, D., and Hansen, D., "A New Family of TEM Cells with enlarged bandwidth and Optimized working Volume," in the Proceedings of the 7th International Symposium on EMC, Zurich, Switzerland, March 1987; 50:9, pp. 127-132.
- 23. Kuk, F., and Hjorstgaard, N. K., "Factors affecting interference from digital cellular telephones," Hearing Journal, 1997; 50:9, pp 32-34.
- 24. Ma, M. A., and Kanda, M., "Electromagnetic Compatibility and Interference Metrology," U.S. Department of Commerce, National Bureau of Standards, Technical Note 1099, July 1986, pp. 17-43.
- 25. Ma, M. A., Sreenivashiah, I., and Chang, D. C., "A Method of Determining the Emission and Susceptibility Levels of Electrically Small Objects Using a TEM Cell," U.S. Department of Commerce, National Bureau of Standards, Technial Note 1040, July 1981.
- 26. McCandless, G. A., and Lyregaard, P. E., Prescription of Gain/Output (POGO) for Hearing Aids, Hearing Instruments 1:16-21, 1983
- 27. Skopec, M., "Hearing Aid Electromagnetic Interference from Digital Wireless Telephones, "IEEE Transactions on Rehabilitation Engineering, vol. 6, no. 2, pp. 235-239, June 1998.
- Technical Report, GSM 05.90, GSM EMC Considerations, European Telecommunications Standards Institute, January 1993.
- 29. Victorian, T. A., "Digital Cellular Telephone Interference and Hearing Aid Compatibility—an Update," Hearing Journal 1998; 51:10, pp. 53-60
- 30. Wong, G. S. K., and Embleton, T. F. W., eds., AIP Handbook of Condenser Microphones: Theory, Calibration and Measurements, AIP Press.

FCC ID: ZNFL414DL	PCTEST	HAC (T-COIL) TEST REPORT	(1) LG	Approved by: Quality Manager
Filename:	Test Dates:	DUT Type:		Page 72 of 75
1M1805030091-08-R1.ZNF	05/24/2018 - 05/31/2018	Portable Handset		Fage 72 0173