

Auden Aluminum Wireless Charging Pad



IC: 21530-101790 FCC ID: 2AGR4-101790 Instruction Manual

Overview




Specification

Qi Certified
Input: 5V/2.0A, 9V/2.0A
Output: 5W/7.5W/10W Charging fr
Transmission Distance: ≤5mm
Efficiency: ≥75%
Product size: Ф100*10.5mm

Operation

- 1. Plug the power adapter into the wall socket (adapter not included)
- 2. USB-A side connects to the power wall adapter, USB-C side connects to the wireless charger side, the LED light will illuminate blue which means the unit is ready to charge your device.
- 3. Place your device on to the wireless charger, the LED light will change from blue to green which denotes the device is being charged.



Note: Only the QC2.0/QC3.0 Standard power adapter can support this product's fast charging. Adapters are not included with the product.

indicator in the state of the s

Indicating status and protection function

- 1. LED blue light: Standby
- 2. LED green light: Charging
- 3. Blue light flashing: device is not correctly placed on the wireless charger, over temperature protection, or detects metal on the back of the device

Packing

- Auden Aluminum Wireless Charging Pad
- USB-A to USB-C Type Charging Cable
- User Manual

Front Cover page 02 page 03 page 04

FCC Statement

This device complies with part 15 of the FCC rules.

Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Changes or modifications not explicitly approved by the party responsible for compliance could void the user's authority to operate this equipment

Note: this equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This

equipment generates, uses and candidate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- · Reorient or relocate the receiving antenna.
- · Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. During the operation of device a distance of 15 cm surrounding the device and 20 cm above the top surface of the device must be respected.

ISED Statement

This device complies with Industry Canada's license-exempt RSSs. Operation is subject to the following two conditions:

- This device may not cause interference; and
- This device must accept any interference, including interference that may cause undesired operation of the device.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes:

- l'appareil ne doit pas produire de brouillage;
- l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

This equipment complies with Canada radiation exposure limits set forth for an uncontrolled environment.

During the operation of device a distance of 10 cm surrounding the device and 10 cm above the top surface of the device must be respected.

Cet équipement est conforme Canada limites d'exposition aux radiations dans un environnement non contrôlé.

au cours de l'opération de l'appareil sur une distance de 10 cm autour de l'appareil et de 10 cm

au - dessus de la surface supérieure de l'appareil doit être respecté.

page 05 page 06 page 07 page 08