






LTE Band 66 QPSK 1.4MHz CH-Low, 1 RB




LTE Band 66 QPSK 1.4MHz CH-High, 1 RB




LTE Band 66 QPSK 1.4MHz CH-Low, 100%RB




LTE Band 66 QPSK 1.4MHz CH-High, 100%RB



LTE Band 66 QPSK 3MHz CH-Low, 1 RB




LTE Band 66 QPSK 3MHz CH-High, 1 RB






LTE Band 66 QPSK 3MHz CH-Low, 100%RB




LTE Band 66 QPSK 3MHz CH-High, 100%RB




LTE Band 66 QPSK 5MHz CH-Low, 1 RB




LTE Band 66 QPSK 5MHz CH-High, 1 RB



LTE Band 66 QPSK 5MHz CH-Low, 100%RB




LTE Band 66 QPSK 5MHz CH-High, 100%RB







LTE Band 66 QPSK 10MHz CH-Low, 1 RB




LTE Band 66 QPSK 10MHz CH-High, 1 RB




LTE Band 66 QPSK 10MHz CH-Low, 100%RB




LTE Band 66 QPSK 10MHz CH-High, 100%RB




LTE Band 66 QPSK 15MHz CH-Low, 1 RB




LTE Band 66 QPSK 15MHz CH-High, 1 RB




LTE Band 66 QPSK 15MHz CH-Low, 100%RB




LTE Band 66 QPSK 15MHz CH-High, 100%RB




LTE Band 66 QPSK 20MHz CH-Low, 1 RB




LTE Band 66 QPSK 20MHz CH-High, 1 RB




LTE Band 66 QPSK 20MHz CH-Low, 100%RB




LTE Band 66 QPSK 20MHz CH-High, 100%RB




LTE Band 66 16QAM 1.4MHz CH-Low, 1 RB




LTE Band 66 16QAM 1.4MHz CH-High, 1 RB




LTE Band 66 16QAM 1.4MHz CH-Low, 100%RB




LTE Band 66 16QAM 1.4MHz CH-High, 100%RB



LTE Band 66 16QAM 3MHz CH-Low, 1 RB




LTE Band 66 16QAM 3MHz CH-High, 1 RB







LTE Band 66 16QAM 3MHz CH-Low, 100%RB




LTE Band 66 16QAM 3MHz CH-High, 100%RB




LTE Band 66 16QAM 5MHz CH-Low, 1 RB




LTE Band 66 16QAM 5MHz CH-High, 1 RB



LTE Band 66 16QAM 5MHz CH-Low, 100%RB




LTE Band 66 16QAM 5MHz CH-High, 100%RB







LTE Band 66 16QAM 10MHz CH-Low, 1 RB




LTE Band 66 16QAM 10MHz CH-High, 1 RB




LTE Band 66 16QAM 10MHz CH-Low, 100%RB




LTE Band 66 16QAM 10MHz CH-High, 100%RB



LTE Band 66 16QAM 15MHz CH-Low, 1 RB




LTE Band 66 16QAM 15MHz CH-High, 1 RB







LTE Band 66 16QAM 15MHz CH-Low, 100%RB




LTE Band 66 16QAM 15MHz CH-High, 100%RB




LTE Band 66 16QAM 20MHz CH-Low, 1 RB



LTE Band 66 16QAM 20MHz CH-High, 1 RB



LTE Band 66 16QAM 20MHz CH-Low, 100%RB




LTE Band 66 16QAM 20MHz CH-High, 100%RB







LTE Band 85 QPSK 5MHz CH-Low, 1 RB




LTE Band 85 QPSK 5MHz CH-High, 1 RB




LTE Band 85 QPSK 5MHz CH-Low, 100%RB




LTE Band 85 QPSK 5MHz CH-High, 100%RB



LTE Band 85 QPSK 10MHz CH-Low, 1 RB




LTE Band 85 QPSK 10MHz CH-High, 1 RB







LTE Band 85 QPSK 10MHz CH-Low, 100%RB




LTE Band 85 QPSK 10MHz CH-High, 100%RB




LTE Band 85 16QAM 5MHz CH-Low, 1 RB




LTE Band 85 16QAM 5MHz CH-High, 1 RB



LTE Band 85 16QAM 5MHz CH-Low, 100%RB




LTE Band 85 16QAM 5MHz CH-High, 100%RB







LTE Band 85 16QAM 10MHz CH-Low, 1 RB




LTE Band 85 16QAM 10MHz CH-High, 1 RB



LTE Band 85 16QAM 10MHz CH-Low, 100%RB



LTE Band 85 16QAM 10MHz CH-High, 100%RB



5.4 Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as PPk. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

Test Setup



Limits

Rule Part 27.50(d)(5) Equipment employed must be authorized in accordance with the provisions of 24.51. Power measurements for transmissions by stations authorized under this section may be made either in accordance with a Commission-approved average power technique or in compliance with paragraph (d)(6) of this section. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.



Test Results

Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)			Limit (dB)	Conclusion
				Peak(dBm)	Avg(dBm)	PAPR(dB)		
LTE Band 4	1.4MHz	QPSK	20175/1732.5	26.02	16.10	9.92	13	PASS
		16QAM	20175/1732.5	26.61	16.11	10.50	13	PASS
	3MHz	QPSK	20175/1732.5	26.00	16.06	9.94	13	PASS
		16QAM	20175/1732.5	26.59	16.06	10.53	13	PASS
	5MHz	QPSK	20175/1732.5	26.77	17.10	9.67	13	PASS
		16QAM	20175/1732.5	26.73	16.37	10.36	13	PASS
	10MHz	QPSK	20175/1732.5	26.63	16.77	9.86	13	PASS
		16QAM	20175/1732.5	27.25	17.31	9.94	13	PASS
	15MHz	QPSK	20175/1732.5	27.34	17.98	9.36	13	PASS
		16QAM	20175/1732.5	27.63	18.54	9.09	13	PASS
	20MHz	QPSK	20175/1732.5	27.29	17.56	9.73	13	PASS
		16QAM	20175/1732.5	27.62	18.64	8.98	13	PASS

Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)			Limit (dB)	Conclusion
				Peak(dBm)	Avg(dBm)	PAPR(dB)		
LTE Band 12	1.4MHz	QPSK	23095/707.5	25.66	14.18	11.48	13	PASS
		16QAM	23095/707.5	26.76	14.66	12.10	13	PASS
	3MHz	QPSK	23095/707.5	25.60	15.68	9.92	13	PASS
		16QAM	23095/707.5	26.38	15.75	10.63	13	PASS
	5MHz	QPSK	23095/707.5	26.60	16.93	9.67	13	PASS
		16QAM	23095/707.5	26.53	16.08	10.45	13	PASS
	10MHz	QPSK	23095/707.5	26.55	16.84	9.71	13	PASS
		16QAM	23095/707.5	27.17	16.67	10.50	13	PASS

Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)			Limit (dB)	Conclusion
				Peak(dBm)	Avg(dBm)	PAPR(dB)		
LTE Band 13	5MHz	QPSK	23230/782	26.39	16.90	9.49	13	PASS
		16QAM	23230/782	26.42	16.14	10.28	13	PASS
	10MHz	QPSK	23230/782	26.22	16.94	9.28	13	PASS
		16QAM	23230/782	26.72	16.86	9.86	13	PASS



Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)			Limit (dB)	Conclusion
				Peak(dBm)	Avg(dBm)	PAPR(dB)		
LTE Band 66	1.4MHz	QPSK	132322/1745	26.08	16.05	10.03	13	PASS
		16QAM	132322/1745	26.69	15.95	10.74	13	PASS
	3MHz	QPSK	132322/1745	26.06	15.97	10.09	13	PASS
		16QAM	132322/1745	26.69	15.97	10.72	13	PASS
	5MHz	QPSK	132322/1745	26.89	17.17	9.72	13	PASS
		16QAM	132322/1745	26.59	15.89	10.70	13	PASS
	10MHz	QPSK	132322/1745	26.78	17.17	9.61	13	PASS
		16QAM	132322/1745	27.42	16.98	10.44	13	PASS
	15MHz	QPSK	132322/1745	27.41	18.65	8.76	13	PASS
		16QAM	132322/1745	27.70	17.65	10.05	13	PASS
	20MHz	QPSK	132322/1745	27.42	17.94	9.48	13	PASS
		16QAM	132322/1745	27.75	18.43	9.32	13	PASS

Mode	Bandwidth	Modulation	Channel/ Frequency(MHz)	Peak-to-Average Power Ratio (PAPR)			Limit (dB)	Conclusion
				Peak(dBm)	Avg(dBm)	PAPR(dB)		
LTE Band 85	5MHz	QPSK	134092/707	26.34	16.55	9.79	13	PASS
		16QAM	134092/707	25.98	15.75	10.23	13	PASS
	10MHz	QPSK	134092/707	26.38	16.13	10.25	13	PASS
		16QAM	134092/707	26.69	16.83	9.86	13	PASS

5.5 Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -40°C to +85°C in 10°C step size.

(1) With all power removed, the temperature was decreased to -10°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -40°C to +85°C . Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.3 V and 4.3 V, with a nominal voltage of 3.8V.

.Test setup



Limits

The frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U=0.01\text{ppm}$.



Test Result

LTE Band 4						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	7.66	17.77	0.00407	0.00945	PASS
Extreme (85℃)		13.32	5.44	0.00709	0.00289	PASS
Extreme (80℃)		6.86	17.96	0.00365	0.00955	PASS
Extreme (70℃)		17.02	1.64	0.00906	0.00087	PASS
Extreme (60℃)		3.78	16.61	0.00201	0.00883	PASS
Extreme (50℃)		4.02	17.61	0.00214	0.00937	PASS
Extreme (40℃)		17.69	10.36	0.00941	0.00551	PASS
Extreme (30℃)		11.53	7.57	0.00613	0.00403	PASS
Extreme (20℃)		12.99	9.39	0.00691	0.00499	PASS
Extreme (10℃)		2.57	9.73	0.00137	0.00518	PASS
Extreme (0℃)		2.20	6.41	0.00117	0.00341	PASS
Extreme (-10℃)		5.77	13.11	0.00307	0.00697	PASS
Extreme (-20℃)		9.35	17.35	0.00498	0.00923	PASS
Extreme (-30℃)		9.81	6.34	0.00522	0.00337	PASS
Extreme (-40℃)		14.88	12.81	0.00791	0.00681	PASS
25℃	LV	4.47	14.75	0.00238	0.00785	PASS
	HV	5.59	1.29	0.00297	0.00068	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	10.11	1.41	0.00538	0.00075	PASS
Extreme (85℃)		2.05	17.79	0.00109	0.00946	PASS
Extreme (80℃)		15.14	10.74	0.00805	0.00571	PASS
Extreme (70℃)		11.61	15.69	0.00618	0.00835	PASS
Extreme (60℃)		15.82	14.29	0.00842	0.00760	PASS
Extreme (50℃)		2.01	17.80	0.00107	0.00947	PASS
Extreme (40℃)		10.10	15.85	0.00537	0.00843	PASS
Extreme (30℃)		8.58	17.86	0.00456	0.00950	PASS
Extreme (20℃)		3.61	9.46	0.00192	0.00503	PASS
Extreme (10℃)		2.08	14.15	0.00111	0.00753	PASS
Extreme (0℃)		13.99	16.77	0.00744	0.00892	PASS
Extreme (-10℃)		6.98	8.29	0.00371	0.00441	PASS
Extreme (-20℃)		14.10	15.36	0.00750	0.00817	PASS
Extreme (-30℃)		10.67	9.09	0.00567	0.00483	PASS



Extreme (-40℃)		7.30	16.72	0.00388	0.00889	PASS
25℃	LV	4.34	5.60	0.00231	0.00298	PASS
	HV	16.04	2.66	0.00853	0.00142	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	11.98	14.25	0.00637	0.00758	PASS
Extreme (85℃)		1.84	12.36	0.00098	0.00658	PASS
Extreme (80℃)		7.92	12.01	0.00421	0.00639	PASS
Extreme (70℃)		11.61	4.18	0.00618	0.00223	PASS
Extreme (60℃)		5.27	5.06	0.00280	0.00269	PASS
Extreme (50℃)		13.80	7.94	0.00734	0.00423	PASS
Extreme (40℃)		13.82	7.68	0.00735	0.00409	PASS
Extreme (30℃)		13.65	3.34	0.00726	0.00177	PASS
Extreme (20℃)		12.50	17.46	0.00665	0.00929	PASS
Extreme (10℃)		15.32	5.42	0.00815	0.00288	PASS
Extreme (0℃)		15.68	8.27	0.00834	0.00440	PASS
Extreme (-10℃)		16.15	9.05	0.00859	0.00481	PASS
Extreme (-20℃)		8.68	15.42	0.00462	0.00820	PASS
Extreme (-30℃)		6.54	8.50	0.00348	0.00452	PASS
Extreme (-40℃)		13.39	1.67	0.00712	0.00089	PASS
25℃	LV	14.25	12.41	0.00758	0.00660	PASS
	HV	5.93	5.91	0.00315	0.00314	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	11.62	9.58	0.00618	0.00510	PASS
Extreme (85℃)		7.64	15.96	0.00407	0.00849	PASS
Extreme (80℃)		9.03	2.28	0.00481	0.00121	PASS
Extreme (70℃)		8.76	16.43	0.00466	0.00874	PASS
Extreme (60℃)		2.38	16.58	0.00126	0.00882	PASS
Extreme (50℃)		8.34	7.08	0.00444	0.00377	PASS
Extreme (40℃)		15.08	11.63	0.00802	0.00618	PASS
Extreme (30℃)		11.15	17.65	0.00593	0.00939	PASS
Extreme (20℃)		12.30	8.17	0.00654	0.00435	PASS
Extreme (10℃)		1.59	12.17	0.00084	0.00648	PASS
Extreme (0℃)		6.01	3.19	0.00320	0.00170	PASS
Extreme (-10℃)		9.47	8.47	0.00503	0.00451	PASS
Extreme (-20℃)		7.14	2.95	0.00380	0.00157	PASS



Extreme (-30℃)		5.16	4.47	0.00274	0.00238	PASS
Extreme (-40℃)		5.50	5.64	0.00292	0.00300	PASS
25℃	LV	15.99	9.36	0.00851	0.00498	PASS
	HV	17.26	10.65	0.00918	0.00566	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	15MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	10.60	11.66	0.00564	0.00620	PASS
Extreme (85℃)		12.76	15.70	0.00679	0.00835	PASS
Extreme (80℃)		8.29	4.52	0.00441	0.00240	PASS
Extreme (70℃)		2.61	6.09	0.00139	0.00324	PASS
Extreme (60℃)		2.69	17.28	0.00143	0.00919	PASS
Extreme (50℃)		16.17	5.53	0.00860	0.00294	PASS
Extreme (40℃)		8.15	14.57	0.00434	0.00775	PASS
Extreme (30℃)		10.69	2.27	0.00569	0.00121	PASS
Extreme (20℃)		4.29	11.21	0.00228	0.00596	PASS
Extreme (10℃)		10.87	16.26	0.00578	0.00865	PASS
Extreme (0℃)		13.18	7.55	0.00701	0.00401	PASS
Extreme (-10℃)		5.23	7.05	0.00278	0.00375	PASS
Extreme (-20℃)		15.65	12.16	0.00833	0.00647	PASS
Extreme (-30℃)		5.78	14.40	0.00307	0.00766	PASS
Extreme (-40℃)		7.47	6.97	0.00397	0.00371	PASS
25℃	LV	14.46	5.56	0.00769	0.00296	PASS
	HV	13.99	2.75	0.00744	0.00146	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	20MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	1.49	7.61	0.00079	0.00405	PASS
Extreme (85℃)		15.62	5.32	0.00831	0.00283	PASS
Extreme (80℃)		15.30	15.02	0.00814	0.00799	PASS
Extreme (70℃)		7.02	12.24	0.00373	0.00651	PASS
Extreme (60℃)		7.17	8.61	0.00381	0.00458	PASS
Extreme (50℃)		15.48	17.73	0.00823	0.00943	PASS
Extreme (40℃)		10.69	9.45	0.00569	0.00503	PASS
Extreme (30℃)		13.13	6.75	0.00699	0.00359	PASS
Extreme (20℃)		8.53	5.49	0.00454	0.00292	PASS
Extreme (10℃)		15.96	14.88	0.00849	0.00791	PASS
Extreme (0℃)		8.67	4.32	0.00461	0.00230	PASS
Extreme (-10℃)		13.84	10.29	0.00736	0.00547	PASS



Extreme (-20℃)		15.40	4.85	0.00819	0.00258	PASS
Extreme (-30℃)		8.55	5.10	0.00455	0.00271	PASS
Extreme (-40℃)		1.16	12.53	0.00061	0.00667	PASS
25℃	LV	2.59	1.42	0.00138	0.00076	PASS
	HV	11.56	10.37	0.00615	0.00552	PASS

LTE Band 12						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	3.07	9.20	0.00163	0.00489	PASS
Extreme (85℃)		13.50	9.10	0.00718	0.00484	PASS
Extreme (80℃)		17.95	14.37	0.00955	0.00764	PASS
Extreme (70℃)		12.76	5.06	0.00679	0.00269	PASS
Extreme (60℃)		8.66	17.19	0.00461	0.00915	PASS
Extreme (50℃)		14.99	2.05	0.00797	0.00109	PASS
Extreme (40℃)		2.37	7.16	0.00126	0.00381	PASS
Extreme (30℃)		1.99	12.07	0.00106	0.00642	PASS
Extreme (20℃)		14.36	12.15	0.00764	0.00646	PASS
Extreme (10℃)		5.24	4.34	0.00278	0.00231	PASS
Extreme (0℃)		10.95	6.63	0.00582	0.00353	PASS
Extreme (-10℃)		16.53	16.49	0.00879	0.00877	PASS
Extreme (-20℃)		10.67	14.10	0.00568	0.00750	PASS
Extreme (-30℃)		10.28	16.66	0.00547	0.00886	PASS
Extreme (-40℃)		6.32	13.89	0.00336	0.00739	PASS
25℃	LV	14.83	3.33	0.00789	0.00177	PASS
	HV	17.62	12.30	0.00937	0.00654	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	15.73	1.10	0.00836	0.00058	PASS
Extreme (85℃)		11.51	7.90	0.00612	0.00420	PASS
Extreme (80℃)		9.91	14.83	0.00527	0.00789	PASS
Extreme (70℃)		10.24	9.45	0.00545	0.00503	PASS
Extreme (60℃)		2.20	11.61	0.00117	0.00617	PASS
Extreme (50℃)		15.54	7.08	0.00826	0.00377	PASS
Extreme (40℃)		3.22	1.32	0.00171	0.00070	PASS
Extreme (30℃)		10.24	15.17	0.00545	0.00807	PASS
Extreme (20℃)		10.05	12.34	0.00535	0.00656	PASS



Extreme (10℃)		1.15	7.58	0.00061	0.00403	PASS
Extreme (0℃)		17.04	6.14	0.00906	0.00327	PASS
Extreme (-10℃)		3.55	13.34	0.00189	0.00709	PASS
Extreme (-20℃)		5.04	1.08	0.00268	0.00057	PASS
Extreme (-30℃)		4.84	1.31	0.00257	0.00070	PASS
Extreme (-40℃)		7.81	14.35	0.00415	0.00763	PASS
25℃	LV	15.04	10.69	0.00800	0.00569	PASS
	HV	5.13	12.17	0.00273	0.00647	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	2.34	13.95	0.00124	0.00742	PASS
Extreme (85℃)		16.66	8.67	0.00886	0.00461	PASS
Extreme (80℃)		7.79	12.31	0.00415	0.00655	PASS
Extreme (70℃)		16.53	13.36	0.00879	0.00710	PASS
Extreme (60℃)		14.76	3.15	0.00785	0.00167	PASS
Extreme (50℃)		7.46	6.45	0.00397	0.00343	PASS
Extreme (40℃)		4.33	12.60	0.00230	0.00670	PASS
Extreme (30℃)		8.88	17.61	0.00472	0.00937	PASS
Extreme (20℃)		4.23	6.51	0.00225	0.00346	PASS
Extreme (10℃)		16.89	10.55	0.00899	0.00561	PASS
Extreme (0℃)		6.14	12.69	0.00327	0.00675	PASS
Extreme (-10℃)		12.75	1.72	0.00678	0.00091	PASS
Extreme (-20℃)		11.79	17.39	0.00627	0.00925	PASS
Extreme (-30℃)		11.07	4.71	0.00589	0.00251	PASS
Extreme (-40℃)		17.73	3.82	0.00943	0.00203	PASS
25℃	LV	5.02	10.51	0.00267	0.00559	PASS
	HV	3.48	1.26	0.00185	0.00067	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	11.38	9.02	0.00605	0.00480	PASS
Extreme (85℃)		14.67	2.24	0.00780	0.00119	PASS
Extreme (80℃)		15.25	2.18	0.00811	0.00116	PASS
Extreme (70℃)		3.56	12.47	0.00189	0.00663	PASS
Extreme (60℃)		7.45	13.14	0.00396	0.00699	PASS
Extreme (50℃)		8.04	1.71	0.00428	0.00091	PASS
Extreme (40℃)		13.75	12.89	0.00731	0.00686	PASS
Extreme (30℃)		17.71	11.62	0.00942	0.00618	PASS



Extreme (20℃)		7.02	3.99	0.00374	0.00212	PASS
Extreme (10℃)		4.62	16.77	0.00246	0.00892	PASS
Extreme (0℃)		17.33	4.98	0.00922	0.00265	PASS
Extreme (-10℃)		7.02	2.62	0.00373	0.00140	PASS
Extreme (-20℃)		17.60	6.56	0.00936	0.00349	PASS
Extreme (-30℃)		16.02	16.77	0.00852	0.00892	PASS
Extreme (-40℃)		12.99	10.80	0.00691	0.00575	PASS
25℃	LV	8.53	9.81	0.00454	0.00522	PASS
	HV	5.36	12.49	0.00285	0.00664	PASS

LTE Band 13						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	4.30	15.41	0.00228	0.00820	PASS
Extreme (85℃)		15.78	11.34	0.00839	0.00603	PASS
Extreme (80℃)		3.47	1.18	0.00185	0.00063	PASS
Extreme (70℃)		7.97	14.08	0.00424	0.00749	PASS
Extreme (60℃)		17.81	7.32	0.00948	0.00389	PASS
Extreme (50℃)		2.11	16.35	0.00112	0.00870	PASS
Extreme (40℃)		17.66	9.45	0.00939	0.00502	PASS
Extreme (30℃)		2.20	8.81	0.00117	0.00469	PASS
Extreme (20℃)		4.66	17.21	0.00248	0.00915	PASS
Extreme (10℃)		17.64	14.81	0.00938	0.00788	PASS
Extreme (0℃)		9.94	14.25	0.00529	0.00758	PASS
Extreme (-10℃)		3.59	2.76	0.00191	0.00147	PASS
Extreme (-20℃)		12.01	6.78	0.00639	0.00361	PASS
Extreme (-30℃)		4.83	16.05	0.00257	0.00854	PASS
Extreme (-40℃)		8.23	5.53	0.00438	0.00294	PASS
25℃	LV	17.79	2.56	0.00946	0.00136	PASS
	HV	10.15	2.70	0.00540	0.00144	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	4.31	8.98	0.00229	0.00478	PASS
Extreme (85℃)		16.09	1.29	0.00856	0.00069	PASS
Extreme (80℃)		17.88	16.38	0.00951	0.00871	PASS
Extreme (70℃)		3.31	7.88	0.00176	0.00419	PASS



Extreme (60℃)		16.81	17.29	0.00894	0.00919	PASS
Extreme (50℃)		15.09	1.40	0.00802	0.00074	PASS
Extreme (40℃)		9.18	6.20	0.00488	0.00330	PASS
Extreme (30℃)		13.71	15.93	0.00729	0.00847	PASS
Extreme (20℃)		2.44	10.83	0.00130	0.00576	PASS
Extreme (10℃)		10.78	12.41	0.00573	0.00660	PASS
Extreme (0℃)		5.24	1.34	0.00279	0.00071	PASS
Extreme (-10℃)		12.56	7.05	0.00668	0.00375	PASS
Extreme (-20℃)		5.13	17.46	0.00273	0.00929	PASS
Extreme (-30℃)		13.62	2.28	0.00725	0.00121	PASS
Extreme (-40℃)		9.82	13.14	0.00522	0.00699	PASS
25℃	LV	13.94	4.48	0.00741	0.00238	PASS
	HV	15.47	10.65	0.00823	0.00567	PASS

LTE Band 66						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	12.04	17.23	0.00640	0.00917	PASS
Extreme (85℃)		3.83	12.48	0.00204	0.00664	PASS
Extreme (80℃)		11.00	5.37	0.00585	0.00285	PASS
Extreme (70℃)		2.13	13.01	0.00113	0.00692	PASS
Extreme (60℃)		6.10	11.60	0.00325	0.00617	PASS
Extreme (50℃)		17.79	15.40	0.00946	0.00819	PASS
Extreme (40℃)		11.51	14.99	0.00612	0.00797	PASS
Extreme (30℃)		9.55	8.35	0.00508	0.00444	PASS
Extreme (20℃)		5.04	17.40	0.00268	0.00926	PASS
Extreme (10℃)		11.77	5.78	0.00626	0.00308	PASS
Extreme (0℃)		13.46	8.34	0.00716	0.00444	PASS
Extreme (-10℃)		1.36	2.02	0.00072	0.00107	PASS
Extreme (-20℃)		5.99	16.75	0.00318	0.00891	PASS
Extreme (-30℃)		7.01	10.96	0.00373	0.00583	PASS
Extreme (-40℃)		1.84	12.43	0.00098	0.00661	PASS
25℃	LV	7.33	1.96	0.00390	0.00104	PASS
	HV	11.74	14.29	0.00625	0.00760	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	6.90	8.50	0.00367	0.00452	PASS



Extreme (85℃)		13.80	17.30	0.00734	0.00920	PASS
Extreme (80℃)		13.25	5.85	0.00705	0.00311	PASS
Extreme (70℃)		1.43	4.49	0.00076	0.00239	PASS
Extreme (60℃)		14.97	9.98	0.00796	0.00531	PASS
Extreme (50℃)		6.12	9.21	0.00326	0.00490	PASS
Extreme (40℃)		16.48	6.96	0.00877	0.00370	PASS
Extreme (30℃)		13.46	15.68	0.00716	0.00834	PASS
Extreme (20℃)		7.92	4.85	0.00421	0.00258	PASS
Extreme (10℃)		3.08	17.77	0.00164	0.00945	PASS
Extreme (0℃)		11.56	15.82	0.00615	0.00841	PASS
Extreme (-10℃)		1.41	8.04	0.00075	0.00428	PASS
Extreme (-20℃)		3.99	1.94	0.00212	0.00103	PASS
Extreme (-30℃)		8.04	17.01	0.00428	0.00905	PASS
Extreme (-40℃)		5.73	7.08	0.00305	0.00377	PASS
25℃	LV	3.50	14.91	0.00186	0.00793	PASS
	HV	11.00	3.98	0.00585	0.00212	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	11.33	16.83	0.00603	0.00895	PASS
Extreme (85℃)		7.91	8.04	0.00421	0.00428	PASS
Extreme (80℃)		9.79	10.47	0.00521	0.00557	PASS
Extreme (70℃)		4.62	6.47	0.00246	0.00344	PASS
Extreme (60℃)		12.47	7.79	0.00663	0.00414	PASS
Extreme (50℃)		3.61	15.31	0.00192	0.00814	PASS
Extreme (40℃)		3.26	3.82	0.00174	0.00203	PASS
Extreme (30℃)		17.94	2.26	0.00954	0.00120	PASS
Extreme (20℃)		14.71	5.51	0.00782	0.00293	PASS
Extreme (10℃)		10.80	14.17	0.00575	0.00754	PASS
Extreme (0℃)		5.00	4.98	0.00266	0.00265	PASS
Extreme (-10℃)		11.73	16.18	0.00624	0.00861	PASS
Extreme (-20℃)		11.73	8.39	0.00624	0.00446	PASS
Extreme (-30℃)		2.72	12.14	0.00145	0.00646	PASS
Extreme (-40℃)		4.65	8.15	0.00247	0.00433	PASS
25℃	LV	12.12	15.54	0.00645	0.00827	PASS
	HV	4.47	8.16	0.00238	0.00434	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	



Normal (25℃)	Normal	16.65	8.72	0.00886	0.00464	PASS
Extreme (85℃)		8.95	2.04	0.00476	0.00109	PASS
Extreme (80℃)		5.54	16.14	0.00295	0.00859	PASS
Extreme (70℃)		6.52	12.51	0.00347	0.00666	PASS
Extreme (60℃)		11.96	16.99	0.00636	0.00904	PASS
Extreme (50℃)		13.56	10.15	0.00721	0.00540	PASS
Extreme (40℃)		5.65	12.37	0.00301	0.00658	PASS
Extreme (30℃)		2.16	13.34	0.00115	0.00709	PASS
Extreme (20℃)		15.40	14.26	0.00819	0.00758	PASS
Extreme (10℃)		9.79	9.07	0.00521	0.00482	PASS
Extreme (0℃)		5.19	14.29	0.00276	0.00760	PASS
Extreme (-10℃)		6.42	4.82	0.00341	0.00257	PASS
Extreme (-20℃)		9.24	6.29	0.00491	0.00334	PASS
Extreme (-30℃)		13.04	5.59	0.00694	0.00298	PASS
Extreme (-40℃)		16.64	3.71	0.00885	0.00197	PASS
25℃	LV	3.38	7.46	0.00180	0.00397	PASS
	HV	16.13	9.08	0.00858	0.00483	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	15MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	5.15	11.13	0.00274	0.00592	PASS
Extreme (85℃)		8.10	15.37	0.00431	0.00818	PASS
Extreme (80℃)		4.96	5.73	0.00264	0.00305	PASS
Extreme (70℃)		8.16	3.23	0.00434	0.00172	PASS
Extreme (60℃)		2.08	1.06	0.00111	0.00056	PASS
Extreme (50℃)		5.96	8.95	0.00317	0.00476	PASS
Extreme (40℃)		12.48	5.07	0.00664	0.00270	PASS
Extreme (30℃)		3.28	4.03	0.00175	0.00214	PASS
Extreme (20℃)		5.06	12.43	0.00269	0.00661	PASS
Extreme (10℃)		3.56	13.14	0.00189	0.00699	PASS
Extreme (0℃)		15.64	8.37	0.00832	0.00445	PASS
Extreme (-10℃)		7.24	15.45	0.00385	0.00822	PASS
Extreme (-20℃)		16.35	5.57	0.00870	0.00296	PASS
Extreme (-30℃)		8.34	4.64	0.00443	0.00247	PASS
Extreme (-40℃)		5.07	2.10	0.00270	0.00112	PASS
25℃	LV	6.52	8.16	0.00347	0.00434	PASS
	HV	6.92	1.95	0.00368	0.00104	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	20MHz					



Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	17.87	6.15	0.00951	0.00327	PASS
Extreme (85℃)		13.66	10.95	0.00726	0.00582	PASS
Extreme (80℃)		5.39	1.25	0.00287	0.00067	PASS
Extreme (70℃)		11.88	10.32	0.00632	0.00549	PASS
Extreme (60℃)		3.04	1.33	0.00162	0.00071	PASS
Extreme (50℃)		1.14	7.31	0.00061	0.00389	PASS
Extreme (40℃)		3.09	17.41	0.00164	0.00926	PASS
Extreme (30℃)		9.11	7.25	0.00484	0.00386	PASS
Extreme (20℃)		14.47	4.64	0.00770	0.00247	PASS
Extreme (10℃)		17.76	3.78	0.00945	0.00201	PASS
Extreme (0℃)		17.61	16.26	0.00937	0.00865	PASS
Extreme (-10℃)		10.58	6.21	0.00563	0.00330	PASS
Extreme (-20℃)		13.93	16.44	0.00741	0.00875	PASS
Extreme (-30℃)		3.96	4.21	0.00211	0.00224	PASS
Extreme (-40℃)		10.80	3.18	0.00574	0.00169	PASS
25℃	LV	1.69	16.63	0.00090	0.00885	PASS
	HV	15.20	11.19	0.00809	0.00595	PASS

LTE Band 85						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	15.61	5.92	0.00830	0.00315	PASS
Extreme (85℃)		14.69	13.42	0.00781	0.00714	PASS
Extreme (80℃)		9.68	3.61	0.00515	0.00192	PASS
Extreme (70℃)		11.27	1.15	0.00599	0.00061	PASS
Extreme (60℃)		4.76	12.84	0.00253	0.00683	PASS
Extreme (50℃)		3.73	15.98	0.00198	0.00850	PASS
Extreme (40℃)		4.43	12.00	0.00236	0.00638	PASS
Extreme (30℃)		11.26	5.19	0.00599	0.00276	PASS
Extreme (20℃)		3.36	12.57	0.00179	0.00669	PASS
Extreme (10℃)		16.61	16.99	0.00884	0.00904	PASS
Extreme (0℃)		5.02	13.56	0.00267	0.00721	PASS
Extreme (-10℃)		2.54	6.51	0.00135	0.00346	PASS
Extreme (-20℃)		11.83	16.34	0.00629	0.00869	PASS
Extreme (-30℃)		3.32	15.73	0.00177	0.00836	PASS
Extreme (-40℃)		15.91	13.03	0.00846	0.00693	PASS
25℃	LV	4.12	17.06	0.00219	0.00907	PASS
	HV	6.04	7.40	0.00321	0.00394	PASS
Condition		Freq.Error	Freq.Error	Frequency	Frequency	Verdict



		(Hz)	(Hz)	Stability (ppm)	Stability (ppm)	
BANDWIDTH	10MHz					
Temperature	Voltage	16QAM	QPSK	16QAM	QPSK	
Normal (25℃)	Normal	2.79	1.91	0.00149	0.00102	PASS
Extreme (85℃)		11.80	7.70	0.00628	0.00409	PASS
Extreme (80℃)		8.76	17.36	0.00466	0.00924	PASS
Extreme (70℃)		14.33	8.25	0.00762	0.00439	PASS
Extreme (60℃)		3.92	4.09	0.00209	0.00218	PASS
Extreme (50℃)		3.56	17.63	0.00190	0.00938	PASS
Extreme (40℃)		14.82	13.02	0.00788	0.00693	PASS
Extreme (30℃)		11.94	17.89	0.00635	0.00952	PASS
Extreme (20℃)		3.44	4.19	0.00183	0.00223	PASS
Extreme (10℃)		18.00	14.48	0.00957	0.00770	PASS
Extreme (0℃)		4.90	3.85	0.00261	0.00205	PASS
Extreme (-10℃)		12.04	6.86	0.00641	0.00365	PASS
Extreme (-20℃)		11.88	4.03	0.00632	0.00214	PASS
Extreme (-30℃)		13.57	13.05	0.00722	0.00694	PASS
Extreme (-40℃)		10.86	14.10	0.00578	0.00750	PASS
25℃	LV	11.34	14.78	0.00603	0.00786	PASS
	HV	3.03	17.97	0.00161	0.00956	PASS

5.6 Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier. The peak detector is used.


RBW is set to 100kHz, VBW is set to 300kHz for 30MHz~1GHz

RBW is set to 1MHz, VBW is set to 3MHz for above 1GHz, Sweep is set to ATUO.

Of those disturbances below (limit – 20 dB), the mark is not required for the EUT.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 27.53(h) specifies that “for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB..”

Rule Part 27.53 (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically



radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Part 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

Part 27.53(a)/(h)/(g) Limit		-13 dBm
Part 27.53(f) Limit	Limit out of the band 1559-1610 MHz	-13 dBm
	Limit in the band 1559-1610 MHz	-40 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-27GHz	1.407 dB




Test Result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.


The signal beyond the limit is carrier.

LTE Band 4 1.4MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 20:49:51

LTE Band 4 1.4MHz CH-Low 1GHz ~20GHz




Date: 11.JUN.2020 20:55:12

LTE Band 4 1.4MHz CH- Middle 30MHz~1GHz




Date: 11.JUN.2020 20:49:58

LTE Band 4 1.4MHz CH- Middle 1GHz ~20GHz




Date: 11.JUN.2020 20:55:41

LTE Band 4 1.4MHz CH- High 30MHz~1GHz



Date: 11.JUN.2020 20:50:06


LTE Band 4 1.4MHz CH- High 1GHz ~20GHz



Date: 11.JUN.2020 20:56:54




LTE Band 4 3MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 20:50:14

LTE Band 4 3MHz CH-Low 1GHz ~20GHz




Date: 11.JUN.2020 20:57:58

LTE Band 4 3MHz CH- Middle 30MHz~1GHz




Date: 11.JUN.2020 20:50:22

LTE Band 4 3MHz CH- Middle 1GHz ~20GHz




Date: 11.JUN.2020 20:58:37

LTE Band 4 3MHz CH- High 30MHz~1GHz



Date: 11.JUN.2020 20:50:30


LTE Band 4 3MHz CH- High 1GHz ~9GHz



Date: 11.JUN.2020 20:59:06




LTE Band 4 5MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 20:50:38

LTE Band 4 5MHz CH-Low 1GHz ~20GHz




Date: 11.JUN.2020 20:59:41

LTE Band 4 5MHz z CH- Middle 30MHz~1GHz




Date: 11.JUN.2020 20:50:45

LTE Band 4 5MHz CH- Middle 1GHz~20GHz




Date: 11.JUN.2020 21:00:07

LTE Band 4 5MHz CH- High 30MHz~1GHz



Date: 11.JUN.2020 20:50:52


LTE Band 4 5MHz CH- High 1GHz ~20GHz



Date: 11.JUN.2020 21:01:07




LTE Band 4 10MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 20:51:00

LTE Band 4 10MHz CH-Low 1GHz ~20GHz




Date: 11.JUN.2020 21:01:46

LTE Band 4 10MHz z CH- Middle 30MHz~1GHz




Date: 11.JUN.2020 20:51:12

LTE Band 4 10MHz CH- Middle 1GHz ~20GHz




Date: 11.JUN.2020 21:02:07

LTE Band 4 10MHz CH- High 30MHz~1GHz



Date: 11.JUN.2020 20:51:20


LTE Band 4 10MHz CH- High 1GHz ~20GHz



Date: 11.JUN.2020 21:02:32




LTE Band 4 15MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 20:51:27

LTE Band 4 15MHz CH-Low 1GHz ~20GHz




Date: 11.JUN.2020 21:03:33

LTE Band 4 15MHz CH- Middle 30MHz~1GHz




Date: 11.JUN.2020 20:51:35

LTE Band 4 15MHz CH- Middle 1GHz ~20GHz




Date: 11.JUN.2020 21:03:55

LTE Band 4 15MHz CH- High 30MHz~1GHz



Date: 11.JUN.2020 20:51:43


LTE Band 4 15MHz CH- High 1GHz ~20GHz



Date: 11.JUN.2020 21:06:35




LTE Band 4 20MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 20:51:51

LTE Band 4 20MHz CH-Low 1GHz ~20GHz




Date: 11.JUN.2020 21:07:52

LTE Band 4 20MHz CH- Middle 30MHz~1GHz




Date: 11.JUN.2020 20:52:00

LTE Band 4 20MHz CH- Middle 1GHz ~20GHz




Date: 11.JUN.2020 21:08:19

LTE Band 4 20MHz CH- High 30MHz~1GHz



Date: 11.JUN.2020 20:52:08


LTE Band 4 20MHz CH- High 1GHz ~20GHz



Date: 11.JUN.2020 21:08:46




LTE Band 12 1.4MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 22:08:45

LTE Band 12 1.4MHz CH-Low 1GHz~20GHz




Date: 11.JUN.2020 22:03:09

LTE Band 12 1.4MHz CH-Middle 30MHz~1GHz




Date: 11.JUN.2020 22:11:44

LTE Band 12 1.4MHz CH-Middle 1GHz~9GHz




Date: 11.JUN.2020 22:03:18

LTE Band 12 1.4MHz CH-High 30MHz~1GHz



Date: 11.JUN.2020 22:13:40


LTE Band 12 1.4MHz CH-High 1GHz~9GHz



Date: 11.JUN.2020 22:03:26




LTE Band 12 3MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 22:15:30

LTE Band 12 3MHz CH-Low 1GHz~9GHz




Date: 11.JUN.2020 22:03:45

LTE Band 12 3MHz CH-Middle 30MHz~1GHz




Date: 11.JUN.2020 22:16:09

LTE Band 12 3MHz CH-Middle 1GHz~9GHz




Date: 11.JUN.2020 22:03:52

LTE Band 12 3MHz CH-High 30MHz~1GHz



Date: 11.JUN.2020 22:16:45


LTE Band 12 3MHz CH-High 1GHz~9GHz



Date: 11.JUN.2020 22:04:00




LTE Band 12 5MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 22:17:20

LTE Band 12 5MHz CH-Low 1GHz~9GHz




Date: 11.JUN.2020 22:04:09

LTE Band 12 5MHz CH-Middle 30MHz~1GHz




Date: 11.JUN.2020 22:17:52

LTE Band 12 5MHz CH-Middle 1GHz~9GHz




Date: 11.JUN.2020 22:04:16

LTE Band 12 5MHz CH-High 30MHz~1GHz




Date: 11.JUN.2020 22:18:24

LTE Band 12 5MHz CH-High 1GHz~9GHz




Date: 11.JUN.2020 22:04:27

LTE Band 12 10MHz CH-Low 30MHz~1GHz




Date: 11.JUN.2020 22:18:57

LTE Band 12 10MHz CH-Low 1GHz~9GHz




Date: 11.JUN.2020 22:04:35

LTE Band 12 10MHz CH-Middle 30MHz~1GHz




Date: 11.JUN.2020 22:19:54

LTE Band 12 10MHz CH-Middle 1GHz~9GHz




Date: 11.JUN.2020 22:04:44

LTE Band 12 10MHz CH-High 30MHz~1GHz



Date: 11 JUN 2020 22:22:08


LTE Band 12 10MHz CH-High 1GHz~9GHz



Date: 11 JUN 2020 22:04:53




LTE Band 13 5MHz CH-Low 30MHz~1GHz




Date: 11 JUN.2020 22:31:08

LTE Band 13 5MHz CH-Low 1GHz~9GHz




Date: 11 JUN.2020 22:36:26

LTE Band 13 5MHz CH-Middle 30MHz~1GHz




Date: 11 JUN.2020 22:33:17

LTE Band 13 5MHz CH-Middle 1GHz~9GHz




Date: 11 JUN.2020 22:36:34

LTE Band 13 5MHz CH-High 30MHz~1GHz



Date: 11 JUN.2020 22:34:40



LTE Band 13 5MHz CH-High 1GHz~9GHz



Date: 11 JUN.2020 22:36:42




LTE Band 13 10MHz CH-Middle 1GHz~9GHz






LTE Band 66 1.4MHz CH-Low 30MHz~1GHz




Date: 12 JUN.2020 22:08:18

LTE Band 66 1.4MHz CH-Low 1GHz ~20GHz




Date: 12 JUN.2020 22:11:22

LTE Band 66 1.4MHz CH- Middle 30MHz~1GHz




Date: 12 JUN.2020 22:08:28

LTE Band 66 1.4MHz CH- Middle 1GHz ~20GHz




Date: 12 JUN.2020 22:12:33

LTE Band 66 1.4MHz CH-High 30MHz~1GHz



Date: 12 JUN.2020 22:08:37


LTE Band 66 1.4MHz CH-High 1GHz ~20GHz



Date: 12 JUN.2020 22:12:59




LTE Band 66 3MHz CH-Low 30MHz~1GHz




Date: 12 JUN.2020 22:08:45

LTE Band 66 3MHz CH-Low 1GHz ~20GHz




Date: 12 JUN.2020 22:13:55

LTE Band 66 3MHz CH- Middle 30MHz~1GHz




Date: 12 JUN.2020 22:08:53

LTE Band 66 3MHz CH- Middle 1GHz ~20GHz




Date: 12 JUN.2020 22:14:14

LTE Band 66 3MHz CH-High 30MHz~1GHz



Date: 12 JUN.2020 22:09:01


LTE Band 66 3MHz CH-High 1GHz ~20GHz



Date: 12 JUN.2020 22:14:49




LTE Band 66 5MHz CH-Low 30MHz~1GHz




Date: 12.JUN.2020 22:09:11

LTE Band 66 5MHz CH-Low 1GHz ~20GHz




Date: 12.JUN.2020 22:15:44

LTE Band 66 5MHz CH- Middle 30MHz~1GHz




Date: 12.JUN.2020 22:09:19

LTE Band 66 5MHz CH- Middle 1GHz ~20GHz




Date: 12.JUN.2020 22:16:02

LTE Band 66 5MHz CH-High 30MHz~1GHz



Date: 12.JUN.2020 22:09:27


LTE Band 66 5MHz CH-High 1GHz ~20GHz



Date: 12.JUN.2020 22:16:27




LTE Band 66 10MHz CH-Low 30MHz~1GHz




Date: 12 JUN.2020 22:09:35

LTE Band 66 10MHz CH-Low 1GHz ~20GHz




Date: 12 JUN.2020 22:17:00

LTE Band 66 10MHz CH- Middle 30MHz~1GHz




Date: 12 JUN.2020 22:09:44

LTE Band 66 10MHz CH- Middle 1GHz ~20GHz




Date: 12 JUN.2020 22:17:19

LTE Band 66 10MHz CH-High 30MHz~1GHz



Date: 12 JUN.2020 22:09:51


LTE Band 66 10MHz CH-High 1GHz ~20GHz



Date: 12 JUN.2020 22:17:37




LTE Band 66 15MHz CH-Low 30MHz~1GHz




Date: 12 JUN.2020 22:10:05

LTE Band 66 15MHz CH-Low 1GHz ~20GHz




Date: 12 JUN.2020 22:10:37

LTE Band 66 15MHz CH- Middle 30MHz~1GHz




Date: 12 JUN.2020 22:10:13

LTE Band 66 15MHz CH- Middle 1GHz ~20GHz




Date: 12 JUN.2020 22:10:54

LTE Band 66 15MHz CH-High 30MHz~1GHz



Date: 12 JUN.2020 22:10:21


LTE Band 66 15MHz CH-High 1GHz ~20GHz



Date: 12 JUN.2020 22:10:11




LTE Band 66 20MHz CH-Low 30MHz~1GHz




Date: 12 JUN.2020 22:10:29

LTE Band 66 20MHz CH-Low 1GHz ~20GHz




Date: 12 JUN.2020 22:20:13

LTE Band 66 20MHz CH- Middle 30MHz~1GHz




Date: 12 JUN.2020 22:10:37

LTE Band 66 20MHz CH- Middle 1GHz ~20GHz




Date: 12 JUN.2020 22:20:33

LTE Band 66 20MHz CH-High 30MHz~1GHz




Date: 12 JUN.2020 22:10:50

LTE Band 66 20MHz CH-High 1GHz ~20GHz




Date: 12 JUN.2020 22:24:36

LTE Band 85 5MHz CH-Low 30MHz~1GHz




Date: 14.JUN.2020 15:26:50

LTE Band 85 5MHz CH-Low 1GHz~9GHz




Date: 14.JUN.2020 15:28:10

LTE Band 85 5MHz CH-Middle 30MHz~1GHz




Date: 14.JUN.2020 15:27:16

LTE Band 85 5MHz CH-Middle 1GHz~9GHz




Date: 14.JUN.2020 15:28:19

LTE Band 85 5MHz CH-High 30MHz~1GHz



Date: 14 JUN 2020 15:27:46


LTE Band 85 5MHz CH-High 1GHz~9GHz



Date: 14 JUN 2020 15:28:28




LTE Band 85 10MHz CH- Low 30MHz~1GHz




Date: 14. JUN.2020 15:25:16

LTE Band 85 10MHz CH- Low 1GHz~9GHz




Date: 14. JUN.2020 15:28:38

LTE Band 85 10MHz CH-Middle 30MHz~1GHz




Date: 14. JUN.2020 15:23:41

LTE Band 85 10MHz CH-Middle 1GHz~9GHz




Date: 14. JUN.2020 15:28:47

LTE Band 85 10MHz CH- High 30MHz~1GHz



Date: 14. JUN.2020 15:25:58

LTE Band 85 10MHz CH- High 1GHz~9GHz



Date: 14. JUN.2020 15:28:55

5.7 Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 D01 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=200Hz,VBW=600Hz for 9kHz150kHz , RBW=10kHz, VBW=30kHz 150kHz-30MHz ,RBW=100kHz,VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:

$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, ERP

= EIRP-2.15dBi.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m

Limits

Rule Part 27.53(h) specifies that “for operations in the 1695-1710 MHz, 1710-1755 MHz, 1755-1780 MHz, 1915-1920 MHz, 1995-2000 MHz, 2000-2020 MHz, 2110-2155 MHz, 2155-2180 MHz, and 2180-2200 bands, the power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10} (P)$ dB.”

Rule Part 27.53 (g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least $43 + 10 \log (P)$ dB. Compliance with this provision is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kilohertz or greater. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

Rule Part 27.53(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

Part 27.53 (c) For operations in the 746-758 MHz band and the 776-788 MHz band, the power of any emission outside the licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, in accordance with the following:

- (1) On any frequency outside the 746-758 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least $43 + 10 \log (P)$ dB;
- (3) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $76 + 10 \log (P)$ dB in a 6.25 kHz band segment, for base and fixed stations;
- (4) On all frequencies between 763-775 MHz and 793-805 MHz, by a factor not less than $65 + 10 \log (P)$ dB in a 6.25 kHz band segment, for mobile and portable stations;
- (5) Compliance with the provisions of paragraphs (c)(1) and (c)(2) of this section is based on the use of measurement instrumentation employing a resolution bandwidth of 100 kHz or greater. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed;

Part 27.53(a)/(h)/(g) Limit		-13 dBm
Part 27.53(f) Limit	Limit out of the band 1559-1610 MHz	-13 dBm
	Limit in the band 1559-1610 MHz	-40 dBm

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = \pm 1.96$, $U = \pm 3.55$ dB.

**Test Result**

For radiated spurious emissions test, the worst mode (Middle Channel) should be reflected in the report.

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

LTE Band 4 QPSK 1.4MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3464.3	-46.45	2.6	10.75	Horizontal	-38.30	-13.00	25.30	45
3	5197.5	-57.55	2.4	11.05	Horizontal	-48.90	-13.00	35.90	0
4	6930.0	-58.95	4.5	11.15	Horizontal	-52.30	-13.00	39.30	45
5	8662.5	-54.45	5.1	11.35	Horizontal	-48.20	-13.00	35.20	270
6	10395.0	-48.75	5.3	11.95	Horizontal	-42.10	-13.00	29.10	135
7	12127.5	-52.55	5.5	13.55	Horizontal	-44.50	-13.00	31.50	90
8	13860.0	-49.41	6.3	13.75	Horizontal	-41.96	-13.00	28.96	225
9	15592.5	-48.95	6.7	13.85	Horizontal	-41.80	-13.00	28.80	45
10	17325.0	-46.45	6.8	14.25	Horizontal	-39.00	-13.00	26.00	90
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 4 QPSK 5MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3460.5	-46.05	2.6	10.75	Horizontal	-37.90	-13.00	24.90	180
3	5191.5	-57.15	2.4	11.05	Horizontal	-48.50	-13.00	35.50	90
4	6930.0	-59.75	4.5	11.15	Horizontal	-53.10	-13.00	40.10	0
5	8662.5	-54.45	5.1	11.35	Horizontal	-48.20	-13.00	35.20	45
6	10395.0	-49.55	5.3	11.95	Horizontal	-42.90	-13.00	29.90	315
7	12127.5	-51.55	5.5	13.55	Horizontal	-43.50	-13.00	30.50	0
8	13860.0	-49.55	6.3	13.75	Horizontal	-42.10	-13.00	29.10	90
9	15592.5	-47.95	6.7	13.85	Horizontal	-40.80	-13.00	27.80	45
10	17325.0	-44.95	6.8	14.25	Horizontal	-37.50	-13.00	24.50	225
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.									



2. The worst emission was found in the antenna is Horizontal position.



LTE Band 4 QPSK 20MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3447.8	-46.32	2.6	10.75	Horizontal	-38.17	-13.00	25.17	45
3	5170.9	-58.45	2.4	11.05	Horizontal	-49.80	-13.00	36.80	315
4	6930.0	-59.05	4.5	11.15	Horizontal	-52.40	-13.00	39.40	90
5	8662.5	-54.45	5.1	11.35	Horizontal	-48.20	-13.00	35.20	0
6	10395.0	-49.45	5.3	11.95	Horizontal	-42.80	-13.00	29.80	45
7	12127.5	-50.35	5.5	13.55	Horizontal	-42.30	-13.00	29.30	225
8	13860.0	-49.35	6.3	13.75	Horizontal	-41.90	-13.00	28.90	315
9	15592.5	-49.10	6.7	13.85	Horizontal	-41.95	-13.00	28.95	45
10	17325.0	-47.35	6.8	14.25	Horizontal	-39.90	-13.00	26.90	90
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 12 QPSK 1.4MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1415.0	-66.80	2.00	10.75	Horizontal	-60.20	-13.00	47.20	45
3	2122.5	-66.99	2.51	11.05	Horizontal	-60.60	-13.00	47.60	135
4	2830.0	-60.75	4.20	11.15	Horizontal	-55.95	-13.00	42.95	225
5	3537.5	-57.10	5.20	11.15	Horizontal	-53.30	-13.00	40.30	180
6	4245.0	-55.20	5.50	11.95	Horizontal	-50.90	-13.00	37.90	225
7	4952.5	-55.10	5.70	13.55	Horizontal	-49.40	-13.00	36.40	45
8	5660.0	-55.10	6.30	13.75	Horizontal	-49.80	-13.00	36.80	315
9	6367.5	-56.10	6.80	13.85	Horizontal	-51.20	-13.00	38.20	90
10	7075.0	-56.40	6.90	14.25	Horizontal	-51.20	-13.00	38.20	45
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									



LTE Band 12 QPSK 5MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1410.6	-65.30	2.00	10.75	Horizontal	-58.70	-13.00	45.70	135
3	2115.9	-63.99	2.51	11.05	Horizontal	-57.60	-13.00	44.60	225
4	2821.2	-61.00	4.20	11.15	Horizontal	-56.20	-13.00	43.20	90
5	3512.5	-57.50	5.20	11.15	Horizontal	-53.70	-13.00	40.70	45
6	4215.0	-55.50	5.50	11.95	Horizontal	-51.20	-13.00	38.20	315
7	4917.5	-54.50	5.70	13.55	Horizontal	-48.80	-13.00	35.80	135
8	5620.0	-55.50	6.30	13.75	Horizontal	-50.20	-13.00	37.20	90
9	6322.5	-55.80	6.80	13.85	Horizontal	-50.90	-13.00	37.90	45
10	7025.0	-55.80	6.90	14.25	Horizontal	-50.60	-13.00	37.60	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 12 QPSK 10MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1406.4	-66.40	2.00	10.75	Horizontal	-59.80	-13.00	46.80	45
3	2109.6	-66.29	2.51	11.05	Horizontal	-59.90	-13.00	46.90	315
4	2812.8	-60.79	4.20	11.15	Horizontal	-55.99	-13.00	42.99	90
5	3537.5	-56.30	5.20	11.15	Horizontal	-52.50	-13.00	39.50	90
6	4245.0	-55.80	5.50	11.95	Horizontal	-51.50	-13.00	38.50	0
7	4952.5	-53.50	5.70	13.55	Horizontal	-47.80	-13.00	34.80	45
8	5660.0	-53.90	6.30	13.75	Horizontal	-48.60	-13.00	35.60	315
9	6367.5	-56.60	6.80	13.85	Horizontal	-51.70	-13.00	38.70	45
10	7075.0	-56.50	6.90	14.25	Horizontal	-51.30	-13.00	38.30	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 13 QPSK 5MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1564.0	-64.74	2.51	11.05	Horizontal	-58.35	-40.00	18.35	45
Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
3	2346.0	-65.59	2.51	11.05	Horizontal	-59.20	-13.00	46.20	315
4	3128.0	-57.40	4.20	11.15	Horizontal	-52.60	-13.00	39.60	270
5	3910.0	-54.60	5.20	11.15	Horizontal	-50.80	-13.00	37.80	135
6	4692.0	-54.00	5.50	11.95	Horizontal	-49.70	-13.00	36.70	225
7	5474.0	-55.00	5.70	13.55	Horizontal	-49.30	-13.00	36.30	45
8	6256.0	-55.50	6.30	13.75	Horizontal	-50.20	-13.00	37.20	90
9	7038.0	-55.30	6.80	13.85	Horizontal	-50.40	-13.00	37.40	45
10	7820.0	-54.80	6.90	14.25	Horizontal	-49.60	-13.00	36.60	315
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									

LTE Band 13 QPSK 10MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1555.3	-65.80	2.00	10.75	Horizontal	-59.20	-13.00	46.20	270
3	2346.0	-62.89	2.51	11.05	Horizontal	-56.50	-13.00	43.50	90
4	3128.0	-57.40	4.20	11.15	Horizontal	-52.60	-13.00	39.60	270
5	3910.0	-54.60	5.20	11.15	Horizontal	-50.80	-13.00	37.80	135
6	4692.0	-54.00	5.50	11.95	Horizontal	-49.70	-13.00	36.70	225
7	5474.0	-55.00	5.70	13.55	Horizontal	-49.30	-13.00	36.30	45
8	6256.0	-55.50	6.30	13.75	Horizontal	-50.20	-13.00	37.20	90
9	7038.0	-55.30	6.80	13.85	Horizontal	-50.40	-13.00	37.40	45
10	7820.0	-54.80	6.90	14.25	Horizontal	-49.60	-13.00	36.60	315
Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor. 2. The worst emission was found in the antenna is Horizontal position.									



LTE Band 66 QPSK 1.4MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3509.3	-52.45	2.6	10.75	Horizontal	-44.30	-13.00	31.30	90
3	5262.5	-56.05	2.4	11.05	Horizontal	-47.40	-13.00	34.40	180
4	7018.0	-56.95	4.5	11.15	Horizontal	-50.30	-13.00	37.30	270
5	8772.5	-53.75	5.1	11.35	Horizontal	-47.50	-13.00	34.50	45
6	10527.0	-50.65	5.3	11.95	Horizontal	-44.00	-13.00	31.00	90
7	12281.5	-50.25	5.5	13.55	Horizontal	-42.20	-13.00	29.20	0
8	14036.0	-49.75	6.3	13.75	Horizontal	-42.30	-13.00	29.30	315
9	15790.5	-48.45	6.7	13.85	Horizontal	-41.30	-13.00	28.30	45
10	17545.0	-46.85	6.8	14.25	Horizontal	-39.40	-13.00	26.40	90

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 66 QPSK 5MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3486.0	-49.25	2.6	10.75	Horizontal	-41.10	-13.00	28.10	0
3	5229.0	-56.35	2.4	11.05	Horizontal	-47.70	-13.00	34.70	225
4	6972.0	-59.25	4.5	11.15	Horizontal	-52.60	-13.00	39.60	45
5	8715.0	-54.85	5.1	11.35	Horizontal	-48.60	-13.00	35.60	135
6	10458.0	-50.65	5.3	11.95	Horizontal	-44.00	-13.00	31.00	315
7	12201.0	-50.95	5.5	13.55	Horizontal	-42.90	-13.00	29.90	225
8	13944.0	-49.43	6.3	13.75	Horizontal	-41.98	-13.00	28.98	90
9	15687.0	-48.85	6.7	13.85	Horizontal	-41.70	-13.00	28.70	45
10	17430.0	-47.15	6.8	14.25	Horizontal	-39.70	-13.00	26.70	270

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 66 QPSK 20MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	EIRP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	3472.9	-49.35	2.6	10.75	Horizontal	-41.20	-13.00	28.20	45
3	5209.0	-58.45	2.4	11.05	Horizontal	-49.80	-13.00	36.80	270
4	6945.8	-59.05	4.5	11.15	Horizontal	-52.40	-13.00	39.40	90
5	8682.0	-53.65	5.1	11.35	Horizontal	-47.40	-13.00	34.40	315
6	10418.6	-49.95	5.3	11.95	Horizontal	-43.30	-13.00	30.30	0
7	12455.0	-50.25	5.5	13.55	Horizontal	-42.20	-13.00	29.20	90
8	13891.5	-49.35	6.3	13.75	Horizontal	-41.90	-13.00	28.90	45
9	15627.0	-48.25	6.7	13.85	Horizontal	-41.10	-13.00	28.10	135
10	17364.4	-46.15	6.8	14.25	Horizontal	-38.70	-13.00	25.70	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.

LTE Band 85 QPSK 5MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1410.6	-66.55	2.00	10.75	Horizontal	-59.95	-13.00	46.95	225
3	2115.9	-67.49	2.51	11.05	Horizontal	-61.10	-13.00	48.10	90
4	2821.2	-60.70	4.20	11.15	Horizontal	-55.90	-13.00	42.90	315
5	3526.5	-57.10	5.20	11.15	Horizontal	-53.30	-13.00	40.30	315
6	4231.8	-55.60	5.50	11.95	Horizontal	-51.30	-13.00	38.30	90
7	4937.1	-54.80	5.70	13.55	Horizontal	-49.10	-13.00	36.10	45
8	5642.4	-56.00	6.30	13.75	Horizontal	-50.70	-13.00	37.70	315
9	6347.7	-55.10	6.80	13.85	Horizontal	-50.20	-13.00	37.20	180
10	7053.0	-56.00	6.90	14.25	Horizontal	-50.80	-13.00	37.80	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



LTE Band 85 QPSK 10MHz CH-Middle, RB 1

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1405.3	-66.49	2.00	10.75	Horizontal	-59.89	-13.00	46.89	0
3	2108.0	-66.29	2.51	11.05	Horizontal	-59.90	-13.00	46.90	90
4	2810.8	-60.80	4.20	11.15	Horizontal	-56.00	-13.00	43.00	135
5	3513.5	-56.76	5.20	11.15	Horizontal	-52.96	-13.00	39.96	180
6	4216.2	-55.20	5.50	11.95	Horizontal	-50.90	-13.00	37.90	270
7	4918.9	-55.30	5.70	13.55	Horizontal	-49.60	-13.00	36.60	135
8	5621.6	-55.70	6.30	13.75	Horizontal	-50.40	-13.00	37.40	0
9	6324.3	-54.80	6.80	13.85	Horizontal	-49.90	-13.00	36.90	45
10	7027.0	-55.70	6.90	14.25	Horizontal	-50.50	-13.00	37.50	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2. The worst emission was found in the antenna is Horizontal position.



6 Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2020-05-18	2021-05-17
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2020-05-18	2021-05-17
Signal Analyzer	R&S	FSV30	100815	2019-12-15	2020-12-14
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2017-09-26	2020-09-25
Trilog Antenna	SCHWARZBECK	VUBL 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	100126	2018-07-07	2020-07-06
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2020-06-19
Signal generator	R&S	SMB 100A	102594	2020-05-18	2021-05-17
Climatic Chamber	ESPEC	SU-242	93000506	2017-12-17	2020-12-16
Preamplifier	R&S	SCU18	102327	2020-05-18	2021-05-17
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2020-05-18	2021-05-17
RF Cable	Agilent	SMA 15cm	0001	2020-06-11	2020-12-10
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****