

# FCC RF EXPOSURE REPORT

**FCC ID:2A4ND-SE7D**

Test Report No.....: RF240220001-01-003

Product(s) Name.....: Active Noise Cancelling Headphones

Model(s).....: SE7D, SE7N, SE7MAX, SE7, SE8, SE8A, Yoozer Comfort

Trade Mark.....: Amusful, Ibeadio, Vonaural, Zenalla, Yoozer

Applicant.....: JiangXi MeiDong Technology Co., Ltd.

Address.....: No.1, Food Avenue, Jingshan Comprehensive District Shanggao Prefecture  
Industrial Park, Yichun city, Jiangxi Province, China


Receipt Date.....: 2024.03.01

Test Date.....: 2024.03.04~2024.03.13

Issued Date.....: 2024.04.02

Standards.....: CFR47 FCC Part 2: Section 2.1093; CFR47 FCC Part 1: Section 1.1310  
FCC KDB Publication 447498 D01v06

Testing Laboratory.....: Shenzhen Haiyun Standard Technical Co., Ltd.

| Prepared By:       | Checked By:      | Approved By:    |  |
|--------------------|------------------|-----------------|---|
| Jason huang        | Tim zhang        | Misue Su        |   |
| <i>Jason huang</i> | <i>Tim.zhang</i> | <i>Misue Su</i> |   |

## History of this test report

Original Report Issue Date: 2024.04.02

- ☒ No additional attachment
- ☐ Additional attachments were issued following record

| Attachment No. | Issue Date | Description |
|----------------|------------|-------------|
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |
|                |            |             |

## 1.. TEST FACILITY

|                           |   |
|---------------------------|---|
| Company:                  | Shenzhen Haiyun Standard Technical CO., Ltd.  |
| Address:                  | No. 110-113, 115, 116, Block B, Jinyuan Business Building, Bao'an District, Shenzhen, China |
| CNAS Registration Number: | CNAS L18252   |
| CAB identifier:           | CN0145  |
| A2LA Certificate Number:  | 6823.01   |
| Telephone:                | 0755-26024411   |

## 2.. MPE CALCULATION METHOD

For 100 MHz to 6 GHz and test separation distances  $\leq 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where

□  $f(\text{GHz})$  is the RF channel transmit frequency in GHz

### Appendix A

#### *SAR Test Exclusion Thresholds for 100 MHz – 6 GHz and $\leq 50$ mm*

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

| MHz  | 5  | 10 | 15  | 20  | 25  | mm   |
|------|----|----|-----|-----|-----|--|
| 150  | 39 | 77 | 116 | 155 | 194 | <i>SAR Test<br/>Exclusion<br/>Threshold (mW)</i> |
| 300  | 27 | 55 | 82  | 110 | 137 |  |
| 450  | 22 | 45 | 67  | 89  | 112 |  |
| 835  | 16 | 33 | 49  | 66  | 82  |  |
| 900  | 16 | 32 | 47  | 63  | 79  |  |
| 1500 | 12 | 24 | 37  | 49  | 61  |  |
| 1900 | 11 | 22 | 33  | 44  | 54  |  |
| 2450 | 10 | 19 | 29  | 38  | 48  |  |
| 3600 | 8  | 16 | 24  | 32  | 40  |  |
| 5200 | 7  | 13 | 20  | 26  | 33  |  |
| 5400 | 6  | 13 | 19  | 26  | 32  |  |
| 5800 | 6  | 12 | 19  | 25  | 31  |  |

## TEST RESULTS

### Table for Filed Antenna

For BLE & BT

| Ant. | Brand | Antenna Type | Connector | Gain (dBi) |
|------|-------|--------------|-----------|------------|
| 1    | N/A   | PCB          | N/A       | 0          |

| Operating Mode | Frequency | Conducted Peak Power | Conducted Peak Power |
|----------------|-----------|----------------------|----------------------|
|                | (MHz)     | (dBm)                | (mW)                 |
| BLE            | 2402-2480 | -2.38                | 0.58                 |
| BT             | 2402-2480 | -0.61                | 0.87                 |

### Measurement Record:

The minimum distance for the EUT is less than 5mm.

$$\frac{3 \cdot d}{\sqrt{f}} = 9.52 \text{ mW.}$$

Since maximum peak output power of the transmitter is -0.61 dBm  $\approx$  0.87 mW < 9.52 mW.

Hence the EUT is excluded from SAR evaluation according to FCC KDB Publication 447498 D01 General RF Exposure Guidance v06.

### ➤ Conclusion

Result: Complies

## Statement

1. The report is invalid without the official seal or special seal of Shenzhen Haiyun Standard Technology Co., Ltd. (hereinafter referred to as the unit).
2. The report is invalid without the signature of the approver.
3. The report is invalid if altered arbitrarily.
4. The report shall not be partially copied without the written approval of the unit.
5. The reported test results are only valid for the tested samples.
6. If there is any objection to the test report, it shall be submitted to the test unit within 15 days from the date of receiving the report, and the overdue shall not be accepted.

## Shenzhen Haiyun Standard Technology Co., Ltd.

Address: Room 110, 111, 112, 113, 115, 116, Block B, Jinyuan Business Building, No. 302, Xixiang Avenue, Labor Community, Xixiang Street, Baoan District, Shenzhen, China

Tel: 0755-26024411

Email: service@hy-lab.cn

---

(END OF REPORT)