



MPE TEST REPORT

Applicant Shanghai Smawave Technology Co. ,Ltd
FCC ID 2AU8HMGL6201A
Product LTE Module
Brand Smawave
Model MGL6201A
Report No. R2001A0002-M1
Issue Date February 12, 2020

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 1.1310**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Yu Wang

Approved by: Guangchang Fan

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



Table of Contents

| | | |
|-----|--|---|
| 1 | Test Laboratory..... | 3 |
| 1.1 | Notes of the Test Report | 3 |
| 1.2 | Testing Location..... | 3 |
| 1.3 | Laboratory Environment..... | 3 |
| 2 | Description of Equipment under Test..... | 4 |
| 3 | Maximum conducted output power (measured) and antenna Gain | 5 |
| 4 | Test Result | 6 |



1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

1.3 Laboratory Environment

| | |
|---|---------------------------|
| Temperature | Min. = 18°C, Max. = 25 °C |
| Relative humidity | Min. = 30%, Max. = 70% |
| Ground system resistance | < 0.5 Ω |
| Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards. | |

2 Description of Equipment under Test

Client Information

| | |
|-----------------------------|---|
| Applicant | Shanghai Smawave Technology Co. ,Ltd |
| Applicant address | 3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China |
| Manufacturer | Shanghai Smawave Technology Co. ,Ltd |
| Manufacturer address | 3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China |

General Technologies

| | |
|-------------------------|-----------------------------------|
| Model | MGL6201A |
| IMEI | 860524031979550 |
| Hardware Version | V2.0 |
| Software Version | CAT12-A |
| Date of Testing: | October 1, 2019~ November 7, 2019 |

3 Maximum conducted output power (measured) and antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

$$\text{Numeric gain (G)} = 10^{(\text{antenna gain}/10)}$$

| Band | Maximum Conducted Output Power (dBm) | | Antenna Gain (dBi) | Numeric gain |
|-------------|--------------------------------------|---------|--------------------|--------------|
| | (dBm) | (mW) | | |
| LTE Band 2 | 24.000 | 251.189 | 2.150 | 1.641 |
| LTE Band 4 | 24.000 | 251.189 | 1.490 | 1.409 |
| LTE Band 5 | 23.500 | 223.872 | 2.780 | 1.897 |
| LTE Band 12 | 24.000 | 251.189 | 1.040 | 1.271 |
| LTE Band 13 | 24.000 | 251.189 | 1.040 | 1.271 |
| LTE Band 14 | 24.000 | 251.189 | 2.780 | 1.897 |
| LTE Band 25 | 24.000 | 251.189 | 2.150 | 1.641 |
| LTE Band 26 | 24.000 | 251.189 | 2.780 | 1.897 |
| LTE Band 41 | 24.000 | 251.189 | 3.990 | 2.506 |
| LTE Band 48 | 24.500 | 281.838 | 3.710 | 2.350 |
| LTE Band 53 | 24.500 | 281.838 | 4.220 | 2.642 |
| LTE Band 66 | 24.000 | 251.189 | 1.490 | 1.409 |

4 Test Result

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

| Frequency Range (MHz) | Electric Field Strength (V/m) | Magnetic Field Strength (A/m) | Power Density (mW/cm ²) | Averaging Time (minutes) |
|---|-------------------------------------|-------------------------------------|--|-----------------------------|
| (A) Limits for Occupational/Controlled Exposures | | | | |
| 0.3-3.0 | 614 | 1.63 | *(100) | 6 |
| 3-30 | 1842/f | 4.89/f | *(900/f ²) | 6 |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 |
| 300-1500 | | | f/300 | 6 |
| 1500-100,000 | | | 5 | 6 |
| (B) Limits for General Population/Uncontrolled Exposure | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 |
| 1.34-30 | 824/f | 2.19/f | *(180/f ²) | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | f/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

f = frequency in MHz

* = Plane-wave equivalent power density

Note1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.



The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

| Band | The maximum permissible exposure |
|-------------|----------------------------------|
| LTE Band 2 | $1.0\text{mW}/\text{cm}^2$ |
| LTE Band 4 | $1.0\text{mW}/\text{cm}^2$ |
| LTE Band 5 | $0.55\text{mW}/\text{cm}^2$ |
| LTE Band 12 | $0.47\text{mW}/\text{cm}^2$ |
| LTE Band 13 | $0.52\text{mW}/\text{cm}^2$ |
| LTE Band 14 | $0.53\text{mW}/\text{cm}^2$ |
| LTE Band 25 | $1.0\text{mW}/\text{cm}^2$ |
| LTE Band 26 | $0.55\text{mW}/\text{cm}^2$ |
| LTE Band 41 | $1.0\text{mW}/\text{cm}^2$ |
| LTE Band 48 | $1.0\text{mW}/\text{cm}^2$ |
| LTE Band 53 | $1.0\text{mW}/\text{cm}^2$ |
| LTE Band 66 | $1.0\text{mW}/\text{cm}^2$ |

**RF Exposure Calculations:**

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in KDB 447498 D01 is used in the calculation.

Equation from KDB 447498 D01 General RF Exposure Guidance v06 (10/23/2015) is:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

| Band | PG (mW) | Test Result (mW/cm ²) | Limit Value (mW/cm ²) | Conclusion |
|------------------------------|---------|-----------------------------------|-----------------------------------|------------|
| LTE Band 2 | 412.098 | 0.082 | 1.000 | Pass |
| LTE Band 4 | 353.997 | 0.070 | 1.000 | Pass |
| LTE Band 5 | 424.620 | 0.084 | 0.550 | Pass |
| LTE Band 12 | 319.154 | 0.063 | 0.470 | Pass |
| LTE Band 13 | 319.154 | 0.063 | 0.520 | Pass |
| LTE Band 14 | 476.431 | 0.095 | 0.530 | Pass |
| LTE Band 25 | 412.098 | 0.082 | 1.000 | Pass |
| LTE Band 26 | 476.431 | 0.095 | 0.550 | Pass |
| LTE Band 41 | 629.506 | 0.125 | 1.000 | Pass |
| LTE Band 48 | 662.217 | 0.132 | 1.000 | Pass |
| LTE Band 53 | 744.732 | 0.148 | 1.000 | Pass |
| LTE Band 66 | 353.997 | 0.070 | 1.000 | Pass |
| Note: R = 20cm π = 3.1416 | | | | |

LTE Antenna can't transmit simultaneously.

Note: For transmitters, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.