FCC ID: 2AB22-C151R

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]· $[\sqrt{f(GHZ)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- f(GHZ) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

BR:

Modulation	Channel Freq. (GHz)	Conduct ed power (dBm)		Tune-up power (dBm)	Max tune-up power (dBm)	Max tune-up power (mW)	Distance (mm)	Result calculatio n	SAR Exclusion threshold	SAR test exclusion
GFSK	2.402	0.508	1.12	1±1	2	1.58	<5	0.49127	3.00	YES
	2.441	1.258	1.34	1±1	2	1.58	<5	0.49524	3.00	YES
	2.480	1.405	1.38	1±1	2	1.58	<5	0.49918	3.00	YES
π/4- DQPSK	2.402	-0.075	0.98	0±1	1	1.26	<5	0.39023	3.00	YES
	2.441	0.047	1.01	0±1	1	1.26	<5	0.39338	3.00	YES
	2.480	0.838	1.21	0±1	1	1.26	<5	0.39651	3.00	YES
8-DQPSK	2.402	0.312	1.07	0±1	1	1.26	<5	0.39023	3.00	YES
	2.441	0.086	1.02	0±1	1	1.26	<5	0.39338	3.00	YES
	2.480	0.792	1.20	0±1	1	1.26	<5	0.39651	3.00	YES

Conclusion:

For the max result : $0.49918 \le 3.0$ for 1g SAR, SAR is not required.

Signature:

NAME AND TITLE (Please print or type): Alex li /Manager

Alex

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.

Date: 2021-11-04