



TEST REPORT

REPORT NUMBER: I22W00023-MPE

ON

Type of Equipment: LTE MODULE
Type of Designation: L508
Manufacturer: Shanghai MobileTek Communication Ltd.
Brand Name: LYNQ
FCC ID: 2AK9DL508

ACCORDING TO

FCC CFR 47 Part 2.1091 《Radiofrequency radiation exposure evaluation: mobile devices》

FCC CFR 47 Part1.1310 《Radiofrequency radiation exposure limits》

Chongqing Academy of Information and Communication Technology

Month date, year

Mar,21,2022

Signature

Xiang Luoyong

Director

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of Chongqing Academy of Information and Communications Technology.



Revision Version

Report Number	Revision	Date	Memo
I22W00023-MPE	00	2022-3-21	Initial creation of test report

CONTENTS

1. TEST LABORATORY	2
1.1. TESTING LOCATION	2
1.2. TESTING ENVIRONMENT	2
1.3. PROJECT DATA	2
1.4. SIGNATURE	2
2. CLIENT INFORMATION	3
2.1. APPLICANT INFORMATION	3
2.2. MANUFACTURER INFORMATION	3
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	4
3.1. ABOUT EUT	4
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	4
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST	4
4. REFERENCE DOCUMENTS	5
4.1. APPLICABLE STANDARDS	5
4.2. TEST LIMITS	5
5. TEST RESULTS	6
5.1. RF POWER OUTPUT	6
5.2. CALCULATION INFORMATION	6
5.3. RESULTS	7
5.4. RESULT OF WCDMA BAND 5	8
5.5. RESULT OF LTE BAND 4	8
ANNEX A: EUT PHOTOGRAPH	9

1. Test Laboratory

1.1. Testing Location

Company Name:	Chongqing Academy of Information and Communications Technology
Address:	Building C, Technology Innovation Center, No.8, Yuma Road, Chayuan New Area, Nan'an District, Chongqing, People's Republic of China
Postal Code:	401336
Telephone:	0086-23-88069965
Fax:	0086-23-88608777


1.2. Testing Environment

Normal Temperature:	21.3°C
Relative Humidity:	65%

1.3. Project Data

Testing Start Date:	2022-3-21
Testing End Date:	2022-3-21

1.4. Signature



2022-3-21

Wang Chengyu
(Prepared this test report)

Date



2022-3-21

Wang Lili
(Reviewed this test report)

Date



2022-3-21

Xiang Luoyong
Director of the laboratory
(Approved this test report)

Date

Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336
Tel: 0086-23-88069965 FAX: 0086-23-88608777

2. Client Information

2.1. Applicant Information

Company Name:	Shanghai MobileTek Communication Ltd.
Address /Post:	Free Trade Zone No. 33, No. 17 building 6H3 Xiya Road China (Shanghai)
Country:	CHINA
Telephone:	15821966417
Fax:	--
Email:	qh.zhang@mobiletek.cn
Contact Person:	Qinghua Zhang

2.2. Manufacturer Information

Company Name:	Shanghai MobileTek Communication Ltd.
Address /Post:	Free Trade Zone No. 33, No. 17 building 6H3 Xiya Road China (Shanghai)
Country:	CHINA
Telephone:	15821966417
Fax:	--
Email:	qh.zhang@mobiletek.cn
Contact Person:	Qinghua Zhang

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

EUT Description:	LTE Module
Model name:	L508
WCDMA Frequency Band:	Band 5
LTE Frequency Band:	Band 4
Note: Photographs of EUT are shown in ANNEX A of this test report.	

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version	Date of receipt
S1	864788050018584	V2	--	2022-3-21

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

EUT ID*	SN	Description
NA	NA	NA

*AE ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Applicable Standards

The MPE report was carried out on a sample equipment to demonstrate limited compliance with FCC CFR 47 Part 2.1091.

FCC CFR 47 Part 2.1091: Radiofrequency radiation exposure evaluation: mobile devices

4.2. Test Limits

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

MPE for the upper tier (people in controlled environments)

Frequency Range [MHz]	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100000	--	--	1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

For the DUT, the limits for the general public when an RF safety program is unavailable.

5. Test Results

5.1. RF Power Output

Frequency Band	Highest Averaged Power Output(dBm)	Highest Frame-Averaged Output Power (dBm)	Antenna Gain(dBi)
WCDMA Band 5	25.0	25.0	6.0
LTE Band 4	25.7	25.7	6.0
Notes: 1) Division Factors To average the power, the division factor is as follows: 1TX-slot = 1 transmit time slot out of 8 time slots=> conducted power divided by (8/1) => -9.03dB 2TX-slots = 2 transmit time slots out of 8 time slots=> conducted power divided by (8/2) => -6.02dB 3TX-slots = 3 transmit time slots out of 8 time slots=> conducted power divided by (8/3) => -4.26dB 4TX-slots = 4 transmit time slots out of 8 time slots=> conducted power divided by (8/4) => -3.01dB 2) According to the conducted power as above, the measurements are performed with 1Txslots for 850MHz and 1900MHz. 3) Disclaimers: The Highest Power Output and antenna gain in the above table are provided by the customer			

5.2. Calculation Information

For conservative evaluation consideration, only maximum power of each frequency band based on the tighter limits respectively are used to calculate the boundary power density.

Based on the FCC KDB 447498 D01 and 47 CFR §2.1091, the DUT is evaluated as a mobile device.

$$S = \frac{PG}{4\pi d^2}$$

Where

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power density in milliwatts / square centimeter



Report NO.: I22W00023-MPE

5.3. Results

Frequency range	Limit(mW/cm ²)	Results(mW/cm ²)	Verdict
WCDMA Band 5	0.55	0.25	Pass
LTE Band 4	1.00	0.29	Pass

Chongqing Academy of Information and Communication Technology

Address: No. 8,Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China,401336
Tel: 0086-23-88069965 FAX:0086-23-88608777

5.4. Result of WCDMA Band 5

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 826.40 MHz~846.60 MHz;
The maximum conducted is 25.00 dBm. The maximum gain is 6.00 dBi. Therefore, maximum limit for general public RF exposure: $826.4/1500=0.55 \text{ mW/cm}^2$.

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (316.23 mW)

G = antenna gain (3.98numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(316.23*3.98)/(4\pi*20^2)=0.25 \text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 0.55 mW/cm^2 limit for uncontrolled exposure.

5.5. Result of LTE Band 4

Test Results: MPE Limit Calculation: the EUT'S operating frequencies @ 1710.0 MHz~1754.9MHz; The maximum conducted is 25.70 dBm. The maximum gain is 6.00 dBi. Therefore, maximum limit for general public RF exposure: 1.00 mW/cm^2 .

$$S = \frac{PG}{4\pi d^2}$$

P= input power of the antenna (371.54 mW)

G = antenna gain (3.98 numeric)

r = distance to the center of radiation of antenna (in meter)=20 cm

$$S=(371.54*3.98)/(4\pi*20^2)=0.29 \text{ mW/cm}^2$$

Therefore, at 20 cm the spectral power density is less than the 1.0 mW/cm^2 limit for uncontrolled exposure.



Report NO.: I22W00023-MPE

ANNEX A: EUT photograph

See the document "LTE MODULE -External Photos".

*****END OF REPORT*****

Chongqing Academy of Information and Communication Technology

Address: No. 8, Yuma Road, Chayuan New City, Nan'an District, Chongqing, P. R. China, 401336
Tel: 0086-23-88069965 FAX: 0086-23-88608777