

RF Exposure Evaluation

REQUIREMENT

KDB 447498 D04 Interim General RF Exposure Guidance v01

Appendix B Exemptions for Single RF Sources

B.3 MPE-based Exemption and B.4 SAR-based Exemption:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \tag{B.1}$$

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \tag{B.2}$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

TEST RESULT

☒ Passed ☐ Not Applicable

| Radio Type | Frequency (MHz) | Conducted Power(dBm) | Conducted Maximum Tune-up(dBm) | Ant Gain(dBi) | Maximum ERP/EIRP (dBm) | Maximum ERP/EIRP (mW) | Minimum Separation Distance(mm) | Pth* (mW) |
|------------|-----------------|----------------------|--------------------------------|---------------|------------------------|-----------------------|---------------------------------|-----------|
| Bluetooth | 2402 | -1.66 | -1.60 | 2.5 | 0.90 | 1.230 | 0 | 2.788 |

Note:

- 1) The safety distance for body exposure assessment is 0mm
- 2) *: when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.