

# TEST REPORT

**Product Name** : 610 (BT) balance car  
KD 3660PA/ KD 3660PA-2/ RT610/  
HOVER25T-XXX / HOVER2020B-XXX/  
HOVER3030B-XXX/ HOVER4040HB-V1/  
HOVER4040HB-V2/ HOVER4040HB-XXX/  
HOVER4040HT-XXX/ HOVER4040K-XXX/  
HOVER5050B-XXX/ HOVER7050-XXX/  
**Model Number** : HOVERC2040-XXX/ AHO629373-XXX/  
AHO629JUS-XXX/ HOVER2040S-XXX/  
HOVER2040F-XXX/ HOVER2050-XXX/  
HOVER3050-XXX/ HOVER3055-XXX  
(X can be letter A to Z indicate appearance  
color are identical to each other except model  
name, color of appearance and package  
artwork for trading purpose.)  
**FCC ID** : 2APO6OTTO610

**Prepared for** : SHENZHEN OTTO INTELLIGENCE TECHNOLOGY CO  
LTD

**Address** : RM.101-102, BLDG, F13, F518 IDEA LAND, NO: 1065  
BAOYUAN RD, XLXLANG AVENUE, BAO-AN,  
SHENZHEN, CHINA

**Prepared by** : EMTEK (DONGGUAN) CO., LTD.  
**Address** : -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology  
Research and Development Base, No.9, Xincheng Avenue,  
Songshanhu High-technology Industrial Development Zone,  
Dongguan, Guangdong, China

TEL: +86-0769-22807078  
FAX: +86-0769-22807079

**Report Number** : EDG2207190089E00202R  
**Date(s) of Tests** : September 26, 2022 to October 9, 2022  
**Date of issue** : October 9, 2022

## Table of Contents

1. TEST RESULT CERTIFICATION .....	3
2. EUT SPECIFICATION .....	5
3. TEST REQUIREMENT: .....	6
RF EXPOSURE EVALUATION .....	6
4. MEASUREMENT RESULT .....	7



## 1. TEST RESULT CERTIFICATION

Applicant : SHENZHEN OTTO INTELLIGENCE TECHNOLOGY CO LTD

Address : RM.101-102, BLDG, F13, F518 IDEA LAND, NO: 1065 BAOYUAN RD,  
XLXLANG AVENUE, BAO-AN, SHENZHEN, CHINA

Manufacturer : Zhejiang Chic Robot Technology Co., Ltd.

Address : 3rd Floor, #1 Plant, 468 Xinji Road, Qiu Bin Neighborhood, Wucheng District,  
Jinhua City, Zhejiang Province, People's Republic of China

EUT : 610 (BT) balance car  
KD 3660PA/ KD 3660PA-2/ RT610/ HOVER25T-XXX / HOVER2020B-XXX/  
HOVER3030B-XXX/ HOVER4040HB-V1/ HOVER4040HB-V2/  
HOVER4040HB-XXX/ HOVER4040HT-XXX/ HOVER4040K-XXX/  
HOVER5050B-XXX/ HOVER7050-XXX/ HOVERC2040-XXX/

Model Name : AHO629373-XXX/ AHO629JUS-XXX/ HOVER2040S-XXX/ HOVER2040F-XXX/  
HOVER2050-XXX/ HOVER3050-XXX/ HOVER3055-XXX  
(X can be letter A to Z indicate appearance color are identical to each other  
except model name, color of appearance and package artwork for trading  
purpose.)

Trademark : N/A

Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
§ 15.247(i), § 2.1093	PASS

The above equipment was tested by EMTEK(DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules FCC § 15.247(i), § 2.1093.

The test results of this report relate only to the tested sample identified in this report

Date of Test : September 26, 2022 to October 9, 2022

Prepared by :

*Warren Deng*

Warren Deng /Editor

Reviewer :

*Tim Dong*

Tim Dong/ Supervisor

Approve & Authorized Signer :

*Sam Lv* / Manager

Modified History

Version	Report No.	Revision Date	Summary
	EDG2207190089E00202R	/	Original Report



## 2. EUT Specification

Characteristics	Description
<b>Product:</b>	610 (BT) balance car
<b>Model Number:</b>	<p>KD 3660PA/ KD 3660PA-2/ RT610/ HOVER25T-XXX / HOVER2020B-XXX/ HOVER3030B-XXX/ HOVER4040HB-V1/ HOVER4040HB-V2/ HOVER4040HB-XXX/ HOVER4040HT-XXX/ HOVER4040K-XXX/ HOVER5050B-XXX/ HOVER7050-XXX/ HOVERC2040-XXX/ AHO629373-XXX/ AHO629JUS-XXX/ HOVER2040S-XXX/ HOVER2040F-XXX/ HOVER2050-XXX/ HOVER3050-XXX/ HOVER3055-XXX</p> <p>(X can be letter A to Z indicate appearance color are identical to each other except model name, color of appearance and package artwork for trading purpose.)</p> <p>These model are the same expect the model name and appearance, Here select HOVER25T-PUR for test.</p>
<b>Sample:</b>	1#
<b>Device Type:</b>	Bluetooth V5.0
<b>Data Rate:</b>	<p>1Mbps for GFSK modulation</p> <p>2Mbps for <math>\pi/4</math>-DQPSK modulation</p> <p>3Mbps for 8DPSK modulation</p>
<b>Modulation:</b>	GFSK, $\pi/4$ -DQPSK, 8DPSK
<b>Operating Frequency Range(s) :</b>	2402-2480MHz
<b>Number of Channels:</b>	79 channels
<b>Transmit Power Max:</b>	-0.1 dBm(0.000977W)
<b>Antenna Gain:</b>	-0.84 dBi
<b>Power supply:</b>	<p>DC 42.0V from Adapter</p> <p>36V 2AH from battery</p>
<b>Evaluation applied:</b>	<p><input checked="" type="checkbox"/> MPE Evaluation</p> <p><input type="checkbox"/> SAR Evaluation</p>

### 3. Test Requirement:

## RF EXPOSURE EVALUATION

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{24} \text{ where}$$

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>25</sup>
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval. One antenna is available for the EUT. The minimum separation distance is 5mm.

## 4. Measurement Result

Antenna gain:-0.58 dBi

Transmit Frequency(MHz)	Mode	Measured Power (dBm)	Tune upPower (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR
2402	GFSK	-1.61	-2±1	-1	0.2462	3
2441	GFSK	-1.48	-2±1	-1	0.2482	3
2480	GFSK	-1.79	-2±1	-1	0.2502	3
2402	Π/4-DQPSK	-0.74	-1±1	0	0.3100	3
2441	Π/4-DQPSK	-0.56	-1±1	0	0.3125	3
2480	Π/4-DQPSK	-0.92	-1±1	0	0.3150	3
2402	8DPSK	-0.25	-1±1	0	0.3100	3
2441	8DPSK	-0.1	-1±1	0	0.3125	3
2480	8DPSK	-0.5	-1±1	0	0.3150	3

According to KDB 447498, no stand-alone required for BT antenna, and no simultaneous SAR measurement is required.

\*\*\* End of Report \*\*\*