

1/18/2024

Lutron Electronics Co., Inc.
7200 Suter Rd.
Coopersburg, PA 18036
USA

Dear Keith Kennedy,

Enclosed is the EMC test report for testing of the Lutron Electronics Co., Inc., UN-D2MEMTRXX tested to the requirements of FCC Part 2.1091 and RSS-102 Issue 6

Thank you for using the services of Eurofins E&E North America. If you have any questions regarding these results or if MET can be of further service to you, please do feel free to contact me.

Sincerely,



Nancy LaBrecque
Documentation Department
Eurofins Electrical and Electronic Testing NA, Inc.

Reference: WIRA130151-MPE



Certificates and reports shall not be reproduced except in full, without the written permission of Eurofins E&E North America. While use of the A2LA logo in this report reflects MET accreditation under these programs, the report must not be used by the client to claim product certification, approval, or endorsement by A2LA or any agency of the Federal Government. This letter of transmittal is not a part of the attached report.

Eurofins MET Laboratories Inc. (Eurofins E&E North America) is part of the Eurofins Electrical & Electronics (E&E) global compliance network.

**RF Exposure Criteria
Test Report
Using Maximum Permissible Exposure (MPE) Calculations**

for the

Lutron Electronics Co., Inc.
UN-D2MEMTRXX

Tested under

FCC Part 2.1091 and RSS-102 Issue 6

Report: WIRA130151-MPE

1/18/2024



Bryan Taylor, Wireless Team Lead
Electromagnetic Compatibility Lab



Nancy LaBrecque
Documentation Department

Engineering Statement: The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 under normal use and maintenance.



Matthew Hinojosa
EMC Manager, Austin Electromagnetic Compatibility Lab

Report Status Sheet

Revision	Report Date	Reason for Revision
0	1/18/2024	Initial Issue.

Table of Contents

1.0 Requirements Summary
2.0 Equipment Configuration
2.1 Overview.....
2.2 Test Site
2.3 References.....
2.4 Description of Test Sample.....
2.5 Modifications
2.5.1 Modifications to EUT
2.5.2 Modifications to Test Standard.....
2.6 Disposition of EUT
3.0 Transmitter Requirements.....

8
9
9
10
10
10
10
10
10
10
10
11

List of Tables

Table 1. Summary of Test Results 8

Table 2. EUT Summary Table 9

Table 3. References 10

List of Terms and Abbreviations

AC	Alternating Current
ACF	Antenna Correction Factor
Cal	Calibration
<i>d</i>	Measurement Distance
dB	Decibels
dBμA	Decibels above one microamp
dBμV	Decibels above one microvolt
dBμA/m	Decibels above one microamp per meter
dBμV/m	Decibels above one microvolt per meter
DC	Direct Current
E	Electric Field
DSL	Digital Subscriber Line
ESD	Electrostatic Discharge
EUT	Equipment Under Test
<i>f</i>	Frequency
CISPR	Comite International Special des Perturbations Radioelectriques (International Special Committee on Radio Interference)
GRP	Ground Reference Plane
H	Magnetic Field
HCP	Horizontal Coupling Plane
Hz	Hertz
IEC	International Electrotechnical Commission
kHz	kiloHertz
kPa	kiloPascal
kV	kilovolt
LISN	Line Impedance Stabilization Network
MHz	MegaHertz
μH	microHenry
μF	microFarad
μs	microseconds
PRF	Pulse Repetition Frequency
RF	Radio Frequency
RMS	Root-Mean-Square
V/m	Volts per meter
VCP	Vertical Coupling Plane

1.0 Requirements Summary

Page Number	Test Name	Result
11	RSS-102 Issue 5 MPE Limits (For General Public Exposure)	Compliant
11	FCC Part 2.1091 MPE Limits (For General Public Exposure)	Compliant

Table 1. Summary of Test Results

2.0 Equipment Configuration

2.1 Overview

Eurofins MET Labs was contracted by Lutron Electronics Co., Inc. to perform testing on the UN-D2MEMTRXX, under Lutron Electronics Co., Inc.'s purchase order number 5317304.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Lutron Electronics Co., Inc. UN-D2MEMTRXX.

The results obtained relate only to the item(s) tested.

Model(s) Tested:	UN-D2MEMTRXX	
Model(s) Covered:	UN-D2MEMTRXX	
EUT Specifications:	Primary Power: 18 – 20VDC	
	Antenna Gain ¹ :	5dBi
	EUT Frequency Ranges:	BLE: 2402 – 2480MHz 802.15.4: 2405 – 2480MHz
	Maximum Conducted Output Power:	BLE: 10.37dBm 802.15.4: 18.99dBm
Analysis:	The results obtained relate only to the item(s) tested.	
Environmental Test Conditions:	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
Type of Filing:	Original	
Evaluated by:	Bryan Taylor	
Report Date(s):	12/21/2023 through 1/17/2024	

Table 2. EUT Summary Table

¹ The antenna gain information was provided by Lutron Electronics Co., Inc. at the time of testing.

2.2 Test Site

All testing was performed at Eurofins E&E North America, Austin, TX. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

2.3 References

RSS-102: Issue 6	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)
FCC Part 2.1091	Radiofrequency radiation exposure evaluation: mobile devices.

Table 3. References

2.4 Description of Test Sample

The EUT is a DC voltage, fully color tunable, dimmable LED product with integrated wireless communication. It contains a RF transceiver (EFR32MG24) with a reference crystal (38.4MHz) and an antenna that cannot be changed by the user. The device is used as part of an integrated lighting system. The purpose of the wireless communication is to send commands to and receive status information back from a control system.

2.5 Modifications

2.5.1 Modifications to EUT

No modifications were made to the EUT.

2.5.2 Modifications to Test Standard

No modifications were made to the test standard.

2.6 Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Lutron Electronics Co., Inc. upon completion of testing.

3.0 Maximum Permissible Exposure Results

3.1 RSS-102 RF Exposure Limits

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range (MHz)	Electric Field (V/m rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Reference Period (minutes)
0.003-10 ²¹	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/f ^{1.2}
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.2 FCC Exposure Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30
f = frequency in MHz. * = Plane-wave equivalent power density.				

Test Procedure:

An MPE evaluation for was performed in order to show that the device was compliant with the general population exposure limits. The maximum power density was calculated for each transmitter band at a separation distance of 20cm using the maximum declared output power including tune up tolerance.

For each transmitter the maximum RF exposure at a 20 cm distance using the formula:

$$ConductedPower_{mW} = 10^{ConductedPower(dBm)/10}$$

$$PowerDensity = \frac{ConductedPower_{mW} \times Ant.Gain}{4\pi \times (20_{cm})^2}$$

For transmitters that could operate simultaneously, the MPE to limit ratio for each was calculated and then summed. If the sum of the MPE to limit ratios was less than 1, that specific combination of transmitters was deemed to comply.

Test Results:

The Universal D2 Module Emitter was **compliant** with FCC Part 2.1091 and RSS-102 Issue 6. The calculated maximum power density at 20cm distance was equal to or less than the required limits for general population exposure for FCC Part 2.1091 and RSS-102 Issue 6. Additionally, the sum of the worst case for each MPE to Limit ratio is less than 1 indicating that all radios may transmit simultaneously.

Test Data:

Duty Cycle	100 (%)							
Separation Dist.	20 (cm)							
Operating Mode	Frequency (MHz)	Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (mW/cm ²)	MPE Limit (mW/cm ²)	Margin to Limit (mW/cm ²)	MPE / Limit Ratio (for Co-Location)
802.15.4	2405	18.99	18.99	5	0.0499	1.0000	0.9501	0.0499
BLE	2402	10.37	10.37	5	0.0069	1.0000	0.9931	0.0069
							Sum:	0.0567

FCC MPE Data

Duty Cycle	100 (%)							
Separation Dist.	20 (cm)							
Operating Mode	Frequency (MHz)	Declared Max Cond. Power (Inc. Tolerance) (dBm)	Duty Cycle Adjusted Cond. Output Power (dBm)	Antenna Gain (dB)	MPE Value (W/m ²)	MPE Limit (W/m ²)	Margin to Limit (W/m ²)	MPE / Limit Ratio (for Co-Location)
802.15.4	2405	18.99	18.99	5	0.4986	5.3554	4.8568	0.0931
BLE	2402	10.37	10.37	5	0.0685	5.3508	5.2823	0.0128
							Sum:	0.1059

ISED MPE Data

Test Engineer(s): Bryan Taylor

Test Date(s): 1/16/2024