

# A Test Lab Techno Corp.

Changan Lab: No. 140 -1, Changan Street, Bade City, Taoyuan County, Taiwan R.O.C.

Tel: 886-3-271-0188 / Fax: 886-3-271-0190

## **SAR Test Exclusion Evaluation**





Test Report No. : 1412FS15

Applicant : Marson Technology Co., Ltd.

Manufacturer : Marson Technology Co., Ltd.

Trade Name : MARSON

Product Type

Model Number : MT7937A

Dates of Received : Dec. 01, 2014

Dates of Test : Dec. 23, 2014

Dates of Issued : Dec. 23, 2014

Test Specification : 47 CFR § 2.1093

IEEE Std. 1528-2013 IEEE Std. 1528a-2005

: Wireless Barcode Scanner

KDB 447498 D01 General RF Exposure Guidance v05r02

KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r03

KDB 865664 D02 RF Exposure Reporting v01r01

Location of Test Lab. : Chang-an Lab.

- 1. The test operations have to be performed with cautious behavior, the test results are as attached.
- 2. The test results are under chamber environment of A Test Lab Techno Corp. A Test Lab Techno Corp. does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples.
- 3. The measurement report has to be written approval of A Test Lab Techno Corp. It may only be reproduced or published in full. This report shall not be reproduced except in full, without the written approval of A Test Lab Techno Corp.
- 4. This document may be altered or revised by A Test Lab Techno. Corp. personnel only, and shall be noted in the revision section of the document.

Approved By

Tested By

(Sky Chou)

Report Number: 1412FS15 Page 1 of 5



## **Contents**

1.	Description of Equipment under Test (EUT)					
2.	SAR	Test Exclusion	4			
	2.1	Antenna Distance	4			
	2.2	Conducted Power	4			
	23	Evaluation Results	5			



## 1. Description of Equipment under Test (EUT)

Applicant	Marson Technology Co., Ltd.				
Applicant Address	9F., No.108-3, Mincyuan Rd., Sindian Dist., New Taipei City 23141, TAIWAN				
Manufacturer	Marson Technology Co.,Ltd.				
Manufacturer Address	ufacturer Address 9F., No.108-3, Mincyuan Rd., Sindian Dist., New Taipei City 23141, TAIWAN				
Product Type	Wireless Barcode Scanner				
Trade Name	MARSON				
Model Number	MT7937A				
FCC ID IRJ-MT7937A					
Frequency Range	2402 - 2480 MHz (Bluetooth v2.0)				
Transmit Power	Dond	Power			
(Avg. conducted power)	Band	mW	dBm		
	Bluetooth v2.0	0.005	7.00		
Antenna Specification	2 dBi				
Antenna Designation chip Antenna					

The above equipment was tested by A Test Lab Techno Corp. For compliance with the requirements set forth in 47 CFR § 2.1093. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Report Number: 1412FS15 Page 3 of 5



### 2. SAR Test Exclusion

As RF exposure evaluation of portable device, SAR test is not required when the evaluation results . According to KDB 447498 4.3.1, unless excluded by specific FCC test procedures, portable devices shall include SAR data for equipment approval. SAR test necessity will be based on the exclusion result.

The test exclusion refers KDB 447498 as below:

#### ≤50mm:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f(GHz)}$ ]  $\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR

#### 2.1 Antenna Distance

Distance of Antenna to edge					
Antenna	Side	Distance (mm)			
Bluetooth	Side 1	5mm			
Bluetooth	Side 2	5mm			
Bluetooth	Side 3	5mm			
Bluetooth	Side 4	5mm			
Bluetooth	Side 5	5mm			
Bluetooth	Side 6	5mm			

#### 2.2 Conducted Power

Band	СН	Frequency (MHz)	Packet Type	RF Conducted Output Power (dBm)		
		(1711 12)	туре	Average		
	0	2402.0		7.00		
Bluetooth v2.0	19 2440.0			6.48		
	39	2480.0		6.95		

Report Number: 1412FS15 Page 4 of 5



### 2.3 Evaluation Results

The evaluation of SAR test reduction according to KDB447498

SAR test is not required when the results showed "SAR is not required".

Transmitter and antenna implementation as below:

Band	Antenna			
Bluetooth v2.0	V			

≤ 50 mm									
Band	Side	Power	Frequency	distance	Power	Result	Result	Limit	Exclusion considerations
'		(dBm)	(GHz)	(mm)	(mW)			SAR <sub>1g</sub>	
	1	7.5	2.402	5	6	1.9	3	SAR is not required	
	2	7.5	2.402	5	6	1.9	3	SAR is not required	
Bluetooth v2.0	3	7.5	2.402	5	6	1.9	3	SAR is not required	
Bidelootii v2.0	4	7.5	2.402	5	6	1.9	3	SAR is not required	
	5	7.5	2.402	5	6	1.9	3	SAR is not required	
	6	7.5	2.402	5	6	1.9	3	SAR is not required	

The assessment result Stand-alone SAR is not required.

Report Number: 1412FS15 Page 5 of 5