

F		E		D		C		B		A	
				REV.	MARK	ECR/ECN NO.	DATE	UPDATE DESCRIPTION		SIGNATURE	
				00	N/A	N/A	13.12.20	First Release		yanfen	

41

technicolor

technicolor

Model : TC8717T

Rating : 120V AC, 60Hz, 1.2A

FCC ID : RSE-TC8717T

FC

UL

LISTED

I.T.E.

E199598

WiFi

CERTIFIED

WI-FI PROTECTED SETUP

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
(1) this device may not cause harmful interference, and
(2) this device must accept any interference received, including interference that may cause undesired operation.

Factory ID: Y

Made in Vietnam

59,5

74,5

R2,5

3

3

車縫線

Package style
scale: 1:2

NOTES:

1. Surface Material: 50# 壓花 Mylar (matte white)

* 2. Surface Material tolerance: 0.052±0.004mm

3. Surface Material color: white

4. printing color is as color defined in artwork

5. Adhesive base: Synthetic Resin

* 6. Adhesive thickness: 0.033±0.003mm

* 7. Adhesion to steel (180# 磨鋼粘着力): 1.0-2.2 kg/inch

* 8. Initial Tack (初期力): 1-6#

9. Release Power (90# 剥离力): 4-20 g/in

* 10. Holding Power (持粘力測試法): minimum 1hr/kg*inch2

11. Package Style: Reel

12. When label is adhesived on housing smooth face (material ABS) after it is tested under test condition -40~70℃ 90%R.H. 72hrs, it must be fine.

13. This part must comply with ROHS.

MATERIAL (SPEC.)										SCALE 1:1		FOXCONN HON HAI PRECISION IND. CO., LTD. CNSBG		
FINISH N/A										SHEET 1/1				
Select										UNIT MM	PART NAME Product Information label			
Dim.	Tol.	A	B	C	EPS	EPE	BAG	CTN	Label					USR
0~6	0.05	0.05	0.10						0.20					
6~30	0.10	0.15	0.20	0.50	0.50	3.00			0.20					
30~120	0.15	0.20	0.30	0.50	0.50	5.00	2.00	0.25						
120~300	0.20	0.30	0.40	1.00	1.00	10.00	3.00	0.30						
300~450	0.25	0.40	0.50	2.00	2.00	15.00	5.00	0.50						
450~600	0.30	0.50	0.60	3.00	3.00	20.00	5.00	0.80						
DRAFT TOLERANCE ±0.2° CRITICAL DIM. MARK *										SIZE A4	MODEL U46C222.09		PART NO. 500.01684.005	DESIGNED yanfen
											CUSTOMER MODEL TC8717T		CUSTOMER PART NO.	APPROVED Sunny