

FCC PART 24 TEST REPORT			
	Part 24 Subpart E		
Report Reference No.:	CTL1507031826-WF-3		
Compiled by: (position+printed name+signature)	Jacky Chen (File administrators)	Jackychen	
Tested by: (position+printed name+signature)	Allen Wang (Test Engineer)	Allen Wang	
Approved by: (position+printed name+signature)	Tracy Qi (Manager)	hung Ch:	
Product Name:	LTE WiFi Router	-14	
Model/Type reference	T-N100	1	
List Model(s)	NE ATTAIN	-	
Trade Mark		H H	
FCC ID	XYOT-N100	1	
Applicant's name	Asiatelco Technologies Co.	3	
Address of applicant	#289 Bisheng Road, Building-8, 3F, 3 Pudong, Shanghai 201204, China	Zhangjiang Hi-Tech Park,	
Test Firm	Shenzhen CTL Testing Technolog	y Co., Ltd.	
Address of Test Firm	Floor 1-A, Baisha Technology Park, District, Shenzhen, China 518055	No.3011, Shahexi Road, Nanshan	
Test specification	esting les		
Standard:	FCC CFR Title 47 Part 2, Part 24E EIA/TIA 603-D: 2010 KDB 971168 D01		
TRF Originator	Shenzhen CTL Testing Technology	Co., Ltd.	
Master TRF:	Dated 2011-01		
Date of Receipt	July 05, 2015		
Date of Test Date	July 07, 2015 - July 14, 2015		
Data of Issue	July 16, 2015		
Result:	Positive		
Shenzhen CTL Testing Technology Co., Ltd. All rights reserved. This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.			

TEST REPORT

Test Report No. :	CTL	.1507031826-WF-3	July. 16, 2015
Equipment under Test		LTE WiFi Router	
моаеі / Гуре	:	1-N1UU	
Listed Models	:	/	
Applicant	:	Asiatelco Technologies	s Co.
Address	:	#289 Bisheng Road, Buil Park, Pudong, Shanghai	lding-8, 3F, Zhangjiang Hi-Tech 201204, China
Manufacturer	:	Asiatelco Technologies	s Co.
Address	:	#289 Bisheng Road, Buil Park, Pudong, Shanghai	lding-8, 3F, Zhangjiang Hi-Tech 201204, China

Test result	Pass *
-------------	--------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

** Modifited History **

Revision	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2015-07-16	CTL1507031826-WF-3	Tracy Qi

Contents

<u>1</u>	SUMMARY	5
		F
1.1	Test Description	ວ ເ
1.2	Test Description	5
1.3	lest Facility	6
1.4	Statement of the measurement uncertainty	0
<u>2</u>	GENERAL INFORMATION	7
2.1	Environmental conditions	7
2.2	General Description of EUT	7
2.3	Description of Test Modes	8
2.4	Equipments Used during the Test	8
2.5	Related Submittal(s) / Grant (s)	8
2.6	Modifications	8
<u>3</u>	TEST CONDITIONS AND RESULTS	9
3.1	Output Power	9
3.3	Peak-to-Average Ratio (PAR)	14
3.4	Occupied Bandwidth and Emission Bandwidth	21
3.5	Band Edge compliance	28
3.6	Spurious Emission	35
3.7	Frequency Stability under Temperature & Voltage Variations	61
<u>4</u>	TEST SETUP PHOTOS OF THE EUT	63
<u>5</u>	EXTERNAL AND INTERNAL PHOTOS OF THE EUT	64

1 <u>SUMMARY</u>

1.1 TEST STANDARDS

The tests were performed according to following standards: <u>FCC Part 24</u> :PUBLIC MOBILE SERVICES

TIA/EIA 603 D June 2010:Land Mobile FM or PM Communications Equipment Measurement and Performance Standards.

FCC Part 2: FREQUENCY ALLOCA-TIONS AND RADIO TREATY MAT-TERS; GENERAL RULES AND REG-ULATIONS

KDB971168 D01: v02r02 MEASUREMENT GUIDANCE FOR CERTIFICATION OF LICENSED DIGITAL TRANSMITTERS

ANSI C63.4: 2009 Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

1.2 Test Description

Test Item	Section in CFR 47	Result
RF Output Power	Part 2.1046 Part 24.232 (c)	Pass
Peak-to-Average Ratio	Part 24.232 (d)	Pass
99% & -26 dB Occupied Bandwidth	Part 2.1049 Part 24.238	Pass
Spurious Emissions at Antenna Terminal	Part 2.1051 Part 24.238 (a)	Pass
Field Strength of Spurious Radiation	Part 2.1053 Part 24.238 (a)	Pass
Out of band emission, Band Edge	Part 22.917 (a) Part 24.238 (a)	Pass
Frequency stability	Part 2.1055 Part 24.235	Pass

1.3 Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd. Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

1.4 Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

	1 2	/ /	
Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

Hereafter the best measurement capability for CTL laboratory is reported:

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2 GENERAL INFORMATION

2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2 General Description of EUT

Product Name:	LTE WiFi Router
Model/Type reference:	T-N100
Power supply:	DC 3.7V from battery or DC 12V from adapter
Serial number:	Prototype
Adapter information:	Model:C1000 Input: 100-240V, 50/60Hz 0.45A Output:12V1.0A
Hardware version:	725-0335-001-01
Software version:	V1.1
WIFI	
Supported type:	802.11b/802.11g/802.11n(H20)/802.11n(H40)
Modulation:	802.11b: DSSS 802.11g/802.11n(H20)/802.11n(H40): OFDM
Operation frequency:	802.11b/802.11g/802.11n(H20): 2412MHz~2462MHz 802.11n(H40): 2422MHz~2452MHz
Channel number:	802.11b/802.11g/802.11n(H20): 11 802.11n(H40): 7
Channel separation:	5MHz
Antenna type:	PCB Antenna : 2*TX 2*RX
Antenna gain:	2.0dBi
3G	
Our set in David	BC0 TX: 824.70 MHz ~ 848.31 MHz BC1 TX:1851.25 MHz ~ 1908.75 MHz
Operation Band:	BC0 RX: 869.70 MHz ~ 893.31 MHz BC1 RX: 1931.25 MHz ~ 1988.75 MHz
Supported Type:	CDMA2000 1xRTT/ CDMA2000 1xEv-DO-Release 0/ CDMA2000 1xEv- DO-Revision A
Modulation Type:	QPSK
Antenna Type:	External omni-antenna: 1*TX 2*RX
Antenna Gain:	ZdBi
	TD TE: Pond 41
Operation Band:	FDD-LTE: Band 2/4/5/12/13/25/26
Modulation Type:	QPSK, 16QAM
Release Version:	Release 9
Category:	Cat 3
Antenna Type:	External Omni-antenna: 1*TX 2*RX
Antenna gain:	2.0dBi

Note: For more details, refer to the user's manual of the EUT.

2.3 Description of Test Modes

The EUT has been tested under typical operating condition. The CMW500 used to control the EUT staying in continuous transmitting and receiving mode for testing. Regards to the frequency band operation: the lowest, middle and highest frequency of channel were selected to perform the test, then shown on this report. Note:

- 1. All tests performed with alternate AC power sulpply and DC power supply , recorded the worst case at AC mode except frequency stability test.
- 2. Test method and refer to 3GPP TS136521.

2.4 Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	2016/06/01
Bilog Antenna	Sunol Sciences Corp.	JB1	A061714	2015/06/02	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	2016/06/01
Spectrum Analyzer	Agilent	E4407B	MY41440676	2015/05/21	2016/05/20
Spectrum Analyzer	Agilent	N9030A	MY51380383	2015/05/21	2016/05/20
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/18
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062014	2015/05/19	2016/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2015/05/19	2016/05/18
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/18
Temperature/Humidi ty Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/19
Radio Communication Tester	R&S	CMU200	115419	2015/05/22	2016/05/21
Wideband Radio Communication Tester	R&S	CMW500	101814	2014/11/23	2015/11/22
High-Pass Filter	K&L	9SH10- 2700/X12750- O/O	N/A	2015/05/20	2016/05/19
High-Pass Filter	K&L	41H10- 1375/U12750- O/O	N/A	2015/05/20	2016/05/19
RF Cable	HUBER+SUHNE R	RG214	N/A	2015/05/20	2016/05/19
Climate Chamber	ESPEC	EL-10KA	A20120523	2015/05/20	2016/05/19
SIGNAL	Agilent	E4421B	US40051744	2015/05/20	2016/05/19
Directional Coupler	Agilent	87300B	3116A03638	2015/05/20	2016/05/19

2.5 Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: XYOT-N100 filing to comply with of the FCC Part 24 Rules.

2.6 Modifications

No modifications were implemented to meet testing criteria.

3 TEST CONDITIONS AND RESULTS

3.1 Output Power

<u>LIMIT</u>

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p.

TEST CONFIGURATION

Conducted Power Measurement



Radiated Power Measurement:



TEST PROCEDURE

The EUT was setup according to EIA/TIA 603D

Conducted Power Measurement:

- a) Place the EUT on a bench and set it in transmitting mode.
- b) Connect a low loss RF cable from the antenna port to a spectrum analyzer and CMW500 by a Directional Couple.
- c) EUT Communicate with CMW500, then select a channel for testing.
- d) Add a correction factor to the display of spectrum, and then test.

Radiated Power Measurement:

- a. The EUT shall be placed at the specified height on a support, and in the position closest to normal use as declared by provider.
- b. The test antenna shall be oriented initially for vertical polarization and shall be chosen to correspond to thefrequency of the transmitter
- c. The output of the test antenna shall be connected to the measuring receiver.
- d. The transmitter shall be switched on and the measuring receiver shall be tuned to the frequency of the transmitter under test.
- e. The test antenna shall be raised and lowered through the specified range of height until a maximum signal level is detected by the measuring receiver.
- f. The transmitter shall then be rotated through 360° in the horizontal plane, until the maximum signal level is detected by the measuring receiver.

V1.0

Page 10 of 64

- g. The test antenna shall be raised and lowered again through the specified range of height until a maximum signal level is detected by the measuring receiver.
- h. The maximum signal level detected by the measuring receiver shall be noted.
- i. The transmitter shall be replaced by a substitution antenna.
- j. The substitution antenna shall be orientated for vertical polarization and the length of the substitution antenna shall be adjusted to correspond to the frequency of the transmitter.
- k. The substitution antenna shall be connected to a calibrated signal generator.
- I. If necessary, the input attenuator setting of the measuring receiver shall be adjusted in order to increase the sensitivity of the measuring receiver.
- m. The test antenna shall be raised and lowered through the specified range of height to ensure that the maximum signal is received.
- n. The input signal to the substitution antenna shall be adjusted to the level that produces a level detected by the measuring receiver, that is equal to the level noted while the transmitter radiated power was measured, corrected for the change of input attenuator setting of the measuring receiver.
- o. The measurement shall be repeated with the test antenna and the substitution antenna orientated for horizontal polarization.
- p. The measure of the effective radiated power is the larger of the two levels recorded at the input to the substitution antenna, corrected for gain of the substitution antenna if necessary.
- q. Test site anechoic chamber refer to ANSI C63.4.

TEST RESULTS

Conducted Measurement:

LTE FDD Band 2				
TX Channel	Channel RR Size/Offset Frequency Average Power [c		ower [dBm]	
Bandwidth	RB Size/Olisel	(MHz)	QPSK	16QAM
		1850.7	22.95	21.82
	1 RB low	1880.0	22.98	22.28
		1909.3	22.25	21.46
		1850.7	22.99	22.02
	1 RB high	1880.0	23.14	22.55
	-	1909.3	22.01	21.40
1.4 IVI⊓Z		1850.7	22.84	21.89
	50% RB mid	1880.0	23.11	22.26
		1909.3	22.10	21.25
		1850.7	22.04	21.01
	100% RB	1880.0	22.80	21.71
		1909.3	21.51	20.47
		1851.5	22.50	21.74
	1 RB low	1880.0	23.02	22.09
		1908.5	21.79	21.06
	1 RB high	1851.5	22.37	21.62
		1880.0	22.98	22.35
0 MI I-		1908.5	21.86	20.90
3 IVI⊓Z	50% RB mid	1851.5	22.12	21.26
		1880.0	22.73	21.86
		1908.5	21.48	20.56
		1851.5	22.13	21.12
	100% RB	1880.0	22.74	21.70
		1908.5	21.49	20.48
		1852.5	22.76	21.75
	1 RB low	1880.0	22.84	22.14
		1907.5	21.80	20.77
		1852.5	22.50	21.92
	1 RB high	1880.0	23.24	22.45
	-	1907.5	21.81	21.22
		1852.5	22.24	21.23
	50% RB mid	1880.0	22.76	21.78
		1907.5	21.47	20.56
		1852.5	22.66	21.89
	100% RB	1880.0	22.60	21.62
		1907.5	22.24	21.32

		1855.0	22.66	21.93
	1 RB low	1880.0	23.07	22.19
		1905.0	21.35	20.95
		1855.0	22.25	21.65
	1 RB high	1880.0	23.47	22.46
10 MH 7		1905.0	22.85	21.86
		1855.0	22.72	21.86
	50% RB mid	1880.0	22.70	21.59
		1905.0	21.57	20.45
		1855.0	22.64	23.48
	100% RB	1880.0	22.36	21.56
		1905.0	21.34	21.05
		1857.5	21.97	21.22
	1 RB low	1880.0	22.44	21.60
		1902.5	21.45	20.81
	1 RB high	1857.5	22.87	20.07
		1880.0	23.10	22.05
15 MHz		1902.5	21.53	20.79
10 10112	50% RB mid	1857.5	22.88	21.56
		1880.0	22.46	21.58
		1902.5	21.89	20.78
	100% RB	1857.5	22.54	21.40
		1880.0	22.53	21.49
		1902.5	21.51	20.42
		1860.0	22.01	21.09
	1 RB low	1880.0	22.16	21.56
		1900.0	22.89	21.95
		1860.0	21.84	21.33
	1 RB high	1880.0	23.14	21.94
20 MH 7		1900.0	21.98	20.87
20 10112		1860.0	22.48	21.35
	50% RB mid	1880.0	22.59	21.52
		1900.0	21.79	20.73
		1860.0	22.42	21.53
	100% RB	1880.0	22.73	21.71
		1900.0	21.99	21.15

Radiated Measurement:

Remark:

- 1. We were tested all RB and RB offset Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2; recorded worst case for each Channel Bandwidth of LTE FDD Band 2.
- 2. $EIRP=P_{Mea}(dBm)-P_{cl}(dB)+P_{Ag}(dB)+G_{a}(dBi)$

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization		
1850.7	-17.87	3.41	10.24	33.60	22.56	33.01	10.45	Н		
1880.0	-16.64	3.49	10.24	33.60	23.71	33.01	9.30	Н		
1909.3	-16.94	3.55	10.23	33.60	23.34	33.01	9.67	Н		

LTE FDD Band 2_Channel Bandwidth 1.4MHz_QPSK

LTE FDD Band 2_Channel Bandwidth 3MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.5	-17.65	3.41	10.24	33.60	22.78	33.01	10.23	Н
1880.0	-16.29	3.49	10.24	33.60	24.06	33.01	8.95	Н
1908.5	-16.39	3.55	10.23	33.60	23.89	33.01	9.12	Н

LTE FDD Band 2_Channel Bandwidth 5MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.5	-17.45	3.41	10.24	33.60	22.98	33.01	10.03	Н
1880.0	-15.78	3.49	10.24	33.60	24.57	33.01	8.44	Н
1907.5	-16.05	3.55	10.23	33.60	24.23	33.01	8.78	Н

LTE FDD Band 2_Channel Bandwidth 10MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.0	-17.62	3.41	10.24	33.60	22.81	33.01	10.20	Н
1880.0	-16.15	3.49	10.24	33.60	24.20	33.01	8.81	Н
1905.0	-16.31	3.55	10.23	33.60	23.97	33.01	9.04	Н

LTE FDD Band 2_Channel Bandwidth 15MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.5	-17.81	3.41	10.24	33.60	22.62	33.01	10.39	Н
1880.0	-16.40	3.49	10.24	33.60	23.95	33.01	9.06	Н
1902.5	-16.80	3.55	10.23	33.60	23.48	33.01	9.53	Н

LTE FDD Band 2_Channel Bandwidth 20MHz_QPSK

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.0	-18.00	3.41	10.24	33.60	22.43	33.01	10.58	Н
1880.0	-16.77	3.49	10.24	33.60	23.58	33.01	9.43	Н
1900.0	-17.21	3.55	10.23	33.60	23.07	33.01	9.94	Н

LTE FDD Band 2_Channel Bandwidth 1.4MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1850.7	-19.24	3.41	10.24	33.60	21.19	33.01	11.82	Н
1880.0	-17.88	3.49	10.24	33.60	22.47	33.01	10.54	Н
1909.3	-18.24	3.55	10.23	33.60	22.04	33.01	10.97	Н

LTE FDD Band 2_Channel Bandwidth 3MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1851.5	-19.08	3.41	10.24	33.60	21.35	33.01	11.66	Н
1880.0	-17.58	3.49	10.24	33.60	22.77	33.01	10.24	Н
1908.5	-17.99	3.55	10.23	33.60	22.29	33.01	10.72	Н

LTE FDD Band 2_Channel Bandwidth 5MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1852.5	-18.87	3.41	10.24	33.60	21.56	33.01	11.45	Н
1880.0	-17.37	3.49	10.24	33.60	22.98	33.01	10.03	Н
1907.5	-17.74	3.55	10.23	33.60	22.54	33.01	10.47	Н

LTE FDD Band 2_Channel Bandwidth 10MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1855.0	-18.93	3.41	10.24	33.60	21.50	33.01	11.51	Н
1880.0	-17.56	3.49	10.24	33.60	22.79	33.01	10.22	Н
1905.0	-17.81	3.55	10.23	33.60	22.47	33.01	10.54	Н

LTE FDD Band 2_Channel Bandwidth 15MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1857.5	-19.13	3.41	10.24	33.60	21.30	33.01	11.71	Н
1880.0	-17.79	3.49	10.24	33.60	22.56	33.01	10.45	Н
1902.5	-18.10	3.55	10.23	33.60	22.18	33.01	10.83	Н

LTE FDD Band 2_Channel Bandwidth 20MHz_16QAM

Frequency (MHz)	P _{Mea} (dBm)	P _{cl} (dB)	G _a Antenna Gain(dB)	P _{Ag} (dB)	EIRP (dBm)	Limit (dBm)	Margin (dB)	Polarization
1860.0	-19.54	3.41	10.24	33.60	20.89	33.01	12.12	Н
1880.0	-18.38	3.49	10.24	33.60	21.97	33.01	11.04	Н
1900.0	-18.83	3.55	10.23	33.60	21.45	33.01	11.56	Н

3.3 Peak-to-Average Ratio (PAR)

<u>LIMIT</u>

The Peak-to-Average Ratio (PAR) of the transmission may not exceed 13 dB.

TEST CONFIGURATION



TEST PROCEDURE

- 1. Refer to instrument's analyzer instruction manual for details on how to use the power statistics/CCDF function;
- 2. Set resolution/measurement bandwidth ≥ signal's occupied bandwidth;
- 3. Set the number of counts to a value that stabilizes the measured CCDF curve;
- 4. Set the measurement interval as follows:
- 1). for continuous transmissions, set to 1 ms,

2). for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.

5. Record the maximum PAPR level associated with a probability of 0.1%.

TEST RESULTS

Remark:

1. We were tested all RB and RB offset Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2; recorded worst case for each Channel Bandwidth of LTE FDD Band 2.

LTE FDD Band 2									
TX Channel	Frequency	DR Size/Offect	PAPR (dB)						
Bandwidth	(MHz)	RB Size/Oliset	QPSK	16QAM					
1.4 MHz	1850.7	100% RB	4.56	5.55					
	1880.0		4.44	5.36					
	1909.3		4.77	5.75					
3 MHz	1851.5	100% RB	4.51	5.56					
	1880.0		4.81	5.63					
	1908.5		5.31	5.88					
5 MHz	1852.5	100% RB	4.85	5.51					
	1880.0		4.99	5.13					
	1907.5		5.94	6.56					
10 MHz	1855.0	100% RB	4.82	5.76					
	1880.0		5.23	6.05					
	1905.0		5.56	6.52					
15 MHz	1857.5	100% RB	4.86	6.58					
	1880.0		4.55	7.24					
	1902.5		5.69	7.23					
20 MHz	1860.0	100% RB	4.97	5.83					
	1880.0		4.22	5.26					
	1900.0		5.28	6.31					













3.4 Occupied Bandwidth and Emission Bandwidth

<u>LIMIT</u>

N/A

TEST CONFIGURATION



TEST PROCEDURE

The transmitter output was connected to a calibrated coaxial cable and coupler, the other end of which was connected to a spectrum analyzer. The occupied bandwidth was measured with the spectrum analyzer at low, middle and high channel in each band. The -26dBc Emission bandwidth was also measured and recorded. Set RBW was set to about 1% of emission BW, VBW≥3 times RBW.

-26dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

TEST RESULTS

Remark:

 We were tested all RB and RB offset Configuration refer 3GPP TS136 521 for each Channel Bandwidth of LTE FDD Band 2; recorded worst case for each Channel Bandwidth of LTE FDD Band 2.

LTE FDD Band 2									
TX Channel RB Size Bandwidth	RB Size/Offset	Frequency	-26dBc Emission		99% Occupied bandwidth				
			bandwidth (MHz)		(MHz)				
		(11112)	QPSK	16QAM	QPSK	16QAM			
1.4 MHz	6RB#0	1850.7	1.249	1.261	1.0785	1.0798			
		1880.0	1.248	1.268	1.0775	1.0810			
		1909.3	1.335	1.266	1.0809	1.0806			
3 MHz	15RB#0	1851.5	2.921	2.932	2.6823	2.6870			
		1880.0	2.926	2.932	2.6840	2.6870			
		1908.5	2.942	2.952	2.6825	2.6837			
5 MHz	25RB#0	1852.5	4.850	4.836	4.4781	4.4812			
		1880.0	4.872	4.830	4.4735	4.4813			
		1907.5	4.853	4.833	4.4785	4.4802			
10 MHz	50RB#0	1855.0	9.516	9.540	8.9421	8.9479			
		1880.0	9.549	9.510	8.9477	8.9385			
		1905.0	9.519	9.571	8.9389	8.9428			
15 MHz	75RB#0	1857.5	14.20	14.20	13.399	13.392			
		1880.0	14.17	14.11	13.403	13.414			
		1902.5	14.15	14.09	13.412	13.417			
20 MHz	100RB#0	1860.0	18.56	18.64	17.849	17.869			
		1880.0	18.69	18.69	17.875	17.867			
		1900.0	18.65	18.69	17.876	17.875			

