



## RF EXPOSURE EVALUATION

### Maximum Permissible Exposure (MPE)

**Applicant Name:**

Skylark Wireless, LLC  
4011 Garrett St  
Houston, TX 77006  
USA

**Date of Testing:**

11/29/2023 – 9/3/2024

**Test Report Issue Date:**

1/8/2025

**Test Site/Location:**

Element Lab. Columbia, MD, USA

**Test Report Serial No.:**

1M2401230005-04.2AS22

**FCC ID:**

**2AS22-FLCOCH2**

**APPLICANT:**

**Skylark Wireless, LLC**

**EUT Type:**

CBRS CPE

**FCC Classification:**

Category B Citizens Band Radio Service Devices (CBSD)

**FCC Rule Part:**

FCC Part 1 (§1.1310) and Part 2 (§2.1091)

**Test Procedure(s):**

KDB 447498 D01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in FCC KDB 447498 D01. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



**RJ Ortanez**  
**Executive Vice President**



<b>FCC ID:</b> 2AS22-FLCOCH2	<b>MAXIMUM PERMISSIBLE EXPOSURE REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401230005-04.2AS22	<b>Test Dates:</b> 11/29/2023 – 9/3/2024	<b>EUT Type:</b> CBRS CPE	Page 1 of 5

## T A B L E O F C O N T E N T S

---

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE) .....	3
1.1	Introduction .....	3
1.2	EUT Description.....	3
1.3	Procedure .....	4
2.0	CONCLUSION .....	5

<b>FCC ID:</b> 2AS22-FLCOCH2	<b>MAXIMUM PERMISSIBLE EXPOSURE REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401230005-04.2AS22	<b>Test Dates:</b> 11/29/2023 – 9/3/2024	<b>EUT Type:</b> CBRS CPE	Page 2 of 5

## 1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 1.1 Introduction

This document is prepared to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

**Table 1-1. Limits for Maximum Permissible Exposure (MPE)**

### 1.2 EUT Description

The **Skylark Wireless, LLC FCC ID: 2AS22-FLCOCH2** is a CBRs CPE Radio Device. It has two antenna ports which transmit simultaneously in the 3550 – 3700 MHz band. Only the highest power mode is assessed for compliance.

<b>FCC ID:</b> 2AS22-FLCOCH2	<b>MAXIMUM PERMISSIBLE EXPOSURE REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401230005-04.2AS22	<b>Test Dates:</b> 11/29/2023 – 9/3/2024	<b>EUT Type:</b> CBRS CPE	Page 3 of 5

### 1.3 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this product was initially measured by a power meter or spectrum analyzer and the powers were recorded. Through use of the Friis transmission formula and knowledge of the maximum antenna gain to be used, the power density level is calculated at a distance of 20cm.

#### Friis Transmission Formula

Friis transmission formula:  $P_d = (P_{out} * G) / (4\pi r^2)$

Where,

$P_d$  = Power Density (mW/cm<sup>2</sup>)

$\pi$  = 3.1416

$P_{out}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

$G$  = gain of antenna in linear scale

#### Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1. Per the manufacturer specification, this device can only operate at a maximum duty cycle of 40% which is used to assess RF exposure compliance in the table below.

Frequency	3625	MHz
FCC Limit	1.000	mW/cm <sup>2</sup>
EIRP Limit	47.00	dBm/10MHz
Distance	23.29	cm
Max Power	29.00	dBm
Duty Cycle	43.00	%
Duty Cycle Correction	-3.67	dB
Max FCC Tx Ant Gain	13.00	dB
Time-Averaged EIRP	38.33	dBm
Time-Averaged EIRP	6815.04	mW
FCC Power Density	1.000	mW/cm <sup>2</sup>

Table 1-2. Calculated MPE Data for CBRS Band

FCC ID: 2AS22-FLCOCH2	MAXIMUM PERMISSIBLE EXPOSURE REPORT		Approved by: Technical Manager
Test Report S/N: 1M2401230005-04.2AS22	Test Dates: 11/29/2023 – 9/3/2024	EUT Type: CBRS CPE	Page 4 of 5



## 2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 23.29cm separation distance as specified in §2.1091 of the FCC Rules and Regulations. An appropriate RF exposure compliance statement will be placed in the user’s manual.

<b>FCC ID:</b> 2AS22-FLCOCH2	<b>MAXIMUM PERMISSIBLE EXPOSURE REPORT</b>		<b>Approved by:</b> Technical Manager
<b>Test Report S/N:</b> 1M2401230005-04.2AS22	<b>Test Dates:</b> 11/29/2023 – 9/3/2024	<b>EUT Type:</b> CBRS CPE	Page 5 of 5