

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15CWLAN_RM-1068_13	Date of Report:	25-Nov-2014
Number of pages:	38	Customer's Contact person:	Zhang David
Testing laboratory:	TCC Microsoft Beijing Laboratory Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550	Customer:	Microsoft Beijing Economic and Technological Development Area No.5 Donghuan Zhonglu Beijing PRC China 100176 Tel. +86 10 8711 8888 Fax. +86 10 8711 4550
FCC listing no.:	975940		
IC recognition no.:	661AH-1		
Tested devices/ accessories:	Phone RM-1068 / Battery BV-5J / Charger AC-18E / Headset WH-108		
FCC ID:	PYA-LVQB	IC:	-
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), DTS procedures KDB 558074, IC standards, RSS-210 (Issue 8, December 2010). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Microsoft.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document		
Date and signature for the contents:			

Fu Roger, Engineer, EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	31-Oct-2014
Testing completed	18-Nov-2014
The customer's contact person	Zhang David
Test Plan referred to	T:\Projects\RM-1068\TestPlan\RS_testplan_RM-1068.xlsm
Notes	-
Document name	FCC15CWLAN_RM-1068_13

1.1. EUT and Accessory Information

The EUT is a mobile phone with following features:

GSM/WCDMA/WLAN/Bluetooth

The EUT is tested with maximum rated TX power.

Devices under tests

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-1068	SIM1:004402740458207; SIM2:004402740458215	0100	-	02048.00000.14431.35000	54623
Battery	BV-5J	4955404426020108545;0670731	LG PWB Ver.1.0	-	-	54624
Charger	AC-18E	4868674142320513794;0675695	-	-	-	54631
Headset	WH-108	3491r3R	-	-	-	54633
Phone	RM-1068	SIM1:004402740457407; SIM2:004402740457415	0100	-	02048.00000.14431.35000	54618
Phone	RM-1068	SIM1:004402740456805; SIM2:004402740456813	0100	-	02048.00000.14431.35000	54620
Battery	BV-5J	4955404426020108485;0670731	LG PWB Ver.1.0	-	-	54627
Charger	AC-18E	4868674142320513785;0675695	-	-	-	54630
Headset	WH-108	3455r3R	-	-	-	54632

1.2. Summary of Test Results

WLAN:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4(4)	Conducted peak output power	PASSED
15.247(d), 15.205(b)	A8.5	Band edge compliance of RF emissions	PASSED
15.247(d)	A8.5	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8.5	Spurious radiated emissions	PASSED
15.207	7.2.4	AC powerline conducted emissions	PASSED
15.247(a)(2)	A8.2(a)	6dB(bandwidth)	PASSED
15.247(e)	A8.2(b)	Power spectral density	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.

The test was not performed by the TCC Microsoft Laboratory.

CONTENTS


1. Summary for FCC Part 15C Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4(4))	5
2.1. Test Setup	5
2.2. Test method and limit	5
2.3. Power results summary	6
2.4. WLAN Test results	7
3. Band edge compliance of RF emissions (FCC 15.247(d), 15.205(b), RSS-210 A8.5)	11
3.2. Test method and limit	11
3.3. WLAN test results	12
4. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)	16
4.1. Test Setup	16
4.2. Test method and limit	16
4.3. WLAN Test results	17
5. Spurious radiated emissions (FCC 15.247(d), 15.209, RSS-210 A8.5)	21
5.2. Test method and limit	21
5.3. WLAN test results	23
6. AC powerline conducted emissions (FCC §15.207, RSS-210 7.2.4)	26
6.1. Test Setup	26
6.2. Test method and limit	26
6.3. WLAN Test results	27
7. 6dB(bandwidth) (FCC §15.247(a)(2), RSS-210 A8.2(a))	28
7.1. Test Setup	28
7.2. Test method and limit	28
7.3. WLAN Test results	29
8. Power spectral density (FCC §15.247(e), RSS-210 A8.2(b))	32
8.1. Test Setup	32
8.2. Test method and limit	32

8.3.	WLAN Test results	33
9.	Test Equipment	36
9.1.	Conducted measurements	36
9.2.	Radiated measurements	36

2. Conducted peak output power (FCC §15.247(b)(1), RSS-210 A8.4(4))

EUT with DUT number	RM-1068, DUT 54623
Accessories with DUT numbers	BV-5J, DUT 54624 ; AC-18E, DUT 54631 ; WH-108, DUT 54633
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/37/101.5 to 20/47/102.4
Date of measurements	11-Nov-2014 to 18-Nov-2014
Measured by	Dou Rubo

2.1. Test Setup



2.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for conducted peak output power measurements

Frequency range [MHz]	Limit [W]	Limit [dBm]
2400 – 2483.5 5725 - 5850	≤ 1	≤ 30

2.3. Power results summary


Channel / f_c [MHz]	Mode	Modulation	Data rate	Level [dBm]
1 / 2412	802.11n	BPSK	6.5 / 7.25 Mbps	19.79
6 / 2437	802.11n	BPSK	6.5 / 7.25 Mbps	23.94
11 / 2462	802.11n	BPSK	6.5 / 7.25 Mbps	18.6
1 / 2412	802.11n	16QAM	26.0 / 28.9 Mbps	19.82
6 / 2437	802.11n	16QAM	26.0 / 28.9 Mbps	24.01
11 / 2462	802.11n	16QAM	26.0 / 28.9 Mbps	18.77

2.4. WLAN Test results


2.4.1 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	19.79	95.28	PASSED
6 / 2437	23.94	247.742	PASSED
11 / 2462	18.6	72.444	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz




2.4.2 802.11n mode, 16QAM modulation, 26.0 / 28.9 Mbps data rate

Channel / f _c [MHz]	P [dBm]	P [mW]	Result
1 / 2412	19.82	95.94	PASSED
6 / 2437	24.01	251.768	PASSED
11 / 2462	18.77	75.336	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz



3. Band edge compliance of RF emissions (FCC 15.247(d), 15.205(b), RSS-210 A8.5)

EUT with DUT number	RM-1068, DUT 54620
Accessories with DUT numbers	BV-5J, DUT 54627 ; AC-18E, DUT 54630 ; WH-108, DUT 54632
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/34/102.4 to 20/36/102.4
Date of measurements	12-Nov-2014 to 18-Nov-2014
Measured by	Dou Rubo

3.1.1 Test setup



3.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).


Limits for band edge compliance of RF emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit
Below 2390 and above 2483.5	54 dBuV/m (avg) and 74 dBuV/m (pk)

3.3. WLAN test results

3.3.1 802.11n, BPSK modulation, 6.5 / 7.25 Mbps data rate.

Channel 1 / 2412 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	71.94	3954.121	72.56	-0.62	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	50.48	334.272	51.1	-0.62	PASSED

Channel 11 / 2462 MHz



Peak (RBW: 1 MHz, VBW: 1 MHz)


Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2484	63.72	1534.794	63.48	0.24	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2484	46.49	211.179	46.25	0.24	PASSED

3.3.2 802.11n, 16QAM modulation, 26.0 / 28.9 Mbps data rate.

Channel 1 / 2412 MHz




Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	70	3160.822	70.62	-0.62	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2390	47.98	250.697	48.6	-0.62	PASSED

Channel 11 / 2462 MHz



Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2484	63.21	1447.438	62.97	0.24	PASSED


Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Results
2484	45.27	183.421	45.03	0.24	PASSED

4. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-1068, DUT 54623
Accessories with DUT numbers	BV-5J, DUT 54624 ; AC-18E, DUT 54631 ; WH-108, DUT 54633
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/37/101.5 to 20/47/102.4
Date of measurements	11-Nov-2014 to 18-Nov-2014
Measured by	Dou Rubo

4.1. Test Setup



4.2. Test method and limit

The measurement is made according to Public notice KDB 558 074 and IC standard RSS-210.

The reference level for the -20 dBc measurement was obtained as instructed in section 11.2 of the KDB 558074, using span of 1.5 times the OBW.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 25000	<= -20

4.3. WLAN Test results

4.3.1 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBm]	Result
24793.000	-29.55	PASSED
24218.000	-29.62	PASSED
9600.000	-29.68	PASSED


Channel 6 / 2437 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBm]	Result
24241.000	-33.96	PASSED
13332.000	-34.07	PASSED
10128.000	-34.10	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
9996.000	-28.17	PASSED
7401.000	-28.24	PASSED
24839.000	-28.46	PASSED

4.3.2 802.11n mode, 16QAM modulation, 26.0 / 28.9 Mbps data rate


Channel 1 / 2412 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
7388.400	-29.74	PASSED
6773.200	-29.84	PASSED
6698.400	-30.00	PASSED


Channel 6 / 2437 MHz



Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
7327.200	-33.83	PASSED
24816.000	-34.27	PASSED
13212.000	-34.59	PASSED

Channel 11 / 2462 MHz




Peak (RBW: 100 kHz, VBW: 300 kHz)

Frequency [MHz]	P [dBc]	Result
7342.200	-27.64	PASSED
10104.000	-28.43	PASSED
10860.000	-28.47	PASSED

5. Spurious radiated emissions (FCC 15.247(d), 15.209, RSS-210 A8.5)

EUT with DUT number	RM-1068, DUT 54620
Accessories with DUT numbers	BV-5J, DUT 54627 ; AC-18E, DUT 54630 ; WH-108, DUT 54632
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/34/102.4 to 20/36/102.4
Date of measurements	12-Nov-2014 to 18-Nov-2014
Measured by	Dou Rubo

5.1.1 Test setup



5.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210 as follows:
The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with absorbers on the floor and measuring antenna at fixed height using 2-axis EUT position system.

The Final Measurement is performed in the Semi-Anechoic Chamber with conducting metal floor, if the Preliminary Measurement results are closer than 20 dB to the permissible value.

The EUT is placed at nonconductive plate at the turntable center.

For each suspected frequency, the turntable is rotated 360 degrees and antenna is scanned from 1 to 4 m. This is repeated for both horizontal and vertical receive antenna polarizations.

The emissions less than 20 dB below the permissible value are reported.

The measurement is made up to 10th harmonic of the EUT highest TX channel.

The measurement results are obtained as described below:

$$E [dB\mu V/m] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable loss, antenna factor and preamplifier gain ($A_{TOT} = L_{CABLES} + A_F - G_{PREAMP}$).

Limits for spurious radiated emissions measurements (3 m measurement distance)

Frequency range [MHz]	Limit [$\mu V/m$]	Limit [dB $\mu V/m$]	Detector
30 - 88	100	40	Quasi peak
88 – 216	150	43.5	Quasi peak
216 – 960	200	46	Quasi peak
960 – 1000	500	54	Quasi peak
Above 1000	500	54	Average
Above 1000	5000	74	Peak

5.3. WLAN test results

5.3.1 802.11n, BPSK modulation, 6.5 / 7.25 Mbps data rate.

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4824.6	48.51	266.379	47.21	1.3	74	25.47	PASSED
7235.7	49.59	301.648	39.59	10	95	45.64	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4824.6	34.5	53.088	33.2	1.3	54	19.48	PASSED
7235.7	36.1	63.826	26.1	10	---	---	PASSED

Channel 6 / 2437 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
31.98	32.11	40.318	40.31	-8.2	40	7.89	PASSED
897.428	23.07	14.24	27.07	-4	46	22.95	PASSED
905.863	23.5	14.962	27.1	-3.6	46	22.52	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4881.5	43.32	146.555	41.82	1.5	74	30.66	PASSED
7318.2	49.97	315.137	39.47	10.5	74	24.01	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4881.5	30.64	34.041	29.14	1.5	54	23.34	PASSED
7318.2	36.59	67.531	26.09	10.5	54	17.39	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4923.8	50.55	336.899	49.05	1.5	74	23.43	PASSED
7385.1	49.72	306.196	39.22	10.5	74	24.26	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4923.8	36.36	65.766	34.86	1.5	54	17.62	PASSED
7385.1	36.46	66.527	25.96	10.5	54	17.52	PASSED

5.3.2 802.11n, 16QAM modulation, 26.0 / 28.9 Mbps data rate.

Channel 1 / 2412 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4825.2	48.14	255.27	46.84	1.3	74	25.84	PASSED
7235	50.94	352.371	40.84	10.1	95	44.29	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4825.2	33.92	49.659	32.62	1.3	54	20.06	PASSED
7235	36.92	70.146	26.82	10.1	---	---	PASSED

Channel 6 / 2437 MHz

Quasi peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
31.35	29.43	29.614	37.23	-7.8	40	10.57	PASSED
31.978	29.4	29.512	37.6	-8.2	40	10.6	PASSED
955.324	42.35	131.069	45.65	-3.3	46	3.67	PASSED

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4878.3	46.88	220.8	45.38	1.5	74	27.1	PASSED
7318.4	49.97	315.137	39.47	10.5	74	24.01	PASSED

Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4878.3	32.2	40.738	30.7	1.5	54	21.78	PASSED
7318.4	36.62	67.764	26.12	10.5	54	17.36	PASSED

Channel 11 / 2462 MHz

Peak (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4925.3	50.41	331.513	48.91	1.5	74	23.57	PASSED
7385.3	50.59	338.454	40.09	10.5	74	23.39	PASSED


Average (RBW: 1 MHz, VBW: 1 MHz)

Frequency [MHz]	E [dBμV/m]	E [μV/m]	U _{RX} [dBμV]	A _{TOT} [dB]	Limit [dBμV/m]	Margin	Results
4925.3	35.8	61.66	34.3	1.5	54	18.18	PASSED
7385.3	36.45	66.451	25.95	10.5	54	17.53	PASSED

6. AC powerline conducted emissions (FCC §15.207, RSS-210 7.2.4)

EUT with DUT number	RM-1068, DUT 54618
Accessories with DUT numbers	BV-5J, DUT 54624 ; AC-18E, DUT 54631 ; WH-108, DUT 54633
Operation Voltage [V] / [Hz]	115/60
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/39/102.1
Date of measurements	10-Nov-2014
Measured by	Dou Rubo

6.1. Test Setup



6.2. Test method and limit

The measurement is made according to procedure KDB 558074 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

6.3. WLAN Test results

6.3.1 802.11b mode, QPSK modulation, 11 Mbps data rate

Channel 6 / 2437 MHz



Emissions exceeding the limit in 160KHz...5 MHz frequency range are based on pre-sweep measurements. Pre-sweep uses wider IF-BW than specified in the standard. Final measurement was performed with correct IF-BW and the result was PASSED."

QuasiPeak (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.16	51.38	L1	PASSED
0.17	53.62	N	PASSED
0.175	54.33	N	PASSED


Average (RBW: 9 kHz)

Frequency [MHz]	U [dBμV]	Line	Result
0.165	37.54	N	PASSED
0.17	38.18	N	PASSED
0.175	38.15	N	PASSED
5.065	38.51	L1	PASSED
5.36	40.1	L1	PASSED
5.465	40.79	L1	PASSED

7. 6dB(bandwidth) (FCC §15.247(a)(2), RSS-210 A8.2(a))

EUT with DUT number	RM-1068, DUT 54623
Accessories with DUT numbers	BV-5J, DUT 54624 ; AC-18E, DUT 54631 ; WH-108, DUT 54633
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/37/101.5 to 20/47/102.4
Date of measurements	11-Nov-2014 to 18-Nov-2014
Measured by	Dou Rubo

7.1. Test Setup



7.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for 6 dB bandwidth measurements


Limit [kHz]
>= 500

7.3. WLAN Test results


7.3.1 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate

Channel / f _c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	17768.6	PASSED
6 / 2437	18495.3	PASSED
11 / 2462	17776.6	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz




7.3.2 802.11n mode, 16QAM modulation, 26.0 / 28.9 Mbps data rate

Channel / f _c [MHz]	6 dB bandwidth [kHz]	Result
1 / 2412	17768.6	PASSED
6 / 2437	17906.5	PASSED
11 / 2462	17760	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz




Channel 11 / 2462 MHz



8. Power spectral density (FCC §15.247(e), RSS-210 A8.2(b))

EUT with DUT number	RM-1068, DUT 54623
Accessories with DUT numbers	BV-5J, DUT 54624 ; AC-18E, DUT 54631 ; WH-108, DUT 54633
Operation Voltage [V] / [Hz]	Nominal
Results	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20/37/101.5 to 20/47/102.4
Date of measurements	11-Nov-2014 to 18-Nov-2014
Measured by	Dou Rubo

8.1. Test Setup



8.2. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for power spectral density measurements

Limit [dBm] @ 3 kHz
<= 8


8.3. WLAN Test results

8.3.1 802.11n mode, BPSK modulation, 6.5 / 7.25 Mbps data rate


Peak (RBW: 3 kHz, VBW: 10 kHz, Max hold)

Channel / f _c [MHz]	P [dBm]	Result
1 / 2412	-12.43	PASSED
6 / 2437	-8.62	PASSED
11 / 2462	-14.25	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz




8.3.2 802.11n mode, 16QAM modulation, 26.0 / 28.9 Mbps data rate


Peak (RBW: 3 kHz, VBW: 10 kHz, Max hold)

Channel / f_c [MHz]	P [dBm]	Result
1 / 2412	-13.63	PASSED
6 / 2437	-9.73	PASSED
11 / 2462	-15.31	PASSED


Channel 1 / 2412 MHz



Channel 6 / 2437 MHz



Channel 11 / 2462 MHz



9. Test Equipment

9.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCHW0020	DC Power supply	Hp6632B	HP	22/24/27, 15C
BJPCPT0040	Receiver	ESCS30	R&S	15C,15B
BJPCPT0069	LISN 50 µH	ESH3-Z5	R&S	15C,15B
BJPCTC0323	Signal Generator	SMR 27	R&S	22/24/27, 15C, 15B
BJPCPT0073	Signal Generator	SMR 20	R&S	22/24/27, 15C, 15B
BJPCPT0191	Pulse Limiter	ESH3-Z2	R&S	15C,15B
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C.15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C.15R
BJPCTC0017	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0062	AC Power source	6812B	Hp	15C.15B
BJPCTC0067	Bluetooth Tester	CBT	R&S	22/24/27, 15C
BJPCTC0082	Humidity and Temperature Sensor	175-H2	Testo	15B,15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B,15C
BJPCTC0089	Tempreture Test chamber	VT4002	Votsch industrietechnik	22/24/27, 15C
BJPCTC0090	FSP spectrum analyzer	FSP30	R&S	22/24/27, 15C
BJPCTC0094	GPIO-RS232 convertor	GPIO-RS232	NI	22/24/27, 15C
BJPCTC0112	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0115	Communication Tester	CMU200	R&S	22/24/27, 15B, 15C
BJPCTC0127	AC Power source	SOYI-500VA	SOYI	15B 15C
BJPCTC0128	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0129	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27 15B 15C
BJPCTC0136	Communication antenna	JXTXLB-880-NF	A-INFOMW	15B 15C
BJPCTC0306	Power Splitter	11667B	Agilent	22/24/27, 15C
BJPCTC0305	GPIO converter	GPIO-RS232	NI	22/24/27, 15C
BJPCTC0304	Spectrum Analyser	FSV30	R&S	22/24/27, 15C
BJPCTC0309	GPIO-RS232 convertor	RS232	NI	22/24/27, 15C
BJPCTC0307	Dual channel battery/charger simulator	2306	KEITHLEY	22/24/27, 15C
BJPCTC0308	Dual channel battery/charger simulator	2306	KEITHLEY	22/24/27, 15C
BJPCTC0352	Signal Generator 20GHz	MG3692B	Anritsu	22/24/27, 15C
BJBDATC0169	Tempreture Test chamber	VT4002	Votsch	22/24/27, 15C
BJPCTC0334	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0342	Communication Tester	CMU200	R&S	15B, 15C
BJPCTC0343	Power Splitter	1167A	Agilent	EN300328
BJPCTC0344	Power Splitter	1167A	Agilent	EN300328
BJPCTC0345	Power Splitter	1167A	Agilent	EN300328
BJPCTC0346	Attenuator	8496A	Agilent	EN300328
BJPCTC0347	Directional Coupler	4226-20	Narda	EN300328
BJPCTC0348	Signal generator	E4438C	Agilent	EN300328
BJPCTC0336	Signal Generator	SMP22	R&S	22/24/27, 15C

9.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	BT / WLAN Antenna	SPA 2400/75/9/0/V	Huber-Suhner	15C, 15B
-	RF Emission Software	EMC32 Test Software	R&S	22/24/27, 15C, 15B
BJPCPT0072	Receiver	ESI B26	R&S	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCPT0150	High Pass Filter	WHKS1200-10SS	Wainwright	22/24/27, 15C, 15B
BJPCPT0151	Band Reject Filter	WRCD1880/2000-0.2/40-5SSK	Wainwright	24, 15B
BJPCPT0154	Band Reject Filter	WRCT2402/2480-2400/2483.5-30-20SS	Wainwright	15C, 15B
BJPCPT0166	Antenna	VUBA 9117	Swarzbeck	22/24/27
BJPCPT0208	UPS	PULSAR RX10	Merlin gerin	15C, 15B
BJPCTC0001	DIGITAL CAMERA	PC1015	CANON	15C, 15R
BJPCTC0007	Antenna	HL562	R&S	22/24/27, 15C, 15B
BJPCTC0029	Antenna	HF906	R&S	22/24/27, 15C, 15B
BJPCTC0034	Band Reject Filter	WRCT 800/880-0.2/40-5SSK	Wainwright	22, 15B
BJPCTC0049	Preamplifier	Blma 0118-1A-Bt	Bonn	22/24/27, 15C, 15B
BJPCTC0055	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0058	Bluetooth Tester	CBT	R&S	15C, 15B
BJPCTC0062	AC Power source	6812B	Hp	15C, 15B
BJPCTC0064	Band Reject Filter	WRCG1877/1883-1870/1890-40/6SS	Wainwright	24, 15B
BJPCTC0071	Multi-Device Controller	2090	EMCO	22/24/27, 15C, 15B
BJPCTC0072	Anechoic Chamber	3 m Semi / Full Anechoic Chamber	ETS	22/24/27, 15C, 15B
BJPCTC0073	MAST	Model-TR/POL	ETS	22/24/27, 15C, 15B
BJPCTC0074	MAST	Model 2070-2	ETS	22/24/27, 15C, 15B
BJPCTC0075	Turntable	Model 2188	ETS-EMCO	22/24/27, 15C, 15B
BJPCTC0081	Humidity and Temperature Sensor	175-H2	Testo	15B, 15C
BJPCTC0088	Absolut pressure meter	testo 511	Testo	22/24/27, 15B, 15C
BJPCTC0115	Communication Tester	CMU200	R&S	22/24/27, 15B, 15C
BJPCTC0124	Attenuator	SA18N200W-40	Fairview Microwave	-
BJPCTC0125	Loop Antenna	HFH2-Z2	R&S	15C
BJPCTC0126	Tripod	FHU-Z	R&S	15C
BJPCTC0128	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0129	Communication antenna	JXTXLB-10180	A-INFOMW	22/24/27 15B 15C
BJPCTC0131	Communication tester	CMW500	R&S	22/24/27 15B 15C
BJPCTC0133	Open Swith and contril unit	OSP 150	R&S	15B, 15C
BJPCTC0134	Open Swith and contril unit	OSP 150	R&S	15B, 15C
BJPCTC0135	Open Swith and contril unit	OSP 130	R&S	15B, 15C
BJPCTC0136	Communication antenna	JXTXLB-880-NF	A-INFOMW	15B 15C
BJPCTC0171	Broad-band Horn Antenna	BBHA9120 D	SCHWARZBECK MESS - ELEKTRONIK	22/24/27, 15C, 15B
BJPCTC0310	Horn Antenna	QSH20SMA	Q-par	22/24/27, 15C, 15B
BJPCTC0311	Horn Antenna	QSH18SMA	Q-par	22/24/27, 15C, 15B
BJPCTC0312	Relay Switch Unit	-	-	22/24/27, 15C, 15B
BJPCTC0313	High Pass Filter	WHKX1.0/15G-12SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0314	High Pass Filter	WHKX8.0/18G-88SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0315	High Pass Filter	WHKX3.0/18G-12SS	Wainwright	22/24/27, 15C, 15B
BJPCTC0316	Preamplifier	AMT-5F-18002550-25-108	-	22/24/27, 15C, 15B
BJPCTC0317	Preamplifier	AMF-6D-02001800-29-20P	-	22/24/27, 15C, 15B
BJPCTC0350	Preamplifier	AMF-4D-01000800-30-29P	Miteq	22/24/27, 15C, 15B
BJPCTC0324	Preamplifier	AFS4-00100300-20-23P-6	Miteq	22/24/27, 15C, 15B
BJPCTC0329	Relay Switch Unit	-	-	22/24/27, 15C, 15B
BJPCTC0334	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
BJPCTC0342	Communication Tester	CMU200	R&S	15B, 15C
BJPCTC0349	Preamplifier	AMF-4D-01000800-30-79P	Miteq	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
BJPCTC0350	Preamplifier	AMF-4D-01000800-30-29P	Miteg	22/24/27, 15C, 15B
BJPCTC0351	Preamplifier	AFS4-00101800	-	22/24/27, 15C, 15B