



Nemko

Test Report: 2W06569
Issue III


Applicant: Instantel Inc.
309 Legget Drive
Kanata, Ontario
K2K 3A3

**Equipment Under Test:
(EUT)** XMARK Large Exciter
312.5KHz Transmitter

FCC ID: ISEXLX

In Accordance With: **FCC Part 15, Subpart C**

Tested By: Nemko Canada Inc.
303 River Road, R.R. 5
Ottawa, Ontario K1V 1H2



Authorized By: Kevin Carr, EMC Specialist

Date: 28 November 2002

Total Number of Pages: 17

Table Of Contents

Section 1. Summary Of Test Results.....3

Section 2. General Equipment Specification5

Section 3. Radiated Emissions.....12

Section 4. Block Diagrams.....16

Section 5. Test Equipment List17

Section 1. Summary Of Test Results

General

All measurements are traceable to national standards.

These tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with FCC Part 15, Subpart C, 15.209. All tests were conducted using measurement procedure ANSI C63.4-1992. Radiated Emissions were made on an open area test site. A description of the test facility is on file with the FCC.

THIS TEST REPORT RELATES ONLY TO THE ITEM(S) TESTED.



TESTED BY: _____
Glen Westwell, Wireless Technologist

DATE: 28 November 2002

Nemko Canada Inc. authorizes the above named company to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only.

Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties. Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

This report applies only to the items tested.

EQUIPMENT:XMARK Large Exciter

Summary Of Test Data

Name Of Test	Para. No.	Result
Powerline Conducted Emissions	15.207	Complies
Radiated Emissions	15.209	Complies

Notes: This unit is power by an external OEM 12Vdc source.

Ferrite 28A-20290A2 was used at the DC input power line to reduce emissions detected at 30 & 60MHz. This ferrite has been incorporated in the B.O.M (see set up photo's).

Test Conditions:

Indoor Temperature: 24°C
 Humidity: 34%


Outdoor Temperature: 17°C
 Humidity: 31%

Section 2. General Equipment Specification

Manufacturer:	Instantel Inc.
Model No.:	805A6201
Serial No.:	none
Date Received In Laboratory:	21 Oct. 2002
Nemko Identification No.:	1
Transmit Frequency (fixed)	312.5KHz
Type of Modulation:	On/Off Keying (OOK)
Emission designator:	16K2POD

EQUIPMENT:XMARK Large Exciter

99% Occupied Bandwidth



EQUIPMENT:XMARK Large Exciter

Section 3. Powerline Conducted Emissions**Para. No.: 15.207****Test Performed By: Glen Westwell****Date of Test: 1 Nov 2002****Minimum Standard:**

Frequency	Maximum Powerline Conducted RF Voltage	
(MHz)	(μV)	(dBμV)
0.45 - 30.0	250	48

Test Results: Complies.**Measurement Data:** See attached tables & graph(s).

*EQUIPMENT:XMARK Large Exciter***No Ferrite installed on AC Power Line****Class B Mains limits (Neutral)**



No.	Frequency of Emission (MHz)	Detector	Emission Level (dBV)	Limit (dBuV)	BB / NB	BB Corr. (dB)	Result (dB)
1	30.0000	Quasi-Peak	54.2	48.0	BB	13	6.8
	30.0000	Average	39		BB	13	
2	0.6300	Quasi-Peak	55.4	48.0	BB	13	5.6
	0.6300	Average	31.7		BB	13	
3	29.1100	Quasi-Peak	47.9	48.0	BB	13	13.1
	29.1100	Average	29.1		BB	13	
4	29.7000	Quasi-Peak	47.8	48.0	BB	13	13.2
	29.7000	Average	29.1		BB	13	
5	28.4600	Quasi-Peak	42.9	48.0	BB	13	18.1
	28.4600	Average	26.2		BB	13	
6	29.4100	Quasi-Peak	41.5	48.0	BB	13	19.5
	29.4100	Average	26.4		BB	13	

Class B Mains limits (Phase)

No.	Frequency of Emission (MHz)	Detector	Emission Level (dBV)	Limit (dBuV)	BB / NB	BB Corr. (dB)	Result (dB)
1	30.0000	Quasi-Peak	55	48.0	BB	13	6.0
	30.0000	Average	39.1		BB	13	
2	29.7000	Quasi-Peak	47.9	48.0	BB	13	13.1
	29.7000	Average	29		BB	13	
3	27.8100	Quasi-Peak	48.3	48.0	BB	13	12.7
	27.8100	Average	29		BB	13	
4	27.5200	Quasi-Peak	43	48.0	BB	13	18.0
	27.5200	Average	29		BB	13	
5	28.1100	Quasi-Peak	34.1	48.0	BB	13	26.9
	28.1100	Average	21.6		BB	13	
6	29.3500	Quasi-Peak	33.2	48.0	BB	13	27.8
	29.3500	Average	21.6		BB	13	



EQUIPMENT:XMARK Large Exciter

No Ferrite installed on AC Power Line



EQUIPMENT:XMARK Large Exciter


28A-20290A2 Ferrite installed on AC Power Line




EQUIPMENT:XMARK Large Exciter

Power Line Conducted Photo

No Ferrite on AC Power Line



28A-20290A2 Ferrite installed on AC Power Line



EQUIPMENT:XMARK Large Exciter

Section 3. Radiated Emissions**Para. No.: 15.209****Test Performed By: Glen Westwell****Date of Test: 21 Oct. 2002****Minimum Standard:**

Tx = 312KHz

Fundamental (MHz)	Field Strength (μV/m)	Field Strength (dBμV)
0.009 - 0.490	2400/F(kHz) @ 300m	17.7
0.490 - 1.705	24000/F(kHz) @ 30m	—
1.705 - 30	30 @ 30m	—
30 - 88	100	40.0
88 - 216	150	43.5
216 - 960	200	46.0
Above 960	500	54.0

Test Results:

Complies.

Note: Ferrite 28A-20290A2 was used at the DC input power line to reduce emissions detected at 30 & 60MHz. This ferrite has been incorporated in the B.O.M.

Measurement Data:

See attached table.

- Worst case emissions data has been presented.
- The EUT was searched up to 1000MHz.
- The input power was varied as per 15.31(e) to determine maximum emission level.
- The EUT was searched for worst case configuration with a 1m unshielded external control wire(s) attached (see set up photo).

*EQUIPMENT:XMARK Large Exciter***Test Data: Fundamental**

Test Distance (meters):											10		Receiver:		ESH3				Range:		A	
Detector:		Avg			RBW(kHz):		10		Environmental Factors:			None										
No.	Freq. (MHz)	Ant.	Pol (V/H)	Field Strength at 10 meters (dBμV)	Ant. Factor (dB)**	Amp. Gain (dB)* **	Dist. Corr. (dB)	Field Strength Extrapolated to 300m (dBμV)	Limit At 300 meters (dBuV)	Margin (dB)												
1	0.312	Active Loop		61.7				2.6	17.7	15.1												

Notes:

B/C = Biconical, BL = Bilog, L/P = Log-Periodic, H = Horn, D/P = Dipole, E/D = EMCO Dipole

* Re-measured using dipole antenna.

** Includes cable loss when amplifier is not used.

*** Includes cable loss.

() Denotes failing emission level.

N.D. = Not Detected

All emissions measured were extrapolated using 40 dB/decade extrapolation factor.

Harmonics

Test Distance (meters):				3		Receiver:			ESH3			Range:		A	
Detector:		Avg			RBW(kHz):		10		Environmental Factors:			None			
No.	Freq. (MHz)	Ant.	Pol (V/H)	Field Strength at 3 meters (dBμV)	Ant. Factor (dB)**	Amp. Gain (dB)* **	Dist. Corr. (dB)	Field Strength Extrapolated to 30m (dBμV)	Limit At 30 meters (dBuV)	Margin (dB)					
1	0.624	Active Loop		42.2				2.2	31.7	29.5					
2	0.936	Active Loop		39.3				-0.7	28.2	28.9					
No.	Freq. (MHz)	Ant.	Pol (V/H)	Received Signal 3 meters (dBμV)	Ant. Factor (dB)**	Amp. Gain (dB)* **	Dist. Corr. (dB)	Field Strength (dBμV)	Limit (dBuV)	Margin (dB)					
3	30.647	BL	V	17.4	20.4			37.8	40.0	2.2					
	30.647	BL	H	16.4	20.4			36.8	40.0	3.2					
4	60.4	BL	V	27.5	8.1			35.6	40.0	4.4					
	60.4	BL	H	23.3	8.1			31.4	40.0	8.6					

Notes:

B/C = Biconical, BL = Bilog, L/P = Log-Periodic, H = Horn, D/P = Dipole, E/D = EMCO Dipole

* Re-measured using dipole antenna.

** Includes cable loss when amplifier is not used.

*** Includes cable loss.

() Denotes failing emission level.

N.D. = Not Detected

All emissions measured were extrapolated using 40 dB/decade extrapolation factor.


EQUIPMENT:XMARK Large Exciter

All harmonic and spurious emissions were searched up to the 10th harmonic

Photo, Test Set-up



Test Configuration




Ferrite on Power Line





Section 4. Block Diagrams

Radiated Prescan



Test Site For Radiated Emissions



*EQUIPMENT:XMARK Large Exciter***Section 5. Test Equipment List**

CAL Cycle	Equipment	Manufacturer	Model No.	Asset/Serial No.	Last Cal.	Next Cal.
1 Year	Receiver	Rohde & Schwarz	ESH3	FA000872	May 02/02	May 02/03
1 Year	Receiver	Rohde & Schwarz	ESVS-30	FA001445	June. 07/02	June. 07/03
1 Year	Spectrum Analyzer	Hewlett-Packard	8565E	FA000981	July. 15/02	July. 15/03
1 Year	Active Loop Antenna	Rohde & Schwarz	HFH2-Z2	FA000631	May. 12/02	May. 12/03
1 Year	Bilog	Schaffner	CBL6112B	FA001503	July. 02/02	July. 02/03
Extended	LISN(peripheral)	Tegam	95300-50	FA000986	Oct. 22/01	Nov. 22/02
Extended	LISN(peripheral)	Tegam	95300-50	FA000987	Oct. 22/01	Nov. 22/02
NCR	International Power Supply	California Instruments	1001WP	FA000965	NCR	NCR
1 Year	Spectrum Analyzer	Hewlett-Packard	8566B	FA001309	Nov. 27/01	Nov. 27/02
1 Year	Spectrum Analyzer Display	Hewlett-Packard	85662A	FA001309	Nov. 27/01	Nov. 27/02
1 Year	Quasi-Peak Adapter	Hewlett-Packard	85650A	FA000801	Nov. 27/01	Nov. 27/02