

## INTERTEK TESTING SERVICES

---

### RF Exposure

The equipment under test (EUT) is a 2.0 Channel Soundbar Home Theater System with Bluetooth EDR 5.3(Single Mode) function operating in 2402-2480MHz. The EUT is powered by AC 100-240V~50/60Hz. For more detail information pls. refer to the user manual.

Modulation Type: GFSK,  $\pi/4$ QPSK, and 8-DPSK

Bluetooth Version: 5.3 EDR

Antenna Type: Integral antenna

Antenna Gain: 2.98dBi (This information is provided by applicant, and the applicant is responsible for the authenticity of the provided information.)

The nominal radiated output power (e.i.r.p) specified: 5dBm ( Tolerance: +/- 2dB)

The nominal conducted output power specified: 2.02dBm ( Tolerance: +/- 2dB)

According to the KDB 447498 D04 V01:

The maximum peak radiated emission for the EUT is 101.4 dB $\mu$ V/m at 3m in the frequency 2441MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 6.1 dBm

which is within the production variation.

The minimum peak radiated emission for the EUT is 99.8 dB $\mu$ V/m at 3m in the frequency 2402MHz

The EIRP =  $[(FS \cdot D)^2 / 30]$  mW = 4.57 dBm

which is within the production variation.

According to FCC Part 2.1091, this unlicensed transmitting devices is categorically excluded from routine environmental evaluation for RF exposure prior to equipment authorization or use, According to the KDB 447498 D04 V01 and OET 65, the simple calculation as below:

The source-based time averaged maximum radiated power = 5dBm+2dB= 7dBm = 5.01mW

The maximum ERP= 5dBm+2dB-2.15dB= 4.85dBm= 3.05mW

At the distance (R) of 20cm to 40cm and in 0.3 GHz to 6 GHz, ERP Exclusion Threshold Level:

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

The ERP Threshold is 3060mW for general population and uncontrolled exposure in the 2.4GHz frequency range according to FCC Part 1.1307. As the maximum ERP at 20cm from the transmitter is lower than the ERP Threshold, the compliance to the ERP Threshold can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structure and body of the user or nearby persons.