



Shenzhen Huaxia Testing Technology Co., Ltd.

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V05

Report Template Revision Date: 2021-11-03

RF Exposure Evaluation Report

Report No.: CQASZ20220400507E-02
Applicant: MOSWS INTERNATIONAL LIMITED
Address of Applicant: FLAT/RM 07 BLK B 5/F KING YIP FACTORY BUILDING 59 KING YIP STREET KWUN TONG
Equipment Under Test (EUT):
EUT Name: 5.1 Channel Home Theater System
Model No.: B901D, H7922, B902D, B903D, B904D, B905D, B906D, B907D, B908D, B909D, B910D, B911D, B912D, B913D, B914D, B915D, B917D, B918D, B919D, B920D, H7901, H7902, H7910, H7911, H7912, H7913, H7915, H7916, H7923, H7925, H7928, H7933, H7935, H7936, H7937, H7938, H7903, H7905, H7906, H7907, H7919, H7920, H7921, B901, H7926, H7927, H7929, H7930, H7931, H7932
Test Model No.: B901D
Brand Name: N/A
FCC ID: 2AZ43-B901D
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
447498 D04 Interim General RF Exposure Guidance v01
Date of Receipt: 2022-04-01
Date of Test: 2022-04-01 to 2022-04-30
Date of Issue: 2022-05-19
Test Result: **PASS***

*In the configuration tested, the EUT complied with the standards specified above

Lewis Zhou
Tested By: _____

(Lewis Zhou)

Rock Huang
Reviewed By: _____

(Rock Huang)

Jack Ai
Approved By: _____

(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20220400507E-02	Rev.01	Initial report	2022-05-19

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
3.3 GENERAL DESCRIPTION OF BT CLASSIC	4
4 MPE EVALUATION	6
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT	6
4.1.1 Limits	6
4.1.2 Test Procedure	6
4.1.3 EUT RF Exposure	7

3 General Information

3.1 Client Information

Applicant:	MOSWS INTERNATIONAL LIMITED
Address of Applicant:	FLAT/RM 07 BLK B 5/F KING YIP FACTORY BUILDING 59 KING YIP STREET KWUN TONG
Manufacturer:	SHENZHEN CITY ENKOR ELECTRONICS LTD
Address of Manufacturer:	he 2nd&3rd floor,Building P and building Q,Shengguang Ind.park,152#Donghuan Road, Huangpu Xinqiao street,Bao'an District,Shenzhen,China
Factory:	SHENZHEN CITY ENKOR ELECTRONICS LTD
Address of Factory:	he 2nd&3rd floor,Building P and building Q,Shengguang Ind.park,152#Donghuan Road, Huangpu Xinqiao street,Bao'an District,Shenzhen,China

3.2 General Description of EUT

Product Name:	5.1 Channel Home Theater System
Model No.:	B901D, H7922, B902D, B903D, B904D, B905D, B906D, B907D, B908D, B909D, B910D, B911D, B912D, B913D, B914D, B915D, B917D, B918D, B919D, B920D, H7901, H7902, H7910, H7911, H7912, H7913, H7915, H7916, H7923, H7925, H7928, H7933, H7935, H7936, H7937, H7938, H7903, H7905, H7906, H7907, H7919, H7920, H7921, B901, H7926, H7927, H7927, H7929, H7930, H7931, H7932
Test Model No.:	B901D
Trade Mark:	N/A
Software Version:	5.0
Hardware Version:	5.0
EUT Power Supply:	110-240V~ 50/60Hz

3.3 General Description of BT Classic

Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Number of Channel:	79
Transfer Rate:	1Mbps/2Mbps/3Mbps
Hopping Channel Type:	Adaptive Frequency Hopping systems
Sample Type:	☒ Mobile ☐ Portable ☐ Fix Location
Antenna Type:	PCB antenna
Antenna Gain:	-0.68dBi

NOTE:

B901D, H7922, B902D, B903D, B904D, B905D, B906D, B907D, B908D, B909D, B910D, B911D, B912D, B913D, B914D, B915D, B917D, B918D, B919D, B920D, H7901, H7902, H7910, H7911, H7912, H7913, H7915, H7916, H7923, H7925, H7928, H7933, H7935, H7936, H7937, H7938, H7903, H7905, H7906, H7907, H7919, H7920, H7921, B901, H7926, H7927, H7927, H7929, H7930, H7931, H7932

The circuit design, layout, components used and internal wiring are all the same, except for the color appearance difference

4 MPE Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator. For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases}$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave Dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.1.3 EUT RF Exposure

1) For BT Classic

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-3.86	-3±1	-2	0.631
Middle(2441MHz)	-3.57	-3±1	-2	0.631
Highest(2480MHz)	-3.72	-3±1	-2	0.631
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-2.3	-2±1	-1	0.794
Middle(2441MHz)	-2.07	-2±1	-1	0.794
Highest(2480MHz)	-2.07	-2±1	-1	0.794
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-2	-2±1	-1	0.794
Middle(2441MHz)	-1.83	-1±1	0	1
Highest(2480MHz)	-1.52	-1±1	0	1

The maximum output power of this product is less than 3060mW

Note: 1) Refer to report No. CQASZ20220400507E-01 for EUT test Max Conducted Peak Output Power value.

2) EUT's Bluetooth module is more than 20cm away from the human body.

*** END OF REPORT ***