



**EMC Technologies Pty Ltd**

ABN 82 057 105 549  
57 Assembly Drive  
Tullamarine Victoria Australia 3043

Ph: + 613 9335 3333  
Fax: + 613 9338 9260  
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION  
to  
FCC PART 15 Subpart C (Section 15.247) & RSS-210**

FCC ID: EJE-WB0031  
Industry Canada ID: 337J-WB0031

Test Sample: LifeBook "C" Series  
Model: C1320

Radio Modules: Mini-PCI WLAN (Calexico2), Model: WM3B2200BG &  
Bluetooth Model: UGXZ5-102A

Report Number M050534\_Cert\_WM3B2200BG\_BT

Tested for: Fujitsu Australia Ltd.

Issue Date: 10<sup>th</sup> June 2005

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full.

NATA Accredited Laboratory  
Number: 5292

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**  
**EMC Technologies Report No. M050534\_Cert\_WM3B2200BG\_BT**  
**Issue Date: 10<sup>th</sup> June 2005**

**CONTENTS**

- 1.0 SUMMARY of TEST RESULTS**
- 2.0 GENERAL INFORMATION**

**RESULTS – Part 1: WLAN Module, Calexico2, WM3B2200BG**

- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 SPURIOUS EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH**
- 7.0 RADIO FREQUENCY EXPOSURE**
- 8.0 PEAK POWER SPECTRAL DENSITY**
- 9.0 ANTENNA REQUIREMENT**
- 10.0 COMPLIANCE STATEMENT**

**RESULTS – Part 2: Bluetooth, Model: UGXZ5-102A**

- 11.0 CONDUCTED EMI MEASUREMENTS**
- 12.0 SPURIOUS EMI MEASUREMENTS**
- 13.0 PEAK OUTPUT POWER**
- 14.0 CHANNEL BANDWIDTH & CHANNEL OCCUPANCY**
- 15.0 RADIO FREQUENCY EXPOSURE**
- 16.0 ANTENNA REQUIREMENT**
- 17.0 COMPLIANCE STATEMENT**

- APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**
- APPENDIX B: REPORT PHOTOGRAPHS**
- APPENDIX C: FUNCTIONAL DESCRIPTION**
- APPENDIX D: BLOCK DIAGRAM**
- APPENDIX E: SCHEMATICS**
- APPENDIX F: ANTENNA INFORMATION**
- APPENDIX G: FCC LABELLING DETAILS**
- APPENDIX H: USER MANUAL**
- APPENDIX I: CHANNEL BANDWIDTH PLOTS**
- APPENDIX J: HARMONICS PLOTS**
- APPENDIX K: BANDEDGE PLOTS**
- APPENDIX L: PEAK POWER OUTPUT PLOTS**
- APPENDIX M: PEAK POWER SPECTRAL DENSITY PLOTS**
- APPENDIX N: BLUETOOTH CHANNEL OCCUPANCY PLOTS**

- Attachment 1: RF Exposure Information**
- Attachment 2: FCC DOC for LifeBook “C” Series**
- Attachment 3: FCC Part 15B Test Report (Report: FG05-053EAL)**



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

**Report Number:** M050534\_Cert\_WM3B2200BG\_BT

**Test Sample:** LifeBook "C" Series  
**Model:** C1320  
**Radio Modules:** Mini-PCI WLAN, Model: WM3B2200BG (INTEL Corp.)  
Bluetooth, Model: UGXZ5-102A (Fujitsu Ltd)

**FCC ID:** EJE-WB0031  
**Industry Canada ID:** 337J-WB0031  
**Equipment Type:** Intentional Radiator (Transceiver)

**Manufacturer (LifeBook):** Fujitsu Ltd  
**Address:** 1405, Ohamaru, Inagi-shi, Tokyo 206-8503, Japan  
**Contact:** Mr. Tsuyoshi Uchihara

**Tested for:** Fujitsu Australia Ltd


**Test Standards:** FCC Part 15, Subpart C – Intentional Radiators  
FCC Part 15.247, 2400 – 2483.5 MHz Operation Band  
ANSI C63.4 – 2003  
OET Bulletin No. 65

RSS-210 Issue 5 Low Power Licence-Exempt RadioCommunication  
Devices: 6.2.2 (o) 2400 – 2483.5 MHz Spread Spectrum

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and  
Portable Radio Transmitters with respect to Health Canada's Safety  
Code 6 for Exposure of Humans to Radio Frequency Fields

**Test Dates:** 2<sup>nd</sup> to 9<sup>th</sup> June 2005


**Test Officer:**

  
\_\_\_\_\_  
**Chieu Huynh - B.Eng (Hons) Electronics**  
**Jorge Lara**

**Attestation:**

*I hereby certify that the device(s) described herein were tested as described  
in this report and that the data included is that which was obtained during  
such testing.*

**Authorised Signatory:**

  
\_\_\_\_\_  
**Chris Zombolas**  
**Technical Director**  
**EMC Technologies Pty Ltd**



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**EMI TEST REPORT FOR CERTIFICATION**  
**to**  
**FCC PART 15 Subpart C (Section 15.247) & RSS-210**

## **1.0 INTRODUCTION**

EMI testing was performed on test sample LifeBook "C" Series, Model: C1320 with Mini-PCI Wireless LAN Module (Calexico2, 11b/g), Model WM3B2200BG & Bluetooth, Model UGXZ5-102A.

The Calexico2 module supports IEEE 802.11b and IEEE 802.11g configurations. Tests were performed in both configurations and also on the Bluetooth. The results for IEEE 802.11b, IEEE 802.11g configurations and the Bluetooth are reported

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complied with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) and the RF exposure requirements of RSS-102.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 1.1 Summary of Results

### 1.1.1 WLAN Module (Refer to Results – Part 1)

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Complies
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (b)(5)		Radio Frequency Hazard	Complies
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (d)	6.2.2(o)(iv)	Peak Power Spectral Density	Complies

### 1.1.2 Bluetooth (Refer to Results – Part 2)

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Not Applicable
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Complies
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(1)&(3)	6.2.2(o)(ii)	Channel Occupancy/Bandwidth	Complies
15.247 (b)(1)	6.2.2(o)(b)	Peak Output Power	Complies
15.247 (b)(5)		Radio Frequency Hazard	Complies
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	Complies

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

## 1.2 Modifications by EMC Technologies

No modifications were required.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 2.0 GENERAL INFORMATION

(Information supplied by the Client)

### 2.1 Product Details

<b>Test Sample (Host PC):</b>	LifeBook "C" Series
<b>Model Number:</b>	C1320
<b>Serial Number:</b>	Pre-production Sample
<b>Manufacturer:</b>	Fujitsu Ltd
<b>CPU Type and Speed:</b>	Pentium-M 2.26 GHz Celeron-M 1.7 GHz
<b>Wired LAN:</b>	Broadcom BCM5751M 10 Base-T/100 Base-TX/1000 Base-T)
<b>Modem:</b>	Agere MDC 1.5, Model: AM2
<b>Port Replicator Model:</b>	FPCPR48 / FPCPR48AP
<b>AC Adapter Model:</b>	SEC80P2-19.0 / UJ99
<b>Voltage:</b>	19 V
<b>Current Specs:</b>	3.16 A
<b>Watts:</b>	60 W
<b>Radio Modules:</b>	WLAN (Calexico2 11b/g) and Bluetooth
<b>WLAN Model Number:</b>	WM3B2200BG
<b>WLAN Manufacturer:</b>	INTEL Corp.
<b>Interface Type:</b>	Mini-PCI Wireless LAN Module
<b>Bluetooth Model Number:</b>	UGXZ5-102A
<b>Bluetooth Manufacturer:</b>	Fujitsu Ltd
<b>FCC ID:</b>	EJE-WB0031
<b>Industry Canada ID:</b>	337J-WB0031
<b>Equipment Type:</b>	Intentional Radiator (Transceiver)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 2.2 Technical Specifications

### 2.2.1 WLAN Transmitter Specifications

<b>Transmitter #1:</b>	Mini-PCI Wireless LAN Module
<b>Wireless Module:</b>	Calexico2
<b>Model Number:</b>	WM3B2200BG
<b>Manufacturer:</b>	INTEL Corp.
<b>Modulation Type:</b>	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11g)
<b>802.11g</b>	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps
<b>802.11b</b>	DBPSK – 1Mbps DQPSK – 2Mbps CCK – 5.5Mbps, 11Mbps
<b>Maximum Data Rate:</b>	802.11b = 11Mbps and 802.11g = 54Mbps
<b>Frequency Range:</b>	2.4 – 2483.5 GHz for 11b/g
<b>Number of Channels:</b>	11 maximum (for 11b/11g)
<b>Antenna Types:</b>	2 x Nissei Electric Inverted-F, Model: CP250925 Located on top edge (left and right) of LCD screen
<b>Antenna gain:</b>	802.11b/g = 0.73 dBi
<b>Max. Output Power:</b>	802.11b = 18 dBm 802.11g = 15 dBm
<b>Power Supply:</b>	3.3 VDC from PCI bus

**Frequency allocation and maximum output power setting for 802.11b/g:**

Channel Number	Frequency (MHz)	Radio Utility Gain Setting	
		802.11b	802.11g
1	2412*	29	23.5
2	2417	29	23.5
3	2422	29	23.5
4	2427	29	23.5
5	2432	29	23.5
6	2437*	29	23.5
7	2442	29	23.5
8	2447	29	23.5
9	2452	29	23.5
10	2457	29	23.5
11	2462*	29	23.5

\*Channels tested and reported in this report – Part 1



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

### 2.2.2 Bluetooth Transmitter Specifications

<b>Transmitter:</b>	Bluetooth
<b>Model Number:</b>	UGXZ5-102A
<b>Manufacturer:</b>	Fujitsu Ltd
<b>Network Standard:</b>	Bluetooth™ RF Test Specification
<b>Modulation Type:</b>	Frequency Hopping Spread Spectrum (FHSS)
<b>Frequency Range:</b>	2402 MHz to 2480 MHz
<b>Number of Channels:</b>	79
<b>Carrier Spacing:</b>	1.0 MHz
<b>Antenna Types:</b>	Yokowo Antenna, Model: YCE-5250 Located on the right hinge of LCD screen
<b>Antenna gain:</b>	0.6 dBi
<b>Max. Output Power:</b>	12 dBm
<b>Reference Oscillator:</b>	16 MHz (Built-in)
<b>Power Supply:</b>	3.3 VDC from host.

#### Frequency allocation:

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
<b>1*</b>	<b>2402</b>	Power (Ext, Int) = 180, 46
2	2403	
3	2404	
.	.	
.	.	
.	.	
39	2440	
<b>40*</b>	<b>2441</b>	
41	2442	
.	.	
.	.	
.	.	
77	2478	
78	2479	
<b>79*</b>	<b>2480</b>	

\*Channels tested and reported in this report – Part 2



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.



## 2.3 Operational Description

The EUT is a LifeBook "C" Series, Model: C1320 installed with a Mini-PCI Wireless LAN (WLAN) Module (Calexico2 11b/g, Model WM3B2200BG) & Bluetooth, Model UGXZ5-102A.

The same WLAN radio module and Bluetooth combination has been previously certified by Fujitsu under FCC ID: EJE-WB0020 and IC: 337J-WB0020 in a different host.

The intention of this application is to re-certify this WLAN and Bluetooth with a different antenna combination in host – LifeBook "C" Series, Model: C1320.

## 2.4 Test Configuration

The INTEL Calexico2 utility software and the BlueSuiteCasira software were used to set-up the WLAN module and Bluetooth devices respectively to continuously transmit during the tests. The LCD screen was observed for the transmitter status shown for the respective softwares.

### Antenna

The Calexico2 WLAN (WM3B2200BG) is configured with Nissei Electric Inverted-F Antenna – Model: CP250925 and ALPS Bluetooth device, Model UGXZ5-102A is configured with Yokowo Antenna - Model: YCE-5250. The installation of the OEM WLAN module, Bluetooth Device and the Antenna in Fujitsu LifeBook "C" Series, Model: C1320 is in a controlled environment. The installation is performed during the production/assembly process at the Fujitsu factory.

Refer to Appendix F – Antenna Information.

There are three antennas: WLAN antennas (x2) are located on the right hand side and left hand side on the top edge of the LCD screen. Bluetooth antenna is located on the right hinge of LCD screen.

Refer to photos in Appendix B3 for WLAN and Bluetooth Antenna locations.

### AC Adapter

The AC adapter SEC80P2-19.0 was used for all the tests. Details of the AC adapter are supplied in section 2.1 of this report.

## 2.5 Block Diagram

Refer to Appendix D - Block Diagram



## 2.6 Support Equipment

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-053EAL)

## 2.7 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 3 and 1 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.

## 2.8 Test Facility

### 2.8.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted emission measurements were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above sites have been fully described in a report submitted to the FCC office, and accepted in a letter dated June 14, 2002, **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional). **Industry Canada File Number, IC 4161**, (Registration Date - November 5<sup>th</sup> 2001).

### 2.8.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

***“FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E).”***

The current full scope of accreditation can be found on the NATA website: [www.nata.asn.au](http://www.nata.asn.au)  
It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A<sup>2</sup>LA).



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 2.9 Units of Measurements

### 2.9.1 Conducted Emissions

Measurements are reported in units of dB relative to one microvolt. (dB $\mu$ V).

### 2.9.2 Radiated Emissions

Measurements are reported in units of dB relative to one microvolt per metre (dB $\mu$ V/m).

## 2.10 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A of this report.

## 2.11 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## RESULTS – PART 1

### WLAN Module – Calxico2 (WM3B2200BG)

#### 3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207  
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-053EAL)

#### 4.0 SPURIOUS EMISSION MEASUREMENTS

##### 4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(c).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115 and EMCO 3116 Horn antennas were used for measurements between 1 to 25 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-053EAL).

The measurement of emissions above 1000 MHz, appearing in the restricted bands, was made using an average detector with a bandwidth of 1.0 MHz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

##### 4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

**E = V + AF - G + L** Where:

<b>E</b>	=	Radiated Field Strength in dBμV/m.
<b>V</b>	=	EMI Receiver Voltage in dBμV. (measured value)
<b>AF</b>	=	Antenna Factor in dB(m <sup>-1</sup> ). (stored as a data array)
<b>G</b>	=	Preamplifier Gain in dB. (stored as a data array)
<b>L</b>	=	Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

##### • Example Field Strength Calculation

Assuming a receiver reading of 34.0 dBμV is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz) ± 4.1 dB



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

### 4.3 Radiated Emissions (Spurious and Harmonics)

#### 4.3.1 Frequency Band: 1 – 25 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 54 dB $\mu$ V/m limit at 3 metres has been converted to 64 dB $\mu$ V/m at 1 metre using a factor of 20 dB per decade where emissions were located in the restricted bands.

Testing was performed with the WLAN transmitter continuously operated. Harmonics related to the WLAN transmitter are reported below. For harmonics related to the Bluetooth transmitter, Refer to Part 2 of this test report.

Measurements for the WLAN were made on a low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

##### 4.3.1.1 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 11 Mbps (CCK).

The field strength at 2483.5 MHz when the EUT was operating at its highest channel (2462 MHz), was 56.9 dB $\mu$ V/m peak & 39.2 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 2400 MHz when the EUT was operating at its lowest channel (2412 MHz), was 70.4 dB $\mu$ V/m peak & 56.6 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

##### Channel 1 - 2412 MHz

Frequency MHz	Level dB $\mu$ V/m		Antenna Polarization	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
	Peak Detector	Average Detector				
2412	Transmitter	Fundamental				
4824	50	37	Vert/Hort	74.0	54.0	Pass
7236	54	41	Vert/Hort	-	-	Pass
9648	56	43	Vert/Hort	-	-	Pass
12060	57	44	Vert/Hort	74.0	54.0	Pass
14472	61	47	Vert/Hort	74.0	54.0	Pass
16884	64	50	Vert/Hort	-	-	Pass
19296	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21708	67	54	Vert/Hort	-	-	Pass
24120	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



**Channel 6 - 2437 MHz**

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2437	Transmitter	Fundamental				
4874	50	37	Vert/Hort	74.0	54.0	Pass
7311	54	41	Vert/Hort	74.0	54.0	Pass
9748	56	43	Vert/Hort	-	-	Pass
12185	57	44	Vert/Hort	74.0	54.0	Pass
14622	61	47	Vert/Hort	-	-	Pass
17059	64	50	Vert/Hort	-	-	Pass
19496	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21933	67	54	Vert/Hort	-	-	Pass
24370	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Channel 11 - 2462 MHz**

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2462	Transmitter	Fundamental				
4924	50	37	Vert/Hort	74.0	54.0	Pass
7386	54	41	Vert/Hort	74.0	54.0	Pass
9848	56	43	Vert/Hort	-	-	Pass
12310	57	44	Vert/Hort	74.0	54.0	Pass
14772	61	47	Vert/Hort	-	-	Pass
17234	64	50	Vert/Hort	-	-	Pass
19696	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22158	67	54	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24620	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Result:** No harmonics were recorded within the restricted bands of up to 25 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**4.3.1.2 Configuration 802.11g**

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

The field strength at 2483.5 MHz when the EUT was operating at its highest channel (2462 MHz), was 62.6 dB $\mu$ V/m peak & 43.8 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 2400 MHz when the EUT was operating at its lowest channel (2412 MHz), was 78.7 dB $\mu$ V/m peak & 56.1 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

**Channel 1 - 2412 MHz**

Frequency MHz	Level dB $\mu$ V/m		Antenna Polarization	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
	Peak Detector	Average Detector				
2412	Transmitter	Fundamental				
4824	50	37	Vert/Hort	74.0	54.0	Pass
7236	54	41	Vert/Hort	-	-	Pass
9648	56	43	Vert/Hort	-	-	Pass
12060	57	44	Vert/Hort	74.0	54.0	Pass
14472	61	47	Vert/Hort	74.0	54.0	Pass
16884	64	50	Vert/Hort	-	-	Pass
19296	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21708	67	54	Vert/Hort	-	-	Pass
24120	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Channel 6 - 2437 MHz**

Frequency MHz	Level dB $\mu$ V/m		Antenna Polarization	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
	Peak Detector	Average Detector				
2437	Transmitter	Fundamental				
4874	50	37	Vert/Hort	74.0	54.0	Pass
7311	54	41	Vert/Hort	74.0	54.0	Pass
9748	56	43	Vert/Hort	-	-	Pass
12185	57	44	Vert/Hort	74.0	54.0	Pass
14622	61	47	Vert/Hort	-	-	Pass
17059	64	50	Vert/Hort	-	-	Pass
19496	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21933	67	54	Vert/Hort	-	-	Pass
24370	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



**Channel 11 - 2462 MHz**

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2462	Transmitter	Fundamental				
4924	50	37	Vert/Hort	74.0	54.0	Pass
7386	54	41	Vert/Hort	74.0	54.0	Pass
9848	56	43	Vert/Hort	-	-	Pass
12310	57	44	Vert/Hort	74.0	54.0	Pass
14772	61	47	Vert/Hort	-	-	Pass
17234	64	50	Vert/Hort	-	-	Pass
19696	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22158	67	54	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24620	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Result:** No harmonics were recorded within the restricted bands of up to 25 GHz. Harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.

**4.3.2 Frequency Band: 30 - 1000 MHz**

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-053EAL)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.



#### 4.3.3 RF Conducted Measurements at the Antenna Terminal

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Measurements for the WLAN were made on a low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

##### 4.3.3.1 Calexico2 (WM3B2200BG) - Configuration 802.11b

Refer to Appendix J1 for Harmonics plots

##### 4.3.3.1 Calexico2 (WM3B2200BG) - Configuration 802.11g

Refer to Appendix J2 for Harmonics plots

**Result:** Complies.

#### 4.3.4 Band Edge Measurements

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Testing was performed while the WLAN transmitter continuously transmitted on a low (2412 MHz) and high frequency (2462 MHz) channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

##### 4.3.4.1 Calexico2 (WM3B2200BG) - Configuration 802.11b

Refer to Appendix K1 for Band Edge plots

**NB:** D1 line indicates the 20 dB limit below the highest level of the transmitter

##### 4.3.4.2 Calexico2 (WM3B2200BG) - Configuration 802.11g

Refer to Appendix K2 for Band Edge plots

**NB:** D1 line indicates the 20 dB limit below the highest level of the transmitter

**Result:** Complies.



**5.0 PEAK OUTPUT POWER - Section 15.247 (b)(1) & (3)**

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(3).

Measurements were performed while the WLAN transmitter continuously transmitted.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The peak output power measurement was performed using the integration method as per test method # 3 of DA 02-2138. The resolution bandwidth of 1 MHz was used. The video bandwidth of 100 kHz was used ( $VBW \geq 1/T$ , where T (worst case) = 204  $\mu$ S

Variation by +/- 15% of the supply voltage, in accordance with Section 15.31(e), to the computer power supply did not vary the output power observed.

**5.1 Configuration 802.11b**

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). Peak output power with CCK modulation (rate = 11 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
2412	15.1	30	32.4	1000	Pass
2437	14.8	30	30.2	1000	Pass
2462	14.1	30	25.7	1000	Pass

**Result:** Complies.

**5.2 Configuration 802.11g**

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in peak output power were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Result
2412	11.4	30	13.8	1000	Pass
2437	11.2	30	13.2	1000	Pass
2462	11.0	30	12.6	1000	Pass

**Result:** Complies



## 6.0 CHANNEL BANDWIDTH

Testing was performed in accordance with the requirements of FCC Part 15.247(a)(2)

In the band 2400 - 2483.5 MHz the minimum 6 dB bandwidth was at least 500 kHz. The 6 dB bandwidth was measured while the transmitter continuously transmitted on a low, middle and high frequency channel.

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised

Measurements were made on a low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

### 6.1 Configuration 802.11b

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operating with the modulation rate of 1 Mbps (DBPSK).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412.0	10.0	Complies	Appendix I1
2437.0	10.0	Complies	Appendix I1
2462.0	10.0	Complies	Appendix I1

The minimum 6 dB bandwidth is at least 500 kHz

**Result:** Complies

### 6.2 Configuration 802.11g

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in bandwidth were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 54 Mbps (64QAM).

Frequency MHz	Bandwidth MHz	Result	6 dB Bandwidth Plots
2412.0	16.4	Complies	Appendix I2
2437.0	16.5	Complies	Appendix I2
2462.0	16.4	Complies	Appendix I2

The minimum 6 dB bandwidth is at least 500 kHz

**Result:** Complies



## 7.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(5)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Transmitter # 1: The WLAN is a mobile device. The antennas are located on the top edge of LCD screen (2 antennas left and right) projected distance of greater than 20cm from the user.

Transmitter # 2: The Bluetooth is a portable device. The antenna is located on the right hinge of LCD screen projected distance of greater than 2.5cm from the bottom of the laptop.

The separation distance between the WLAN and BT antennas is greater than 20cm. Therefore, they are not co-located transmitters.

MPE calculation for Bluetooth is not applicable and SAR is not required as the power for BT is below the low threshold.

The MPE calculation shown below is for the WLAN mobile device for a separation distance of greater than 20cm.

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 1mW/cm<sup>2</sup>.

Friis transmission formula:  $P_d = (P \cdot G) / (4 \cdot \pi \cdot r^2)$

where:  $P_d$  = power density (mW/cm<sup>2</sup>)

$P$  = power input to the antenna (mW)

$G$  = antenna gain (numeric)

$r$  = distance to the center of radiation of the antenna (cm)

### The result was extracted from section 5.0 of this report (WLAN Module):

Maximum peak output power = 15.1dBm = 32.4mW

Antenna (Inverted F) gain (typical) = 0.73 dBi = 1.18 numeric

Prediction distance = 20 cm

Prediction frequency = 2412 MHz

MPE limit for uncontrolled exposure at prediction frequency = 1 mW/cm<sup>2</sup>

The power density calculated = 0.008 mW/cm<sup>2</sup>

**Results:** Calculations show that the Radio devices with described antennas complied with Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure



**8.0 PEAK POWER SPECTRAL DENSITY - Section 15.247(d)**

Testing was performed accordance with the requirements of FCC Part 15.247(d)

The transmitter output (antenna port) was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 3 kHz and the video bandwidth of 30 kHz were utilised

Testing was performed while the transmitter continuously transmitted on a low (channel 1, 2412 MHz), middle (channel 6, 2437 MHz) and high (Channel 11, 2462 MHz) frequency channel.

**8.1 Configuration 802.11b**

Initial investigations were performed with three modulation types: (DBPSK, DQPSK and CCK). Peak power spectral density with CCK modulation (rate = 11 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operating with the modulation rate of 11 Mbps (CCK).

Frequency MHz	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	-11.3	8.0	Complies	Appendix M1
2437.0	-11.9	8.0	Complies	Appendix M1
2462.0	-12.4	8.0	Complies	Appendix M1

The specification limit is 8 dBm in any 3 kHz band during a continuous transmission.

**Result:** Complies

**8.2 Configuration 802.11g**

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). Peak power spectral density with BPSK modulation (rate = 6 Mbps) was observed to be slightly worst. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

Frequency Hz	Level dBm	Limit dBm	Result	Spectral Density plots
2412.0	-17.5	8.0	Complies	Appendix M2
2437.0	-17.5	8.0	Complies	Appendix M2
2462.0	-18.8	8.0	Complies	Appendix M2

The specification limit is 8 dBm in any 3 kHz band during a continuous transmission.

**Result:** Complies



## 9.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## 10.0 COMPLIANCE STATEMENT

The LifeBook "C" Series, Model: C1320 with Mini-PCI Wireless LAN Module (Calexico2, 11b/g), Model WM3B2200BG & Bluetooth, Model UGXZ5-102A, tested on behalf of Fujitsu Australia Ltd, **complies** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 -Operation in the frequency band 2400 - 2483.5 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

### WLAN Module

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	<b>Complies</b>
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (b)(5)		Radio Frequency Hazard	<b>Complies</b>
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>
15.247 (d)	6.2.2(o)(iv)	Peak Power Spectral Density	<b>Complies</b>

### Bluetooth (Refer to Results – Part 2)

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(1)&(3)	6.2.2(o)(ii)	Channel Occupancy/Bandwidth	<b>Complies</b>
15.247 (b)(1)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (b)(5)		Radio Frequency Hazard	<b>Complies</b>
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>



## RESULTS – PART 2

### Bluetooth, Model UGXZ5-102A

#### 11.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207  
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-053EAL)

#### 12.0 RADIATED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.247(c).

##### 12.1 Test Procedure

As per section 4.1, Part 1

##### 12.2 Results – Out of Band Emissions (Spurious and Harmonics)

###### 12.2.1 Frequency Band: 1 – 25 GHz

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 54 dB $\mu$ V/m limit at 3 metres has been converted to 64 dB $\mu$ V/m at 1 metre using a factor of 20 dB per decade where emissions were located in the restricted bands.

Testing was performed with the Bluetooth transmitter continuously operated. Harmonics related to the Bluetooth transmitter are reported below. For harmonics related to the WLAN transmitter, Refer to Part 1 of this test report (Calexico2 - 802.11b/g).

Measurements for the WLAN were made on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

The field strength at 2483.5 MHz when the EUT was operating at its highest channel (2480 MHz), was 47.3 dB $\mu$ V/m peak & 35.0 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

The field strength at 2400 MHz when the EUT was operating at its lowest channel (2402 MHz), was 61.6 dB $\mu$ V/m peak & 51.9 dB $\mu$ V/m average and was > 20 dB below the maximum field strength of the in-band carrier.

###### Channel 1 - 2402 MHz

Frequency MHz	Level dB $\mu$ V/m		Antenna Polarization	Peak Limit dB $\mu$ V/m	Average Limit dB $\mu$ V/m	Result
	Peak Detector	Average Detector				
2402	Transmitter	Fundamental		-	-	
4804	50	37	Vert/Hort	74.0	54.0	Pass
7206	55.1	40.2	Vert/Hort	-	-	Pass
9608	56	43	Vert/Hort	-	-	Pass
12010	57	44	Vert/Hort	74.0	54.0	Pass
14412	61	47	Vert/Hort	-	-	Pass
16814	64	50	Vert/Hort	-	-	Pass
19216	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21618	67	54	Vert/Hort	-	-	Pass
24020	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

**Channel 40 - 2441 MHz**

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2441	Transmitter	Fundamental		-	-	
4882	50	37	Vert/Hort	74.0	54.0	Pass
7323	54.3	40.0	Vert/Hort	74.0	54.0	Pass
9764	56	43	Vert/Hort	-	-	Pass
12205	57	44	Vert/Hort	74.0	54.0	Pass
14646	61	47	Vert/Hort	-	-	Pass
17087	64	50	Vert/Hort	-	-	Pass
19528	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
21969	67	54	Vert/Hort	-	-	Pass
24410	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Channel 79 - 2480 MHz**

Frequency MHz	Level dBuV/m		Antenna Polarization	Peak Limit dBuV/m	Average Limit dBuV/m	Result
	Peak Detector	Average Detector				
2480	Transmitter	Fundamental		-	-	
4960	50	37	Vert/Hort	74.0	54.0	Pass
7440	54.4	39.7	Vert/Hort	74.0	54.0	Pass
9920	56	43	Vert/Hort	-	-	Pass
12400	57	44	Vert/Hort	74.0	54.0	Pass
14880	61	47	Vert/Hort	-	-	Pass
17360	64	50	Vert/Hort	-	-	Pass
19840	65	52	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
22320	67	54	Vert/Hort	84.0* (1m)	64.0* (1m)	Pass
24800	68	55	Vert/Hort	-	-	Pass

\*Measurement was performed at 1 metre distance and the limits were corrected accordingly.

**Result:** 3<sup>rd</sup> harmonic was recorded within the restricted bands of up to 25 GHz. Other harmonics were confirmed low with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Harmonics were complied with the FCC limits in sections 15.209 and 15.247 by a margin of 14.0 dB. The measurement uncertainty for radiated emissions in this band was  $\pm 4.1$  dB.

**12.2.2 Frequency Band: 30 - 1000 MHz**

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG05-053EAL)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.



**12.2.3 RF Conducted Measurements at the antenna terminal**

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Measurements for the WLAN were made on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

Refer to Appendix J3 for Harmonics plots

**Result:** Complies.

**12.2.4 Band Edge Measurements**

In the 100 kHz bandwidth within the operating band, the highest emissions (spurious/harmonics) level that is produced by the intentional radiator shall be at least 20 dB below.

Testing was performed while the Bluetooth transmitter continuously transmitted on a low (2402 MHz) and high frequency (2480 MHz) channel.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 100 kHz and the video bandwidth of 300 kHz were utilised.

Refer to Appendix K3 for Band Edge plots

*NB:* D1 line indicates 20 dB limits below the highest level of the transmitter.

**Result:** Complies.

**13.0 PEAK OUTPUT POWER - Section 15.247 (b)(1) & (3)**

Testing was performed in accordance with the requirements of FCC Part 15.247(b)(3).

Measurements were performed while the Bluetooth transmitter continuously transmitted.

The transmitter output was connected to the spectrum analyser in peak hold mode.

The resolution bandwidth of 1 MHz and the video bandwidth of 3 MHz were utilised.

Testing was performed while the transmitter continuously transmitted on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

Variation by +/- 15% of the supply voltage, in accordance with section 15.31(e), to the computer power supply power did not cause any variations to the RF output power.

Frequency MHz	P dBm	Limit dBm	P mW	Limit mW	Power Plots
2402	9.8	30	9.6	1000	Appendix L
2441	9.1	30	8.1	1000	Appendix L
2480	8.8	30	7.6	1000	Appendix L

**Result:** Complies.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## 14.0 CHANNEL BANDWIDTH & CHANNEL OCCUPANCY

Testing was carried out in accordance with the requirements of FCC Part 15.247(a)(1)(i)&(iii)

The EUT was a Frequency Hopping Spread Spectrum transmitter and operated as described in section 2 of this report.

### 14.1 Channel Bandwidth

In the band 2400 - 2483.5 MHz the hopping channel carrier frequencies separated by a minimum of 25kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

The transmitter output was connected to the spectrum analyser in peak hold mode.

A resolution bandwidth of 30 kHz and the video bandwidth of 100 kHz were utilised.

Testing was performed while the transmitter continuously transmitted on a low (channel 1, 2402 MHz), middle (channel 40, 2441 MHz) and high (Channel 79, 2480 MHz) frequency channel.

Frequency MHz	Bandwidth kHz	Result	20 dB Bandwidth Plots
2402	739	Complies	Appendix I3
2441	745	Complies	Appendix I3
2480	733	Complies	Appendix I3

### 14.2 Channel Occupancy

79 channels were observed operating between 2400 – 2483.5 MHz. Refer to Appendix N for number of channel plot.

The channel separation of 1 MHz was recorded. Refer to Appendix N for number of channel separation plot.

The device was observed to have a dwell time of 410.8 uS. This measurement was made on a channel using a spectrum analyser with a 0 Hz span and a sweep time of 5 mS. Refer to Appendix N for dwell time plot.

The specification allows for a dwell time not exceeding 0.4 seconds.

The maximum period is 79 channels x 0.4 seconds = 31.6 seconds

During the test the transmitter was observed to activate on average 315 times in 31.6 seconds.

The transmitter therefore occupies in one channel for  $315 \times 410.8\mu\text{S} = 0.129$  seconds

**Result:** Complies.



## 15.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Refer to Results Part 1, Section 7.0

## 16.0 ANTENNA REQUIREMENT

Testing to the requirements of FCC Part 15.203 was not applicable as this intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## 17.0 COMPLIANCE STATEMENT

The LifeBook "C" Series, Model: C1320 with Mini-PCI Wireless LAN Module (Calexico2, 11b/g), Model WM3B2200BG & Bluetooth, Model UGXZ5-102A, tested on behalf of Fujitsu Australia Ltd, **complies** with the requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 -Operation in the frequency band 2400 - 2483.5 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 5 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

### Bluetooth

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(1)&(3)	6.2.2(o)(ii)	Channel Occupancy/Bandwidth	<b>Complies</b>
15.247 (b)(1)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (b)(5)		Radio Frequency Hazard	<b>Complies</b>
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>

### WLAN Module (Refer to Results – Part 1)

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	<b>Not Applicable</b>
15.205	6.3	Operation in Restricted Band	<b>Complies</b>
15.207	6.6	Conducted Emissions	<b>Complies</b>
15.209	6.3	Radiated Emissions	<b>Complies</b>
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	<b>Complies</b>
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	<b>Complies</b>
15.247 (b)(5)		Radio Frequency Hazard	<b>Complies</b>
15.247 (c)	6.2.2(o)(e1)	Out of Band Emissions	<b>Complies</b>
15.247 (d)	6.2.2(o)(iv)	Peak Power Spectral Density	<b>Complies</b>



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

## TEST REPORT APPENDICES

**APPENDIX A: MEASUREMENT INSTRUMENT DETAILS**  
**APPENDIX B: REPORT PHOTOGRAPHS**  
**APPENDIX C: FUNCTIONAL DESCRIPTION**  
**APPENDIX D: BLOCK DIAGRAM**  
**APPENDIX E: SCHEMATICS**  
**APPENDIX F: ANTENNA INFORMATION**  
**APPENDIX G: FCC LABELLING DETAILS**  
**APPENDIX H: USER MANUAL**  
**APPENDIX I: CHANNEL BANDWIDTH PLOTS**  
**APPENDIX J: HARMONICS PLOTS**  
**APPENDIX K: BANDEDGE PLOTS**  
**APPENDIX L: PEAK POWER OUTPUT PLOTS**  
**APPENDIX M: PEAK POWER SPECTRAL DENSITY PLOTS**  
**APPENDIX N: BLUETOOTH CHANNEL OCCUPANCY PLOTS**

**Attachment 1: RF Exposure Information**

**Attachment 2: FCC DOC for LifeBook "C" Series**

**Attachment 3: FCC Part 15B Test Report (Report: FG05-053EAL)**



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.