

Transmitter Solutions  
2480 South 3850 West, Suite B Salt Lake City UT 84120 United States

Federal Communications Commission  
Authorization and Evaluation Division  
Equipment Authorization Branch  
7435 Oakland Mills Road  
Columbia, MD 21046

### **Applicant's declaration concerning RF Radiation Exposure**

We hereby indicate that the product  
Product description: Remote Controller  
Model No: TX100A


The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. ~~The integral antennas used for this transmitter must not be co-located or~~ operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the  
Product : Remote Controller  
will be integrated in the user's manual to provide end-users with transmitter operating conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6M21806-18167-C-1 and the accompanying calculations.

Company: Transmitter Solutions  
Address: 2480 South 3850 West, Suite B Salt Lake City UT 84120 United States

Date: 2019-03-22

  
Signature



# ***Worldwide Testing Services(Taiwan) Co., Ltd.***

Registration number: W6M21806-18167-C-1

FCC ID: 2ASPOTX100A

## **3.2 RF Exposure Compliance Requirements**

FCC Rule: 15.247(b)(3)

Test exclusion = max. conducted output power

Test exclusion = 29.28 dBm

Test equipment used: ETSTW-RE 055

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

$$S = \frac{PG}{4\pi R^2}$$

S – Power Density

P – Output power ERP

R – Distance

D – Cable Loss

AG – Antenna Gain

Item	Unit	Value	Remarks
P	mW	847.2274	Peak value
D	dB		
AG	dBi	3.32	
G		2.15	Calculated Value
R	cm	20	Assumed value
S	mW/cm <sup>2</sup>	0.36	Calculated value

Limits:

Limit for General Population / Uncontrolled Exposure	
Frequency (MHz)	Power Density (mW/cm <sup>2</sup> )
1500 – 100.000	1.0