APPENDIX E: MULTI-TX AND ANTENNA SAR CONSIDERATIONS

E.1 Introduction

The following procedures adopted from FCC KDB Publication 447498 D01v06 are applicable to devices with builtin unlicensed transmitters such as 802.11 and Bluetooth devices which may simultaneously transmit with the licensed transmitter

E.2 Simultaneous Transmission Procedures

This device contains transmitters that may operate simultaneously. Therefore, simultaneous transmission analysis is required. Per FCC KDB Publication 447498 D01v06 and IEEE 1528-2013 Section 6.3.4.1.2, simultaneous transmission SAR test exclusion may be applied when the sum of the 1g SAR for all the simultaneous transmitting antennas in a specific a physical test configuration is ≤ 1.6 W/kg. The different test positions in an exposure condition may be considered collectively to determine SAR test exclusion according to the sum of 1g or 10g SAR. Total Exposure Ratio (TER) is used to show the maximum TER between APD and SAR values therefor the limit for simultaneous exposure becomes TER ≤ 1.0 .

Per FCC KDB Publication 941225 D06v02r01, the devices edges with antennas more than 2.5 cm from edge are not required to be evaluated for SAR ("-").

This device is enabled with Qualcomm® Smart Transmit Gen2 with pre-defined antenna groups (AG0 and AG1) and 1 mmW module group (MG). Sub6 and mmW antennas cannot be decoupled from each other due to lack of regulatory criteria. This device operates using GEN2_SUB6 (Sub6-favor mode) which assumes all mmW modules (MG) are collocated with each sub6 AG0 and AG1 in this device. The Simultaneous transmission analysis is performed per antenna groups. Below analysis demonstrates the mutually exclusive operation of AG0 and AG1, and the compliance between each antenna group with non-Smart Transmit Radios. For this model, WWAN/WLAN/BT/mmWave Radios are managed under Smart Transmit. Non-Smart Transmit Radios include NFC/UWB.

When operating in the same antenna group, the compliance under dynamic transmission condition, including all supported simultaneous transmission scenarios, should be assessed and demonstrated in the Part 2 Report during algorithm validation. Therefore, no further simultaneous analysis is needed within an antenna group.

When all WWAN/WLAN/BT/mmWave Radios are managed under Smart Transmit, TER for WWAN/WLAN/BT/mmWave is covered in Part 2 testing. Only external radios outside of WWAN/WLAN/BT/mmWave (UWB, NFC) require TER analysis with WWAN/WLAN/BT/mmWave during simultaneous transmissions.

E.3 Antenna Groups

The 2nd generation of Smart Transmit (GEN2) operates based on pre-defined antenna groups (AG). Sub6/WLAN/BT Tx antennas and/or mmW module groups (MG) in the device are grouped based on spatial variation of RF exposure distributions, where the RF exposure of one AG is mutually exclusive from other AG. This is accomplished by demonstrating either of below conditions for all exposure scenarios:

a) Sum of SAR of one antenna from each of the sub6 AGs and the RF exposure from radios outside Smart Transmit is less than regulatory limits. This condition must be demonstrated for all antenna combinations of sub6 AGs.

(or)

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by:
		Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 1 of 8

 b) Every antenna from each sub6 AG meets SPLSR criteria (Section 4.3.2(c) in FCC KDB 447498 D04) with every antenna from another sub6 AG. These criteria must be demonstrated for all antenna combinations for each pair of AGs.

This device supports two AGs: AG0 and AG1, with AG0 having 4 antennas (A, B, C, D) and AG1 having 5 antennas (E, F, H, I, J) and MG having 1 antenna (M)The conditions are verified through the following criteria:

- In Sub6-favor mode: All mmW antennas are assumed to collocate with each sub6 antenna group (AG). Also, since all mmW MGs are controlled by Smart Transmit, maximum mmW exposure is given by maximum out of all mmW modules: max.norm.exp.mmW = max.norm.exp.MG
- ii) Sum of SAR: Demonstrate that the sum of *max.norm.exp.AG*0 and *max.norm.exp.AG*1 and the reported normalized SAR values from radios outside Smart Transmit (denoted as *reported.norm.exp.ER*) should be less than the regulatory limit for each supported DSI following the below procedure:
- 1. Obtain the worst-case *adjusted SAR* for each antenna group, i.e., maximum *reported* SAR at EFS P_{iimt} +unc (or max of { P_{max} +unc, EFS P_{iimt} } when EFS $P_{iimt} > P_{max}$) out of all supported technologies, frequency bands and antennas in AG0 and AG1, then normalized to the regulatory limit to get the maximum normalized SAR for each antenna group, denoted as *max.norm.exp.AG0* and *max.norm.exp.AG1*
- For external radios outside of Smart Transmit (NFC/UWB): Obtain the worst-case RF exposure for each external radio normalized to regulatory limit to get the normalized SAR for each external radio, denoted as *reported.norm.exp.NFC* and *reported.norm.exp.UWB*
- 3. Demonstrate that the sum of these RF exposures meets: $\{max.norm.exp.AG0 + max.norm.exp.AG1 + normalized NFC SAR + normalized UWB SAR \} \le 1$.
- iii) SPLSR or composite exposure distribution criteria: when TER sum of an antenna pair is over the limit for a DSI/exposure position, SPLSR or composite exposure distribution can be done to demonstrate simultaneous transmission compliance.
- 1. SPLSR analysis for sub6 antenna pairs: For each antenna, obtain the highest *adjusted* SAR at EFS P_{tent} +unc (or max of { P_{max} +unc, EFS P_{tent} } when EFS $P_{tent} > P_{max}$) out of all supported technologies for each frequency band. Using these values, demonstrate for a given DSI that every antenna from one AG meets SPLSR criteria with every antenna in another AG for all frequency bands. This criterion must be demonstrated for all antenna pair combinations irrespective of supported simultaneous transmission scenarios as given below for each DSI. As it can be seen, these include all combinations of antenna groups, antennas, and frequency bands.
 - If SPLSR criteria evaluation and analysis is needed to determine compliance for a certain DSI configuration, SPLSR is performed by taking the highest reported SAR for each of the supported technologies and bands per antenna, along with the peak SAR locations. Per Qualcomm guidance, only Y-axis coordinates are recorded in the analysis for calculation simplicity (assumes all 0mm of separation on the x-axis). Peak locations are documented in the Highest Report SAR and Hotspot Location Section below for each DSI configuration. For bottom AG0, Y_max coordinates represents the worst-case hotspot location that is closest to the top AG1. Similarly, for top AG1, Y_min coordinate represents the worst-case hotspot location that is closest to the bottom AG0
 - The following formula is used to calculate the SPLSR between AG0 and AG1 for each exposure configuration:

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 2 of 8

$$SPLSR = \frac{(Max SAR AG0 + Max SAR AG1)^{1.5}}{|Y_{max} - Y_{min}|}$$

E.4 Head (DSI = 1) Antenna Group Analysis

Table E-1 DSI=1 Held-to-ear AG0 Highest Adjusted Ratio to Limit

	AG0 Ratio to Limit						
	Configuration	А	В	С	D	Max	
	Right Cheek	0.624	0.228	0.000	0.000	0.624	
Head	Right Tilt	0.394	0.228	0.000	0.000	0.394	
	Left Cheek	0.625	0.622	0.000	0.000	0.625	
	Left Tilt	0.324	0.204	0.008	0.000	0.324	

Table E-2

DSI=1 Held-to-ear AG1 Highest Adjusted Ratio to Limit

			AG1	Ratio to Limit				
	Configuration	E	F	Н	I	J	MIMO	Max
	Right Cheek	0.554	0.728	0.388	0.183	0.141	0.615	0.728
Head	Right Tilt	0.497	0.750	0.138	0.016	0.019	0.227	0.750
	Left Cheek	0.740	0.469	0.070	0.240	0.235	0.598	0.740
	Left Tilt	0.672	0.594	0.053	0.014	0.030	0.097	0.672

Table E-3 DSI=1 Held-to-ear AG Verification

Head	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit	
	Right Cheek	0.624	0.728	See Table Below	
	Right Tilt	0.394	0.750	See Table Below	
	Left Cheek	0.625	0.740	See Table Below	
	Left Tilt	0.324	0.672	0.996	

			Rig	ht Cheek				
	AG0			AG1			CDI CD	
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	SPLSR	
Ant A	0.624	-84.17	Ant E	0.554	-1.81	See Note 1	0.01	
Ant A	0.624	-84.17	Ant F	0.728	-3.22	See Note 1	0.02	
Ant A	0.624	-84.17	Ant H	0.388	-25.63	See Note 1	0.02	
Ant A	0.624	N/A	Ant I	0.183	N/A	0.807	N/A	
Ant A	0.624	N/A	Ant J	0.141	N/A	0.765	N/A	
Ant A	0.624	-84.17	MIMO	0.615	-0.82	See Note 1	0.01	
Ant B	0.228	N/A	Ant E	0.554	N/A	0.782	N/A	
Ant B	0.228	N/A	Ant F	0.728	N/A	0.956	N/A	
Ant B	0.228	N/A	Ant H	0.388	N/A	0.616	N/A	
Ant B	0.228	N/A	Ant I	0.183	N/A	0.411	N/A	
Ant B	0.228	N/A	Ant J	0.141	N/A	0.369	N/A	
Ant B	0.228	N/A	MIMO	0.615	N/A	0.843	N/A	
Ant C	0.000	N/A	Ant E	0.554	N/A	0.554	N/A	
Ant C	0.000	N/A	Ant F	0.728	N/A	0.728	N/A	
Ant C	0.000	N/A	Ant H	0.388	N/A	0.388	N/A	
Ant C	0.000	N/A	Ant I	0.183	N/A	0.183	N/A	
Ant C	0.000	N/A	Ant J	0.141	N/A	0.141	N/A	
Ant C	0.000	N/A	MIMO	0.615	N/A	0.615	N/A	
Ant D	0.000	N/A	Ant E	0.554	N/A	0.554	N/A	
Ant D	0.000	N/A	Ant F	0.728	N/A	0.728	N/A	
Ant D	0.000	N/A	Ant H	0.388	N/A	0.388	N/A	
Ant D	0.000	N/A	Ant I	0.183	N/A	0.183	N/A	
Ant D	0.000	N/A	Ant J	0.141	N/A	0.141	N/A	
Ant D	0.000	N/A	MIMO	0.615	N/A	0.615	N/A	

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by:
DUT Type: Portable Handset		APPENDIX E: Page 3 of 8

			Rig	ht Tilt			
	AG0			AG1			
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	SPLSK
Ant A	0.394	N/A	Ant E	0.497	N/A	0.891	N/A
Ant A	0.394	-67.00	Ant F	0.750	1.95	See Note 1	0.01
Ant A	0.394	N/A	Ant H	0.138	N/A	0.532	N/A
Ant A	0.394	N/A	Ant I	0.016	N/A	0.410	N/A
Ant A	0.394	N/A	Ant J	0.019	N/A	0.413	N/A
Ant A	0.394	N/A	MIMO	0.227	N/A	0.621	N/A
Ant B	0.228	N/A	Ant E	0.497	N/A	0.725	N/A
Ant B	0.228	N/A	Ant F	0.750	N/A	0.978	N/A
Ant B	0.228	N/A	Ant H	0.138	N/A	0.366	N/A
Ant B	0.228	N/A	Ant I	0.016	N/A	0.244	N/A
Ant B	0.228	N/A	Ant J	0.019	N/A	0.247	N/A
Ant B	0.228	N/A	MIMO	0.227	N/A	0.455	N/A
Ant C	0.000	N/A	Ant E	0.497	N/A	0.497	N/A
Ant C	0.000	N/A	Ant F	0.750	N/A	0.750	N/A
Ant C	0.000	N/A	Ant H	0.138	N/A	0.138	N/A
Ant C	0.000	N/A	Ant I	0.016	N/A	0.016	N/A
Ant C	0.000	N/A	Ant J	0.019	N/A	0.019	N/A
Ant C	0.000	N/A	MIMO	0.227	N/A	0.227	N/A
Ant D	0.000	N/A	Ant E	0.497	N/A	0.497	N/A
Ant D	0.000	N/A	Ant F	0.750	N/A	0.750	N/A
Ant D	0.000	N/A	Ant H	0.138	N/A	0.138	N/A
Ant D	0.000	N/A	Ant I	0.016	N/A	0.016	N/A
Ant D	0.000	N/A	Ant J	0.019	N/A	0.019	N/A
Ant D	0.000	N/A	MIMO	0.227	N/A	0.227	N/A

	Left Cheek								
	AG0 AG1		AG0		AG0 AG1			AG0 + AG1	CDI CD
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	SPLSK		
Ant A	0.625	-53.95	Ant E	0.740	0.07	See Note 1	0.02		
Ant A	0.625	-53.95	Ant F	0.469	-0.50	See Note 1	0.01		
Ant A	0.625	N/A	Ant H	0.070	N/A	0.695	N/A		
Ant A	0.625	N/A	Ant I	0.240	N/A	0.865	N/A		
Ant A	0.625	N/A	Ant J	0.235	N/A	0.860	N/A		
Ant A	0.625	-53.95	MIMO	0.598	1.61	See Note 1	0.02		
Ant B	0.622	-76.00	Ant E	0.740	0.07	See Note 1	0.02		
Ant B	0.622	-76.00	Ant F	0.469	-0.50	See Note 1	0.01		
Ant B	0.622	N/A	Ant H	0.070	N/A	0.692	N/A		
Ant B	0.622	N/A	Ant I	0.240	N/A	0.862	N/A		
Ant B	0.622	N/A	Ant J	0.235	N/A	0.857	N/A		
Ant B	0.622	-76.00	MIMO	0.598	1.61	See Note 1	0.01		
Ant C	0.000	N/A	Ant E	0.740	N/A	0.740	N/A		
Ant C	0.000	N/A	Ant F	0.469	N/A	0.469	N/A		
Ant C	0.000	N/A	Ant H	0.070	N/A	0.070	N/A		
Ant C	0.000	N/A	Ant I	0.240	N/A	0.240	N/A		
Ant C	0.000	N/A	Ant J	0.235	N/A	0.235	N/A		
Ant C	0.000	N/A	MIMO	0.598	N/A	0.598	N/A		
Ant D	0.000	N/A	Ant E	0.740	N/A	0.740	N/A		
Ant D	0.000	N/A	Ant F	0.469	N/A	0.469	N/A		
Ant D	0.000	N/A	Ant H	0.070	N/A	0.070	N/A		
Ant D	0.000	N/A	Ant I	0.240	N/A	0.240	N/A		
Ant D	0.000	N/A	Ant J	0.235	N/A	0.235	N/A		
Ant D	0 000	N/A	MIMO	0 598	N/A	0 598	Ν/Δ		

Notes:

- 1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D01v06. Since TER was used in this evaluation the FCC SPLSR Limit of 0.04 is equivalent to the TER SPLSR of 0.02.
- 2. As a conservative assessment, the distances between AG0 and AG1 were determined using the worst case Y-axis coordinates of the peak locations only (assumes 0 mm separation on x/z axis) per antenna.
- 3. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 4 of 8

E.5 Body-worn (DSI = 0) Antenna Group Analysis

	DSI=0 Body-v	۲ worn AG0 I	able E-4 Highest Ad	justed Rat	io to Limit	
	AGO Ratio to Limit					
Reduuero	Configuration	А	В	C	D	Max
воцумот	Back	0.581	0.187	0.058	0.113	0.581

Table E-5
DSI=0 Body-worn AG1 Highest Adjusted Ratio to Limit

AG1 Ratio to Limit								
Reduwern	Configuration	E	F	н	I	J	MIMO	Max
Bouyworn	Back	0.620	0.199	0.329	0.053	0.258	0.405	0.620

Table E-6 DSI=0 Body-worn AG Verification

Bodyworn	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.581	0.620	See Table Below

Back								
	AG0			AG1			601.60	
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	JF LJN	
Ant A	0.581	-66.60	Ant E	0.620	64.70	See Note 1	0.01	
Ant A	0.581	N/A	Ant F	0.199	N/A	0.780	N/A	
Ant A	0.581	N/A	Ant H	0.329	N/A	0.910	N/A	
Ant A	0.581	N/A	Ant I	0.053	N/A	0.634	N/A	
Ant A	0.581	N/A	Ant J	0.258	N/A	0.839	N/A	
Ant A	0.581	N/A	MIMO	0.405	N/A	0.986	N/A	
Ant B	0.187	N/A	Ant E	0.620	N/A	0.807	N/A	
Ant B	0.187	N/A	Ant F	0.199	N/A	0.386	N/A	
Ant B	0.187	N/A	Ant H	0.329	N/A	0.516	N/A	
Ant B	0.187	N/A	Ant I	0.053	N/A	0.240	N/A	
Ant B	0.187	N/A	Ant J	0.258	N/A	0.445	N/A	
Ant B	0.187	N/A	MIMO	0.405	N/A	0.592	N/A	
Ant C	0.058	N/A	Ant E	0.620	N/A	0.678	N/A	
Ant C	0.058	N/A	Ant F	0.199	N/A	0.257	N/A	
Ant C	0.058	N/A	Ant H	0.329	N/A	0.387	N/A	
Ant C	0.058	N/A	Ant I	0.053	N/A	0.111	N/A	
Ant C	0.058	N/A	Ant J	0.258	N/A	0.316	N/A	
Ant C	0.058	N/A	MIMO	0.405	N/A	0.463	N/A	
Ant D	0.113	N/A	Ant E	0.620	N/A	0.733	N/A	
Ant D	0.113	N/A	Ant F	0.199	N/A	0.312	N/A	
Ant D	0.113	N/A	Ant H	0.329	N/A	0.442	N/A	
Ant D	0.113	N/A	Ant I	0.053	N/A	0.166	N/A	
Ant D	0.113	N/A	Ant J	0.258	N/A	0.371	N/A	
Ant D	0.113	N/A	MIMO	0.405	N/A	0.518	N/A	

Notes:

- 1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D01v06. Since TER was used in this evaluation the FCC SPLSR Limit of 0.04 is equivalent to the TER SPLSR of 0.02.
- 2. As a conservative assessment, the distances between AG0 and AG1 were determined using the worst case Y-axis coordinates of the peak locations only (assumes 0 mm separation on x/z axis) per antenna.
- 3. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 5 of 8

E.6 Hotspot (DSI = 0) SAR Antenna Group Analysis

DSI=0 Hotspot AG0 Highest Adjusted Ratio to Limit									
AG0 Ratio to Limit									
	Configuration	А	В	С	D	Max			
	Back	0.581	0.187	0.058	0.113	0.581			
	Front	0.391	0.101	0.009	0.008	0.391			
Hotspot	Тор	-	-	-	-	-			
	Bottom	0.742	0.146	0.007	0.026	0.742			
	Right	0.274	-	-	0.003	0.274			
	Left	0.248	0.176	0.098	-	0.248			

Table E-7 DSI=0 Hotspot AG0 Highest Adjusted Ratio to Limit

Table E-8 DSI=0 Hotspot AG1 Highest Adjusted Ratio to Limit

AG1 Ratio to Limit									
	Configuration	E	F	Н	_	J	MIMO	Max	
	Back	0.620	0.199	0.329	0.053	0.258	0.405	0.620	
	Front	0.606	0.216	0.188	0.049	0.498	0.256	0.606	
Hotspot	Тор	0.617	0.561	0.147	0.000	0.017	0.265	0.617	
	Bottom	-	-	-	-	-	-	-	
	Right	0.448	-	-	-	0.124	0.073	0.448	
	Left	-	0.127	0.330	0.012	-	0.340	0.340	

Table E-9 DSI=0 Hotspot AG Verification

Hotspot	Configuration	AG0 Ratio to Limit	AG1 Ratio to Limit	AG0 + AG1 Ratio to Limit
	Back	0.581	0.620	See Table Below
	Front	0.391	0.606	0.997
	Тор	-	0.617	0.617
	Bottom	0.742	-	0.742
	Right	0.274	0.448	0.722
	Left	0.248	0.340	0.588

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 6 of 8

Back								
	AG0			AG1			SPI SR	
Antenna	Ratio to Limit	Position	Antenna	Ratio to Limit	Position	Ratio to Limit	01 2011	
Ant A	0.581	-66.60	Ant E	0.620	64.70	See Note 1	0.01	
Ant A	0.581	N/A	Ant F	0.199	N/A	0.780	N/A	
Ant A	0.581	N/A	Ant H	0.329	N/A	0.910	N/A	
Ant A	0.581	N/A	Ant I	0.053	N/A	0.634	N/A	
Ant A	0.581	N/A	Ant J	0.258	N/A	0.839	N/A	
Ant A	0.581	N/A	MIMO	0.405	N/A	0.986	N/A	
Ant B	0.187	N/A	Ant E	0.620	N/A	0.807	N/A	
Ant B	0.187	N/A	Ant F	0.199	N/A	0.386	N/A	
Ant B	0.187	N/A	Ant H	0.329	N/A	0.516	N/A	
Ant B	0.187	N/A	Ant I	0.053	N/A	0.240	N/A	
Ant B	0.187	N/A	Ant J	0.258	N/A	0.445	N/A	
Ant B	0.187	N/A	MIMO	0.405	N/A	0.592	N/A	
Ant C	0.058	N/A	Ant E	0.620	N/A	0.678	N/A	
Ant C	0.058	N/A	Ant F	0.199	N/A	0.257	N/A	
Ant C	0.058	N/A	Ant H	0.329	N/A	0.387	N/A	
Ant C	0.058	N/A	Ant I	0.053	N/A	0.111	N/A	
Ant C	0.058	N/A	Ant J	0.258	N/A	0.316	N/A	
Ant C	0.058	N/A	MIMO	0.405	N/A	0.463	N/A	
Ant D	0.113	N/A	Ant E	0.620	N/A	0.733	N/A	
Ant D	0.113	N/A	Ant F	0.199	N/A	0.312	N/A	
Ant D	0.113	N/A	Ant H	0.329	N/A	0.442	N/A	
Ant D	0.113	N/A	Ant I	0.053	N/A	0.166	N/A	
Ant D	0.113	N/A	Ant J	0.258	N/A	0.371	N/A	
Ant D	0.113	N/A	MIMO	0.405	N/A	0.518	N/A	

Notes:

- 1. No evaluation was performed to determine the aggregate 1g SAR for these configurations as the SPLS ratio between the antenna pairs was not greater than 0.02 per FCC KDB 447498 D01v06. Since TER was used in this evaluation the FCC SPLSR Limit of 0.04 is equivalent to the TER SPLSR of 0.02.
- 2. As a conservative assessment, the distances between AG0 and AG1 were determined using the worst case Y-axis coordinates of the peak locations only (assumes 0 mm separation on x/z axis) per antenna.
- 3. For all combinations where the TER sum of AG0+AG1 is not greater than 1, there's no further analysis required for compliance demonstration.

E.7 Phablet (DSI = 0) Antenna Group Analysis

Per FCC KDB Publication 648474 D04 Handset SAR, Phablet SAR tests were not required if wireless router 1g SAR (scaled to the maximum output power, including tolerance) < 1.2 W/kg. Therefore, no further analysis beyond the tables included in this section was required to determine that possible simultaneous transmission scenarios would not exceed the SAR limit.

DSI=0 Phablet AG1 Highest Adjusted Ratio to Limit								
AG1 Ratio to Limit								
	Configuration	E	Н	MIMO	Max			
Phablet	Back	0.554	0.231	0.286	0.554			
	Front	0.069	0.226	0.237	0.237			
	Тор	0.114	0.080	0.145	0.145			
	Bottom	-	-	-	-			
	Right	0.028	-	0.034	0.034			
	Left	-	0.607	0.735	0.735			

Table E-10
DSI=0 Phablet AG1 Highest Adjusted Ratio to Limit

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 7 of 8

Phablet SAR	Configuration	AG1 Ratio to Limit	NFC Ratio to Limit	UWB Ratio to Limit	AG0 + AG1 + NFC + UWB Ratio to Limit
	Back	0.554	0.005	0.001	0.560
	Front	0.237	0.000	0.002	0.239
	Тор	0.145	0.000	0.001	0.146
	Bottom	-	-	-	-
	Right	0.034	_	_	0.034
	Left	0.735	0.000	0.004	0.739

Table E-11 DSI=0 Phablet AG, NFC and UWB Verification

Notes:

- 1. For all combinations where the TER sum of AG1 +UWB+NFC is not greater than 1, there's no further analysis required for compliance demonstration.
- 2.

E.8 Conclusion

The above numerical summed SAR results and SPLSR for all the combinations of antenna groups are sufficient to show that AG0 is mutually exclusive from AG1 and that MG is <1 TER. TER simultaneous transmission cases will not exceed the SAR limit or PD limit and therefore no measured volumetric simultaneous SAR summation is required per FCC KDB Publication 447498 D01v06 and IEEE 1528- 2013 Section 6.3.

FCC ID A3LSMS936B	RF EXPOSURE PART 1 TEST REPORT	Approved by: Technical Manager
DUT Type: Portable Handset		APPENDIX E: Page 8 of 8