



RADIO TEST REPORT

Report No:STS1806067W09

Issued for

SOURCENEXT CORPORATION

Shiodome City Center 33F, 1-5-2 Higashi Shinbashi
Minato-ku, Tokyo 105-7133, Japan

Product Name:	POCKETALK
Brand Name:	POCKETALK
Model Name:	W1PGK
Series Model:	W1PGG, W1PGW, W1PWG, W1PWK, W1PWW
FCC ID:	2AOJA-W1P
Test Standard:	FCC Part 22H and 24E

Any reproduction of this document must be done in full. No single part of this document may be reproduced without permission from STS, All Test Data Presented in this report is only applicable to presented Test sample.





TEST RESULT CERTIFICATION

Applicant's name : SOURCENEXT CORPORATION
Address: Shiodome City Center 33F, 1-5-2 Higashi Shinbashi Minato-ku, Tokyo 105-7133, Japan
Manufacture's Name : JENESIS(SHENZHEN)CO.,LTD
Address: 3F,Building A,Dajiahao Plaza,Yuan 2nd Road 362,Baoan 28th disctrict,Shenzhen, China

Product discription

Product Name : POCKETALK
Brand Name : POCKETALK
Model Name : W1PGK
Series Model : W1PGG, W1PGW, W1PWG, W1PWK, W1PWW

Test Standards : FCC Part 22H and 24E

Test procedure : KDB 971168 D01 v03r01,ANSI C63.26(2015)

This device described above has been tested by STS and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of STS, this document only be altered or revised by STS, personal only, and shall be noted in the revision of the document.

Date of Test

Date of performance of tests : 28 June 2018~06 Aug. 2018

Date of Issue : 06 Aug. 2018

Test Result : Pass

Testing Engineer : Chris chen
(Chris chen)

Technical Manager : Sean she
(Sean she)

Authorized Signatory : Vita Li
(Vita Li)





TABLE OF CONTENTS	Page
1 INTRODUCTION	6
1.1 TEST FACTORY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 PRODUCT INFORMATION	7
3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
4 MEASUREMENT INSTRUMENTS	9
5 TEST ITEMS	10
5.1 CONDUCTED OUTPUT POWER	10
5.2 PEAK TO AVERAGE RATIO	11
5.3 TRANSMITTER RADIATED POWER (EIRP/ERP)	12
5.4 OCCUPIED BANDWIDTH	13
5.5 FREQUENCY STABILITY	14
5.6 SPURIOUS EMISSIONS AT ANTENNA TERMINALS	15
5.7 BAND EDGE	16
5.8 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	17
APPENDIX A.TESTRESULT	19
A1.CONDUCTED OUTPUT POWER	19
A2. PEAK-TO-AVERAGE RADIO	21
A3. TRANSMITTER RADIATED POWER (EIRP/ERP)	22
A4. OCCUPIED BANDWIDTH (99% OCCUPIED BANDWIDTH/26DB BANDWIDTH)	23
A5.FREQUENCY STABILITY	26
A6. SPURIOUS EMISSIONS AT ANTENNA TERMINALS	27
A7. BAND EDGE	29
A8. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT	31
APPENDIX BPHOTOS OF TEST SETUP	33



Revision History

Rev.	Issue Date	Report NO.	Effect Page	Contents
00	06 Aug. 2018	STS1806067W09	ALL	Initial Issue





SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

The radiated emission testing was performed according to the procedures of KDB 971168 D01 v03r01 and ANSI C63.26(2015)

FCC Rules	Test Description	Test Limit	Test Result	Reference
2.1049	Conducted OutputPower	Reporting Only	PASS	
2.0146 24.232	Peak-to-AverageRatio	< 13 dB	PASS	
2.1046 22.913 24.232	Effective Radiated Power/Equivalent Isotropic Radiated Power	< 7 Watts max. ERP(Part 22) < 2 Watts max. EIRP(Part 24)	PASS	
2.1049 22.917 24.238	Occupied Bandwidth	Reporting Only	PASS	
2.1055 22.355 24.235	Frequency Stability	< 2.5 ppm (Part 22) Emission must remain in band (Part 24)	PASS	
2.1051 22.917 24.238	Spurious Emission at Antenna Terminals	< 43+10log ₁₀ (P[Watts])	PASS	
2.1053 22.917 24.238	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	
2.1051 22.917 24.238	Band Edge	< 43+10log ₁₀ (P[Watts])	PASS	



1 INTRODUCTION

1.1 TEST FACTORY

Shenzhen STS Test Services Co., Ltd.

Add. : 1/F., Building B, Zhuoke Science Park, No.190, Chongqing Road,
Fuyong Street, Bao'an District, Shenzhen, Guangdong, China

CNAS Registration No.: L7649; FCC Registration No.: 625569

IC Registration No.: 12108A; A2LA Certificate No.: 4338.01;

1.2 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement data shown herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

No.	Item	Uncertainty
1	RF power, conducted	± 0.70 dB
2	Spurious emissions, conducted	± 1.19 dB
5	All emissions, radiated (<1G) 30MHz-200MHz	± 2.83 dB
6	All emissions, radiated (<1G) 200MHz-1000MHz	± 2.94 dB
7	All emissions, radiated (>1G)	± 3.03 dB
8	Temperature	± 0.5 °C
9	Humidity	± 2 %



2 PRODUCT INFORMATION

Product Name	POCKETALK
Trade Name	POCKETALK
Model Name	W1PGK
Series Model	W1PGG, W1PGW, W1PWG, W1PWK, W1PWW
Model Difference	The structure of the circuit is the same, only the name of the model is different
Tx Frequency:	WCDMA: Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz
Rx Frequency:	WCDMA: Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz
Max RF Output Power:	WCDMA Band V: 23.80dBm, WCDMA Band II: 21.67dBm
Type of Emission:	WCDMA850: 4M77F9W WCDMA1900: 4M76F9W
SIM Card:	Only support single SIM Card.
Antenna:	PIFA Antenna
Antenna gain:	WCDMA 850: 0dBi, WCDMA1900: 0dBi,
Power Supply:	DC 3.7V by battery
Battery parameter:	Capacity: 2200mAh, Rated Voltage: 3.7V
Extreme Vol. Limits:	DC 3.33 V to 4.07 V (Nominal DC3.7V)
Extreme Temp. Tolerance:	-30°C to +50°C
Hardware version number:	PT2_MB_V1.0
Software version number:	0.2.8P
** Note: The High Voltage 4.07V and Low Voltage 3.33 V was declared by manufacturer, The EUT couldn't be operate normally with higher or lower voltage.	



3 TEST CONFIGURATION OF EQUIPMENT UNDER TEST

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 and ANSI C63.26 2015 Power Meas. License Digital Systems with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

- 1. 30 MHz to 10th harmonic for WCDMA Band V.
- 2. 30 MHz to 10th harmonic for WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

	TEST MODES	
BAND	RADIATED TCS	CONDUCTED TCS
WCDMA BAND V	RMC 12.2KBPS LINK	RMC 12.2KBPS LINK
WCDMA BAND II	RMC 12.2KBPS LINK	RMC 12.2KBPS LINK



4 MEASUREMENT INSTRUMENTS

Kind of Equipment	Manufacturer	Type No.	Serial No.	Last Calibration	Calibrated Until
EMI Test Receiver	R&S	ESCI	102086	2017.10.15	2018.10.14
Signal Analyzer	Agilent	N9020A	MY49100060	2017.10.15	2018.10.14
Test Receiver	R&S	ESCI	101427	2017.10.15	2018.10.14
Universal Radio Communication Tester	R&S	CMW500	131428	2018.03.11	2019.03.10
Bilog Antenna	TESEQ	CBL6111D	34678	2017.11.02	2018.11.01
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-1343	2017.10.27	2018.10.26
SHF-EHF Horn Antenna (18G-40GHz)	A-INFO	LB-180400-KF	N/A	2018.03.11	2019.03.10
Low frequency cable	EM	R01	N/A	2018.03.11	2019.03.10
Low frequency cable	EM	R06	N/A	2018.03.11	2019.03.10
High frequency cable	SCHWARZBECK	R04	N/A	2018.03.11	2019.03.10
High frequency cable	SCHWARZBECK	R02	N/A	2018.03.11	2019.03.10
Pre-mpifier (0.1M-3GHz)	EM	EM330	60538	2018.03.11	2019.03.10
PreAmplifier (1G-26.5GHz)	Agilent	8449B	60538	2017.10.15	2018.10.14
Band Reject filter(1920-1980MHz)	COM-MW	ZBSF-1920-1980	0092	2017.10.15	2018.10.14
Band Reject filter(880-915MHz)	COM-MW	ZBSF-C897.5-35	707	2017.10.15	2018.10.14
Band Reject filter(1710-1785MHz)	COM-MW	ZBSF-C1747.5-75	708	2017.10.15	2018.10.14
Band Reject filter(1850-1910MHz)	COM-MW	ZBSF-C1880-60	709	2017.10.15	2018.10.14
Band Reject filter(2500-2570MHz)	COM-MW	ZBSF-C2535-70	710	2017.10.15	2018.10.14
Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	2017.10.15	2018.10.14
trun table	EM	SC100_1	60531	N/A	N/A
Antnna mast	EM	SC100	N/A	N/A	N/A

Equipment with a calibration date of “NCR” shown in this list was not used to make direct calibrated measurements.

5 TEST ITEMS

5.1 CONDUCTED OUTPUT POWER


Test overview

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

Test procedures

1. The transmitter output port was connected to the system simulator.
2. Set eut at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

Test setup



5.2 PEAK TO AVERAGE RATIO


TEST OVERVIEW

According to §24.232(d), power measurements for transmissions by stations authorized under this section may be made either in accordance with a commission-approved average power technique or in compliance with paragraph (e) of this section. In both instances, equipment employed must be authorized in accordance with the provisions of §24.51. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 db.

TEST PROCEDURES

1. The testing follows fcckdb 971168 v03r01 section
2. The eut was connected to the and peak and av system simulator& spectrum analysis reads
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Set the test probe and measure average power of the spectrum analysis

TEST SETUP





5.3 TRANSMITTER RADIATED POWER (EIRP/ERP)

TEST OVERVIEW

Effective Radiated Power (ERP) and Equivalent Isotropic Radiated Power (EIRP) measurements are performed using the substitution method described in ANSI C63.26 2015 with the EUT transmitting into an integral antenna. Measurements on signals operating below 1GHz are performed using vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically polarized broadband horn antennas. All measurements are performed as RMS average measurements while the EUT is operating at maximum power, and at the appropriate frequencies.

TEST PROCEDURE

1. The testing follows FCC KDB 971168 D01 Section 5.2.1. (for CDMA/WCDMA), ANSI C63.26-2015 Section 5.2.
2. The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.
3. The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.
4. The frequency range up to tenth harmonic of the fundamental frequency was investigated.
5. Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a nonradiating cable. The absolute levels of the spurious emissions were measured by the substitution.
6. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to ANSI C63.26-2015. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP/ERP was calculated with the correction factor,
$$\text{ERP/EIRP} = \text{P.SG} + \text{GT} - \text{LC}$$

ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas} as, typically dBW or dBm);
P_{Meas}(PK) = measured transmitter output power or PSD, in dBm or dBW;
GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);
LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

5.4 OCCUPIED BANDWIDTH

TEST OVERVIEW

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.


The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

All modes of operation were investigated and the worst case configuration results are reported in this section.

TEST PROCEDURE

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. $RBW = 1 - 5\%$ of the expected OBW
3. $VBW \geq 3 \times RBW$
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

TEST SETUP



5.5 FREQUENCY STABILITY

Test Overview

Frequency stability testing is performed in accordance with the guidelines of ANSI C63.26 2015. The frequency stability of the transmitter is measured by:

- a.) Temperature: The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- b.) Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

For Part 22, the frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ (± 2.5 ppm) of the center frequency. For Part 24 the frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

Test Procedure


Temperature Variation

1. The testing follows fccdb 971168 D01 section 9.0
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

Voltage Variation

1. The testing follows FCC KDB 971168 D01 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^\circ\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

TEST SETUP



5.6 SPURIOUS EMISSIONS AT ANTENNA TERMINALS

Test Overview

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

Test procedure

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0. and ANSI C63.26-2015-Section 5.5
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm.}$$

Test Setup



5.7 BAND EDGE

OVERVIEW

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power, and at the appropriate frequencies. All data rates were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible attenuation level of any spurious emission is $43 + \log_{10}(P[\text{Watts}])$, where P is the transmitter power in Watts.

TEST PROCEDURE

1. The testing FCC KDB 971168 D01 v03r01 Section 6.0. and ANSI C63.26-2015-Section 5.7
2. Start and stop frequency were set such that the band edge would be placed in the center of the Plot.
3. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
4. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.

The path loss was compensated to the results for each measurement.

5. The band edges of low and high channels for the highest RF powers were measured.

6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(\text{W}) - [43 + 10\log(P)] (\text{dB})$$

$$= [30 + 10\log(P)] (\text{dBm}) - [43 + 10\log(P)] (\text{dB})$$

$$= -13\text{dBm}.$$

TEST SETUP





5.8 FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT

Test overview

Radiated spurious emissions measurements are performed using the substitution method described in ANSI C63.26-2015 with the EUT transmitting into an integral antenna. Measurements on signal-operating below 1GHz are performed using horizontally and vertically polarized tuned dipole antennas. Measurements on signals operating above 1GHz are performed using vertically and horizontally polarized horn antennas. All measurements are performed as peak measurements while the EUT isoperating at maximum power and at the appropriate frequencies.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


Test procedure

1. The testing FCC KDB 971168 D01 Section 5.8 and ANSI C63.26-2015-Section 5.5.
2. RBW = 100kHz for emissions below 1GHz and 1MHz for emissions above 1GHz
3. VBW $\geq 3 \times$ RBW
4. Span = 1.5 times the OBW
- 5.No. of sweep points $> 2 \times$ span/RBW
6. Detector = Peak
7. Trace mode = max hold
8. The trace was allowed to stabilize
9. Effective Isotropic Spurious Radiation was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP/ERP was calculated with the correction factor,
$$ERP/EIRP = P.SG + GT - LC$$


ERP/EIRP = effective or equivalent radiated power, respectively (expressed in the same units as P_{Meas}, typically dBW or dBm);
P.SG = measured transmitter output power or PSD, in dBm or dBW;
GT = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);
LC = signal attenuation in the connecting cable between the transmitter and antenna, in dB.

TEST SETUP

For radiated test from 30MHz to 1GHz



For radiated test from above 1GHz





APPENDIX A.TESTRESULT
 A1.CONDUCTED OUTPUT POWER
 UMTS BAND V

Mode	Frequency(MHz)	AVG Power
WCDMA 850 RMC	826.4	23.67
	836.6	23.80
	846.6	23.78
HSDPA Subtest 1	826.4	22.66
	836.6	22.83
	846.6	22.79
HSDPA Subtest 2	826.4	22.20
	836.6	22.43
	846.6	22.33
HSDPA Subtest 3	826.4	21.80
	836.6	22.00
	846.6	21.83
HSDPA Subtest 4	826.4	21.45
	836.6	21.67
	846.6	21.49
HSUPA Subtest 1	826.4	22.58
	836.6	22.67
	846.6	22.43
HSUPA Subtest 2	826.4	21.70
	836.6	21.74
	846.6	21.49
HSUPA Subtest 3	826.4	21.67
	836.6	21.27
	846.6	21.02
HSUPA Subtest 4	826.4	21.24
	836.6	20.78
	846.6	20.67
HSUPA Subtest 5	826.4	19.80
	836.6	19.35
	846.6	19.25



UMTS BAND II

Mode	Frequency(MHz)	AVG Power
WCDMA 1900 RMC	1852.4	20.86
	1880	20.82
	1907.6	21.67
HSDPA Subtest 1	1852.4	19.75
	1880	19.73
	1907.6	20.26
HSDPA Subtest 2	1852.4	19.30
	1880	19.24
	1907.6	19.79
HSDPA Subtest 3	1852.4	18.93
	1880	18.75
	1907.6	19.37
HSDPA Subtest 4	1852.4	18.58
	1880	18.41
	1907.6	18.91
HSUPA Subtest 1	1852.4	19.70
	1880	19.65
	1907.6	19.77
HSUPA Subtest 2	1852.4	18.75
	1880	18.66
	1907.6	18.77
HSUPA Subtest 3	1852.4	18.71
	1880	18.24
	1907.6	18.47
HSUPA Subtest 4	1852.4	18.23
	1880	17.80
	1907.6	18.00
HSUPA Subtest 5	1852.4	16.78
	1880	16.35
	1907.6	16.55



A2. PEAK-TO-AVERAGE RADIO

Mode	Frequency (MHz)	PEAK Power (dBm)	AVG Power (dBm)	PAR (dB)
WCDMA 850 RMC	826.4	25.13	22.96	2.04
	836.6	25.82	23.09	2.48
	846.6	25.13	22.98	1.98
HSDPA 850	826.4	26.35	21.78	3.08
	836.6	26.55	21.85	3.43
	846.6	26.07	21.80	3.03
HSUPA 850	826.4	26.48	21.17	4.77
	836.6	26.49	22.26	3.55
	846.6	26.36	22.49	3.52
WCDMA 1900 RMC	1852.4	22.99	20.02	2.67
	1880	22.80	20.43	2.15
	1907.6	23.37	20.94	2.24
HSDPA 1900	1852.4	23.60	19.42	3.63
	1880	23.85	19.68	3.28
	1907.6	24.61	20.19	3.25
HSUPA 1900	1852.4	23.01	18.96	3.26
	1880	22.24	18.82	3.02
	1907.6	22.55	19.08	2.95

NOTE:Test chart See Appendix D



A3. TRANSMITTER RADIATED POWER (EIRP/ERP)

Radiated Power (ERP) for WCDMA Band V							
Mode	Frequency	Result					Conclusion
		S G. Level (dBm)	Cable loss	Gain (dBi)	PMeas E.R.P (dBm)	Polarization Of Max.ERP	
Band V	826.4	15.13	0.44	6.5	21.19	Horizontal	Pass
	826.4	17.09	0.44	6.5	23.15	Vertical	Pass
	836.6	15.37	0.45	6.5	21.42	Horizontal	Pass
	836.6	17.22	0.45	6.5	23.27	Vertical	Pass
	846.4	15.42	0.46	6.5	21.46	Horizontal	Pass
	846.4	17.22	0.46	6.5	23.26	Vertical	Pass
Limit	E.R.P < 7W=38.45dBm						

Radiated Power (EIRP) for WCDMA Band II							
Mode	Frequency	Result					Conclusion
		S G. Level (dBm)	Cable loss	Gain (dBi)	PMeas E.I.R.P.(dBm)	Polarization Of Max.EIRP	
Band II	1852.4	10.35	2.41	10.35	18.29	Horizontal	Pass
	1852.4	12.22	2.41	10.35	20.16	Vertical	Pass
	1880	10.29	2.42	10.35	18.22	Horizontal	Pass
	1880	12.2	2.42	10.35	20.13	Vertical	Pass
	1907.4	12.09	2.43	10.35	20.01	Horizontal	Pass
	1907.4	13.82	2.43	10.35	21.74	Vertical	Pass
Limit	E.I.R.P < 2W=33dBm						

Note: Test is divided into three directions, X/Y/Z. X pattern for the worst.




A4. OCCUPIED BANDWIDTH (99% OCCUPIED BANDWIDTH/26dB BANDWIDTH)

Occupied Bandwidth for UMTS band V			
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(MHz)	Emission Bandwidth (-26dBc)(MHz)
Low Channel	826.4	4.1775	4.753
Middle Channel	836.6	4.1761	4.707
High Channel	846.6	4.1856	4.769


Occupied Bandwidth for UMTS band II			
Mode	Frequency(MHz)	Occupied Bandwidth (99%)(MHz)	Emission Bandwidth (-26dBc)(MHz)
Low Channel	1852.4	4.1673	4.698
Middle Channel	1880	4.1786	4.746
High Channel	1907.6	4.1767	4.755




UMTS BAND V CH 4132



UMTS BAND V CH 4183




UMTS BAND V CH 4233







UMTS BAND II CH 9262



UMTS BAND II CH 9400



UMTS BAND II CH 9538





A5.FREQUENCY STABILITY

Normal Voltage = 3.7V. ; Battery End Point (BEP) = 3.33V.; Maximum Voltage =4.07 V

WCDMA V Middle Channel/836.6MHz					
Temperature (°C)	Voltage (Volt)	Freq. Dev. (Hz)	Freq. Dev. (ppm)	Limit	Result
50	Normal Voltage	27.91	0.033	2.5ppm	PASS
40		24.95	0.030		
30		17.12	0.020		
20		34.28	0.041		
10		18.59	0.022		
0		27.22	0.033		
-10		24.33	0.029		
-20		25.53	0.031		
-30		18.40	0.022		
25		Maximum Voltage	15.06		
25	BEP	24.43	0.029		

1. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.
- 2.

WCDMA II Middle Channel/1880MHz					
Temperature (°C)	Voltage (Volt)	Freq. Dev. (Hz)	Freq. Dev. (ppm)	Limit	Result
50	Normal Voltage	27.60	0.015	Within Authorized Band	PASS
40		16.77	0.009		
30		29.44	0.016		
20		28.88	0.015		
10		20.55	0.011		
0		20.35	0.011		
-10		34.19	0.018		
-20		18.71	0.010		
-30		17.31	0.009		
25		Maximum Voltage	12.73		
25	BEP	34.04	0.018		


1. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.




A6. SPURIOUS EMISSIONS AT ANTENNA TERMINALS

WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Middle Channel




Highest Channel






WCDMA Band II (RMC 12.2Kbps)(30M-20G)


Lowest Channel



Middle Channel



Highest Channel





A7. BAND EDGE

WCDMA Band VRMC 12.2Kbps

Lowest Band Edge



Highest Band Edge





WCDMA Band IIRMC 12.2Kbps

Lowest Band Edge



Highest Band Edge





A8. FIELD STRENGTH OF SPURIOUS RADIATION MEASUREMENT
UMTS band V(30-9000)MHz

WCDMA Band V: (30-9000)MHz							
The most testresults channel 4132/826.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dB)	
1652.21	-41.25	9.40	4.75	-36.60	-13.00	-23.60	H
2479.44	-40.36	10.60	8.39	-38.15	-13.00	-25.15	H
3305.52	-31.75	12.00	11.79	-31.54	-13.00	-18.54	H
1652.30	-43.90	9.40	4.75	-39.25	-13.00	-26.25	V
2479.35	-45.29	10.60	8.39	-43.08	-13.00	-30.08	V
3305.71	-43.44	12.00	11.79	-43.23	-13.00	-30.23	V
The Worst Test Results Channel 4183/836.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dB)	
1673.22	-40.33	9.50	4.76	-35.59	-13.00	-22.59	H
2509.54	-40.26	10.70	8.40	-37.96	-13.00	-24.96	H
3346.32	-30.88	12.20	11.80	-30.48	-13.00	-17.48	H
1673.17	-43.67	9.40	4.75	-39.02	-13.00	-26.02	V
2509.46	-44.43	10.60	8.39	-42.22	-13.00	-29.22	V
3346.07	-43.83	12.20	11.82	-43.45	-13.00	-30.45	V
The Worst Test Results Channel 4233/846.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dB)	
1693.47	-41.60	9.60	4.77	-36.77	-13.00	-23.77	H
2539.37	-39.81	10.80	8.50	-37.51	-13.00	-24.51	H
3385.92	-32.16	12.50	11.90	-31.56	-13.00	-18.56	H
1693.33	-43.57	9.60	4.77	-38.74	-13.00	-25.74	V
2539.35	-44.87	10.80	8.50	-42.57	-13.00	-29.57	V
3386.12	-43.02	12.50	11.90	-42.42	-13.00	-29.42	V

- Note:** (1) Below 30MHz no Spurious found is the worst condition.
 (2) Above 3GHz amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value
 (3) Test is divided into three directions, X/Y/Z. X pattern for the worst.



UMTS band II(30-20000)MHz



WCDMA Band II: (30-20000)MHz							
The Worst Test Results for Channel 9262/1852.4MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dB)	
3704.07	-33.87	12.60	12.93	-34.20	-13.00	-21.20	H
5557.52	-34.67	13.10	17.11	-38.68	-13.00	-25.68	H
7409.93	-32.40	11.50	22.20	-43.10	-13.00	-30.10	H
3704.39	-34.80	12.60	12.93	-35.13	-13.00	-22.13	V
5557.54	-34.87	13.10	17.11	-38.88	-13.00	-25.88	V
7409.80	-32.87	11.50	22.20	-43.57	-13.00	-30.57	V
The Worst Test Results for Channel 9400/1880MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dB)	
3759.98	-34.49	12.60	12.93	-34.82	-13.00	-21.82	H
5640.13	-34.55	13.10	17.11	-38.56	-13.00	-25.56	H
7520.11	-33.37	11.50	22.20	-44.07	-13.00	-31.07	H
3759.98	-35.05	12.60	12.93	-35.38	-13.00	-22.38	V
5639.86	-34.66	13.10	17.11	-38.67	-13.00	-25.67	V
7519.90	-32.86	11.50	22.20	-43.56	-13.00	-30.56	V
The Worst Test Results for Channel 9538/1907.6MHz							
Frequency(MHz)	S G.Lev (dBm)	Ant(dBi)	Loss	PMea	Limit	Margin	Polarity
				(dBm)	(dBm)	(dB)	
3815.51	-34.57	12.60	12.93	-34.90	-13.00	-21.90	H
5722.17	-34.81	13.10	17.11	-38.82	-13.00	-25.82	H
7630.21	-33.46	11.50	22.20	-44.16	-13.00	-31.16	H
3815.50	-35.99	12.60	12.93	-36.32	-13.00	-23.32	V
5722.21	-34.21	13.10	17.11	-38.22	-13.00	-25.22	V
7630.21	-32.75	11.50	22.20	-43.45	-13.00	-30.45	V

- Note:** (1) Below 30MHz no Spurious found is the worst condition.
 (2) Above 6GHz amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value
 (3) Test is divided into three directions, X/Y/Z. X pattern for the worst.



APPENDIX B PHOTOS OF TEST SETUP

RADIATED SPURIOUS EMISSION



※※※※END OF THE REPORT※※※※