




Test mode:	Transmitting	Horizontal
------------	--------------	------------




	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1846.00	42.39	-4.06	38.33	54.00	-15.67	Average	HORIZONTAL
2	2017.00	43.62	-2.61	41.01	54.00	-12.99	Average	HORIZONTAL
3 pp	2287.00	50.57	-4.33	46.24	54.00	-7.76	Average	HORIZONTAL
4	2674.00	47.47	-2.44	45.03	54.00	-8.97	Average	HORIZONTAL
5	3241.00	42.31	2.25	44.56	54.00	-9.44	Average	HORIZONTAL
6	3763.00	41.66	4.45	46.11	54.00	-7.89	Average	HORIZONTAL



	Read			Limit	Over		
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1873.00	53.70	-3.67	50.03	74.00	-23.97 Peak	HORIZONTAL
2	2188.00	55.95	-4.65	51.30	74.00	-22.70 Peak	HORIZONTAL
3 pp	2287.00	66.09	-4.33	61.76	74.00	-12.24 Peak	HORIZONTAL
4	2674.00	62.71	-2.44	60.27	74.00	-13.73 Peak	HORIZONTAL
5	3223.00	53.03	2.06	55.09	74.00	-18.91 Peak	HORIZONTAL
6	3745.00	52.23	4.44	56.67	74.00	-17.33 Peak	HORIZONTAL




		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	pp 2483.48	50.18	-2.20	47.98	54.00	-6.02	Average	HORIZONTAL
2	2500.00	46.75	-2.11	44.64	54.00	-9.36	Average	HORIZONTAL




		Read		Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Pol/Phase
1	pp 2483.48	58.81	-2.20	56.61	74.00	-17.39	Peak
2	2500.00	54.83	-2.11	52.72	74.00	-21.28	Peak

3DH5(2402MHz)


Test mode:	Transmitting	Vertical
------------	--------------	----------




	Read			Limit	Over		
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1918.00	44.60	-3.24	41.36	54.00	-12.64	Average
2	1999.00	43.37	-2.47	40.90	54.00	-13.10	Average
3	2593.00	43.71	-2.46	41.25	54.00	-12.75	Average
4	3115.00	42.69	0.13	42.82	54.00	-11.18	Average
5	3277.00	43.00	2.49	45.49	54.00	-8.51	Average
6 pp	3754.00	42.75	4.46	47.21	54.00	-6.79	Average



	Read			Limit	Over		
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1918.00	57.01	-3.24	53.77	74.00	-20.23 Peak	VERTICAL
2	2206.00	58.74	-4.86	53.88	74.00	-20.12 Peak	VERTICAL
3	3196.00	51.31	1.71	53.02	74.00	-20.98 Peak	VERTICAL
4	3277.00	51.06	2.49	53.55	74.00	-20.45 Peak	VERTICAL
5	3583.00	51.58	3.16	54.74	74.00	-19.26 Peak	VERTICAL
6 pp	3763.00	50.56	4.45	55.01	74.00	-18.99 Peak	VERTICAL




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2310.00	44.76	-3.12	41.64	54.00	-12.36	Average	VERTICAL
2 pp	2390.00	46.57	-2.76	43.81	54.00	-10.19	Average	VERTICAL




		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1 pp	2310.00	52.60	-3.12	49.48	74.00	-24.52	Peak	VERTICAL
2	2390.00	51.92	-2.76	49.16	74.00	-24.84	Peak	VERTICAL


Test mode:	Transmitting	Horizontal
------------	--------------	------------




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2206.00	49.10	-4.86	44.24	54.00	-9.76	Average	HORIZONTAL
2	2593.00	46.98	-2.46	44.52	54.00	-9.48	Average	HORIZONTAL
3	3223.00	42.25	2.06	44.31	54.00	-9.69	Average	HORIZONTAL
4	3475.00	42.02	2.49	44.51	54.00	-9.49	Average	HORIZONTAL
5	3790.00	41.55	4.43	45.98	54.00	-8.02	Average	HORIZONTAL
6 pp	3997.00	40.94	5.19	46.13	54.00	-7.87	Average	HORIZONTAL



	Read			Limit	Over		
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1927.00	52.11	-3.21	48.90	74.00	-25.10	Peak
2	2206.00	65.55	-4.86	60.69	74.00	-13.31	Peak
3	2593.00	62.11	-2.46	59.65	74.00	-14.35	Peak
4	3259.00	53.26	2.40	55.66	74.00	-18.34	Peak
5	3547.00	52.14	2.85	54.99	74.00	-19.01	Peak
6	3736.00	52.81	4.38	57.19	74.00	-16.81	Peak




	Read			Limit	Over		
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2310.00	44.56	-3.12	41.44	54.00	-12.56	Average HORIZONTAL
2 pp	2390.00	49.87	-2.76	47.11	54.00	-6.89	Average HORIZONTAL




		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2310.00	51.74	-3.12	48.62	74.00	-25.38	Peak	HORIZONTAL
2	pp 2390.00	53.38	-2.76	50.62	74.00	-23.38	Peak	HORIZONTAL

3DH5(2441MHz)

Test mode:	Transmitting	Vertical
------------	--------------	----------




	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1990.00	42.57	-2.58	39.99	54.00	-14.01	Average	VERTICAL
2	2206.00	44.56	-4.86	39.70	54.00	-14.30	Average	VERTICAL
3	2593.00	42.42	-2.46	39.96	54.00	-14.04	Average	VERTICAL
4	3241.00	42.21	2.25	44.46	54.00	-9.54	Average	VERTICAL
5	3484.00	42.16	2.51	44.67	54.00	-9.33	Average	VERTICAL
6 pp	3718.00	41.67	4.30	45.97	54.00	-8.03	Average	VERTICAL




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1900.00	53.73	-3.33	50.40	74.00	-23.60	Peak	VERTICAL
2	2206.00	57.85	-4.86	52.99	74.00	-21.01	Peak	VERTICAL
3	2593.00	54.87	-2.46	52.41	74.00	-21.59	Peak	VERTICAL
4	3277.00	51.45	2.49	53.94	74.00	-20.06	Peak	VERTICAL
5	3655.00	50.66	3.61	54.27	74.00	-19.73	Peak	VERTICAL
6 pp	3799.00	51.12	4.42	55.54	74.00	-18.46	Peak	VERTICAL

Test mode:	Transmitting	Horizontal
------------	--------------	------------




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1990.00	42.63	-2.58	40.05	54.00	-13.95	Average	HORIZONTAL
2	2206.00	48.49	-4.86	43.63	54.00	-10.37	Average	HORIZONTAL
3	2593.00	45.70	-2.46	43.24	54.00	-10.76	Average	HORIZONTAL
4	3286.00	41.92	2.54	44.46	54.00	-9.54	Average	HORIZONTAL
5	3547.00	42.27	2.85	45.12	54.00	-8.88	Average	HORIZONTAL
6 pp	3745.00	41.64	4.44	46.08	54.00	-7.92	Average	HORIZONTAL




	Freq	Read		Limit	Over		
	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	
1	1990.00	52.67	-2.58	50.09	74.00	-23.91	Peak
2	2206.00	63.93	-4.86	59.07	74.00	-14.93	Peak
3	2593.00	60.31	-2.46	57.85	74.00	-16.15	Peak
4	3313.00	52.50	2.62	55.12	74.00	-18.88	Peak
5	3448.00	52.68	2.43	55.11	74.00	-18.89	Peak
6	3772.00	51.70	4.44	56.14	74.00	-17.86	Peak

3DH5(2480MHz)


Test mode:	Transmitting	Vertical
------------	--------------	----------




	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2008.00	42.72	-2.53	40.19	54.00	-13.81	Average	VERTICAL
2	2287.00	45.07	-4.33	40.74	54.00	-13.26	Average	VERTICAL
3	3205.00	42.07	1.86	43.93	54.00	-10.07	Average	VERTICAL
4	3457.00	42.66	2.45	45.11	54.00	-8.89	Average	VERTICAL
5	3709.00	41.73	4.26	45.99	54.00	-8.01	Average	VERTICAL
6 pp	3952.00	41.28	4.87	46.15	54.00	-7.85	Average	VERTICAL



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	1918.00	53.93	-3.24	50.69	74.00	-23.31	Peak	VERTICAL
2	2287.00	58.45	-4.33	54.12	74.00	-19.88	Peak	VERTICAL
3	2674.00	55.74	-2.44	53.30	74.00	-20.70	Peak	VERTICAL
4	3250.00	53.00	2.35	55.35	74.00	-18.65	Peak	VERTICAL
5 pp	3745.00	52.63	4.44	57.07	74.00	-16.93	Peak	VERTICAL
6	4033.00	51.88	5.08	56.96	74.00	-17.04	Peak	VERTICAL




		Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	pp 2483.50	49.73	-2.20	47.53	54.00	-6.47	Average	VERTICAL
2	2500.00	45.33	-2.11	43.22	54.00	-10.78	Average	VERTICAL




	Freq	Read		Limit	Over			
	MHz	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1 pp	2483.50	54.22	-2.20	52.02	74.00	-21.98	Peak	VERTICAL
2	2500.00	53.57	-2.11	51.46	74.00	-22.54	Peak	VERTICAL


Test mode:	Transmitting	Horizontal
------------	--------------	------------




	Read Freq	Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2008.00	42.56	-2.53	40.03	54.00	-13.97	Average	HORIZONTAL
2	2287.00	51.38	-4.33	47.05	54.00	-6.95	Average	HORIZONTAL
3	2674.00	47.14	-2.44	44.70	54.00	-9.30	Average	HORIZONTAL
4	3322.00	42.09	2.63	44.72	54.00	-9.28	Average	HORIZONTAL
5	3754.00	41.67	4.46	46.13	54.00	-7.87	Average	HORIZONTAL
6	4033.00	41.49	5.08	46.57	54.00	-7.43	Average	HORIZONTAL



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	2008.00	53.57	-2.53	51.04	74.00	-22.96	Peak	HORIZONTAL
2	2188.00	57.58	-4.65	52.93	74.00	-21.07	Peak	HORIZONTAL
3 pp	2287.00	66.39	-4.33	62.06	74.00	-11.94	Peak	HORIZONTAL
4	2665.00	62.58	-2.43	60.15	74.00	-13.85	Peak	HORIZONTAL
5	3241.00	52.79	2.25	55.04	74.00	-18.96	Peak	HORIZONTAL
6	3763.00	52.51	4.45	56.96	74.00	-17.04	Peak	HORIZONTAL



	Read			Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Pol/Phase
1	pp 2483.50	52.12	-2.20	49.92	54.00	-4.08	Average HORIZONTAL
2	2500.00	45.75	-2.11	43.64	54.00	-10.36	Average HORIZONTAL



		Read		Limit	Over		
	Freq	Level	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Pol/Phase
1	pp 2483.50	60.27	-2.20	58.07	74.00	-15.93	Peak
2	2500.00	53.83	-2.11	51.72	74.00	-22.28	Peak

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, the disturbance above 10GHz and below 30MHz was very low.

6 Photographs - EUT Test Setup

Refer to Photographs - EUT Constructional Details OF EUT for Setup photos.

7 Photographs - EUT Constructional Details

Refer to Photographs - EUT Constructional Details OF EUT for Internal photos and External photos.

*** END OF REPORT ***