



TESTING LABORATORY  
CERTIFICATE#4323.01



## FCC PART 15.225

### TEST REPORT

For

## Queclink Wireless Solutions Co., Ltd

No.30, Lane 500, Xinlong Road, Minhang District, Shanghai, China, 201101

**FCC ID: YQDEA00022**

<b>Report Type:</b> Original Report	<b>Product Type:</b> Telematics Device
<div>Miller Xie</div> <b>Project Engineer:</b> <u>Miller Xie</u>	
<b>Report Number:</b> <u>RSHA210824001-00B</u>	
<b>Report Date:</b> <u>2021-09-07</u>	
<div>Kyle Xu</div> <b>Reviewed By:</b> <u>Kyle Xu</u>	
<b>Prepared By:</b> Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 <a href="http://www.baclcorp.com.cn">www.baclcorp.com.cn</a>	

## **TABLE OF CONTENTS**

<b>GENERAL INFORMATION</b>	<b>3</b>
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
<b>SYSTEM TEST CONFIGURATION</b>	<b>5</b>
JUSTIFICATION	5
EUT EXERCISE SOFTWARE	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE	5
BLOCK DIAGRAM OF TEST SETUP	6
<b>SUMMARY OF TEST RESULTS</b>	<b>7</b>
<b>TEST EQUIPMENT LIST</b>	<b>8</b>
<b>FCC§15.203 - ANTENNA REQUIREMENT</b>	<b>9</b>
APPLICABLE STANDARD	9
ANTENNA CONNECTED CONSTRUCTION	9
<b>FCC§15.225, §15.205 &amp; §15.209 - RADIATED EMISSIONS TEST</b>	<b>10</b>
APPLICABLE STANDARD	10
EUT SETUP	10
EMI TEST RECEIVER SETUP	11
CORRECTED AMPLITUDE & MARGIN CALCULATION	11
TEST RESULTS SUMMARY	11
TEST DATA	11
<b>FCC§15.225(E) - FREQUENCY STABILITY</b>	<b>17</b>
APPLICABLE STANDARD	17
TEST PROCEDURE	17
TEST DATA	18
<b>§15.215(C) - 20DB EMISSION BANDWIDTH TESTING</b>	<b>19</b>
REQUIREMENT	19
TEST PROCEDURE	19
TEST DATA	19

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

Applicant:	Queclink Wireless Solutions Co., Ltd
Product Type:	Telematics Device
Tested Model:	EA00022
Power Supply:	DC 12~60V power by external power supply and DC 3.6V from rechargeable li-ion battery
Field strength of fundamental:	83.02 dBμV/m@3m
RF Function:	NFC
Operating Band/Frequency:	13.56MHz
Antenna Type:	PCB antenna
* Maximum Antenna Gain:	1.0 dBi

*\*Note: The maximum antenna gain is provided by the applicant.*

*All measurement and test data in this report was gathered from production sample serial number: RSHA210824001-1. (Assigned by the BACL. The EUT supplied by the applicant was received on 2021-08-24)*

### Objective

This Type approval report is prepared on behalf of *Queclink Wireless Solutions Co., Ltd* in accordance with Part 2- Subpart J, and Part 15-Subparts A and C of the Federal Communication Commission's rules.

The objective is to determine the Compliance of the EUT with FCC rules, sec 15.203,15.205,15.209, 15.215,15.225.

### Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All radiated and conducted emissions measurement was performed at Bay Area Compliance Lab Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

**Measurement Uncertainty**

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19 dB
RF conducted test with spectrum		0.9dB
Radiated emission	9kHz~30MHz	6.07dB
	30MHz~1GHz	6.11dB
Occupied Bandwidth		0.5kHz
Temperature		1.0℃
Humidity		6%

**Test Facility**

The Test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01), the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

## SYSTEM TEST CONFIGURATION

### Justification

The system was configured for testing in a typical mode (as normally used by a typical user).

### EUT Exercise Software

The EUT was tested in the engineering mode.

### Equipment Modifications

No modification on the EUT.

### Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
ZHAOXIN	DC Source	RXN-605D	DC002

### External I/O Cable

Cable Description	Length (m)	From Port	To Port
Power cable1	1.5	EUT	DC Source
Power cable2	1.0	DC Source	AC Source

**Block Diagram of Test Setup**

For Radiated Emissions (Below 30MHz&Above 30MHz):



**SUMMARY OF TEST RESULTS**

<b>FCC Rules</b>	<b>Description of Test</b>	<b>Result</b>
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Not Applicable (See Note)
§15.225 §15.209 §15.205	Radiated Emission Test	Compliant
§15.225(e)	Frequency Stability	Compliant
§15.215(c)	20dB Emission Bandwidth Testing	Compliant

Note: EUT is used in scooter and powered by battery.

**TEST EQUIPMENT LIST**

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2020-11-27	2021-11-26
Sunol Sciences	Broadband Antenna	JB3	A090314-2	2020-01-07	2023-01-06
Sonoma Instrument	Pre-amplifier	310N	171205	2021-08-14	2022-08-13
ETS-LINDGREN	Loop Antenna	6512	00108100	2020-12-22	2023-12-21
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2021-08-15	2022-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2021-08-15	2022-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2021-08-15	2022-08-14
ZHAOXIN	DC Power Supply	PS-6005D	DC003	2020-10-10	2021-10-09
BACL	Temperature & Humidity Chamber	BTH-150	30023	2020-11-25	2021-11-24

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).



**FCC§15.203 - ANTENNA REQUIREMENT**

---

**Applicable Standard**

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

**Antenna Connected Construction**

The EUT has a PCB Antenna for 13.56MHz and the antenna gain is 1.0 dBi, which was permanently attached to the EUT, fulfill the requirement of this section, please refer to the EUT photos.

**Result:** Compliant.


## FCC§15.225, §15.205 & §15.209 - RADIATED EMISSIONS TEST

### Applicable Standard

As per FCC Part 15.225

- (a) The field strength of any emissions within the band 13.553–13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.
- (b) Within the bands 13.410–13.553 MHz and 13.567–13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.
- (c) Within the bands 13.110–13.410 MHz and 13.710–14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110–14.010 MHz band shall not exceed the general radiated emission limits in §15.209.

### EUT Setup



The radiated emission tests were performed in the 3-meter chamber a test site, using the setup accordance with the ANSI C63.10. The specification used was the FCC Part Subpart C limits.

The spacing between the peripherals was 10 cm.

## EMI Test Receiver Setup

According to FCC Rules, 47 CFR 15.33, the EUT emissions were investigated up to 1000 MHz.

During the radiated emission test, the EMI test Receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	Detector
9 kHz – 150 kHz	200 Hz	1 kHz	QP/Average
150 kHz –30 MHz	9 kHz	30 kHz	QP/Average
30 MHz – 1000 MHz	120 kHz	300 kHz	QP

## Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Factor = Antenna Factor + Cable Loss- Amplifier Gain

Corrected Amplitude = Meter Reading + Corrected Factor

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

Margin = Limit – Corrected Amplitude

## Test Results Summary

According to the data in the following table, the EUT complied with the FCC Part 15.209, 15.205, 15.225.

## Test Data


### Environmental Conditions

Temperature:	24.6-25.3 °C
Relative Humidity:	48-52 %
ATM Pressure:	101.1-101.3 kPa

*The testing was performed by Miller Xie from 2021-09-02 to 2021-09-05.*

*Test mode: Transmitting*

1) (9 kHz~150 kHz):




Date: 2.SEP.2021 11:52:03

Indicated		PK/QP/AV	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
Frequency (kHz)	Corrected Amplitude (dBμV/m) @3m			Limit (dBμV/m) @3m	Margin (dB)
9.68	54.88	PK	56.57	127.89	73.01
17.81	50.13	PK	51.39	122.59	72.46
27.53	44.32	PK	47.89	118.81	74.49
135.09	39.71	PK	50.69	104.99	65.28

Note: The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

2) (150 kHz~30 MHz):




Date: 5.SEP.2021 14:33:52

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/AV	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m)@3m	Margin (dB)
2.11	66.85	PK	13.94	69.54	2.69
10.82	52.15	PK	6.33	69.54	17.39
13.56	83.02	PK	6.12	124.00	40.98
24.74	38.73	PK	5.51	69.54	30.81

Note:


1. The average emissions which fall into frequencies 9-90 kHz, 110-490 kHz was not recorded, because the peak emissions are below the average limit.

3) (13.11MHz~13.41 MHz):




Date: 2.SEP.2021 11:59:31

(13.41MHz~13.553 MHz):




Date: 2.SEP.2021 12:01:35

(13.567MHz~13.710 MHz):



Date: 2.SEP.2021 12:05:31


(13.710MHz~14.010 MHz):



Date: 2.SEP.2021 12:03:08

Frequency (MHz)	Corrected Amplitude (dBμV/m)@3m	Detector PK/QP/AV	Corrected Factor (dB/m)	FCC Part 15.225/15.209	
				Limit (dBμV/m) @3m	Margin (dB)
13.349	57.69	PK	6.13	80.5	22.81
13.553	59.98	PK	6.12	90.5	30.52
13.567	64.76	PK	6.12	90.5	25.74
13.772	57.27	PK	6.10	80.5	23.23

4) Spurious Emissions (30 MHz ~1 GHz):



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
33.639900	17.60	100.0	V	163.0	-5.6	40.00	22.40
40.540950	14.78	100.0	V	174.0	-10.7	40.00	25.22
59.827350	11.02	100.0	V	341.0	-14.7	40.00	28.98
125.302700	11.72	200.0	H	312.0	-11.1	43.50	31.78
262.191650	25.41	100.0	H	245.0	-11.7	46.00	20.59
309.602800	25.60	100.0	H	101.0	-10.6	46.00	20.40

**Note:**

Corrected Amplitude = Corrected Factor + Reading

Corrected Factor = Antenna factor (Rx) + cable loss – amplifier factor

Margin = Limit - Corrected Amplitude



---

## FCC§15.225(e) - FREQUENCY STABILITY

---

### Applicable Standard

The frequency tolerance of the carrier signal shall be maintained within  $\pm 0.01\%$  of the operating frequency over a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

### Test Procedure

a) Supply the EUT with a dc voltage, or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn on the EUT, and tune it to the center frequency of the operating band..

b) Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.

NOTE—An instrument that has an adequate level of accuracy as specified by the procuring or regulatory agency is the recommended measuring instrument.

c) Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).

d) Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.

e) Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.

f) While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.

g) Measure the frequency.

h) Switch OFF the EUT but do not switch OFF the oscillator heater.

i) Lower the chamber temperature by not more than  $10^{\circ}\text{C}$ , and allow the temperature inside the chamber to stabilize.

j) Repeat step f) through step i) down to the lowest specified temperature.

**Test Data****Environmental Conditions**

<b>Temperature:</b>	24.8 °C
<b>Relative Humidity:</b>	53 %
<b>ATM Pressure:</b>	101.3 kPa

The testing was performed by Miller Xie on 2021-08-31.

Test Mode: Transmitting.

Test Result: Compliant (worst case)

<b>F<sub>0</sub>=13.56MHz</b>				
<b>Power Supply (V<sub>DC</sub>)</b>	<b>Temperature (°C)</b>	<b>Measured Frequency (MHz)</b>	<b>Frequency Error (%)</b>	<b>Part 15.225 Limit</b>
36	-20	13.5592332	-0.00565	±0.01%
	-10	13.5599527	-0.00035	±0.01%
	0	13.5591837	-0.00602	±0.01%
	10	13.5591254	-0.00645	±0.01%
	20	13.5590856	-0.00674	±0.01%
	30	13.5594856	-0.00379	±0.01%
	40	13.5594581	-0.00400	±0.01%
	50	13.5592332	-0.00565	±0.01%
12	20	13.5595213	-0.00353	±0.01%
60	20	13.5594682	-0.00392	±0.01%

## §15.215(c) - 20dB EMISSION BANDWIDTH TESTING

### Requirement

Per 15.215 (c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

### Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.

### Test Data

#### Environmental Conditions

Temperature:	24.9 °C
Relative Humidity:	52 %
ATM Pressure:	101.4kPa


*The testing was performed by Miller Xie on 2021-09-02.*

*Test Mode: Transmitting*

*Test Result: Compliant*

Frequency (MHz)	20 dB Bandwidth (kHz)
13.56	1.506

20 dB Emission Bandwidth-13.56MHz



Date: 2.SEP.2021 11:44:11

## Declarations

- 1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '\*'. Customer model name, addresses, names, trademarks etc. are not considered data.
- 2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.
- 3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.
- 4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.
- 5: This report cannot be reproduced except in full, without prior written approval of the Company.
- 6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

**\*\*\*\*\* END OF REPORT \*\*\*\*\***