

FCC PART 15.247


TEST REPORT

For

WUXI IDATA TECHNOLOGY COMPANY LTD.

Floor 11,Building B1,Wuxi Binhu National Sensing Information Center,No.999 Gaolang East Road, Wuxi, China

FCC ID: 2ADE3IDATA60

Report Type: Original Report	Product Type: NEW MOBILE COMPUTER
Test Engineer:	<u>Lion Xiao</u> 
Report Number:	<u>RSZ160114005-00C</u>
Report Date:	<u>2016-02-17</u>
Reviewed By:	<u>Sula Huang</u>  RF Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan).

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
MEASUREMENT UNCERTAINTY	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST RESULTS SUMMARY	20
TEST DATA	20
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA	34
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	43

APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA	43
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	45
APPLICABLE STANDARD	45
TEST PROCEDURE	45
TEST EQUIPMENT LIST AND DETAILS.....	45
TEST DATA	45
FCC §15.247(e) - POWER SPECTRAL DENSITY	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST EQUIPMENT LIST AND DETAILS.....	51
TEST DATA	51

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *WUXI IDATA TECHNOLOGY COMPANY LTD.*'s product, model number: *iData 60 (FCC ID: 2ADE3IDATA60)* (the "EUT") in this report was a *NEW MOBILE COMPUTER*, which was measured approximately: 18.3cm (L) x 6.9cm (W) x 3.2cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5V charging from adapter.

Adapter information:

Model: FJ-SW1260502000UU

Input: 100-240V~ 50/60Hz 0.4A Max

Output: DC 5V, 2000mA

All measurement and test data in this report was gathered from production sample serial number: 160114005 (Assigned by BACL, Dongguan). The EUT was received on 2016-01-14.

Objective

This report is prepared on behalf of *WUXI IDATA TECHNOLOGY COMPANY LTD.* in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2ADE3IDATA60.

FCC Part 15C DSS submissions with FCC ID: 2ADE3IDATA60.

FCC Part 15C DXX submissions with FCC ID: 2ADE3IDATA60.

FCC Part 22H, 24E PCE submissions with FCC ID: 2ADE3IDATA60.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.
For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11.
For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Test Mode	Test Software Version	Engineering Mode-TX		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	17	18	19
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	14	15	16
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	14	15	16
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	14	15	15
BLE	Test Frequency	2402MHz	2440MHz	2480MHz
	BLE	N/A	N/A	N/A


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	no	no	1.1	USB Port of Adapter	EUT

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For Wi-Fi mode

Compliant, please refer to the SAR report No: RSZ160114005-20.

For bluetooth LE mode

The Max tune-up power is -0.2 dBm (0.95mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.95/5 \cdot (\sqrt{2.48}) = 0.3 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement for Wi-Fi and the antenna gain is 1.5 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

FINAL

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2015-10-20	2016-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-06-09	2016-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2015-11-26	2016-11-25
N/A	Coaxial Cable	1.8m	N/A	2015-05-06	2016-05-06
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

15.3 dB at 0.181612 MHz in the **Line** conducted mode for BLE


Test Data**Environmental Conditions**

Temperature:	23.3°C
Relative Humidity:	49 %
ATM Pressure:	101.3kPa

The testing was performed by Lion Xiao on 2016-01-21


Test Mode: Transmitting (Wi-Fi)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.174519	48.5	9.000	L1	9.7	16.2	64.7	Compliance
0.180171	48.9	9.000	L1	9.7	15.6	64.5	Compliance
0.195114	42.4	9.000	L1	9.7	21.4	63.8	Compliance
0.238124	41.9	9.000	L1	9.7	20.3	62.2	Compliance
0.243884	41.5	9.000	L1	9.7	20.5	62.0	Compliance
0.255827	38.3	9.000	L1	9.7	23.3	61.6	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.173134	31.1	9.000	L1	9.7	23.7	54.8	Compliance
0.180171	32.2	9.000	L1	9.7	22.3	54.5	Compliance
0.184529	31.4	9.000	L1	9.7	22.9	54.3	Compliance
1.239175	23.5	9.000	L1	9.8	22.5	46.0	Compliance
1.289541	23.1	9.000	L1	9.8	22.9	46.0	Compliance
1.385415	24.6	9.000	L1	9.8	21.4	46.0	Compliance


AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.171759	47.9	9.000	N	9.7	17.0	64.9	Compliance
0.178741	49.0	9.000	N	9.7	15.5	64.5	Compliance
0.195114	42.7	9.000	N	9.7	21.1	63.8	Compliance
0.234359	41.5	9.000	N	9.7	20.8	62.3	Compliance
0.253797	39.1	9.000	N	9.7	22.5	61.6	Compliance
0.255827	38.3	9.000	N	9.7	23.3	61.6	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.173134	32.6	9.000	N	9.7	22.2	54.8	Compliance
0.178741	33.6	9.000	N	9.7	20.9	54.5	Compliance
0.234359	24.9	9.000	N	9.7	27.4	52.3	Compliance
1.023481	21.1	9.000	N	9.8	24.9	46.0	Compliance
1.239175	24.9	9.000	N	9.8	21.1	46.0	Compliance
1.453260	23.9	9.000	N	9.8	22.1	46.0	Compliance


Test Mode: Transmitting (BLE)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.167702	43.1	9.000	L1	9.7	22.0	65.1	Compliance
0.174519	48.9	9.000	L1	9.7	15.8	64.7	Compliance
0.181612	49.1	9.000	L1	9.7	15.3	64.4	Compliance
0.196675	39.9	9.000	L1	9.7	23.8	63.7	Compliance
0.227007	39.3	9.000	L1	9.7	23.3	62.6	Compliance
0.236234	42.1	9.000	L1	9.7	20.1	62.2	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.174519	31.4	9.000	L1	9.7	23.3	54.7	Compliance
0.187494	21.8	9.000	L1	9.7	32.3	54.1	Compliance
0.238124	21.0	9.000	L1	9.7	31.2	52.2	Compliance
1.048242	20.2	9.000	L1	9.8	25.8	46.0	Compliance
1.239175	24.3	9.000	L1	9.8	21.7	46.0	Compliance
1.407671	23.7	9.000	L1	9.8	22.3	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170396	47.1	9.000	N	9.7	17.8	64.9	Compliance
0.177322	49.1	9.000	N	9.7	15.5	64.6	Compliance
0.193566	44.8	9.000	N	9.7	19.1	63.9	Compliance
0.230654	41.7	9.000	N	9.7	20.7	62.4	Compliance
0.241949	41.9	9.000	N	9.7	20.1	62.0	Compliance
0.257874	37.1	9.000	N	9.7	24.4	61.5	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.170396	30.9	9.000	N	9.7	24.0	54.9	Compliance
0.177322	36.1	9.000	N	9.7	18.5	54.6	Compliance
0.192030	28.4	9.000	N	9.7	25.5	53.9	Compliance
0.230654	28.3	9.000	N	9.7	24.1	52.4	Compliance
1.239175	24.9	9.000	N	9.8	21.1	46.0	Compliance
1.385415	26.5	9.000	N	9.8	19.5	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS


Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non- compliance with a disturbance limit shall be determined in the following manner

FINAL

Above 1GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	AV

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-08-03	2016-08-02
Sunol Sciences	Antenna	JB3	A060611-3	2014-11-06	2017-11-05
HP	Amplifier	8447E	2434A02181	2015-09-01	2016-09-01
Agilent	Spectrum Analyzer	E4440A	SG43360054	2014-12-04	2015-12-04
ETS-Lindgren	Horn Antenna	3115	9808-5557	2015-09-06	2018-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2015-09-06	2016-09-06
N/A	Coaxial Cable	14m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	8m	N/A	2015-05-06	2016-05-06
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

2.85 dB at 2390 MHz in the Horizontal polarization for Wi-Fi

Test Data

Environmental Conditions

Temperature:	17.3~18.2 °C
Relative Humidity:	70 ~72 %
ATM Pressure:	102 ~102.1kPa

* The testing was performed by Lion Xiao from 2016-02-02 to 2016-02-03.

Test Mode: Transmitting

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	74.9	PK	H	25.67	3.68	0.00	104.25	N/A	N/A
2412	68.39	AV	H	25.67	3.68	0.00	97.74	N/A	N/A
2412	72.52	PK	V	25.67	3.68	0.00	101.87	N/A	N/A
2412	66.09	AV	V	25.67	3.68	0.00	95.44	N/A	N/A
2390	29.15	PK	H	25.61	3.63	0.00	58.39	74.00	15.61
2390	16.72	AV	H	25.61	3.63	0.00	45.96	54.00	8.04
4824	37.56	PK	H	30.64	5.03	27.41	45.82	74.00	28.18
4824	25.49	AV	H	30.64	5.03	27.41	33.75	54.00	20.25
7236	40.45	PK	H	34.17	6.65	25.90	55.37	74.00	18.63
7236	28.8	AV	H	34.17	6.65	25.90	43.72	54.00	10.28
9648	30.65	PK	H	36.06	8.55	27.46	47.80	74.00	26.20
9648	18.16	AV	H	36.06	8.55	27.46	35.31	54.00	18.69
3381	37.29	PK	H	28.42	5.03	27.22	43.52	74.00	30.48
3381	29.34	AV	H	28.42	5.03	27.22	35.57	54.00	18.43
251.7	36.1	QP	H	12.13	1.90	21.49	28.64	46.00	17.36
Middle Channel: 2437 MHz									
2437	74.05	PK	H	25.74	3.75	0.00	103.54	N/A	N/A
2437	68.35	AV	H	25.74	3.75	0.00	97.84	N/A	N/A
2437	72.51	PK	V	25.74	3.75	0.00	102.00	N/A	N/A
2437	66.29	AV	V	25.74	3.75	0.00	95.78	N/A	N/A
4874	37.96	PK	H	30.77	5.14	27.42	46.45	74.00	27.55
4874	25.6	AV	H	30.77	5.14	27.42	34.09	54.00	19.91
7311	40.55	PK	H	34.35	6.74	25.88	55.76	74.00	18.24
7311	28.31	AV	H	34.35	6.74	25.88	43.52	54.00	10.48
9748	30.27	PK	H	36.30	8.61	27.24	47.94	74.00	26.06
9748	18.86	AV	H	36.30	8.61	27.24	36.53	54.00	17.47
3381	37.83	PK	H	28.42	5.03	27.22	44.06	74.00	29.94
3381	25.18	AV	H	28.42	5.03	27.22	31.41	54.00	22.59
3190	35.43	PK	H	27.81	6.26	27.38	42.12	74.00	31.88
3190	23.32	AV	H	27.81	6.26	27.38	30.01	54.00	23.99
251.7	36.9	QP	H	12.13	1.90	21.49	29.44	46.00	16.56
High Channel: 2462 MHz									
2462	74.36	PK	H	25.80	3.75	0.00	103.91	N/A	N/A
2462	68.53	AV	H	25.80	3.75	0.00	98.08	N/A	N/A
2462	72.68	PK	V	25.80	3.75	0.00	102.23	N/A	N/A
2462	66.19	AV	V	25.80	3.75	0.00	95.74	N/A	N/A
2483.5	28.99	PK	H	25.86	3.67	0.00	58.52	74.00	15.48
2483.5	16.84	AV	H	25.86	3.67	0.00	46.37	54.00	7.63
4924	37.79	PK	H	30.90	5.34	27.43	46.60	74.00	27.40
4924	25.48	AV	H	30.90	5.34	27.43	34.29	54.00	19.71
7386	40.32	PK	H	34.53	6.83	25.86	55.82	74.00	18.18
7386	28.88	AV	H	34.53	6.83	25.86	44.38	54.00	9.62
9848	30.75	PK	H	36.54	8.66	26.94	49.01	74.00	24.99
9848	18.14	AV	H	36.54	8.66	26.94	36.40	54.00	17.60
3381	37.18	PK	H	28.42	5.03	27.22	43.41	74.00	30.59
3381	29.51	AV	H	28.42	5.03	27.22	35.74	54.00	18.26
251.7	36.5	QP	H	12.13	1.90	21.49	29.04	46.00	16.96

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	72.89	PK	H	25.67	3.68	0.00	102.24	N/A	N/A
2412	60.51	AV	H	25.67	3.68	0.00	89.86	N/A	N/A
2412	68.89	PK	V	25.67	3.68	0.00	98.24	N/A	N/A
2412	56.17	AV	V	25.67	3.68	0.00	85.52	N/A	N/A
2390	32.39	PK	H	25.61	3.63	0.00	61.63	74.00	12.37
2390	20.51	AV	H	25.61	3.63	0.00	49.75	54.00	4.25
4824	32.16	PK	H	30.64	5.03	27.41	40.42	74.00	33.58
4824	20.42	AV	H	30.64	5.03	27.41	28.68	54.00	25.32
7236	31.22	PK	H	34.17	6.65	25.90	46.14	74.00	27.86
7236	20.47	AV	H	34.17	6.65	25.90	35.39	54.00	18.61
9648	28.67	PK	H	36.06	8.55	27.46	45.82	74.00	28.18
9648	17.91	AV	H	36.06	8.55	27.46	35.06	54.00	18.94
3381	37.93	PK	H	28.42	5.03	27.22	44.16	74.00	29.84
3381	25.56	AV	H	28.42	5.03	27.22	31.79	54.00	22.21
251.7	36.2	QP	H	12.13	1.90	21.49	28.74	46.00	17.26
Middle Channel: 2437 MHz									
2437	72.38	PK	H	25.74	3.75	0.00	101.87	N/A	N/A
2437	60.19	AV	H	25.74	3.75	0.00	89.68	N/A	N/A
2437	68.03	PK	V	25.74	3.75	0.00	97.52	N/A	N/A
2437	56.39	AV	V	25.74	3.75	0.00	85.88	N/A	N/A
4874	30.3	PK	H	30.77	5.14	27.42	38.79	74.00	35.21
4874	18.18	AV	H	30.77	5.14	27.42	26.67	54.00	27.33
7311	31.29	PK	H	34.35	6.74	25.88	46.50	74.00	27.50
7311	18.87	AV	H	34.35	6.74	25.88	34.08	54.00	19.92
9748	28.72	PK	H	36.30	8.61	27.24	46.39	74.00	27.61
9748	16.03	AV	H	36.30	8.61	27.24	33.70	54.00	20.30
3381	37.7	PK	H	28.42	5.03	27.22	43.93	74.00	30.07
3381	25.29	AV	H	28.42	5.03	27.22	31.52	54.00	22.48
3190	35.92	PK	H	27.81	6.26	27.38	42.61	74.00	31.39
3190	23.75	AV	H	27.81	6.26	27.38	30.44	54.00	23.56
251.7	36.7	QP	H	12.13	1.90	21.49	29.24	46.00	16.76
High Channel: 2462 MHz									
2462	72.06	PK	H	25.80	3.75	0.00	101.61	N/A	N/A
2462	60.73	AV	H	25.80	3.75	0.00	90.28	N/A	N/A
2462	68.14	PK	V	25.80	3.75	0.00	97.69	N/A	N/A
2462	56.88	AV	V	25.80	3.75	0.00	86.43	N/A	N/A
2483.5	30.82	PK	H	25.86	3.67	0.00	60.35	74.00	13.65
2483.5	18.3	AV	H	25.86	3.67	0.00	47.83	54.00	6.17
4924	31.22	PK	H	30.90	5.34	27.43	40.03	74.00	33.97
4924	18.35	AV	H	30.90	5.34	27.43	27.16	54.00	26.84
7386	31.51	PK	H	34.53	6.83	25.86	47.01	74.00	26.99
7386	18.44	AV	H	34.53	6.83	25.86	33.94	54.00	20.06
9848	30.1	PK	H	36.54	8.66	26.94	48.36	74.00	25.64
9848	17.03	AV	H	36.54	8.66	26.94	35.29	54.00	18.71
3381	37.5	PK	H	28.42	5.03	27.22	43.73	74.00	30.27
3381	25.83	AV	H	28.42	5.03	27.22	32.06	54.00	21.94
251.7	36.4	QP	H	12.13	1.90	21.49	28.94	46.00	17.06

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	71.38	PK	H	25.67	3.68	0.00	100.73	N/A	N/A
2412	59.34	AV	H	25.67	3.68	0.00	88.69	N/A	N/A
2412	67.46	PK	V	25.67	3.68	0.00	96.81	N/A	N/A
2412	55.18	AV	V	25.67	3.68	0.00	84.53	N/A	N/A
2390	33.15	PK	H	25.61	3.63	0.00	62.39	74.00	11.61
2390	20.93	AV	H	25.61	3.63	0.00	50.17	54.00	3.83
4824	32.42	PK	H	30.64	5.03	27.41	40.68	74.00	33.32
4824	20.38	AV	H	30.64	5.03	27.41	28.64	54.00	25.36
7236	31.31	PK	H	34.17	6.65	25.90	46.23	74.00	27.77
7236	20.4	AV	H	34.17	6.65	25.90	35.32	54.00	18.68
9648	28.61	PK	H	36.06	8.55	27.46	45.76	74.00	28.24
9648	17.59	AV	H	36.06	8.55	27.46	34.74	54.00	19.26
3381	37.02	PK	H	28.42	5.03	27.22	43.25	74.00	30.75
3381	25.22	AV	H	28.42	5.03	27.22	31.45	54.00	22.55
251.7	36.8	QP	H	12.13	1.90	21.49	29.34	46.00	16.66
Middle Channel: 2437 MHz									
2437	71.51	PK	H	25.74	3.75	0.00	101.00	N/A	N/A
2437	59.09	AV	H	25.74	3.75	0.00	88.58	N/A	N/A
2437	67.66	PK	V	25.74	3.75	0.00	97.15	N/A	N/A
2437	55.99	AV	V	25.74	3.75	0.00	85.48	N/A	N/A
4874	30.02	PK	H	30.77	5.14	27.42	38.51	74.00	35.49
4874	18.26	AV	H	30.77	5.14	27.42	26.75	54.00	27.25
7311	31.38	PK	H	34.35	6.74	25.88	46.59	74.00	27.41
7311	18.94	AV	H	34.35	6.74	25.88	34.15	54.00	19.85
9748	28.55	PK	H	36.30	8.61	27.24	46.22	74.00	27.78
9748	16.82	AV	H	36.30	8.61	27.24	34.49	54.00	19.51
3381	37.84	PK	H	28.42	5.03	27.22	44.07	74.00	29.93
3381	25.13	AV	H	28.42	5.03	27.22	31.36	54.00	22.64
3190	35.18	PK	H	27.81	6.26	27.38	41.87	74.00	32.13
3190	23.69	AV	H	27.81	6.26	27.38	30.38	54.00	23.62
251.7	36.3	QP	H	12.13	1.90	21.49	28.84	46.00	17.16
High Channel: 2462 MHz									
2462	71.92	PK	H	25.80	3.75	0.00	101.47	N/A	N/A
2462	59.94	AV	H	25.80	3.75	0.00	89.49	N/A	N/A
2462	67.88	PK	V	25.80	3.75	0.00	97.43	N/A	N/A
2462	55.45	AV	V	25.80	3.75	0.00	85.00	N/A	N/A
2483.5	31.38	PK	H	25.86	3.67	0.00	60.91	74.00	13.09
2483.5	19.81	AV	H	25.86	3.67	0.00	49.34	54.00	4.66
4924	31.26	PK	H	30.90	5.34	27.43	40.07	74.00	33.93
4924	18.15	AV	H	30.90	5.34	27.43	26.96	54.00	27.04
7386	31.48	PK	H	34.53	6.83	25.86	46.98	74.00	27.02
7386	18.42	AV	H	34.53	6.83	25.86	33.92	54.00	20.08
9848	30.04	PK	H	36.54	8.66	26.94	48.30	74.00	25.70
9848	17.14	AV	H	36.54	8.66	26.94	35.40	54.00	18.60
3381	37.64	PK	H	28.42	5.03	27.22	43.87	74.00	30.13
3381	25.82	AV	H	28.42	5.03	27.22	32.05	54.00	21.95
251.7	36.6	QP	H	12.13	1.90	21.49	29.14	46.00	16.86

802.11 n ht40 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	70.67	PK	H	25.70	3.71	0.00	100.08	N/A	N/A
2422	58.9	AV	H	25.70	3.71	0.00	88.31	N/A	N/A
2422	65.81	PK	V	25.70	3.71	0.00	95.22	N/A	N/A
2422	53.83	AV	V	25.70	3.71	0.00	83.24	N/A	N/A
2390	33.74	PK	H	25.61	3.63	0.00	62.98	74.00	11.02
2390	21.91	AV	H	25.61	3.63	0.00	51.15	54.00	2.85
4844	32.39	PK	H	30.69	4.99	27.42	40.65	74.00	33.35
4844	19.99	AV	H	30.69	4.99	27.42	28.25	54.00	25.75
7266	31.19	PK	H	34.24	6.68	25.89	46.22	74.00	27.78
7266	20.5	AV	H	34.24	6.68	25.89	35.53	54.00	18.47
9688	28.72	PK	H	36.15	8.58	27.37	46.08	74.00	27.92
9688	17.86	AV	H	36.15	8.58	27.37	35.22	54.00	18.78
3381	37.89	PK	H	28.42	5.03	27.22	44.12	74.00	29.88
3381	25.41	AV	H	28.42	5.03	27.22	31.64	54.00	22.36
251.7	36	QP	H	12.13	1.90	21.49	28.54	46.00	17.46
Middle Channel: 2437 MHz									
2437	70.01	PK	H	25.74	3.75	0.00	99.50	N/A	N/A
2437	58.4	AV	H	25.74	3.75	0.00	87.89	N/A	N/A
2437	65.85	PK	V	25.74	3.75	0.00	95.34	N/A	N/A
2437	53.44	AV	V	25.74	3.75	0.00	82.93	N/A	N/A
4874	30.24	PK	H	30.77	5.14	27.42	38.73	74.00	35.27
4874	18.03	AV	H	30.77	5.14	27.42	26.52	54.00	27.48
7311	31.19	PK	H	34.35	6.74	25.88	46.40	74.00	27.60
7311	18.64	AV	H	34.35	6.74	25.88	33.85	54.00	20.15
9748	28.74	PK	H	36.30	8.61	27.24	46.41	74.00	27.59
9748	15.91	AV	H	36.30	8.61	27.24	33.58	54.00	20.42
3381	37.11	PK	H	28.42	5.03	27.22	43.34	74.00	30.66
3381	25.74	AV	H	28.42	5.03	27.22	31.97	54.00	22.03
3190	35.99	PK	H	27.81	6.26	27.38	42.68	74.00	31.32
3190	23.74	AV	H	27.81	6.26	27.38	30.43	54.00	23.57
251.7	36.8	QP	H	12.13	1.90	21.49	29.34	46.00	16.66
High Channel: 2452 MHz									
2452	70.35	PK	H	25.78	3.78	0.00	99.91	N/A	N/A
2452	58.66	AV	H	25.78	3.78	0.00	88.22	N/A	N/A
2452	65.2	PK	V	25.78	3.78	0.00	94.76	N/A	N/A
2452	53.5	AV	V	25.78	3.78	0.00	83.06	N/A	N/A
2483.5	31.55	PK	H	25.86	3.67	0.00	61.08	74.00	12.92
2483.5	19.32	AV	H	25.86	3.67	0.00	48.85	54.00	5.15
4904	30.93	PK	H	30.85	5.31	27.43	39.66	74.00	34.34
4904	18.52	AV	H	30.85	5.31	27.43	27.25	54.00	26.75
7356	31.25	PK	H	34.45	6.79	25.87	46.62	74.00	27.38
7356	18.46	AV	H	34.45	6.79	25.87	33.83	54.00	20.17
9808	29.93	PK	H	36.44	8.64	27.09	47.92	74.00	26.08
9808	16.85	AV	H	36.44	8.64	27.09	34.84	54.00	19.16
3381	37.58	PK	H	28.42	5.03	27.22	43.81	74.00	30.19
3381	25.69	AV	H	28.42	5.03	27.22	31.92	54.00	22.08
251.7	36.5	QP	H	12.13	1.90	21.49	29.04	46.00	16.96

BLE Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	64.2	PK	H	25.65	3.66	0.00	93.51	N/A	N/A
2402	54.06	AV	H	25.65	3.66	0.00	83.37	N/A	N/A
2402	61.01	PK	V	25.65	3.66	0.00	90.32	N/A	N/A
2402	51.75	AV	V	25.65	3.66	0.00	81.06	N/A	N/A
2390	26.85	PK	H	25.61	3.63	0.00	56.09	74.00	17.91
2390	14.36	AV	H	25.61	3.63	0.00	43.60	54.00	10.40
4804	33.22	PK	H	30.59	5.06	27.41	41.46	74.00	32.54
4804	21.8	AV	H	30.59	5.06	27.41	30.04	54.00	23.96
7206	31.18	PK	H	34.09	6.61	25.91	45.97	74.00	28.03
7206	19.05	AV	H	34.09	6.61	25.91	33.84	54.00	20.16
9608	29.48	PK	H	35.96	8.53	27.55	46.42	74.00	27.58
9608	17.21	AV	H	35.96	8.53	27.55	34.15	54.00	19.85
3381	37.66	PK	H	28.42	5.03	27.22	43.89	74.00	30.11
3381	25.54	AV	H	28.42	5.03	27.22	31.77	54.00	22.23
259.1	36.7	QP	H	12.67	1.94	21.50	29.81	46.00	16.19
Middle Channel: 2440 MHz									
2440	64.98	PK	H	25.74	3.76	0.00	94.48	N/A	N/A
2440	54.62	AV	H	25.74	3.76	0.00	84.12	N/A	N/A
2440	61.59	PK	V	25.74	3.76	0.00	91.09	N/A	N/A
2440	51.55	AV	V	25.74	3.76	0.00	81.05	N/A	N/A
4880	33.06	PK	H	30.79	5.18	27.42	41.61	74.00	32.39
4880	21.24	AV	H	30.79	5.18	27.42	29.79	54.00	24.21
7320	31.81	PK	H	34.37	6.75	25.88	47.05	74.00	26.95
7320	19.01	AV	H	34.37	6.75	25.88	34.25	54.00	19.75
9760	29.02	PK	H	36.32	8.62	27.21	46.75	74.00	27.25
9760	17.88	AV	H	36.32	8.62	27.21	35.61	54.00	18.39
3381	37.1	PK	H	28.42	5.03	27.22	43.33	74.00	30.67
3381	25.22	AV	H	28.42	5.03	27.22	31.45	54.00	22.55
3695	35.96	PK	H	29.23	4.63	27.32	42.50	74.00	31.50
3695	23.15	AV	H	29.23	4.63	27.32	29.69	54.00	24.31
259.1	36.3	QP	H	12.67	1.94	21.50	29.41	46.00	16.59
High Channel: 2480 MHz									
2480	65.18	PK	H	25.85	3.68	0.00	94.71	N/A	N/A
2480	55.97	AV	H	25.85	3.68	0.00	85.50	N/A	N/A
2480	61.69	PK	V	25.85	3.68	0.00	91.22	N/A	N/A
2480	51.46	AV	V	25.85	3.68	0.00	80.99	N/A	N/A
2483.5	26.3	PK	H	25.86	3.67	0.00	55.83	74.00	18.17
2483.5	14.02	AV	H	25.86	3.67	0.00	43.55	54.00	10.45
4960	33.66	PK	H	31.00	5.34	27.43	42.57	74.00	31.43
4960	21.49	AV	H	31.00	5.34	27.43	30.40	54.00	23.60
7440	31.8	PK	H	34.66	6.89	25.97	47.38	74.00	26.62
7440	19.03	AV	H	34.66	6.89	25.97	34.61	54.00	19.39
9920	29.96	PK	H	36.71	8.71	26.66	48.72	74.00	25.28
9920	17.05	AV	H	36.71	8.71	26.66	35.81	54.00	18.19
3381	37.26	PK	H	28.42	5.03	27.22	43.49	74.00	30.51
3381	25.21	AV	H	28.42	5.03	27.22	31.44	54.00	22.56
259.1	36.9	QP	H	12.67	1.94	21.50	30.01	46.00	15.99

Conducted Spurious Emissions at Antenna Port


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel




802.11g High Channel




802.11n ht20 Low Channel




802.11n ht20 Middle Channel




802.11n ht20 High Channel




802.11n ht40 Low Channel




802.11n ht40 Middle Channel




802.11n ht40 High Channel




BLE Low Channel



BLE Middle Channel



BLE High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance


- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW)

Test Mode: Transmitting


Test Result: Compliant. Please refer to the following table and plots.

Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.30	


802.11b Middle Channel




802.11b High Channel




802.11g Low Channel




802.11g Middle Channel



802.11g High Channel



802.11n ht20 Low Channel



Delta 1 [T1] 2.09 dB RBW 100 kHz RF Att 30 dB
 Ref Lvl 20 dBm 17.71543086 MHz VBW 300 kHz Unit dBm
 0.5 dB Offset

-D1 1.08 dBm
 -D2 -4.92 dBm

1MAX

1 [T1] -6.17 dBm
 2.42814228 GHz
 2.09 dB
 17.71543086 MHz
 1.08 dBm
 2.43768136 GHz

Center 2.437 GHz 4 MHz/ Span 40 MHz

Date: 02.FEB.2016 14:23:36

Ref Lvl 20 dBm

Delta 1 [T1] -1.02 dB

RBW 100 kHz

VBW 300 kHz

RF Att 30 dB

SWT 10 ms

Unit dBm

0.5 dB Offset

D1 1.57 dBm

D2 -4.43 dBm

1MAX

1 [T1] -3.12 dBm

2 [T1] -1.02 dB

17.63527054 MHz

2.4532244 GHz

2.45915431 GHz


Center 2.462 GHz

4 MHz/


Span 40 MHz



Date: 02.FEB.2016 14:28:32

802.11n ht40 Low Channel




802.11n ht40 Middle Channel




802.11n ht40 High Channel**BLE Low Channel**

BLE Middle Channel



BLE High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2015-11-03	2016-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2015-11-03	2016-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2015-11-03	2016-11-03
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	21.1°C
Relative Humidity:	42 %
ATM Pressure:	102.1 kPa

* The testing was performed by Lion Xiao on 2016-02-02

Test Mode: Transmitting

FINAL

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09
N/A	Coaxial Cable	0.1m	N/A	2015-05-06	2016-05-06
E-Microwave	DC Blocking	EMDCB-00036	0E01201047	2015-05-06	2016-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	21.1°C
Relative Humidity:	42 %
ATM Pressure:	102.1 kPa

* The testing was performed by Lion Xiao on 2016-02-02


Test mode: Transmitting

Test Result: Compliant. Please refer to following plots.


802.11b: Band Edge, Left Side




802.11b: Band Edge, Right Side




802.11g: Band Edge, Left Side




802.11g: Band Edge, Right Side





802.11n ht20 Band Edge, Left Side



802.11n ht20 Band Edge, Right Side



802.11n ht40 Band Edge, Left Side**802.11n ht40 Band Edge, Right Side**

BLE Band Edge

FINAL

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure



According to KDB 558074 D01 DTS Meas Guidance

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW ≥ 3


Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-10.70	

Power Spectral Density, 802.11b Middle Channel**Power Spectral Density, 802.11b High Channel**


Power Spectral Density, 802.11g Low Channel




Power Spectral Density, 802.11g Middle Channel




Power Spectral Density, 802.11g High Channel




Power Spectral Density, 802.11n ht20 Low Channel




Power Spectral Density, 802.11n ht20 Middle Channel




Power Spectral Density, 802.11n ht20 High Channel




Power Spectral Density, 802.11n ht40 Low Channel




Power Spectral Density, 802.11n ht40 Middle Channel




Power Spectral Density, 802.11n ht40 High Channel




Power Spectral Density, BLE Low Channel



Power Spectral Density, BLE Middle Channel



Power Spectral Density, BLE High Channel



***** END OF REPORT *****