RF Exposure Evaluation Report

1 RF EXPOSURE

Product Name: digital camera

Model No.: S150Pro, X9, S96pro FCC ID: 2A6Q7-S150PRO

2. RF Exposure Evaluation

FCC KDB447498 D01 General RF Exposure Guidance v06: Mobile and Portable Device, RF Exposure, Equipment Authorization Procedures.

FCC CFR 47 part1 1.1310: Radiofrequency radiation exposure limits.

FCC CFR 47 part2 2.1093 Radiofrequency radiation exposure evaluation: portable devices.

2.1 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] *[$\sqrt{f(GHz)}$] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2.2 EUT RF EXPOSURE EVALUATION

Worst Mode: 802.11n						
Channel (MHz)	Conducted	Tune up	Maximum		Calculated value	Limit
	Power	Tolerance	tune-up Power			
	(dBm)	(dBm)	(dBm)	(mW)	value	
2462.00	8.32	8±1.0	9.0	7.943	2.493	3.0

Calculated value is 2.493< 3.0, So there is no require SAR test.