

Issue Date : May 25, 2005
Page 1 of 34

***EMC* EMISSION - TEST REPORT**

JQA APPLICATION No. : KL80050091R

Name of Product : Microwave Oven

Model/Type No. : R-25JT-F

FCC ID : APYDMR0164

Applicant : Sharp Corporation, Kitchen Appliances Systems Div.

Address : 3-1-72 Kitakamei-Cho, Yao, Osaka 581-8585, Japan

Manufacturer : Sharp Corporation, Kitchen Appliances Systems Div.

Address : 3-1-72 Kitakamei-Cho, Yao, Osaka 581-8585, Japan

Receive date of EUT : April 25, 2005

Final Judgement : **Passed**

TEST RESULTS IN THIS REPORT are obtained in use of equipment that is traceable to National Institute of Advanced Industrial Science and Technology (AIST) under METI Japan and National Institute of Information and Communications Technology (NICT) under MPHPT Japan.

THE TEST RESULTS only responds to the test sample. This test report shall not be reproduced except in full.

Authorized by:



Yuichi Fukumoto, Manager
JQA KITA-KANSAI Testing Center

DIRECTORY

	Page
A) Documentation	
Directory	<u>2</u>
Test Regulation / General Information	<u>3</u>
Test Conditions	<u>4 - 9</u>
Configuration of EUT / Operation mode of the EUT	<u>10 - 11</u>
EUT Modification / Responsible Party / Deviation from Standard	<u>12</u>
Test results / Measurement Uncertainty	<u>13 - 16</u>
Summary	<u>17</u>
Test System-Arrangement (Drawings)	<u>18</u>
Test-setup (Drawings)	<u>19 - 22</u>
Test-setup (Photographs) at worst case	<u>23</u>
B) Test data	
RF Power Output	<u>24 - 25</u>
ISM Frequency	<u>26</u>
Conducted Emission	150 kHz - 30 MHz
	<u>27 - 28</u>
Magnetic Field Radiated Emission	9 kHz - 30 MHz
	<u>29 - 30</u>
Electromagnetic Field Radiated Emission	30 MHz - 1000 MHz
	<u>31 - 32</u>
Electromagnetic Field Radiated Emission	1 GHz - 26 GHz
	<u>33 - 34</u>

TEST REGULATION

FCC Rules and Regulations Part 18 Subpart A, B and C (October 1, 2003)

- - Miscellaneous equipment
- - Medical diathermy
- - Industrial heaters and RF stabilized arc welder
- - Induction cooking ranges
- - ISM Frequency Device
- - Non-ISM Frequency Device

Test procedure:

The test was performed according to the procedures in FCC/OET MP-5 (1986).

GENERAL INFORMATION

Test facility:

- 1) Test Facility located at Kita-Kansai : 1st Open Site (3 m Site)
Test Facility located at Kameoka : 1st Open Site (3, 10 and 30 m, on common plane)
: 2nd Open Site (3 and 10 m, on common plane)

FCC filing No. : 31040/SIT 1300F2

- 2) KITA-KANSAI TESTING CENTER is recognized under the National Voluntary Laboratory Accreditation Program for satisfactory compliance established in Title 15, Part 285 Code of Federal Regulations.
NVLAP Lab Code: 200191-0

- 3) Average Measurement Method
FCC filing No. : 950523A 1300F2

Description of the Equipment Under Test (EUT):

- 1) Name : Microwave Oven
- 1) Model/Type No. : R-25JT-F
- 3) Product Type : Prototype
- 4) Category : ISM Frequency Device
- 5) EUT Authorization : ○ - Verification ● - Certification ○ - D.o.C.
- 6) Highest frequency used/generated : 2450 MHz
- 7) Rated RF Power Output : 2100 W
- 9) Power Rating : AC 208/230V 60Hz

Definitions for symbols used in this test report:

- - Black box indicates that the listed condition, standard or equipment is applicable for this Report.
- - Blank box indicates that the listed condition, standard or equipment is not applicable for this Report.

TEST CONDITIONS

RF Power Output Measurement

was performed in the following test site.

Test location:

KITA-KANSAI Testing Center

7-7, Ishimaru, 1-Chome, Mino-Shi, Osaka, 562-0027, Japan

● - Shielded room

○ - Anechoic chamber

○ - 1st open test site

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-Cho, Kameoka-Shi, Kyoto, 621-0126, Japan

○ - Shielded room

○ - 1st open test site

○ - 2nd open test site

Used test instruments:

Model No.	Assigned C/N	Last Cal. Date	Cal. Interval
● - 2533-21	08011090	June, 2004	1 Year
● - 245506	Q47097361	March, 2005	1 Year
● - SIII-5000	Q47097350	February, 2005	1 Year

Environmental conditions:

Temperature: 28 °C Humidity: 50 %

ISM Frequency Measurement

was performed for line voltage variation from 80 % to 125 % of normal rated voltage, in the following test site.

Test location:

KITA-KANSAI Testing Center

7-7, Ishimaru, 1-Chome, Mino-Shi, Osaka, 562-0027, Japan

○ - Shielded room

● - Anechoic chamber

○ - 1st open test site

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-Cho, Kameoka-Shi, Kyoto, 621-0126, Japan

○ - Shielded room

○ - 1st open test site

○ - 2nd open test site

Used test instruments:

Model No.	Device ID	Last Cal. Date	Cal. Interval
○ - 8566B	A - 13	October, 2004	1 Year
○ - 8593A	A - 15		
● - E4446A	A - 39		
○ - 4T-10	D - 73		
○ - 4T-10	D - 74		
○ - WJ-6611-513	A - 23	May, 2004	1 Year
○ - WJ-6882-824	A - 21		
○ - DBL-0618N515	A - 33		
○ - 91888-2	C - 41 - 1		
● - 91889-2	C - 41 - 2		
○ - 94613-1	C - 41 - 3	June, 2004	1 Year
○ - 91891-2	C - 41 - 4		
○ - 94614-1	C - 41 - 5		
● - 2-10	D - 40		
● - TR5212	B - 30		
● - Cable	C - 40 - 8	May, 2004	1 Year
○ - Cable	C - 40 - 11		
○ - Cable	C - 40 - 12		

Environmental conditions:

Temperature: 24 °C Humidity: 68 %

AC Powerline Conducted Emission Measurement

was performed in the following test site.

Test location:

KITA-KANSAI Testing Center

7-7, Ishimaru, 1-Chome, Mino-Shi, Osaka, 562-0027, Japan

● - Shielded room

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-Cho, Kameoka-Shi, Kyoto, 621-0126, Japan

○ - Shielded room

○ - On metal plane of open site

Used test instruments and sites:

Model No.	Device ID	Last Cal. Date	Cal. Interval
○ - ESCS 30	A - 1	September, 2004	1 Year
● - ESCS 30	A - 9		
○ - ESH 2	A - 2		
○ - ESH 2	A - 3		
○ - KNW-407	D - 6	February, 2005	1 Year
● - KNW-408	D - 11		
○ - KNW-242	D - 7		
○ - ESH3-Z5	D - 12		
○ - KNW-341C	D - 13	February, 2005	1 Year
○ - KNW-408	D - 14		
○ - KNW-244C	D - 77		
○ - KNW-408	D - 78		
○ - ESH2-Z5	D - 10	February, 2005	1 Year
○ - ESH2-Z3	D - 17		
○ - 65 BNC-50-0-1	H - 26		
○ - 65 BNC-50-0-1	H - 27		
○ - Cable	H - 7	February, 2005	1 Year
● - Cable	H - 8		

Environmental conditions:

Temperature: 23 °C Humidity: 58 %

Magnetic Field Radiated Emission Measurement

was performed in the frequency range of 9 kHz - 30 MHz, in the following test site.

Test location:

KITA-KANSAI Testing Center

7-7, Ishimaru, 1-Chome, Mino-Shi, Osaka, 562-0027, Japan

● - 1st open test site (3 meters)

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-Cho, Kameoka-Shi, Kyoto, 621-0126, Japan

○ - 1st open test site ○ - 3 m ○ - 10 m ○ - 30 m
○ - 2nd open test site ○ - 3 m ○ - 10 m

Used test instruments:

Model No.	Device ID	Last Cal. Date	Cal. Interval
● - ESCS 30	A - 1	August, 2004	1 Year
○ - ESCS 30	A - 9		
○ - ESH 2	A - 2		
○ - ESH 2	A - 3		
● - HFH2-Z2	C - 2	July, 2004	1 Year
○ - HFH2-Z2	C - 3		
● - Cable	H - 28	July, 2004	1 Year
○ - Cable	H - 29		

Environmental conditions:

Temperature: 24 °C Humidity: 68 %

Electromagnetic Field Radiated Emission Measurement

was performed in horizontal and vertical polarization, in the frequency range of 30 MHz - 1000 MHz, in the following test site.

Test location:

KITA-KANSAI Testing Center

7-7, Ishimaru, 1-Chome, Mino-Shi, Osaka, 562-0027, Japan

○ - 1st open test site (3 meters)

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-Cho, Kameoka-Shi, Kyoto, 621-0126, Japan

● - 1st open test site ○ - 3 m ● - 10 m ○ - 30 m

○ - 2nd open test site ○ - 3 m ○ - 10 m

Validation of Site Attenuation:

1) Last Confirmed Date : November 11, 2004

2) Interval : 1 Year

Used test instruments:

Model No.	Device ID	Last Cal. Date	Cal. Interval
○ - ESV/ESV-Z3	A - 7 / A - 17	May, 2004	1 Year
○ - ESV/ESV-Z3	A - 6 / A - 18		
○ - ESV/ESV-Z3	A - 4 / A - 20		
● - ESV/ESV-Z3	A - 8 / A - 19		
○ - ESVS 10	A - 5		
○ - KBA-511A	C - 11	August, 2004	1 Year
○ - KBA-611	C - 21		
○ - VHA9103/BBA9106	C - 43		
○ - UHALP9107	C - 42		
● - VHA9103/FBAB9177	C - 25		
● - UHALP9108-A1	C - 28		
● - Cable	H - 2		

Environmental conditions:

Temperature: 17 °C Humidity: 43 %

Electromagnetic Field Radiated Emission Measurement

was performed in horizontal and vertical polarization, in the frequency range of 1 GHz - 26 GHz, in the following test site.

Test location:

KITA-KANSAI Testing Center

7-7, Ishimaru, 1-Chome, Mino-Shi, Osaka, 562-0027, Japan

● - 1st open test site (3 meters)

KAMEOKA EMC Branch

9-1, Ozaki, Inukanno, Nishibetsuin-Cho, Kameoka-Shi, Kyoto, 621-0126, Japan

○ - 1st open test site ○ - 3 m ○ - 10 m ○ - 30 m

○ - 2nd open test site ○ - 3 m ○ - 10 m

Used test instruments:

Model No.	Device ID	Last Cal. Date	Cal. Interval
● - ESCS 30	A - 1	August, 2004	1 Year
○ - ESCS 30	A - 9		
○ - 8566B	A - 13		
● - E4446A	A - 39	October, 2004	1 Year
● - 4T-10	D - 73	May, 2004	1 Year
● - 4T-10	D - 74	May, 2004	1 Year
● - WJ-6611-513	A - 23	May, 2004	1 Year
● - WJ-6882-824	A - 21	May, 2004	1 Year
● - DBL-0618N515	A - 33	May, 2004	1 Year
● - ALN-22093545-1	A - 37	February, 2005	1 Year
● - 91888-2	C - 41 - 1	May, 2004	1 Year
● - 91889-2	C - 41 - 2	May, 2004	1 Year
● - 94613-1	C - 41 - 3	May, 2004	1 Year
● - 91891-2	C - 41 - 4	May, 2004	1 Year
● - 94614-1	C - 40 - 5	May, 2004	1 Year
● - 3160-09	C - 48	December, 2003	2 Years
● - Cable	C - 40 - 11	May, 2004	1 Year
● - Cable	C - 40 - 12	May, 2004	1 Year
● - Cable	C - 53	February, 2005	1 Year
● - Cable	C - 54	February, 2005	1 Year

Environmental conditions:

Temperature: 24 °C Humidity: 68 %

CONFIGURATION OF EUT**The Equipment Under Test (EUT) consists of:**

Description	Applicant (Manufacturer)	Model No. (Serial No.)	FCC ID
Microwave Oven	Sharp Corporation (Sharp Corporation)	R-25JT-F (--)	APYDMR0164

The measurement was carried out with the following equipment connected:

Description	Grantee/Distributor	Model No. (Serial No.)	FCC ID
None			

Type of Interference Cable(s) and the AC Power Cord used with the EUT:

	Description	Port	Shielded Cable	Shell Material	Ferrite Core	Cable Length
1	AC Power Cord (EUT) 1 ϕ 3-pin Plug	--	NO	--	NO	1.4 m

Operation - mode of the EUT:

The EUT was operated during the measurement under following load condition according to Sec. 4.1 in FCC/OET MP-5 (1986).

- 1) RF Power Output Measurement
2500 ml of water, with the beaker located in the center of the food container.
- 2) ISM Frequency Measurement
2500 ml of water, with the beaker located in the center of the food container.
- 3) Radiated Emission Measurement (radiation on second and third harmonics)
Two loads, one of 1750 ml and the other of 750 ml, of water are used. Each load is tested both with the beaker located in the center of the food container and with it in the right front center.
- 4) All Other Measurement (conducted and radiated emission)
1750 ml of water, with the beaker located in the center of the food container.

Test system:

The EUT is an microwave oven.
There is not any interface ports on the EUT.

Special accessories:

None

Type of Magnetron:

Cat. No. 2M248H(L) (manufactured by Toshiba Corporation)

The used (generated) frequencies in the EUT:

Magnetron : 2450 MHz
CPU : 4 MHz

EUT Modification

- - No modifications were conducted by JQA to achieve compliance to applied levels.
- - To achieve compliance to applied levels, the following change(s) were made by JQA during the compliance test.

— The modification(s) will be implemented in all production models of this equipment. —

Applicant : N/A Date : N/A

Typed Name : N/A Position : N/A

Responsible Party

— Responsible Party of Test Item(Product) —

Responsible party :

Contact Person :

Signatory

Deviation from Standard

- - No deviations from the standard described in page 3.
- - The following deviations were employed from the standard described in page 3.

TEST RESULTS

Supply Voltage : 208VAC 60Hz

RF Power Output

Measurement Results (Calorimetric method) 1986.6 W

Applied Limits of Radiated Emission 49.8 μ V/m at 300 m
10.0 μ V/m at 1600 m

Remarks: _____

ISM Frequency 2.4 GHz - 2.5 GHz

The requirements are ● - Passed ○ - Not Passed

Worst (lowest/highest) range 2430.8 MHz - 2474.2 MHz
 against 2.45 GHz \pm 50 MHz

Uncertainty of measurement results \pm 100 kHz

Remarks: _____

AC Powerline Conducted Emission 150 kHz - 30 MHz

The requirements are ● - Passed ○ - Not Passed

Min. limit margin 15.9 dB at 1.20 MHz

Max. limit exceeding _____ dB at _____ MHz

Uncertainty of measurement results + 2.1 dB(2 σ) - 2.1 dB(2 σ)

Remarks: _____

Magnetic Field Radiated Emission 9 kHz - 30 MHz

The requirements are		● - Passed	○ - Not Passed
Min. limit margin	More than	<u>31.6</u> dB	at <u>0.01</u> MHz
Max. limit exceeding		<u> </u> dB	at <u> </u> MHz
Uncertainty of measurement results		<u>+ 2.5</u> dB(2σ)	<u>- 2.5</u> dB(2σ)

Remarks: _____

Electromagnetic Field Radiated Emission 30 MHz - 1000 MHz

The requirements are		● - Passed	○ - Not Passed
Min. limit margin	More than	<u>38.9</u> dB	at <u>778.0</u> MHz
Max. limit exceeding		<u> </u> dB	at <u> </u> MHz
Uncertainty of measurement results		<u>+ 3.8</u> dB(2σ)	<u>- 3.9</u> dB(2σ)

Remarks: _____

Electromagnetic Field Radiated Emission 1 GHz - 26 GHz

The requirements are		● - Passed	○ - Not Passed
Min. limit margin		<u>2.6</u> dB	at <u>2397.0</u> MHz
Max. limit exceeding		<u> </u> dB	at <u> </u> MHz
Uncertainty of measurement results		<u>+ 3.2</u> dB(2σ)	<u>- 3.2</u> dB(2σ)

Remarks: The measured result is below the specification limit by a margin less than the measurement uncertainty; it is therefore not possible to state compliance based on the 95% level of confidence. However, the result indicates that compliance is more probable than non-compliance with the specification limit.

Supply Voltage : 230VAC 60Hz

RF Power Output

Measurement Results (Calorimetric method) 2089.5 W

Applied Limits of Radiated Emission 51.1 $\mu\text{V/m}$ at 300 m
10.0 $\mu\text{V/m}$ at 1600 m

Remarks: _____

ISM Frequency 2.4 GHz - 2.5 GHz

The requirements are ● - Passed ○ - Not Passed

Worst (lowest/highest) range 2431.0 MHz - 2473.1 MHz
 against 2.45 GHz \pm 50 MHz

Uncertainty of measurement results ± 100 kHz

Remarks: _____

AC Powerline Conducted Emission 150 kHz - 30 MHz

The requirements are ● - Passed ○ - Not Passed

Min. limit margin 16.8 dB at 0.15 MHz

Max. limit exceeding _____ dB at _____ MHz

Uncertainty of measurement results + 2.1 dB(2 σ) - 2.1 dB(2 σ)

Remarks: _____

Magnetic Field Radiated Emission 9 kHz - 30 MHz

The requirements are	● - Passed	○ - Not Passed
Min. limit margin	More than <u>31.8</u> dB at <u>0.01</u> MHz	
Max. limit exceeding	<u> </u> dB at <u> </u> MHz	
Uncertainty of measurement results	<u>+ 2.5</u> dB(2σ)	<u>- 2.5</u> dB(2σ)

Remarks: _____

Electromagnetic Field Radiated Emission 30 MHz - 1000 MHz

The requirements are	● - Passed	○ - Not Passed
Min. limit margin	More than <u>39.1</u> dB at <u>778.0</u> MHz	
Max. limit exceeding	<u> </u> dB at <u> </u> MHz	
Uncertainty of measurement results	<u>+ 3.8</u> dB(2σ)	<u>- 3.9</u> dB(2σ)

Remarks: _____

Electromagnetic Field Radiated Emission 1 GHz - 26 GHz

The requirements are	● - Passed	○ - Not Passed
Min. limit margin	<u>7.9</u> dB at <u>2397.0</u> MHz	
Max. limit exceeding	<u> </u> dB at <u> </u> MHz	
Uncertainty of measurement results	<u>+ 3.2</u> dB(2σ)	<u>- 3.2</u> dB(2σ)

Remarks: _____

SUMMARY

GENERAL REMARKS :

The EUT was tested according to the requirements of FCC Rules and Regulations Part 18 Subpart A, B and C (October 1, 2003) under the test configuration, as shown in page 18.

The conclusion for the test items of which are required by the applied regulation is indicated under the final judgement.

FINAL JUDGEMENT :

The "as received" sample;

- - fulfill the test requirements of the regulation mentioned on page 3.
- - fulfill the test requirements of the regulation mentioned on page 3, but with certain qualifications.
- - doesn't fulfill the test regulation mentioned on page 3.

Begin of testing : May 10, 2005

End of testing : May 22, 2005

- JAPAN QUALITY ASSURANCE ORGANIZATION -

Approved by :


Issued by :



Akio Hosoda
Manager
EMC Div.
JQA KITA-KANSAI Testing Center




Shigeru Kinoshita
Deputy Manager
EMC Div.
JQA KITA-KANSAI Testing Center

Test System-Arrangement (Drawings)


Test-setup(Drawings)**Conducted Disturbance 150 kHz - 30 MHz:**

The test was performed according to the description of FCC/OET MP-5 (1986) Sec.7.0 (Conducted Powerline Measurements).




Magnetic Field Radiated Emission 9 kHz - 30 MHz:

The test was performed according to the description of FCC/OET MP-5 (1986) Sec.5.0 (Radiated Emissions Measurements for Certified Equipment).




Electromagnetic Field Radiated Emission 30 MHz - 1000 MHz:

The test was performed according to the description of FCC/OET MP-5 (1986) Sec.5.0 (Radiated Emissions Measurements for Certified Equipment).



Electromagnetic Field Radiated Emission 1 GHz - 26 GHz:

The test was performed according to the description of FCC/OET MP-5 (1986) Sec.5.0 (Radiated Emissions Measurements for Certified Equipment).



Test-Setup (Photographs) at worst case

Conducted Emission 150kHz - 30MHz:



Front View



Side View

Radiated Emission :



Front View



Rear View

RF Power Output Measurement

ISM Frequency Device

Supply Voltage : 208VAC 60Hz

Test Date: May 10, 2005
 Temp.: 28 °C ; Humi.: 50 %

The power output was measured by the calorimetric method, computing the power output from the observed temperature rise of the load over a period of time.

Load (water) : 2500 ml
 Measurement time : 50.0 sec. (calculated by the rated RF power output)

No.	Water temperature [°C]		RF Power Output (※) [W]
	t ₁ (before test)	t ₂ (after test)	
1	11.10	20.43	1959.3
2	10.40	19.93	2001.3
3	9.20	18.80	2016.0
4	10.37	19.73	1967.7
5	10.37	19.83	1988.7
Average			1986.6

※) RF Power Output [W] = $4.2 \times 2500 \times (t_2 - t_1) / 50.0$

Results of RF power output : 1986.6 W

The limit of the radiated emission at 300 m : $25 \times \sqrt{1986.6/500} = 49.8 \text{ } [\mu\text{V/m}] = 34.0 \text{ } [\text{dB}(\mu\text{V/m})]$

The AC power input to the oven is measured to determine if the oven is operating in accordance with the manufacturer's specifications.

Rated AC power input : 3200 W
 Measured AC power input : AC 208 V, 14.52 A, 2896 W

Tester : Akio Hosoda

Supply Voltage : 230VAC 60Hz

Test Date: May 2, 2005
Temp.: 28 °C ; Humi.: 50 %

The power output was measured by the calorimetric method, computing the power output from the observed temperature rise of the load over a period of time.

Load (water) : 2500 ml
Measurement time : 50.0 sec. (calculated by the rated RF power output)

No.	Water temperature [°C]		RF Power Output (※) [W]
	t ₁ (before test)	t ₂ (after test)	
1	10.70	20.80	2121.0
2	9.37	19.45	2121.0
3	10.23	21.33	2079.0
4	10.73	20.77	2106.3
5	9.37	19.47	2121.0
Average			2089.5

※) RF Power Output [W] = $4.2 \times 2500 \times (t_2 - t_1) / 50.0$

Results of RF power output : 2089.5 W

The limit of the radiated emission at 300 m : $25 \times \sqrt{2089.5/500} = 51.1$ [μV/m] = 34.2 [dB(μV/m)]

The AC power input to the oven is measured to determine if the oven is operating in accordance with the manufacturer's specifications.

Rated AC power input : 3200 W
Measured AC power input : AC 230 V, 13.38 A, 2969 WTester : Akio Hosoda

ISM Frequency Measurement

ISM Frequency Device

Test Date: May 22, 2005
 Temp.: 24 °C ; Humi.: 68 %

The maximum frequency deviation was measured at -26dB with respect to the maximum level.

Supply Voltage : 208VAC 60Hz

Maximum Frequency Deviation [MHz]		Voltage Variation	Remarks
Lower Frequency	Upper Frequency		
2438.5	2468.8	166.4V (80 %)	A
2440.2	2474.2	208.0V (100 %)	A
2430.8	2471.8	260.0V (125 %)	A

Supply Voltage : 230VAC 60Hz

Maximum Frequency Deviation [MHz]		Voltage Variation	Remarks
Lower Frequency	Upper Frequency		
2447.7	2470.7	166.4V (80 %)	A
2431.0	2473.1	208.0V (100 %)	A
2437.9	2472.0	260.0V (125 %)	A

The results were within 2450 MHz \pm 50 MHz.

Remarks:

	Detector Function	RES. B.W.	V.B.W.	Sweep Time	Span
A	Peak	100 kHz	300 kHz	30 msec	100 MHz

Tester : Akio Hosoda

AC Powerline Conducted Emission Measurement

Test condition : 208V 60Hz

Test Date: May 20, 2005
 Temp.: 23 °C, Humi: 58 %

Frequency	Corr. Factor	Meter Readings [dB(μV)]				Limits		Results		Margin	Remarks
		VA		VB		[dB(μV)]		[dB(μV)]			
[MHz]	[dB]	QP	AVE	QP	AVE	QP	AVE	QP	AVE	[dB]	
0.15	0.2	47.0	23.0	47.0	23.0	66.0	56.0	47.2	23.2	+18.8	A/B
0.24	0.2	43.0	--	42.0	--	62.1	52.1	43.2	--	+18.9	A
0.50	0.1	38.0	--	38.0	--	56.0	46.0	38.1	--	+17.9	A
1.20	0.1	40.0	--	36.0	--	56.0	46.0	40.1	--	+15.9	A
2.23	0.2	35.0	--	30.0	--	56.0	46.0	35.2	--	+20.8	A
8.00	0.5	30.0	--	28.0	--	60.0	50.0	30.5	--	+29.5	A
14.90	0.7	35.0	--	36.0	--	60.0	50.0	36.7	--	+23.3	A
15.04	0.7	36.0	--	35.0	--	60.0	50.0	36.7	--	+23.3	A
20.00	0.8	21.0	--	22.0	--	60.0	50.0	22.8	--	+37.2	A
29.90	0.9	< 20.0	--	< 20.0	--	60.0	50.0	< 20.9	--	> +39.1	A

Sample of calculated result at 1.20 MHz, as the Minimum Margin point:

Corr. Factor = 0.1 dB
 +) Meter Reading = 40.0 dB(μV)
 Result = 40.1 dB(μV)

Minimum Margin: 56.0 - 40.1 = 15.9 (dB)

The point shown on “ ____ ” is the Minimum Margin Point.

Note: The correction factor includes the LISN insertion loss and the cable loss.

Remarks:

	Detector Function	IF Bandwidth
A	CISPR QP	9 kHz
B	Average	10 kHz

Tester : Akio Hosoda

AC Powerline Conducted Emission Measurement

Test condition : 230V 60Hz

Test Date: May 20, 2005
 Temp.: 23 °C, Humi: 58 %

Frequency [MHz]	Corr. Factor [dB]	Meter Readings [dB(μV)]				Limits [dB(μV)]		Results [dB(μV)]		Margin [dB]	Remarks
		VA		VB							
		QP	AVE	QP	AVE	QP	AVE	QP	AVE		
0.15	0.2	49.0	< 20.0	49.0	< 20.0	66.0	56.0	49.2	< 20.2	+16.8	A/B
0.24	0.2	42.0	--	42.0	--	62.1	52.1	42.2	--	+19.9	A
0.44	0.0	34.0	--	36.0	--	57.1	47.1	36.0	--	+21.1	A
0.50	0.1	35.0	--	35.0	--	56.0	46.0	35.1	--	+20.9	A
0.60	0.1	38.0	--	39.0	--	56.0	46.0	39.1	--	+16.9	A
1.00	0.1	35.0	--	35.0	--	56.0	46.0	35.1	--	+20.9	A
1.40	0.2	26.0	--	31.0	--	56.0	46.0	31.2	--	+24.8	A
2.34	0.2	37.0	--	35.0	--	56.0	46.0	37.2	--	+18.8	A
14.90	0.7	39.0	--	39.0	--	60.0	50.0	39.7	--	+20.3	A
15.30	0.7	38.0	--	38.0	--	60.0	50.0	38.7	--	+21.3	A

Sample of calculated result at 0.15 MHz, as the Minimum Margin point:

Corr. Factor	=	0.2 dB
+) Meter Reading	=	49.0 dB(μV)
Result	=	49.2 dB(μV)

Minimum Margin: 66.0 - 49.2 = 16.8 (dB)

The point shown on “ ____ ” is the Minimum Margin Point.

Note: The correction factor includes the LISN insertion loss and the cable loss.

Remarks:

	Detector Function	IF Bandwidth
A	CISPR QP	9 kHz
B	Average	10 kHz

Tester : Akio Hosoda

Electromagnetic Field Radiated Emission Measurement

Test condition : 208VAC 60Hz

Test Date: May 22, 2005
 Temp.: 24 °C, Humi: 68 %

Frequency [MHz]	Correction Factor [dB(1/m)]	Meter Readings at 3 m [dB(μV)]	Limits at 300 m [dB(μV/m)]	Results at 300 m [dB(μV/m)]	Margin [dB]	Remarks
0.01	6.4	< 36.0	34.0	< 2.4	> +31.6	A
0.02	2.6	< 30.0	34.0	< - 7.4	> +41.4	A
0.03	1.9	< 30.0	34.0	< - 8.1	> +42.1	A
0.05	0.6	< 30.0	34.0	< - 9.4	> +43.4	A
0.15	0.1	< 30.0	34.0	< - 9.9	> +43.9	B
0.20	0.1	< 30.0	34.0	< - 9.9	> +43.9	B
2.41	0.0	< 30.0	34.0	< -10.0	> +44.0	B
5.00	-0.2	< 30.0	34.0	< -10.2	> +44.2	B
22.00	0.8	< 30.0	34.0	< - 9.2	> +43.2	B
29.90	1.8	< 30.0	34.0	< - 8.2	> +42.2	B

Calculated result at 0.01 MHz, as the worst point shown on underline:

Corr. Factor	=	6.4 dB(1/m)
Conversion Factor	=	-40.0 dB (20dB/decade)
+) Meter Reading	=	<36.0 dB(μV)
Result	=	<2.4 dB(μV/m) at 300 m = <1.3 μV/m

Minimum Margin: 34.0 - <2.4 = >31.6 (dB)

NOTES

1. Test Distance : 3 m (Specified Distance : 300 m)
2. The spectrum was checked from 9 kHz to 30 MHz.
3. The correction factor includes the antenna factor and the cable loss.
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. Setting of measuring instrument(s) :

	Detector Function	IF Bandwidth
A	Average	200 Hz
B	Average	10 kHz

Tester : Akio Hosoda

Electromagnetic Field Radiated Emission Measurement

Test condition : 230VAC 60Hz

Test Date: May 22, 2005
 Temp.: 24 °C, Humi: 68 %

Frequency [MHz]	Correction Factor [dB(1/m)]	Meter Readings at 3 m [dB(μV)]	Limits at 300 m [dB(μV/m)]	Results at 300 m [dB(μV/m)]	Margin [dB]	Remarks
0.01	6.4	< 36.0	34.2	< 2.4	> +31.8	A
0.02	2.6	< 30.0	34.2	< - 7.4	> +41.6	A
0.03	1.9	< 30.0	34.2	< - 8.1	> +42.3	A
0.05	0.6	< 30.0	34.2	< - 9.4	> +43.6	A
0.15	0.1	< 30.0	34.2	< - 9.9	> +44.1	B
0.20	0.1	< 30.0	34.2	< - 9.9	> +44.1	B
2.41	0.0	< 30.0	34.2	< -10.0	> +44.2	B
5.00	-0.2	< 30.0	34.2	< -10.2	> +44.4	B
10.00	-0.3	< 30.0	34.2	< -10.3	> +44.5	B
13.30	-0.2	< 30.0	34.2	< -10.2	> +44.4	B

Calculated result at 0.01 MHz, as the worst point shown on underline:

Corr. Factor	=	6.4 dB(1/m)
Conversion Factor	=	-40.0 dB (20dB/decade)
+) Meter Reading	=	<36.0 dB(μV)
Result	=	<2.4 dB(μV/m) at 300 m = <1.3 μV/m

Minimum Margin: 34.2 - <2.4 = >31.8 (dB)

NOTES

1. Test Distance : 3 m (Specified Distance : 300 m)
2. The spectrum was checked from 9 kHz to 30 MHz.
3. The correction factor includes the antenna factor and the cable loss.
4. The symbol of "<" means "or less".
5. The symbol of ">" means "more than".
6. Setting of measuring instrument(s) :

	Detector Function	IF Bandwidth
A	Average	200 Hz
B	Average	10 kHz

Tester : Akio Hosoda

Electromagnetic Field Radiated Emission Measurement

Test condition : 208VAC 60Hz

Test Date: May 16, 2005
 Temp.: 17 °C, Humi: 43 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Cable Loss [dB]	Meter Readings at 10 m [dB(μV)]		Limits at 300 m [dB(μV/m)]	Results at 300 m [dB(μV/m)]		Margin [dB]	Remarks
			Hori.	Vert.		Hori.	Vert.		
40.0	15.9	0.7	< 0.0	< 0.0	34.0	< -12.9	< -12.9	> +46.9	B
42.3	15.1	0.8	< 0.0	< 0.0	34.0	< -13.6	< -13.6	> +47.6	B
57.5	10.2	0.9	< 0.0	< 0.0	34.0	< -18.4	< -18.4	> +52.4	B
111.0	11.1	1.3	< 0.0	< 0.0	34.0	< -17.1	< -17.1	> +51.1	B
296.0	17.5	2.2	< 0.0	< 0.0	34.0	< - 9.8	< - 9.8	> +43.8	B
321.7	14.5	2.3	< 0.0	< 0.0	34.0	< -12.7	< -12.7	> +46.7	B
625.0	19.3	3.4	< 0.0	< 0.0	34.0	< - 6.8	< - 6.8	> +40.8	B
676.0	20.0	3.6	< 0.0	< 0.0	34.0	< - 5.9	< - 5.9	> +39.9	B
723.0	20.4	3.7	< 0.0	< 0.0	34.0	< - 5.4	< - 5.4	> +39.4	B
778.0	20.8	3.8	< 0.0	< 0.0	34.0	< - 4.9	< - 4.9	> +38.9	B

Calculated result at 778.0 MHz, as the worst point shown on underline:

Antenna Factor	=	20.8 dB(1/m)
Cable Loss	=	3.8 dB
Conversion Factor	=	-29.5 dB (20dB/decade)
+) Meter Reading	=	<0.0 dB(μV)
Result	=	<-4.9 dB(μV/m) at 300 m = <0.6 μV/m

Minimum Margin: 34.0 - (<-4.9) = >38.9 (dB)

NOTES

1. Test Distance : 10 m (Specified Distance : 300 m)
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. Setting of measuring instrument(s) :

	Detector Function	IF Bandwidth	Antenna
A	CISPR QP	120 kHz	Broadband
B	Average	120 kHz	
C	CISPR QP	120 kHz	Tuned Dipole
D	Average	120 kHz	

Tester : Akio Hosoda

Electromagnetic Field Radiated Emission Measurement

Test condition : 230VAC 60Hz

Test Date: May 16, 2005
 Temp.: 17 °C, Humi: 43 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Cable Loss [dB]	Meter Readings at 10 m [dB(μV)]		Limits at 300 m [dB(μV/m)]	Results at 300 m [dB(μV/m)]		Margin [dB]	Remarks
			Hori.	Vert.		Hori.	Vert.		
40.0	15.9	0.7	< 0.0	< 0.0	34.2	< -12.9	< -12.9	> +47.1	B
42.3	15.1	0.8	< 0.0	< 0.0	34.2	< -13.6	< -13.6	> +47.8	B
57.5	10.2	0.9	< 0.0	< 0.0	34.2	< -18.4	< -18.4	> +52.6	B
111.0	11.1	1.3	< 0.0	< 0.0	34.2	< -17.1	< -17.1	> +51.3	B
296.0	17.5	2.2	< 0.0	< 0.0	34.2	< - 9.8	< - 9.8	> +44.0	B
321.7	14.5	2.3	< 0.0	< 0.0	34.2	< -12.7	< -12.7	> +46.9	B
625.0	19.3	3.4	< 0.0	< 0.0	34.2	< - 6.8	< - 6.8	> +41.0	B
676.0	20.0	3.6	< 0.0	< 0.0	34.2	< - 5.9	< - 5.9	> +40.1	B
723.0	20.4	3.7	< 0.0	< 0.0	34.2	< - 5.4	< - 5.4	> +39.6	B
778.0	20.8	3.8	< 0.0	< 0.0	34.2	< - 4.9	< - 4.9	> +39.1	B

Calculated result at 778.0 MHz, as the worst point shown on underline:

Antenna Factor = 20.8 dB(1/m)
 Cable Loss = 3.8 dB
 Conversion Factor = -29.5 dB (20dB/decade)
 +) Meter Reading = <0.0 dB(μV)
 Result = <-4.9 dB(μV/m) at 300 m = <0.6 μV/m

Minimum Margin: 34.2 - (<-4.9) = >39.1 (dB)

NOTES

1. Test Distance : 10 m (Specified Distance : 300 m)
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The symbol of "<" means "or less".
4. The symbol of ">" means "more than".
5. Setting of measuring instrument(s) :

	Detector Function	IF Bandwidth	Antenna
A	CISPR QP	120 kHz	Broadband
B	Average	120 kHz	
C	CISPR QP	120 kHz	Tuned Dipole
D	Average	120 kHz	

Tester : Akio Hosoda

Electromagnetic Field Radiated Emission Measurement

Test condition : 208VAC 60Hz

Test Date: May 22, 2005
 Temp.: 24 °C, Humi: 68 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings at 3 m [dB(μV)]		Limits at 300 m [dB(μV/m)]	Results at 300 m [dB(μV/m)]		Margin [dB]	Remarks
			Hori.	Vert.		Hori.	Vert.		
2397.0	21.5	10.8	35.0	39.0	34.0	27.3	31.3	+ 2.6	B
2503.0	21.2	10.8	< 25.0	< 25.0	34.0	< 17.0	< 17.0	> +16.9	B
6905.0	36.6	-19.8	< 35.0	38.0	34.0	< 11.8	14.8	+19.2	B
8359.0	40.8	-27.2	37.5	44.0	34.0	11.1	17.6	+16.4	B
10087.0	39.2	-26.8	41.0	45.0	34.0	13.4	17.4	+16.6	B
14758.8	45.4	-26.1	39.0	40.0	34.0	18.3	19.3	+14.7	B
17195.0	43.5	-26.5	34.0	38.0	34.0	11.0	15.0	+19.0	B
19702.0	40.3	-30.8	< 35.0	37.0	34.0	< 4.5	6.5	+27.5	B
22138.0	40.3	-30.8	< 35.0	36.0	34.0	< 4.5	5.5	+28.5	B
24580.0	40.4	-28.8	39.0	43.0	34.0	10.6	14.6	+19.4	B

Calculated result at 2397.0 MHz, as the worst point shown on underline:

Antenna Factor	=	21.5	dB(1/m)
Corr. Factor	=	10.8	dB
Conversion Factor	=	-40.0	dB (20dB/decade)
+) Meter Reading	=	39.0	dB(μV)
Result	=	31.3	dB(μV/m) at 300 m = 36.8 μV/m

Minimum Margin: 34.0 - 31.3 = 2.6 (dB)

NOTES

- Test Distance : 3 m (Specified Distance : 300 m)
- The spectrum was checked from 1.0 GHz to 24.5 GHz.
- The correction factor is shown as follows:
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. [dB] (1.0 - 3.6GHz)
 - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (3.6 - 7.6GHz)
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (18.0 - 26.0GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- Setting of measuring instrument(s) :

	Detector Function	IF Bandwidth
A	Peak	1 MHz
B	Average	1 MHz

Tester : Akio Hosoda

Electromagnetic Field Radiated Emission Measurement

Test condition : 230VAC 60Hz

Test Date: May 22, 2005
 Temp.: 24 °C, Humi: 68 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings at 3 m [dB(μV)]		Limits at 300 m [dB(μV/m)]	Results at 300 m [dB(μV/m)]		Margin [dB]	Remarks
			Hori.	Vert.		Hori.	Vert.		
2397.0	21.5	10.8	34.0	32.0	34.2	26.3	24.3	+ 7.9	B
2503.0	21.2	10.8	< 25.0	< 25.0	34.2	< 17.0	< 17.0	> +17.1	B
7087.6	36.7	-19.7	37.0	38.0	34.2	14.0	15.0	+19.2	B
7313.2	37.1	-19.5	35.0	38.0	34.2	12.6	15.6	+18.6	B
8344.5	40.8	-27.2	34.0	44.0	34.2	7.6	17.6	+16.6	B
14730.8	45.5	-26.1	36.0	42.0	34.2	15.4	21.4	+12.8	B
17191.0	43.5	-26.5	37.0	37.0	34.2	14.0	14.0	+20.2	B
19624.7	40.3	-30.8	35.0	34.0	34.2	4.5	3.5	+29.7	B
22155.6	40.3	-30.8	< 34.0	35.0	34.2	< 3.5	4.5	+29.7	B
24578.0	40.4	-28.8	36.0	37.0	34.2	7.6	8.6	+25.6	B

Calculated result at 2397.0 MHz, as the worst point shown on underline:

Antenna Factor	=	21.5 dB(1/m)
Corr. Factor	=	10.8 dB
Conversion Factor	=	-40.0 dB (20dB/decade)
+) Meter Reading	=	34.0 dB(μV)
Result	=	26.3 dB(μV/m) at 300 m = 20.7 μV/m

Minimum Margin: 34.2 - 26.3 = 7.9 (dB)

NOTES

- Test Distance : 3 m (Specified Distance : 300 m)
- The spectrum was checked from 1.0 GHz to 24.5 GHz.
- The correction factor is shown as follows:
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. [dB] (1.0 - 3.6GHz)
 - Corr. Factor [dB] = Cable Loss + 20dB Pad Att. - Pre-Amp. Gain [dB] (3.6 - 7.6GHz)
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (7.6 - 18.0GHz)
 - Corr. Factor [dB] = Cable Loss + 10dB Pad Att. - Pre-Amp. Gain [dB] (18.0 - 26.0GHz)
- The symbol of "<" means "or less".
- The symbol of ">" means "more than".
- Setting of measuring instrument(s) :

	Detector Function	IF Bandwidth
A	Peak	1 MHz
B	Average	1 MHz

Tester : Akio Hosoda