



RF TEST REPORT

Applicant	Smawave Technology Co. ,Ltd
FCC ID	2AU8HSPH320-A
Product	smart phone
Brand	Smawave
Model	SPH320-a
Report No.	R2005A0340-R7V1
Issue Date	January 11, 2022

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 15E (2019)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	5
1.1. Notes of the test report.....	5
1.2. Test facility	5
1.3. Testing Location.....	5
2. General Description of Equipment under Test.....	6
2.1. Applicant and Manufacturer Information.....	6
2.2. General information.....	6
3. Applied Standards	7
4. Test Configuration	8
5. Test Case Results	9
5.1. Occupied Bandwidth	9
5.2. Average Power Output.....	19
5.3. Frequency Stability.....	23
5.4. Power Spectral Density	26
5.5. Unwanted Emission	34
5.6. Conducted Emission	75
6. Main Test Instruments	78
ANNEX A: The EUT Appearance	79
ANNEX B: Test Setup Photos	79



Version	Revision description	Issue Date
Rev.0	Initial issue of report.	November 19, 2020
Rev.1	Delete U-NII-2A&U-NII-2C.	January 11, 2022
Note: This revised report (Report No. R2005A0340-R7V1) supersedes and replaces the previously issued report (Report No. R2005A0340-R7). Please discard or destroy the previously issued report and dispose of it accordingly.		

Summary of measurement results

Number	Test Case	Clause in FCC rules	Verdict
1	Average output power	15.407(a)	PASS
2	Occupied bandwidth	15.407(e)	PASS
3	Frequency stability	15.407(g)	PASS
4	Power spectral density	15.407(a)	PASS
5	Unwanted Emissions	15.407(b)	PASS
6	Conducted Emissions	15.207	PASS
Date of Testing: June 13, 2020~ August 10, 2020			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			



1. Test Laboratory

1.1. Notes of the test report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.1. Applicant and Manufacturer Information

Applicant	Smawave Technology Co. ,Ltd
Applicant address	3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China
Manufacturer	Smawave Technology Co. ,Ltd
Manufacturer address	3/F, Building 8, 1001 North Qinzhou Road, Xuhui District, Shanghai, China

2.2. General information

EUT Description	
Model	SPH320-a
IMEI	IMEI 1:869922040046018 IMEI 2:869922040056017
Hardware Version	V2.2
Software Version	SMAWAVE-SPH320-a
Power Supply	Battery/AC adapter
Antenna Type	PIFA Antenna
Antenna Gain	1.5dBi
Test Mode(s)	U-NII-1(5150MHz-5250MHz) U-NII-3(5725MHz-5850MHz)
Modulation Type	802.11a/n (HT20/HT40) : OFDM 802.11ac (VHT20/VHT40): OFDM
Max. Conducted Power	14.69 dBm
Operating Frequency Range(s)	U-NII-1: 5150MHz-5250MHz U-NII-3: 5725MHz -5850MHz
Operating temperature range:	-20 ° C to 55° C
Operating voltage range:	3.6 V to 4.35 V
State DC voltage:	3.8V
EUT Accessory	
Battery	Manufacturer: Guangdong fenghua New Energy Co.,Ltd Model: A106
Adapter	Manufacturer: Shenzhen Aquilstar Technology Co., LTD Model: ASSA107W-050200
Note:1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.	



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR47 Part 15E (2019) Unlicensed National Information Infrastructure Devices

ANSI C63.10 (2013)

Reference standard:

KDB 789033 D02 General UNII Test Procedures New Rules v02r01

4. Test Configuration

Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The radiated emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (X axis) and the worst case was recorded.

In order to find the worst case condition, Pre-tests are needed at the presence of different data rate. Preliminary tests have been done on all the configuration for confirming worst case. Data rate below means worst-case rate of each test item.

Worst-case data rates are shown as following table.

Test Mode	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0
802.11ac VHT20	MCS0
802.11ac VHT40	MCS0

Wireless Technology and Frequency Range

Wireless Technology		Bandwidth	Channel	Frequency
Wi-Fi	U-NII-1	20 MHz	36	5180MHz
			40	5200MHz
			44	5220MHz
			48	5240MHz
		40 MHz	38	5190MHz
			46	5230MHz
	U-NII-3	20 MHz	149	5745MHz
			153	5765MHz
			157	5785MHz
			161	5805MHz
			165	5825MHz
		40 MHz	151	5755MHz
159	5795MHz			
Does this device support TPC Function? ☐ Yes ☒ No				
Does this device support TDWR Band? ☒ Yes ☐ No				

5. Test Case Results

5.1. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable.


For U-NII-1, set RBW $\approx 1\%$ OCB kHz, VBW $\geq 3 \times$ RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 26 dB relative to the maximum level measured in the fundamental emission.

For U-NII-3, Set RBW = 100 kHz, VBW $\geq 3 \times$ RBW, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

Use the 99 % power bandwidth function of the instrument

Test Setup



Limits

Rule FCC Part §15.407(e)

Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 936$ Hz.

Test Results:
U-NII-1


Test Mode	Carrier frequency (MHz)	99% bandwidth (MHz)	Minimum 26 dB bandwidth (MHz)	Conclusion
802.11a	5180	17.240	29.82	PASS
	5200	17.576	29.97	PASS
	5240	17.035	28.99	PASS
802.11n HT20	5180	17.955	29.95	PASS
	5200	18.036	29.80	PASS
	5240	17.884	29.67	PASS
802.11n HT40	5190	36.397	59.93	PASS
	5230	36.278	59.70	PASS
802.11ac VHT20	5180	17.983	29.72	PASS
	5200	18.030	29.76	PASS
	5240	18.022	29.74	PASS
802.11ac VHT40	5190	36.266	59.10	PASS
	5230	36.104	58.09	PASS

U-NII-3


Test Mode	Carrier frequency (MHz)	99% bandwidth (MHz)	Minimum 6 dB bandwidth (MHz)	Limit (kHz)	Conclusion
802.11a	5745	17.072	17.150	500	PASS
	5785	17.505	17.448	500	PASS
	5825	18.328	18.480	500	PASS
802.11n HT20	5745	18.041	17.846	500	PASS
	5785	18.320	17.995	500	PASS
	5825	18.818	18.930	500	PASS
802.11n HT40	5755	36.583	36.586	500	PASS
	5795	37.227	36.995	500	PASS
802.11ac VHT20	5745	18.088	17.820	500	PASS
	5785	18.511	18.525	500	PASS
	5825	18.020	18.323	500	PASS
802.11ac VHT40	5755	36.724	36.338	500	PASS
	5795	37.092	36.908	500	PASS




U-NII-1, 802.11a
Carrier frequency (MHz): 5180




U-NII-1, 802.11n HT20
Carrier frequency (MHz): 5180




U-NII-1, 802.11a
Carrier frequency (MHz): 5200




U-NII-1, 802.11n HT20
Carrier frequency (MHz): 5200



U-NII-1, 802.11a
Carrier frequency (MHz): 5240




U-NII-1, 802.11n HT20
Carrier frequency (MHz): 5240







U-NII-1, 802.11n HT40
Carrier frequency (MHz): 5190




U-NII-1, 802.11ac VHT20
Carrier frequency (MHz): 5180




U-NII-1, 802.11n HT40
Carrier frequency (MHz): 5230




U-NII-1, 802.11ac VHT20
Carrier frequency (MHz): 5200




U-NII-1, 802.11ac VHT40
Carrier frequency (MHz): 5190



U-NII-1, 802.11ac VHT20
Carrier frequency (MHz): 5240









U-NII-1, 802.11ac VHT40 Carrier frequency (MHz): 5230






99% bandwidth


U-NII-3, 802.11a
Carrier frequency (MHz): 5745U-NII-3, 802.11n HT20
Carrier frequency (MHz): 5745U-NII-3, 802.11a
Carrier frequency (MHz): 5785U-NII-3, 802.11n HT20
Carrier frequency (MHz): 5785U-NII-3, 802.11a
Carrier frequency (MHz): 5825U-NII-3, 802.11n HT20
Carrier frequency (MHz): 5825




U-NII-3, 802.11n HT40
Carrier frequency (MHz): 5755




U-NII-3, 802.11ac VHT20
Carrier frequency (MHz): 5745




U-NII-3, 802.11n HT40
Carrier frequency (MHz): 5795




U-NII-3, 802.11ac VHT20
Carrier frequency (MHz): 5785



U-NII-3, 802.11ac VHT40
Carrier frequency (MHz): 5755




U-NII-3, 802.11ac VHT20
Carrier frequency (MHz): 5825






U-NII-3, 802.11ac VHT40
Carrier frequency (MHz): 5795




Minimum 6 dB bandwidth


U-NII-3, 802.11a
Carrier frequency (MHz): 5745




U-NII-3, 802.11n HT20
Carrier frequency (MHz): 5745



U-NII-3, 802.11a
Carrier frequency (MHz): 5785




U-NII-3, 802.11n HT20
Carrier frequency (MHz): 5785







U-NII-3, 802.11a
Carrier frequency (MHz): 5825




U-NII-3, 802.11n HT20
Carrier frequency (MHz): 5825




U-NII-3, 802.11n HT40
Carrier frequency (MHz): 5755




U-NII-3, 802.11ac VHT20
Carrier frequency (MHz): 5745




U-NII-3, 802.11n HT40
Carrier frequency (MHz): 5795




U-NII-3, 802.11ac VHT20
Carrier frequency (MHz): 5785




U-NII-3, 802.11ac VHT40
Carrier frequency (MHz): 5755



U-NII-3, 802.11ac VHT20
Carrier frequency (MHz): 5825



U-NII-3, 802.11ac VHT40
Carrier frequency (MHz): 5795



5.2. Average Power Output


Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to the average power meter through an external attenuator and a known loss cable. The EUT is max power transmission with proper modulation. We use Maximum average Conducted Output Power Level Method in KDB789033 for this test

Test Setup



Limits

Rule FCC Part 15.407(a)(1)(2)(3)

(1) For the band 5.15-5.25 GHz.

(i) For an outdoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi. The maximum e.i.r.p. at any elevation angle above 30 degrees as measured from the horizon must not exceed 125 mW (21 dBm).

(ii) For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(iii) For fixed point-to-point access points operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. Fixed point-to-point U-NII devices may employ antennas with directional gain up to 23 dBi without any corresponding reduction in the maximum conducted output power or maximum power spectral density. For fixed point-to-point transmitters that employ a directional antenna gain greater than 23 dBi, a 1 dB reduction in maximum conducted output power and maximum power spectral density is

required for each 1 dB of antenna gain in excess of 23 dBi. Fixed, point-to-point operations exclude the use of point-to-multipoint systems, omnidirectional applications, and multiple collocated transmitters transmitting the same information. The operator of the U-NII device, or if the equipment is professionally installed, the installer, is responsible for ensuring that systems employing high gain directional antennas are used exclusively for fixed, point-to-point operations.

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(2) For the band 5.725-5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W. In addition, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.44$ dB.

Test Results

Test Mode	T _{on} (ms)	T _(on+off) (ms)	Duty cycle	Duty cycle correction Factor(dB)
802.11a	1.39	1.43	0.97	0.11
802.11n HT20	1.30	1.34	0.97	0.12
802.11n HT40	0.65	0.68	0.95	0.23
802.11ac VHT20	1.30	1.34	0.97	0.12
802.11ac VHT40	0.65	0.68	0.95	0.21
Note: when Duty cycle ≥ 0.98 , Duty cycle correction Factor not required.				

Single Antenna Power Index						
Test Mode	CH36	CH40	CH48	CH149	CH157	CH165
802.11a	19	19	19	19	18	17
802.11n HT20	19	19	19	19	18	18
802.11ac VHT20	19	19	19	19	18	17
Test Mode	CH38	CH46	CH142	CH151	CH159	/
802.11n HT40	18	18	19	18	18	/
802.11ac VHT40	17	17	19	18	18	/



Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor.

U-NII-1

Test Mode	Channel/ Frequency (MHz)	Average Power Measured (dBm)	Average Power with duty factor (dBm)	Limit (dBm)	Conclusion
802.11a	36/5180	12.44	12.55	24	PASS
	40/5200	12.49	12.60	24	PASS
	48/5240	13.92	14.03	24	PASS
802.11n HT20	36/5180	12.14	12.26	24	PASS
	40/5200	12.57	12.69	24	PASS
	48/5240	13.96	14.08	24	PASS
802.11n HT40	38/5190	11.74	11.97	24	PASS
	46/5230	13.72	13.95	24	PASS
802.11ac VHT20	36/5180	12.11	12.23	24	PASS
	40/5200	12.08	12.20	24	PASS
	48/5240	14.57	14.69	24	PASS
802.11ac VHT40	38/5190	10.96	11.17	24	PASS
	46/5230	12.44	12.65	24	PASS

Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor

U-NII-3

Test Mode	Channel/ Frequency (MHz)	Average Power Measured (dBm)	Average Power with duty factor (dBm)	Limit (dBm)	Conclusion
802.11a	149/5745	12.44	12.55	30	PASS
	157/5785	12.54	12.65	30	PASS
	165/5825	11.18	11.29	30	PASS
802.11n HT20	149/5745	12.95	13.07	30	PASS
	157/5785	12.74	12.86	30	PASS
	165/5825	12.10	12.22	30	PASS
802.11n HT40	151/5755	11.91	12.14	30	PASS
	159/5795	12.92	13.15	30	PASS
802.11ac VHT20	149/5745	13.02	13.14	30	PASS
	157/5785	12.68	12.80	30	PASS
	165/5825	11.53	11.65	30	PASS
802.11ac VHT40	151/5755	12.46	12.67	30	PASS
	159/5795	13.02	13.23	30	PASS

Note: Average Power with duty factor = Average Power Measured +Duty cycle correction factor

5.3. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. Frequency stability with respect to ambient temperature

- Supply the EUT with a nominal ac voltage or install a new or fully charged battery in the EUT. If possible, a dummy load shall be connected to the EUT because an antenna near the metallic walls of an environmental test chamber could affect the output frequency of the EUT. If the EUT is equipped with a permanently attached, adjustable-length antenna, then the EUT shall be placed in the center of the chamber with the antenna adjusted to the shortest length possible. Turn ON the EUT and tune it to one of the number of frequencies shown in 5.6.
- Couple the unlicensed wireless device output to the measuring instrument by connecting an antenna to the measuring instrument with a suitable length of coaxial cable and placing the measuring antenna near the EUT (e.g., 15 cm away), or by connecting a dummy load to the measuring instrument, through an attenuator if necessary.
- Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
- Turn the EUT OFF and place it inside the environmental temperature chamber. For devices that have oscillator heaters, energize only the heater circuit.
- Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
- While maintaining a constant temperature inside the environmental chamber, turn the EUT ON and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized. Four measurements in total are made.
- Measure the frequency at each of frequencies specified in 5.6.
- Switch OFF the EUT but do not switch OFF the oscillator heater.
- Lower the chamber temperature by not more than 10°C, and allow the temperature inside the chamber to stabilize.
- Repeat step f) through step i) down to the lowest specified temperature.

2. Frequency stability when varying supply voltage

Unless otherwise specified, these tests shall be made at ambient room temperature (+15°C to +25 °C). An antenna shall be connected to the antenna output terminals of the EUT if possible. If the EUT is equipped with or uses an adjustable-length antenna, then it shall be fully extended.

- Supply the EUT with nominal voltage or install a new or fully charged battery in the EUT. Turn ON the EUT and couple its output to a frequency counter or other frequency-measuring instrument.



- b) Tune the EUT to one of the number of frequencies required in 5.6. Adjust the location of the measurement antenna and the controls on the measurement instrument to obtain a suitable signal level (i.e., a level that will not overload the measurement instrument but is strong enough to allow measurement of the operating or fundamental frequency of the EUT).
- c) Measure the frequency at each of the frequencies specified in 5.6.
- d) Repeat the above procedure at 85% and 115% of the nominal supply voltage.

Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the users manual.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 936\text{Hz}$

**Test Results**

Voltage (V)	Temperature (°C)	U-NII-1 Test Results			
		5200MHz			
		1min	2min	5min	10min
3.8	-20	5200.002291	5199.991110	5199.986876	5199.991059
3.8	-10	5200.001201	5199.988643	5199.977581	5199.990491
3.8	0	5199.992963	5199.979063	5199.972389	5199.983326
3.8	10	5199.988503	5199.969427	5199.963188	5199.976906
3.8	25	5199.986769	5199.963818	5199.956310	5199.969131
3.8	35	5199.977073	5199.960605	5199.953381	5199.966374
3.8	45	5199.967718	5199.956880	5199.952070	5199.965980
3.8	55	5199.965647	5199.952069	5199.947718	5199.957063
3.6	25	5199.959728	5199.944203	5199.938428	5199.953270
4.35	25	5200.002291	5199.991110	5199.986876	5199.991059
MHz		-0.040272	-0.055797	-0.061572	-0.046730
PPM		-7.744682	-10.730246	-11.840719	-8.986531

Voltage (V)	Temperature (°C)	U-NII-3 Test Results			
		5785MHz			
		1min	2min	5min	10min
3.8	-20	5785.001590	5784.994410	5784.990104	5784.986199
3.8	-10	5785.001106	5784.993794	5784.987209	5784.984143
3.8	0	5784.991945	5784.985096	5784.985472	5784.975652
3.8	10	5784.987444	5784.982323	5784.980382	5784.971502
3.8	25	5784.985650	5784.977214	5784.974928	5784.964193
3.8	35	5784.981652	5784.977035	5784.973704	5784.963129
3.8	45	5784.980667	5784.968726	5784.966323	5784.954723
3.8	55	5784.971867	5784.964255	5784.963451	5784.945384
3.6	25	5784.967552	5784.957620	5784.958521	5784.944734
4.35	25	5784.958016	5784.957419	5784.954469	5784.939835
MHz		-0.041984	-0.042581	-0.045531	-0.060165
PPM		-7.257461	-7.360672	-7.870567	-10.400119

5.4. Power Spectral Density

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement


The EUT was connected to the spectrum analyzer through an external attenuator (20dB) and a known loss cable.

Set RBW = 1MHz, VBW =3MHz for the band 5.150-5.250GHz.

Set RBW = 510kHz, VBW =1.5MHz for the band 5.725-5.850GHz

The conducted PSD is measured at each antenna port. The measured results at the various antenna ports are then summed mathematically.

Test setup



Limits

Rule FCC Part 15.407(a)(1)/ Part 15.407(a)(2) / Part 15.407(a)(3)

(iv) For client devices in the 5.15-5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For the band 5.725-5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500kHz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Frequency Bands/MHz	Limits
5150-5250	11dBm/MHz
5725-5850	30dBm/500kHz

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.75\text{dB}$.

**Test Results:**

Note: Power Spectral Density =Read Value+Duty cycle correction factor

U-NII-1


Test Mode	Channel Number	Read Value (dBm /MHz)	Power Spectral Density (dBm /MHz)	Limit (dBm /MHz)	Conclusion
802.11a	36	2.40	2.51	11	PASS
	40	2.27	2.38	11	PASS
	48	4.56	4.67	11	PASS
802.11n HT20	36	1.51	1.62	11	PASS
	40	1.98	2.10	11	PASS
	48	3.61	3.73	11	PASS
802.11n HT40	38	-1.45	-1.21	11	PASS
	46	0.44	0.68	11	PASS
802.11ac VHT20	36	1.82	1.94	11	PASS
	40	1.56	1.67	11	PASS
	48	3.78	3.90	11	PASS
802.11ac VHT40	38	-3.28	-3.07	11	PASS
	46	-1.31	-1.10	11	PASS

U-NII-3


Test Mode	Channel Number	Read Value (dBm/500kHz)	Power Spectral Density (dBm/500kHz)	Limit (dBm/500kHz)	Conclusion
802.11a	149	-0.71	-0.59	30	PASS
	157	-0.53	-0.42	30	PASS
	165	-0.75	-0.64	30	PASS
802.11n HT20	149	-0.79	-0.67	30	PASS
	157	-0.65	-0.53	30	PASS
	165	-0.95	-0.83	30	PASS
802.11n HT40	151	-4.71	-4.47	30	PASS
	159	-3.77	-3.53	30	PASS
802.11ac VHT20	149	-0.57	-0.45	30	PASS
	157	-0.68	-0.56	30	PASS
	165	-1.71	-1.59	30	PASS
802.11ac VHT40	151	-4.65	-4.44	30	PASS
	159	-3.95	-3.74	30	PASS




U-NII-1, 802.11a, Channel No.: 36




U-NII-1, 802.11n HT20, Channel No.: 36




U-NII-1, 802.11a, Channel No.: 40




U-NII-1, 802.11n HT20, Channel No.: 40



U-NII-1, 802.11a, Channel No.: 48




U-NII-1, 802.11n HT20, Channel No.: 48







U-NII-1, 802.11n HT40, Channel No.: 38




U-NII-1, 802.11ac VHT20, Channel No.: 36




U-NII-1, 802.11n HT40, Channel No.: 46




U-NII-1, 802.11ac VHT20, Channel No.: 40



U-NII-1, 802.11ac VHT40, Channel No.: 38




U-NII-1, 802.11ac VHT20, Channel No.: 48






U-NII-1, 802.11ac VHT40, Channel No.: 46







U-NII-3, 802.11a, Channel No.: 149




U-NII-3, 802.11n HT20, Channel No.: 149




U-NII-3, 802.11a, Channel No.: 157




U-NII-3, 802.11n HT20, Channel No.: 157



U-NII-3, 802.11a, Channel No.: 165




U-NII-3, 802.11n HT20, Channel No.: 165







U-NII-3, 802.11n HT40, Channel No.: 151




U-NII-3, 802.11ac VHT20, Channel No.: 149




U-NII-3, 802.11n HT40, Channel No.: 159




U-NII-3, 802.11ac VHT20, Channel No.: 157



U-NII-3, 802.11ac VHT40, Channel No.: 151




U-NII-3, 802.11ac VHT20, Channel No.: 165





U-NII-3, 802.11ac VHT40, Channel No.: 159



5.5. Unwanted Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The test set-up was made in accordance to the general provisions of ANSI C63.10-2013. The Equipment Under Test (EUT) was set up on a non-conductive table in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna. The radiated emissions measurements were made in a typical installation configuration. Sweep the whole frequency band range from 9kHz to the 10th harmonic of the carrier, and the emissions less than 20 dB below the permissible value are reported.

During the test, the height of receive antenna shall be moved from 1 to 4 meters, and the antenna shall be performed under horizontal and vertical polarization. The turntable shall be rotated from 0 to 360 degrees for detecting the maximum of radiated spurious signal level. The measurements shall be repeated with orthogonal polarization of the test antenna. The data of cable loss and antenna factor has been calibrated in full testing frequency range before the testing.

Set the spectrum analyzer in the following:

9kHz~150 kHz

RBW=200Hz, VBW=1kHz/ Sweep=AUTO

150 kHz~30MHz

RBW=9KHz, VBW=30KHz,/ Sweep=AUTO

Below 1GHz

RBW=100kHz / VBW=300kHz / Sweep=AUTO

a) Peak emission levels are measured by setting the instrument as follows:

Above 1GHz

PEAK: RBW=1MHz VBW=3MHz/ Sweep=AUTO

b) Average emission levels are measured by setting the instrument as follows:

Above 1GHz

AVERAGE: RBW=1MHz / VBW=3MHz / Sweep=AUTO

c) Detector: The measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific



emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:


- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is $[10 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is $[20 \log (1 / D)]$, where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

Reduce the video bandwidth until no significant variations in the displayed signal are observed in subsequent traces, provided the video bandwidth is no less than 1 Hz. For regulatory requirements that specify averaging only over the transmit duration (e.g., digital transmission system [DTS] and Unlicensed National Information Infrastructure [U-NII]), the video bandwidth shall be greater than $[1 / (\text{minimum transmitter on time})]$ and no less than 1 Hz.


The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in stand-up position (Z axis) and the loop antenna is vertical, others antenna are vertical and horizontal.

The test is in transmitting mode.


9KHz~~~30MHz



30MHz~~~ 1GHz



Above 1GHz



Note: Area side:2.4mX3.6m



Limits

- (1) For transmitters operating in the 5725-5850 MHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
- (2) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz(68.2dBμV/m).
- (3) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz(68.2dBμV/m).
- (4) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz(68.2dBμV/m).

Note: the following formula is used to convert the EIRP to field strength

§1、 $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{meters}]) + 104.77$, where E = field strength and

d = distance at which field strength limit is specified in the rules;

§2、 $E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] + 95.2$, for d = 3 meters

- (5) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table.

Frequency of emission (MHz)	Field strength(uV/m)	Field strength(dBuV/m)
0.009–0.490	2400/F(kHz)	/
0.490–1.705	24000/F(kHz)	/
1.705–30.0	30	/
30-88	100	40
88-216	150	43.5
216-960	200	46
Above960	500	54

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)
13.36 - 13.41			

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9KHz-30MHz	3.55 dB
30MHz-200MHz	4.17 dB
200MHz-1GHz	4.84 dB
1-18GHz	4.35 dB
18-26.5GHz	5.90 dB
26.5GHz~40GHz	5.92 dB


Test Results:

The modulation and bandwidth are similar for 802.11n mode for 20MHz/40MHz and 802.11ac mode for V20MHz/V40MHz, therefore investigated worst case to representative mode in test report.


The signal beyond the limit is carrier.

U-NII-1


802.11a-Channel 36: Peak




802.11a-Channel 48: Peak




802.11a-Channel 36: Average




802.11a-Channel 48: Average




802.11n HT20-Channel 36: Peak




802.11n HT20-Channel 48: Peak




802.11n HT20-Channel 36: Average




802.11n HT20-Channel 48: Average




802.11n HT40-Channel 38: Peak




802.11n HT40-Channel 46: Peak



802.11n HT40-Channel 38: Average




802.11n HT40-Channel 46: Average






U-NII-3


802.11a-Channel 149: Peak




802.11a-Channel 165: Peak




802.11n HT20-Channel 149: Peak




802.11n HT20-Channel 165: Peak



802.11n HT40-Channel 151: Peak



802.11n HT40-Channel 159: Peak




Result of RE

Test result

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the Emissions in the frequency band 9kHz-30MHz and 26.5GHz-40GHz are more than 20dB below the limit are not reported.

During the test, the Radiates Emission from 30MHz to 1GHz was performed in all modes with all channels, 802.11a, Channel 40 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.

Continuous TX mode:




Radiates Emission from 30MHz to 1GHz

Frequency (MHz)	Quasi-Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
36.911250	27.6	100.0	V	171.0	16.6	12.4	40.0
86.745000	22.2	225.0	H	70.0	11.9	17.8	40.0
139.973750	27.2	100.0	V	250.0	9.6	16.3	43.5
203.145000	22.4	100.0	V	336.0	12.1	21.1	43.5
332.518750	25.4	200.0	V	8.0	16.7	20.6	46.0
526.761250	30.4	100.0	H	26.0	21.6	15.6	46.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss(cable loss+amplifier gain)


2. Margin = Limit – Quasi-Peak

802.11a CH36



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1165.375000	44.4	100.0	V	0.0	-1.3	23.8	68.2
2008.875000	46.5	100.0	V	350.0	1.1	21.7	68.2
2621.375000	48.1	200.0	H	24.0	3.8	20.1	68.2
3093.000000	50.3	100.0	V	22.0	5.0	17.9	68.2
3486.750000	50.6	200.0	V	254.0	6.0	17.6	68.2
6588.625000	58.5	200.0	V	145.0	15.0	9.7	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1488.250000	33.8	200.0	V	289.0	-0.4	20.2	54.0
1694.750000	35.5	200.0	H	16.0	0.4	18.5	54.0
2233.750000	37.4	100.0	V	2.0	2.4	16.6	54.0
2770.125000	38.3	200.0	H	16.0	4.2	15.7	54.0
3653.875000	40.9	200.0	V	359.0	6.5	13.1	54.0
4143.875000	42.5	100.0	V	84.0	7.7	11.5	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11a CH40



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1143.500000	44.9	200.0	H	50.0	-1.3	23.3	68.2
1989.625000	46.6	100.0	H	348.0	1.1	21.6	68.2
2604.750000	49.0	100.0	V	5.0	3.8	19.2	68.2
3092.125000	50.0	100.0	V	2.0	5.0	18.2	68.2
3478.875000	50.4	100.0	V	12.0	6.0	17.8	68.2
6504.625000	59.9	100.0	V	0.0	14.9	8.3	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1513.625000	34.1	200.0	V	354.0	-0.4	19.9	54.0
1682.500000	34.8	100.0	H	327.0	0.3	19.2	54.0
2230.250000	37.3	200.0	V	351.0	2.4	16.7	54.0
2808.625000	39.3	200.0	H	20.0	4.3	14.7	54.0
3653.875000	40.6	100.0	V	74.0	6.5	13.4	54.0
4118.500000	42.0	200.0	V	22.0	7.7	12.0	54.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11a CH48



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz




Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1141.750000	44.7	100.0	V	277.0	-1.3	23.5	68.2
2018.500000	45.9	100.0	H	212.0	1.2	22.3	68.2
2596.000000	48.4	200.0	H	165.0	3.8	19.8	68.2
3114.875000	50.0	200.0	H	26.0	5.0	18.2	68.2
3464.875000	50.9	200.0	V	0.0	6.0	17.3	68.2
6126.625000	57.1	100.0	V	277.0	12.7	11.1	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1566.125000	34.4	100.0	H	323.0	-0.2	19.6	54.0
1694.750000	34.9	100.0	V	3.0	0.4	19.1	54.0
2300.250000	37.5	100.0	H	358.0	2.7	16.5	54.0
2765.750000	38.6	100.0	H	323.0	4.2	15.4	54.0
3687.125000	40.6	100.0	H	0.0	6.5	13.4	54.0
4061.625000	41.6	100.0	H	158.0	7.5	12.4	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11a CH149



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1360.500000	45.0	100.0	H	347.0	-0.8	29.0	74.0
1504.000000	45.2	100.0	V	32.0	-0.4	28.8	74.0
2262.625000	47.5	100.0	V	0.0	2.6	26.5	74.0
2796.375000	48.6	100.0	H	176.0	4.3	25.4	74.0
4019.625000	51.4	100.0	H	284.0	7.4	22.6	74.0
4909.500000	53.1	200.0	H	19.0	9.5	20.9	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1362.250000	33.9	100.0	H	0.0	-0.8	20.1	54.0
1614.250000	35.5	200.0	V	334.0	0.0	18.5	54.0
2273.125000	37.4	200.0	V	232.0	2.7	16.6	54.0
2806.875000	38.8	200.0	V	325.0	4.3	15.2	54.0
3765.875000	40.8	200.0	H	92.0	6.7	13.2	54.0
4155.250000	41.9	100.0	H	359.0	7.7	12.1	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11a CH157



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz




Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1369.250000	45.4	100.0	H	215.0	-0.8	28.6	74.0
1535.500000	45.0	200.0	V	324.0	-0.3	29.0	74.0
2361.500000	48.0	200.0	V	357.0	3.0	26.0	74.0
2813.000000	48.7	200.0	H	59.0	4.3	25.3	74.0
3989.000000	51.0	100.0	V	17.0	7.2	23.0	74.0
4905.125000	52.6	200.0	H	319.0	9.5	21.4	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1362.250000	33.9	200.0	H	164.0	-0.8	20.1	54.0
1679.000000	35.3	200.0	V	324.0	0.3	18.7	54.0
2335.250000	37.8	200.0	V	355.0	3.0	16.2	54.0
2808.625000	38.6	200.0	H	146.0	4.3	15.4	54.0
3771.125000	40.6	100.0	V	181.0	6.8	13.4	54.0
4560.375000	42.7	100.0	V	357.0	8.9	11.3	54.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11a CH165



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz




Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1406.000000	44.7	100.0	V	0.0	-0.7	29.3	74.0
1683.375000	45.9	100.0	H	358.0	0.3	28.1	74.0
2356.250000	47.3	200.0	H	42.0	3.0	26.7	74.0
2754.375000	49.7	100.0	H	0.0	4.2	24.3	74.0
3829.750000	51.7	200.0	V	358.0	6.8	22.3	74.0
4878.875000	53.7	200.0	V	250.0	9.5	20.3	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1374.500000	34.7	200.0	V	355.0	-0.8	19.3	54.0
1607.250000	34.8	100.0	V	2.0	0.0	19.2	54.0
2331.750000	38.2	200.0	V	347.0	2.9	15.8	54.0
2777.125000	39.3	100.0	V	8.0	4.2	14.7	54.0
3941.750000	41.4	100.0	V	162.0	7.1	12.6	54.0
4373.125000	42.1	200.0	V	357.0	8.4	11.9	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT20) CH36



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1123.375000	43.7	100.0	V	7.0	-1.3	24.5	68.2
2001.000000	46.8	100.0	V	1.0	1.1	21.4	68.2
2601.250000	48.9	200.0	V	110.0	3.8	19.3	68.2
3128.875000	50.6	100.0	H	0.0	5.1	17.6	68.2
3485.000000	51.1	200.0	H	0.0	6.0	17.1	68.2
6574.625000	58.5	200.0	V	356.0	15.0	9.7	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1348.250000	34.0	200.0	V	148.0	-0.9	20.0	54.0
1619.500000	35.4	200.0	H	126.0	0.1	18.6	54.0
2343.125000	37.9	200.0	V	222.0	3.0	16.1	54.0
2806.875000	38.8	100.0	H	251.0	4.3	15.2	54.0
3648.625000	41.0	100.0	V	7.0	6.5	13.0	54.0
4143.875000	42.9	100.0	V	72.0	7.7	11.1	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT20) CH40



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1099.750000	44.6	200.0	H	3.0	-1.4	23.6	68.2
1991.375000	47.0	100.0	V	106.0	1.1	21.2	68.2
2560.125000	49.0	200.0	H	323.0	3.7	19.2	68.2
3080.750000	50.0	100.0	H	232.0	5.0	18.2	68.2
3503.375000	51.6	100.0	V	217.0	6.1	16.6	68.2
6537.000000	58.4	200.0	V	357.0	14.9	9.8	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1378.875000	34.6	100.0	H	348.0	-0.7	19.4	54.0
1601.125000	35.3	200.0	H	0.0	0.0	18.7	54.0
2215.375000	37.4	200.0	H	0.0	2.3	16.6	54.0
2768.375000	39.3	100.0	V	57.0	4.2	14.7	54.0
3624.125000	40.2	200.0	H	202.0	6.4	13.8	54.0
3968.000000	41.1	100.0	V	17.0	7.1	12.9	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT20) CH48



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1098.000000	44.6	200.0	V	326.0	-1.4	23.6	68.2
1868.875000	46.8	100.0	H	334.0	0.8	21.4	68.2
2582.875000	49.5	100.0	H	358.0	3.8	18.7	68.2
3079.000000	48.7	200.0	H	164.0	5.0	19.5	68.2
3555.000000	51.5	100.0	V	44.0	6.3	16.7	68.2
6482.750000	58.3	100.0	V	274.0	14.7	9.9	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1386.750000	34.6	200.0	H	59.0	-0.7	19.4	54.0
1603.750000	35.3	200.0	H	183.0	0.0	18.7	54.0
2264.375000	37.2	200.0	H	12.0	2.6	16.8	54.0
2795.500000	39.0	100.0	V	88.0	4.3	15.0	54.0
3662.625000	40.6	200.0	V	302.0	6.5	13.4	54.0
3968.875000	41.5	200.0	H	295.0	7.1	12.5	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT20) CH149



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1410.375000	44.9	100.0	V	197.0	-0.7	29.1	74.0
1678.125000	45.8	100.0	H	0.0	0.3	28.2	74.0
2284.500000	47.6	100.0	H	329.0	2.7	26.4	74.0
2706.250000	49.9	100.0	H	319.0	4.0	24.1	74.0
3936.500000	51.7	200.0	V	358.0	7.1	22.3	74.0
4958.500000	53.7	200.0	H	2.0	9.5	20.3	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1333.375000	33.5	100.0	V	5.0	-0.9	20.5	54.0
1537.250000	35.1	100.0	H	345.0	-0.3	18.9	54.0
2258.250000	38.2	200.0	H	2.0	2.5	15.8	54.0
2811.250000	39.5	100.0	V	44.0	4.3	14.5	54.0
3946.125000	41.2	100.0	H	350.0	7.1	12.8	54.0
4985.625000	43.5	200.0	V	354.0	9.5	10.5	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT20) CH157



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1337.750000	43.9	100.0	H	85.0	-0.9	30.1	74.0
1588.875000	45.0	100.0	V	57.0	-0.1	29.0	74.0
2291.500000	48.4	200.0	H	71.0	2.7	25.6	74.0
2772.750000	48.3	100.0	H	352.0	4.2	25.7	74.0
3873.500000	51.5	200.0	H	295.0	7.0	22.5	74.0
4894.625000	53.7	200.0	H	4.0	9.6	20.3	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)


Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1348.250000	33.9	200.0	H	57.0	-0.9	20.1	54.0
1695.625000	36.4	200.0	H	57.0	0.4	17.6	54.0
2263.500000	37.8	200.0	V	0.0	2.6	16.2	54.0
2792.875000	39.4	100.0	V	0.0	4.3	14.6	54.0
3961.875000	41.2	100.0	V	180.0	7.1	12.8	54.0
4836.875000	43.2	200.0	H	21.0	9.4	10.8	54.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT20) CH165



Note: The signal beyond the limit is carrier.
Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz




Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1333.375000	43.6	100.0	H	351.0	-0.9	30.4	74.0
1587.125000	45.0	100.0	V	24.0	-0.1	29.0	74.0
2271.375000	48.6	100.0	H	221.0	2.7	25.4	74.0
2774.500000	48.3	100.0	H	148.0	4.2	25.7	74.0
3793.000000	51.6	200.0	V	336.0	6.8	22.4	74.0
4891.125000	52.8	200.0	H	7.0	9.6	21.2	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1378.000000	34.1	100.0	H	276.0	-0.7	19.9	54.0
1574.000000	35.2	100.0	V	0.0	-0.1	18.8	54.0
2320.375000	37.9	100.0	V	0.0	2.8	16.1	54.0
2822.625000	39.3	200.0	V	303.0	4.4	14.7	54.0
3880.500000	41.8	100.0	V	5.0	7.0	12.2	54.0
4828.125000	43.4	100.0	H	320.0	9.4	10.6	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT40) CH38



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1015.750000	45.0	100.0	H	0.0	-1.8	23.2	68.2
1648.375000	45.4	200.0	V	81.0	-0.3	22.8	68.2
1953.750000	47.3	200.0	H	1.0	1.0	20.9	68.2
2550.500000	49.3	200.0	H	21.0	3.7	18.9	68.2
3532.250000	51.2	100.0	H	355.0	6.3	17.0	68.2
4472.875000	53.0	100.0	H	125.0	7.7	15.0	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1393.750000	35.0	200.0	V	234.0	-0.7	19.0	54.0
1687.750000	35.8	100.0	V	54.0	0.4	18.2	54.0
2279.250000	37.8	100.0	H	355.0	2.7	16.2	54.0
2824.375000	39.7	200.0	H	0.0	4.4	14.3	54.0
3856.875000	41.4	200.0	V	9.0	6.9	12.6	54.0
4709.125000	43.3	200.0	H	1.0	9.2	10.7	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT40) CH46



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1150.500000	44.4	200.0	V	343.0	-1.3	23.8	68.2
1653.625000	46.3	200.0	V	327.0	-0.5	21.9	68.2
1822.500000	47.8	100.0	H	356.0	0.7	20.4	68.2
2596.000000	49.7	100.0	V	16.0	3.8	18.5	68.2
3436.875000	51.3	200.0	V	343.0	5.9	16.9	68.2
4420.375000	52.6	200.0	H	141.0	7.9	15.6	68.2

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1371.000000	34.8	200.0	H	23.0	-0.8	19.2	54.0
1683.375000	35.6	100.0	H	356.0	0.3	18.4	54.0
2276.625000	38.0	200.0	V	336.0	2.7	16.0	54.0
2758.750000	39.4	100.0	V	0.0	4.2	14.6	54.0
3929.500000	41.3	100.0	V	140.0	7.1	12.7	54.0
4811.500000	43.1	100.0	H	0.0	9.3	10.9	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT40) CH151



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz


Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1398.125000	45.6	100.0	V	161.0	-0.7	28.4	74.0
1698.250000	46.3	100.0	V	3.0	0.4	27.7	74.0
2243.375000	48.2	100.0	H	359.0	2.4	25.8	74.0
2791.125000	50.8	100.0	V	198.0	4.3	23.2	74.0
3919.000000	52.1	100.0	V	0.0	7.1	21.9	74.0
4849.125000	53.7	100.0	V	255.0	9.4	20.3	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1401.625000	35.0	200.0	H	276.0	-0.7	19.0	54.0
1678.125000	35.8	100.0	H	356.0	0.3	18.2	54.0
2343.125000	38.2	200.0	H	2.0	3.0	15.8	54.0
2779.750000	39.5	100.0	H	356.0	4.2	14.5	54.0
3996.000000	41.4	200.0	H	6.0	7.3	12.6	54.0
5049.500000	43.5	100.0	H	0.0	9.8	10.5	54.0


Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

802.11n (HT40) CH159



Note: The signal beyond the limit is carrier.

Radiates Emission from 1GHz to 8GHz



Radiates Emission from 8GHz to 18GHz

Frequency (MHz)	Peak (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1385.875000	46.2	100.0	H	65.0	-0.7	27.8	74.0
1684.250000	45.5	100.0	V	3.0	0.3	28.5	74.0
2229.375000	47.3	200.0	H	156.0	2.4	26.7	74.0
2841.000000	50.0	100.0	V	99.0	4.4	24.0	74.0
3872.625000	51.7	200.0	H	6.0	7.0	22.3	74.0
4872.750000	53.1	100.0	V	136.0	9.5	20.9	74.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

Frequency (MHz)	Average (dBuV/m)	Height (cm)	Polarization	Azimuth (deg)	Correct Factor (dB)	Margin (dB)	Limit (dBuV/m)
1377.125000	34.9	100.0	H	44.0	-0.7	19.1	54.0
1601.222000	35.9	200.0	H	53.0	0.2	18.1	54.0
2253.000000	37.4	200.0	V	0.0	2.5	16.6	54.0
2841.000000	38.2	100.0	V	99.0	4.4	15.8	54.0
3980.250000	41.5	200.0	V	0.0	7.2	12.5	54.0
4962.875000	43.3	100.0	H	350.0	9.5	10.7	54.0

Remark: 1. Correction Factor = Antenna factor+ Insertion loss (cable loss + amplifier gain)

5.6. Conducted Emission

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

The EUT IS placed on a non-metallic table of 80cm height above the horizontal metal reference ground plane. During the test, the EUT was operating in its typical mode. The test method is according to ANSI C63.10-2013. Connect the AC power line of the EUT to the LISN Use EMI receiver to detect the average and Quasi-peak value. RBW is set to 9kHz, VBW is set to 30kHz The measurement result should include both L line and N line.

The test is in transmitting mode.

Test Setup



Note: AC Power source is used to change the voltage 110V/60Hz.

Limits


Frequency (MHz)	Conducted Limits(dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 to 56 *	56 to 46 *
0.5 - 5	56	46
5 - 30	60	50
*: Decreases with the logarithm of the frequency.		

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 2.69$ dB.

Test Results:


Following plots, Blue trace uses the peak detection and Green trace uses the average detection. During the test, the Conducted Emission was performed in all modes with all channels, 802.11a, Channel 40 are selected as the worst condition. The test data of the worst-case condition was recorded in this report.



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15	52.65	---	66.00	13.35	1000.0	9.000	L1	ON	19
0.20	---	34.69	53.82	19.13	1000.0	9.000	L1	ON	19
0.55	39.03	---	56.00	16.97	1000.0	9.000	L1	ON	19
0.63	---	27.28	46.00	18.72	1000.0	9.000	L1	ON	19
0.97	---	25.34	46.00	20.66	1000.0	9.000	L1	ON	19
1.11	37.86	---	56.00	18.14	1000.0	9.000	L1	ON	19
2.81	26.46	---	56.00	29.54	1000.0	9.000	L1	ON	19
4.58	---	18.90	46.00	27.10	1000.0	9.000	L1	ON	19
12.21	33.10	---	60.00	26.90	1000.0	9.000	L1	ON	19
12.21	---	29.65	50.00	20.35	1000.0	9.000	L1	ON	19
13.56	34.85	---	60.00	25.15	1000.0	9.000	L1	ON	19
19.84	---	33.19	50.00	16.81	1000.0	9.000	L1	ON	20

Remark: Correct factor=cable loss + LISN factor

L line Conducted Emission from 150 KHz to 30 MHz



Frequency (MHz)	QuasiPeak (dBμV)	Average (dBμV)	Limit (dBμV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Filter	Corr. (dB)
0.15	48.17	---	66.00	17.83	1000.0	9.000	N	ON	19
0.20	---	31.69	53.82	22.13	1000.0	9.000	N	ON	19
0.54	37.64	---	56.00	18.36	1000.0	9.000	N	ON	19
0.55	---	24.06	46.00	21.94	1000.0	9.000	N	ON	19
1.52	34.68	---	56.00	21.32	1000.0	9.000	N	ON	19
1.53	---	24.20	46.00	21.80	1000.0	9.000	N	ON	19
3.23	31.24	---	56.00	24.76	1000.0	9.000	N	ON	19
4.58	---	21.73	46.00	24.27	1000.0	9.000	N	ON	19
12.21	37.13	---	60.00	22.87	1000.0	9.000	N	ON	19
12.21	---	32.33	50.00	17.67	1000.0	9.000	N	ON	19
19.84	---	35.22	50.00	14.78	1000.0	9.000	N	ON	19
19.84	40.62	---	60.00	19.38	1000.0	9.000	N	ON	19

Remark: Correct factor=cable loss + LISN factor

N line Conducted Emission from 150 KHz to 30 MHz



6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Spectrum Analyzer	R&S	FSV40	15195-01-00	2020-05-18	2021-05-17
EMI Test Receiver	R&S	ESCI	100948	2020-05-18	2021-05-17
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	9163-201	2017-11-18	2020-11-17
Horn Antenna	R&S	HF907	102723	2018-08-11	2021-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2021-06-19
Standard Gain Horn	STEATITE	QSH-SL-26-40 -K-15	16779	2019-12-24	2022-12-23
Broadband Horn Antenna	SCHWARZBECK	BBHA 9120D	430	2018-07-07	2021-07-06
EMI Test Receiver	R&S	ESR	101667	2020-05-18	2021-05-17
LISN	R&S	ENV216	101171	2018-12-15	2021-12-14
Spectrum Analyzer	KEYSIGHT	N9020A	MY54420163	2019-12-15	2020-12-14
RF Cable	Agilent	SMA 15cm	0001	2020-06-12	2020-12-11
TEMPERATURE CHAMBER	WEISS	VT4002	582261194500 10	2019-12-15	2020-12-14
WLAN AP	Cisco	Air-AP1262N- A-K9	LDK102073 (FCC ID)	/	/
Power Meter	R&S	NRP2	104306	2020-05-18	2021-05-17
Power Sensor	R&S	NRP-Z21	104799	2020-05-18	2021-05-17
DC Power Supply	GWINSTEK	GPS-3030D	GEP882653	2020-05-18	2021-05-17
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.