

HOT CIRCUIT. BE CAREFUL AND USE AN ISOLATION TRANSFORMER WHEN SERVICING

NOTE: IF YOU CHECK THE VOLTAGE FOR PARTS IN HOT CIRCUIT, YOU MUST USE [PRIMARY GND] AS A COMMON TERMINAL

CAUTION TO SERVICE TECHNICIANS:
BEFORE RETURNING THE APPLIANCE TO THE CUSTOMER, LEAKAGE CURRENT OR RESISTANCE MEASUREMENTS SHOULD BE PERFORMED TO DETERMINE THAT EXPOSED PARTS ARE PROPERLY INSULATED FROM SUPPLY CIRCUIT.

CAUTION:
THE PARTS IDENTIFIED BY ★ MARKS ARE CRITICAL FOR SAFETY.
REPLACE ONLY WITH TYPE IDENTICAL TO THOSE IN THE ORIGINAL CIRCUIT OR SPECIFIED IN THE 'PARTLIST'.
DO NOT DEGRADE THE SAFETY OF THE APPLIANCE THROUGH IMPROPER SERVICING.

LEADLESS(CHIP) COMPONENTS:
VOLTAGES TAKEN IN THE OPEN STATE
() RECORD MODE

제2원도

DRAWN	DESIGNED	CHECKED	APPROVED	MODEL	2017.08.10
KIM DUCK HYUN	KIM DUCK HYUN	KIM DUCK HYUN	KIM DUCK HYUN	FILE NAME: ISSUED DATE	2017.08.10
DESIGNER VCR DEPT	TEAM	REV NO	30	SHEET	1
DAEWOO ELECTRONICS VCR RESEARCH CENTER					

DRAWN		DESIGNED		CHECKED	APPROVED	MODEL	2014.08.20
KIM DUCK HYUN	KIM DUCK HYUN	KIM DUCK HYUN				FILE NAME	2014.08.20
	검제	검제	검제			ISSUED DATE	2014.08.20
						REVISED	
DESIGNER VCR DEPT		1	TEAM		REV NO	00	SHEET
 DAEWOO ELECTRONICS		VCR RESEARCH CENTER					1 / 2