RF EXPOSURE EVALUATION

| 1. PRODUCT INFORMATION | |
|------------------------|---------------------|
| Product Description | 2.4G Wireless Mouse |
| Model Name | GSKBWMA1 |
| FCC ID | 2AMSUWMA1 |

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f}(GHz)] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

2.4G:

Pt= -4.452dBm=0.359mW

The value of the Maximum output power P_t is referred to the test report of the CFR47 §15.247.

The result for RF exposure evaluation SAR=(0.359mW /5mm) .[$\sqrt{2.405GHz}$)]=0.111<3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR.

4. CONCLUSION

The SAR evaluation is not required.