

Report No.: SEWM2304000122RG04

Rev.: 01 Page: 1 of 12

TEST REPORT

Application No.: SEWM2304000122RG

Applicant: Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin **Address of Applicant:**

Road, Minhang District, Shanghai, China 200233

Manufacturer: Quectel Wireless Solutions Co., Ltd.

Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Address of Manufacturer:

Road, Minhang District, Shanghai, China 200233

EUT Description: 5G Sub-6 GHz M.2 Module

Model No.: RM520N-GL Trade Mark: Quectel

FCC ID: XMR2023RM520NGL Standards: 47 CFR Part 2.1091

FCC KDB 447498 D01 v06


Date of Receipt: 2023/04/19 (for new report SEWM2304000122RG04)

Date of Issue: 2023/06/21

Test Result: PASS*

In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Well Wei Wireless Laboratory Manager



South of No. 6 Plant, No. 1, Runsheng Road, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 • 苏州 • 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

t (86-512) 62992980 t (86-512) 62992980



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 2 of 12

1 Version

Revision Record							
Version	Chapter	Modifier	Remark				
01		2023/06/21		Original			

Prepared By	(Nick Hu) / Test Engineer
Checked By	Stone Gu) / Reviewer



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration. Forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CND occheck@sss.com

South of No. 6 Plant, No. 1, Runsheng Read, Suzhou Indushia Park, Suzhou Area, Chine (Jiangsu) Pikit Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区海胜高1号的6号厂房南部 鄉鄉: 215000



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 3 of 12

Contents

1 Version 2 General Information 2.1 Client Information 2.2 Test Facility 2.3 General Description of EUT 3 RF Exposure Evaluation 3.1 RF Exposure Compliance Requirement 3.1.1 Limits 3.1.2 Test Procedure 3.1.3 EUT RF Exposure Evaluation		
2.2	Test Facility	4
	•	
3.1	RF Exposure Compliance Requirement	8
3	.1.2 Test Procedure	9
	1.1.3 EUT RF Exposure Evaluation	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at http://www.sgc.com/en/Terms-and-Conditions.apx and, for electronic format documents subject to Terms and Conditions for Electronic Documents at http://www.sgc.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits cClient's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content cappearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention:To check the authenticity of testing /inspection report & certificate, please econtact us at telephone: (86-75) 8307 144.

South of No. 6 Plant, No. 1, Runsheng Read, Suzhou Industrial Park, Suzhou Arva, China (Jängsu) Plot Free Trade Zone 215000中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区湖胜路1号的6号厂房南部 鄉鄉: 215000

t (86–512) 62992980 t (86–512) 62992980



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 4 of 12

2 General Information

2.1 Client Information

Applicant:	Quectel Wireless Solutions Co., Ltd.
Address of Applicant:	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233
Manufacturer:	Quectel Wireless Solutions Co., Ltd.
Address of Manufacturer:	Building 5, Shanghai Business Park Phase III (Area B), No.1016 Tianlin Road, Minhang District, Shanghai, China 200233

2.2 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 6336.01)

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6336.01.

• Innovation, Science and Economic Development Canada

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0120.

IC#: 27594.

• FCC -Designation Number: CN1312

SGS-CSTC STANDARDS TECHNICAL SERVICES (SUZHOU) CO., LTD. has been recognized as an

accredited testing laboratory. Designation Number: CN1312.

Test Firm Registration Number: 717327





Report No.: SEWM2304000122RG04

Rev.: 01 Page: 5 of 12

2.3 General Description of EUT

EUT Description:	5G Sub-6 GHz M.2	5G Sub-6 GHz M.2 Module								
Model No.:	RM520N-GL									
Trade Mark:	Quectel	Quectel								
Hardware Version:	R1.0									
Software Version:	RM520NGLAAR03	RM520NGLAAR03A01M4G								
Antenna Type:	External Antenna	External Antenna								
	WCDMA Band II:	0.25dBi	WCDMA Band IV:	1.47dBi						
	WCDMA Band V:	2.68dBi								
	LTE Band 2:	0.25dBi(Ant0)	LTE Band 4:	1.47dBi(Ant0)						
	LTE Band 5:	2.68dBi(Ant0)	LTE Band 7:	0.55dBi(Ant0)						
	LTE Band 12:	-0.2dBi(Ant0)	LTE Band 13:	1.54dBi(Ant0)						
	LTE Band 14:	2.42dBi(Ant0)	LTE Band 17:	-0.2dBi(Ant0)						
	LTE Band 25:	0.25dBi(Ant0)	LTE Band 26:	2.87dBi(Ant0)						
	LTE Band 30:	-5.7dBi(Ant0)	LTE Band 38:	-0.23dBi(Ant0)						
	LTE Band 41:	0.78dBi(Ant0)	LTE Band 42:	-6.1dBi(Ant2)						
	LTE Band 43:	and 43: -6.1dBi(Ant2) LTE Band 66:		1.47dBi(Ant0)						
	LTE Band 71:	TE Band 71: 1.22dBi(Ant0) LTE CA_2C:		0.25dBi(Ant0)						
	LTE CA_5B:	2.68dBi(Ant0)	LTE CA_7C:	0.55dBi(Ant0)						
	LTE CA_38C:	-0.23dBi(Ant0)	LTE CA_41C:	0.78dBi(Ant0)						
Antenna Gain:	LTE CA_42C:	-6.1dBi(Ant2)	LTE CA_43C:	-6.1dBi(Ant2)						
	LTE CA_66B:	1.47dBi(Ant0)	LTE CA_66C:	1.47dBi(Ant0)						
	LTE Band 48:	-6.1dBi (Ant2)	LTE CA_48C:	-6.1dBi (Ant2)						
	NR Band n2:	0.25dBi (Ant0)	NR Band n5:	2.68dBi (Ant0)						
	NR Band n7:	0.55dBi (Ant0)	NR Band n12:	-0.2dBi (Ant0)						
	NR Band n13:	1.54dBi (Ant0)	NR Band n14:	2.42dBi (Ant0)						
	NR Band n25:	0.25dBi (Ant0)	NR Band n26:	2.87dBi (Ant0)						
	NR Band n30:	-5.7dBi (Ant0)	NR Band n38 MIMO:	-0.23dBi (Ant0); -0.23dBi (Ant2)						
	NR Band n41 MIMO:	0.78dBi (Ant0); 0.78dBi (Ant2)	NR Band n66:	1.47dBi (Ant0)						
	NR Band n48 MIMO:	-6.10dBi (Ant0) -6.10dBi (Ant2)	NR Band n70:	1.3dBi (Ant2)						
	NR Band n71:	1.22dBi (Ant0)	NR Band n77 MIMO:	-6.1dBi (Ant0);						



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indeminification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or applied CPU Descheck/Genes come.

South of No. 6 Paint, No. 1, Runsherry Road, Suchou Industrial Park, Suzhou Area, Chira (Liangsu) Plot Free Trade Zone
中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 6 of 12

 Page: 6 of 12	
-6.1dBi (Ant2)	
NR Band n78 -6.1dBi (Ant0);	
MIMO: -6.1dBi (Ant2)	
CA:	
UL CA_2C; UL CA_5B; UL CA_7C; UL CA_38C; UL CA_41C; UL CA_43C;	
UL CA_66C; UL CA_66B; UL CA_48C; UL CA_42C;	
UL CA_2A-4A; UL CA_2A-5A; UL CA_2A-7A; UL CA_2A-12A; UL CA_2A-13A;	
UL CA_2A-30A; UL CA_2A-66A;	
UL CA_4A-5A; UL CA_4A-7A; UL CA_4A-12A; UL CA_4A-13A;	
UL CA_4A-30A;	
UL CA_5A-7A; UL CA_5A-30A; UL CA_5A-66A;	
UL CA_12A-30A; UL CA_12A-66A; UL CA_13A-66A; UL CA_14A-30A;	
ENDC:	
DC_13A_n66A;DC_5A_n2A;DC_14A_n2A;DC_30A_n2A;DC_2A_n5A;	
DC_30A_n5A;DC_66A_n5A;DC_2A_n12A;DC_66A_n12A;DC_2A_n66A;	
DC_5A_n66A;DC_12A_n66A;DC_14A_n66A;DC_30A_n66A;DC_12A_n2A;	
DC_66A_n2A;DC_71A_n2A;DC_12A_n41A;DC_71A_n66A;DC_2A_n71A	
DC_66A_n71A;DC_66A_n25A;DC_25A_n41A;DC_12A_n78A;DC_13A_n78A	
DC_25A_n78A;DC_12A_n77A;DC_13A_n77A;DC_14A_n77A;DC_26A_n78A	
DC_2A_n78A;DC_26A_n41A;DC_2A_n41A;DC_7A_n5A;DC_38A_n78A	
DC_7A_n71A;DC_41A_n78A;DC_5A_n7A;DC_12A_n7A;DC_66A_n7A	
DC_13A_n2A;DC_48A_n5A;DC_48A_n66A;DC_7A_n66A;DC_2A_n48A	
DC_5A_n48A;DC_13A_n48A;DC_66A_n48A;DC_4A_n78A;DC_20A_n77A	
DC_5A_n78A;DC_4A_n41A;DC_66A_n38A;DC_2A_n38A;DC_12A_n38A	
DC_4A_n38A;DC_5A_n38A;DC_66A_n78A;DC_12A_n25A;DC_25A_n77A	
DC_2A_n77A;DC_71A_n78A;DC_71A_n38A;DC_13A_n7A;DC_5A_n41A	
DC_66A_n41A;DC_2A_n7A;DC_7A_n2A;DC_5A_n40A;DC_30A_n77A	
DC_41A_n77A;DC_7A_n78A;DC_48A_n25A;DC_66A_n28A;DC_71A_n41A	
DC_28A_n66A;DC_30A_n12A;DC_2A_n14A;DC_30A_n14A;DC_66A_n14A	
DO 04 004 DO 54 004 DO 404 004 DO 444 004 DO 004	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document one one excenter parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

DC_2A_n30A;DC_5A_n30A;DC_12A_n30A;DC_14A_n30A;DC_66A_n30A DC_71A_n7A;DC_7A_n12A;DC_5A_n77A;DC_66A_n77A;DC_71A_n77A DC_4A_n2A;DC_7A_n25A;DC_71A_n25A;DC_5A_n25A;DC_26A_n25A

South of No. 6 Plant, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jiangsu) Pikot Free Trade Zone 中国 - 苏州 - 中国 (江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000 t (86–512) 62992980 w t (86–512) 62992980 sg



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 7 of 12

DC_4A_n7A;DC_13A_n25A;DC_7A_n77A;DC_48A_n71A;DC_48A_n12A
NR UL CA:
n25A-n41A;n41A-n66A;n41A-n71A;n7A-n78A;n5A-n78A
n66A-n78A;n7A-n77A;n2A-n77A;n5A-n77A;n66A-n77A
n30A-n77A;n48A-n66A;n2A-n48A;n5A-n48A;n48A-n70A
n48A-n71A;n71A-n77A;n71A-n78A;n25A-n78A;n38A-n66A
n25A-n48A;n25A-n77A;n25A-n38A;n13A-n77A; n2A-n41A
Note:
The antenna gain are derived from the gain information report provided by the manufacturer.

Remark:

As above information is provided and confirmed by the applicant. SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Directional Gain Calculations

a) Basic methodology with NANT transmit antennas, each with the same directional gain GANT dBi, being driven by NANT transmitter outputs of equal power. Directional gain is to be computed as follows (ii) all transmit signals are completely uncorrelated with each other. Directional gain = GANT

Band	ANT Gain0 (dBi)	ANT Gain2 (dBi)	Directional gain (dBi)
NR Band n38:	-0.23	-0.23	-0.23
NR Band n41:	0.78	0.78	0.78
NR Band n48:	-6.10	-6.10	-6.10
NR Band n77:	-6.10	-6.10	-6.10
NR Band n78:	-6.10	-6.10	-6.10



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.agpx and, for electronic format documents subject to Terms and Conditions (Terms-and-Conditions) ferms-and-Conditions (Terms-and-Conditions) ferms-and-Conditions) ferms-and-Conditions (Terms-and-Conditions) ferms-and-Conditions) ferms-and-Conditions (Terms-and-Conditions) ferms-and-Conditions) ferms-and-Conditions (Terms-and-Conditions) ferms-and-Conditions) ferms-and-Conditions ferms-and-Conditions ferms-and-Conditions ferms-and-Conditions (Terms-and-Conditions) ferms-and-Conditions ferms-and-Conditions ferms-and-Conditions) ferms-and-Conditions ferms-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-and-Conditions-

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 8 of 12

3 RF Exposure Evaluation

3.1 RF Exposure Compliance Requirement

3.1.1 Limits

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm2)	Averaging time (minutes)							
	(A) Limits for Occupational/Controlled Exposures										
0.3-3.0	614	1.63	*(100)	6							
3.0-30	1842/f	4.89/f	*(900/f2)	6							
30-300	61.4	0.163	1.0	6							
300-1500	1	1	f/300	6							
1500-100,000	1	1	5	6							
	B) Limits for General P	opulation/Uncontrolled I	Exposure								
0.3-1.34	614	1.63	*(100)	30							
1.34-30	824/f	2.19/f	*(180/f2)	30							
30-300	27.5	0.073	0.2	30							
300-1500	1	1	f/1500	30							
1500-100,000	1	1	1.0	30							

F=frequency in MHz

RF exposure compliance will need to be determined with respect to 1.1307(c) and (d) of the FCC rules. The emissions should be within the limits at 300kHz in Table 1 of 1.1310(use the 300kHz limits for 150kHz:614V/m,1.63A/m).

Friis Formula

Friis transmission formula: $Pd = (Pout*G)/(4*Pi*R^2)$

Where

Pd = power density in mW/cm2

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE, 1 mW/cm2. If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, considering a for a for a for a for a formal to the first of the formal formal formal for the first of the first

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

215000 t (86–512) 62992980 215000 t (86–512) 62992980

^{*=}Plane-wave equivalent power density



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 9 of 12

3.1.2 Test Procedure

Software provided by client enabled the EUT to transmit data at lowest, middle and highest channel individually

3.1.3 EUT RF Exposure Evaluation

Output Power Into Antenna & RF Exposure Evaluation Distance:

This confirmed that the device comply with MPE limit.

	F	Antenna	Max	EIRP(ERP	EIRP(ERP	Power Density	1 : :4	Gain according	Gain	Max Gain	
Operating Band	Frequency (MHz)	Gain (dBi)	Conducte d Power (dBm)	(dBm)) Limit (dBm)	at R = 20 cm (mW/cm2)	Limit (mW/cm2)	to EIRP(ERP) (dBi)	according to Pd (dBi)	Allowed (dBi)	conclusio n
WCDMA Band II	1852.4	0.25	25.00	25.25	33.00	0.0666	1.0000	8.00	12.01	8.00	Pass
WCDMA Band IV	1712.4	1.47	25.00	26.47	30.00	0.0883	1.0000	5.00	12.01	5.00	Pass
WCDMA Band V	826.4	2.68	25.00	25.53	38.45	0.1166	0.5509	15.60	9.42	9.42	Pass
LTE Band 2/LTE CA_2C	1850.7	0.25	25.00	25.25	33.00	0.0666	1.0000	8.00	12.01	8.00	Pass
LTE Band 4	1710.7	1.47	25.00	26.47	30.00	0.0883	1.0000	5.00	12.01	5.00	Pass
LTE Band 5/LTE CA_5B	824.7	2.68	25.00	25.53	38.45	0.1166	0.5498	15.60	9.41	9.41	Pass
LTE Band 7/LTE CA_7C	2502.5	0.55	25.00	25.55	33.00	0.0714	1.0000	8.00	12.01	8.00	Pass
LTE Band 12	699.7	-0.20	25.00	22.65	34.77	0.0601	0.4665	11.92	8.70	8.70	Pass
LTE Band 13	779.5	1.54	25.00	24.39	34.77	0.0897	0.5197	11.92	9.16	9.16	Pass
LTE Band 14	790.5	2.42	25.00	25.27	34.77	0.1098	0.5270	11.92	9.23	9.23	Pass
LTE Band 17	706.5	-0.20	25.00	22.65	34.77	0.0601	0.4710	11.92	8.74	8.74	Pass
LTE Band 25	1850.7	0.25	25.00	25.25	33.00	0.0666	1.0000	8.00	12.01	8.00	Pass
LTE Band 26(814- 824)	814.7	2.87	25.00	25.72	NA	0.1218	0.5431	NA	9.36	9.36	Pass
LTE Band 26(824- 849)	824.7	2.87	25.00	25.72	38.45	0.1218	0.5498	15.60	9.41	9.41	Pass
LTE Band 30	2307.5	-5.70	25.00	19.30	23.98	0.0169	1.0000	-1.02	12.01	-1.02	Pass
LTE Band 38/LTE CA_38C	2572.5	-0.23	28.00	27.77	33.00	0.1191	1.0000	5.00	9.01	5.00	Pass
LTE Band 41/LTE CA_41C	2498.5	0.78	28.00	28.78	33.00	0.1502	1.0000	5.00	9.01	5.00	Pass
LTE Band 42(3450- 3550) /LTE CA_42C	3452.5	-6.10	28.00	21.90	30.00	0.0308	1.0000	2.00	9.01	2.00	Pass
LTE Band 43(3700- 3800)/LTE CA_43C	3702.5	-6.10	28.00	21.90	30.00	0.0308	1.0000	2.00	9.01	2.00	Pass
LTE Band 48/LTE CA_48C	3552.5	-6.10	25.00	18.90	23.00	0.0154	1.0000	-2.00	12.01	-2.00	Pass
LTE Band 66/LTE CA_66B/LTE CA_66C	1710.7	1.47	25.00	26.47	30.00	0.0883	1.0000	5.00	12.01	5.00	Pass
LTE Band 71	665.5	1.22	25.00	24.07	34.77	0.0833	0.4437	11.92	8.48	8.48	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printer overleaf, available on request or accessible at https://www.sgs.com/en/Ferms-and-Conditions.aspx and, for electronic format documents subject to Terms and Conditions [Ferms-and-Conditions] Ferms-and-Conditions Ferms-and-Conditions Ferms-and-Conditions Ferms-and-Conditions Ferms-and-Conditions Ferms-and-Conditions Ferms-and-Conditions ferms-and-Conditions approximate advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction document comment cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 10 of 12

Operating Band	Frequency (MHz)	Antenna Gain (dBi)	MIMO Directional gain	Max Conducte d Power (dBm)	EIRP(ERP) (dBm)	EIRP(ERP) Limit (dBm)	Power Density at R = 20 cm (mW/cm2)	Limit (mW/cm2)	Gain according to EIRP(ERP) (dBi)	Gain according to Pd (dBi)	Max Gain Allowed (dBi)	conclusio n
NR Band n2	1852.5	0.25	NA	25.00	25.25	33.00	0.0666	1.0000	8.00	12.01	8.00	Pass
NR Band n5	826.5	2.68	NA	25.00	25.53	38.45	0.1166	0.5510	15.60	9.42	9.42	Pass
NR Band n7	2502.5	0.55	NA	25.00	25.55	33.00	0.0714	1.0000	8.00	12.01	8.00	Pass
NR Band n12	701.5	-0.20	NA	25.00	22.65	34.77	0.0601	0.4677	11.92	8.71	8.71	Pass
NR Band n13	779.5	1.54	NA	25.00	24.39	34.77	0.0897	0.5197	11.92	9.16	9.16	Pass
NR Band n14	790.5	2.42	NA	25.00	25.27	34.77	0.1098	0.5270	11.92	9.23	9.23	Pass
NR Band n25	1852.5	0.25	NA	25.00	25.25	33.00	0.0666	1.0000	8.00	12.01	8.00	Pass
NR Band n26(814- 824)	816.5	2.87	NA	25.00	25.72	NA	0.1218	0.5443	NA	9.37	9.37	Pass
NR Band n26(824- 849)	826.5	2.87	NA	25.00	25.72	38.45	0.1218	0.5510	15.60	9.42	9.42	Pass
NR Band n30	2307.5	-5.70	NA	25.00	19.30	23.98	0.0169	1.0000	-1.02	12.01	-1.02	Pass
NR Band n38	2575.0	-0.23	NA	28.00	27.77	33.00	0.1191	1.0000	5.00	9.01	5.00	Pass
NR Band n38(MIMO)	2575.0	-0.23	-0.23	28.00	27.77	33.00	0.1191	1.0000	5.00	9.01	5.00	Pass
NR Band n41	2506.0	0.78	NA	28.00	28.78	33.00	0.1502	1.0000	5.00	9.01	5.00	Pass
NR Band n41(MIMO)	2506.0	0.78	0.78	30.00	30.78	33.00	0.2381	1.0000	3.00	7.01	3.00	Pass
NR Band n48	3555.0	-6.10	NA	25.00	18.90	23.00	0.0154	1.0000	-2.00	12.01	-2.00	Pass
NR Band n48(MIMO)	3555.0	-6.10	-6.10	25.00	18.90	23.00	0.0154	1.0000	-2.00	12.01	-2.00	Pass
NR Band n66	1712.5	1.47	NA	25.00	26.47	30.00	0.0883	1.0000	5.00	12.01	5.00	Pass
NR Band n70	1697.5	1.30	NA	25.00	26.30	30.00	0.0849	1.0000	5.00	12.01	5.00	Pass
NR Band n71	665.5	1.22	NA	25.00	24.07	34.77	0.0833	0.4437	11.92	8.48	8.48	Pass
NR Band n77 (3450-3550)	3455.0	-6.10	NA	28.00	21.90	30.00	0.0308	1.0000	2.00	9.01	2.00	Pass
NR Band n77 (3450-3550)(MIMO)	3455.0	-6.10	-6.10	30.00	23.90	30.00	0.0488	1.0000	0.00	7.01	0.00	Pass
NR Band n77 (3700-3980)	3707.5	-6.10	NA	28.00	21.90	30.00	0.0308	1.0000	2.00	9.01	2.00	Pass
NR Band n77 (3700-3980)(MIMO)	3707.5	-6.10	-6.10	30.00	23.90	30.00	0.0488	1.0000	0.00	7.01	0.00	Pass
NR Band n78 (3450-3550)	3455.0	-6.10	NA	28.00	21.90	30.00	0.0308	1.0000	2.00	9.01	2.00	Pass
NR Band n78 (3450-3550)(MIMO)	3455.0	-6.10	-6.10	30.00	23.90	30.00	0.0488	1.0000	0.00	7.01	0.00	Pass
NR Band n78 (3700-3800)	3705.0	-6.10	NA	28.00	21.90	30.00	0.0308	1.0000	2.00	9.01	2.00	Pass
NR Band n78 (3700-3800)(MIMO)	3705.0	-6.10	-6.10	30.00	23.90	30.00	0.0488	1.0000	0.00	7.01	0.00	Pass
Bluetooth	2402.0	5.00	NA	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA
WLAN2.4GHz	2412.0	5.00	NA	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA
WLAN5GHz	5180.0	5.00	NA	23.00	28.00	NA	0.1255	1.0000	NA	NA	NA	NA

Note:

- 1. This MPE analysis is applicable to any collocated transmitters with transmit power for WLAN is less than or equal to 28dBm and for Bluetooth is less than or equal to 28dBm.
- 2. A maximum antenna gain of 5dBi for WLAN/BT has been assumed for all collocated antennas.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, considering a for a for a for a for a formal to the first of the formal formal formal for the first of the first

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000 t (86–512) 62992980 t (86–512) 62992980



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 11 of 12

Due to the EUT support NR ENDC and CA

Both LTE and NR/LTE band can transmit simultaneously, the formula of the calculated the MPE is:

$$\sum_{i=1}^{n} \frac{S_{E_{i}}(dutyfactor)}{MPE_{E_{i}}} < 1$$

NOTE The corresponding MEs must be expressed in terms of power density in the above summation Therefore, the worst-case(DC_26A_n41A) situation is 0.2238+0.1502=0.3740,which is less than "1", this confirmed that the device comply with MPE limit.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printe overleaf, available on request or accessible at https://www.sgs.com/en/Ferms-and-Conditions.aspx.and, for electronic format documents subject to Terms and Conditions for Electronic Documents at https://www.sgs.com/en/Ferms-and-Conditions/Ferms-a-Document.aspx.attention is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction document comment cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content cappearance of this document is unlawful and offenders may be prosecuted to the fullest stort of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

South of No. 6 Pfart, No. 1, Runsheng Read, Suchou Industrial Park, Suchou Area, China (Jangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000



Report No.: SEWM2304000122RG04

Rev.: 01 Page: 12 of 12

3.1.4 Exposure calculations for multiple sources

When a number of sources at different frequencies, and/or broadband sources, contribute to the total exposure, it becomes necessary to weigh each contribution relative to the MPE in accordance with the provisions of Table(A) and Table(B). To comply with the MPE, the fraction of the MPE in terms of E2, H2 (or power density) incurred within each frequency interval should be determined and the sum of all such fractions should not exceed unity.

In order to ensure compliance with the MPE for a controlled environment, the sum of the ratios of the power density to the corresponding MPE should not exceed unity. That is

$$\sum_{i=1}^{n} \frac{S_i}{MPE_i} \le 1$$

The product also has multiple transmitters The Simultaneous Transmission Possibilities are as below:

Simultaneous Tx Combination	Configuration	
1	WWAN + WiFi 2.4G + WiFi 5G + Bluetooth	

No.	Mode	Power Density (mW/cm²)	MPE Limit (mW/cm²)	Result Ratio	Total Ratio	Limit	Result
	NR Band n71	0.0833	0.4437	0.1877			
1	Bluetooth	ooth 0.1255 1.0000 0.1255		0.5642	4.00	Dana	
	WiFi 2.4G	0.1255	1.0000	0.1255	0.5642	1.00	Pass
	WiFi 5G	0.1255	1.0000	0.1255			

Note: Considering the WWAN module collocation with the WLAN and Bluetooth transmitter of the EIRP performance listed in the table above, the aggregated (power density /limit) is smaller than 1, and MPE of 3 collocated transmitters is compliant.

---End of Report---



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document cannot be reproduced except in full, without prior written approval of the Company Any unauthorized alteration, forgery or faisification of the content or except in full, without prior written approval of the Company Any unauthorized alteration, forgery or faisification of the content or results shown in this test report refer only to the sample (s) tested and such sample (s) are retained for 30 days only.

**Authorized Act as the Authorized and such sample (s) are retained for 30 days only.

South of No. 6 Plant, No. 1, Runsheng Read, Suzhou Industrial Park, Suzhou Area, China (Jiangsu) Pilot Free Trade Zone 215000 中国 - 苏州 - 中国(江苏)自由贸易试验区苏州片区苏州工业园区润胜路1号的6号厂房南部 邮编: 215000

5000 t (86–512) 62992980 5000 t (86–512) 62992980