

FCC Test Report (BT-LE)

Report No.: RF190308C34-3

FCC ID: HD5-CN85L0N

Test Model: CN85L0N

Received Date: Mar. 08, 2019

Test Date: Apr. 18 to 29, 2019

Issued Date: May 30, 2019

Applicant: Honeywell International Inc.

Address: 9680 Old Bailes Road, Fort Mill, SC 29707 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

Test Location: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

**FCC Registration /
Designation Number:** 723255 / TW2022



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	4
1 Certificate of Conformity.....	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information.....	7
3.1 General Description of EUT (BT-LE)	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement.....	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures.....	17
4.1.4 Deviation from Test Standard	17
4.1.5 Test Setup.....	18
4.1.6 EUT Operating Conditions.....	19
4.1.7 Test Results (Mode 1).....	20
4.1.8 Test Results (Mode 2).....	25
4.1.9 Test Results (Mode 3).....	30
4.2 6dB Bandwidth Measurement	35
4.2.1 Limits of 6dB Bandwidth Measurement	35
4.2.2 Test Setup.....	35
4.2.3 Test Instruments	35
4.2.4 Test Procedure	35
4.2.5 Deviation from Test Standard	35
4.2.6 EUT Operating Conditions.....	35
4.2.7 Test Results (Mode 1).....	36
4.2.8 Test Results (Mode 2).....	37
4.2.9 Test Results (Mode 3).....	38
4.3 Conducted Output Power Measurement.....	39
4.3.1 Limits of Conducted Output Power Measurement	39
4.3.2 Test Setup.....	39
4.3.3 Test Instruments	39
4.3.4 Test Procedures.....	39
4.3.5 Deviation from Test Standard	39
4.3.6 EUT Operating Conditions.....	39
4.3.7 Test Results (Mode 1).....	40
4.3.8 Test Results (Mode 2).....	40
4.3.9 Test Results (Mode 3).....	41
4.4 Power Spectral Density Measurement.....	42
4.4.1 Limits of Power Spectral Density Measurement	42
4.4.2 Test Setup.....	42
4.4.3 Test Instruments	42
4.4.4 Test Procedure	42
4.4.5 Deviation from Test Standard	42
4.4.6 EUT Operating Condition	42
4.4.7 Test Results (Mode 1).....	43
4.4.8 Test Results (Mode 2).....	44

4.4.9 Test Results (Mode 3).....	45
4.5 Conducted Out of Band Emission Measurement.....	46
4.5.1 Limits of Conducted Out of Band Emission Measurement.....	46
4.5.2 Test Setup.....	46
4.5.3 Test Instruments	46
4.5.4 Test Procedure	46
4.5.5 Deviation from Test Standard	46
4.5.6 EUT Operating Condition	46
4.5.7 Test Results (Mode 1).....	47
4.5.8 Test Results (Mode 2).....	48
4.5.9 Test Results (Mode 3).....	49
5 Pictures of Test Arrangements.....	50
Appendix – Information of the Testing Laboratories	51

Release Control Record

Issue No.	Description	Date Issued
RF190308C34-3	Original release.	May 30, 2019

1 Certificate of Conformity

Product: Mobile computer

Brand: Honeywell

Test Model: CN85L0N

Sample Status: ENGINEERING SAMPLE

Applicant: Honeywell International Inc.

Test Date: Apr. 18 to 29, 2019

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)
ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Phoenix Huang, **Date:** May 30, 2019
Phoenix Huang / Specialist

Approved by : May Chen, **Date:** May 30, 2019
May Chen / Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	NA	Without AC power port of the EUT.
15.205 / 15.209 / 15.247(d)	Radiated Emissions and Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -5.8dB at 4960.00MHz.
15.247(d)	Antenna Port Emission	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	Antenna connector is POGO pin not a standard connector.

Note:

Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.1 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.1 dB
	6GHz ~ 18GHz	5.0 dB
	18GHz ~ 40GHz	5.2 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT (BT-LE)

Product	Mobile computer
Brand	Honeywell
Test Model	CN85L0N
Status of EUT	ENGINEERING SAMPLE
HW Version	V1.0
HW P/N	V2.0 (DVT)
Software Version	OS.02.001-HON.01.102
SW P/N	86.00.00-Debug(0633)
Power Supply Rating	3.85Vdc from battery
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	Up to 2Mbps
Operating Frequency	2.402 ~ 2.480GHz
Number of Channel	40
Output Power	For Radio 1 LE 1M: 1.297 mW LE 2M (BT 5.0): 1.901 mW For Radio 2 LE 1M: 2.382 mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Battery x 1, Touch pen x 1, Handstrap x 1
Data Cable Supplied	NA

Note:

1. There're 2 configurations for the EUT listed as below.

Item
Sample A: Scanner: N6703ER with Keypad 1 (Number) + 4G RAM
Sample B: Scanner: N6703ER with Keypad 2 (Letter) + 4G RAM
Note: From the above samples, the Sample B was selected for the test and its data was recorded in this report.

2. There are WLAN, Bluetooth, Zigbee and NFC technology used for the EUT. The EUT has below radios as following table:

Radio 1	Radio 2	Radio 3	Radio 4
WLAN+BT 1	Zigbee+BT 2	NFC	Wireless charger (Rx)

Note: For Bluetooth technology the Radio 1 support BT 5.0 dual mode, the Radio 2 support BT-LE (4.2) single mode only.

3. Simultaneously transmission condition.

Condition	Technology		
1	WLAN 2.4GHz	NFC	Zigbee
2	WLAN 5GHz	NFC	Zigbee
3	Bluetooth (Radio 1)	NFC	Zigbee

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

4. The EUT needs to be supplied from battery, the information is as below table:

Brand	Model No.	Spec.
Inventus Power, Inc. / Honeywell	CW-BAT	3.85Vdc, 5800mAh, 22.3Wh

5. The antennas provided to the EUT, please refer to the following table:

Radio 1					
WLAN Antenna Spec. / Bluetooth Antenna No. 1 Spec.					
Chain No.	Antenna Gain include trace loss (dBi)	Frequency range (GHz)	Antenna type	Connector type	Trace loss (dB)
Chain 0	0.4	2.4~2.4835	PIFA	POGO pin	1.4
	1.62	5.15~5.25			2
	1.62	5.25~5.35			2
	1.15	5.47~5.725			2.4
	1.15	5.725~5.85			2.4
Chain 1	1.7	2.4~2.4835	PIFA	POGO pin	0.3
	1.3	5.15~5.25			0.9
	1.3	5.25~5.35			0.9
	2	5.47~5.725			0.9
	2	5.725~5.85			0.9
Radio 2					
Bluetooth Antenna No. 2 Spec. / Zigbee Antenna Spec.					
Antenna Gain include trace loss (dBi)	Frequency range (GHz)	Antenna type	Connector type	Trace loss (dB)	
-0.1	2.4~2.4835	PIFA	POGO pin	0.5	
Radio 3					
NFC Antenna Spec.					
Frequency range (MHz)		Antenna type		Connector type	
13~14		Loop		NA	

6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

40 channels are provided for BT-LE mode:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	APCM	
1	√	√	-	√	Radio 1: Technology LE 1M (BT 4.2)
2	√	√	-	√	Radio 1: Technology LE 2M (BT 5.0)
3	√	√	-	√	Radio 2: Technology LE 1M (BT 4.2)

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note:

1. No need to concern of Conducted Emission due to the EUT is powered by battery.
2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane (below 1GHz) & Z-plane (above 1GHz)**.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Radio 1			
AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
0 to 39	0, 19, 39	GFSK	2
Radio 2			
AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Radio 1			
AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	19	GFSK	1
0 to 39	39	GFSK	2
Radio 2			
AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	39	GFSK	1

Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

Radio 1			
AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1
0 to 39	0, 19, 39	GFSK	2
Radio 2			
AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TYPE	DATA RATE (Mbps)
0 to 39	0, 19, 39	GFSK	1

Test Condition:


APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE $\geq$ 1G	23deg. C, 69%RH	3.85Vdc	Andy Ho
RE<1G	23deg. C, 68%RH	3.85Vdc	Andy Ho
APCM	25deg. C, 60%RH	3.85Vdc	Anderson Chen

3.3 Duty Cycle of Test Signal

Radio 1: Technology LE 1M (BT 4.2)

Duty cycle of test signal is < 98 %, duty factor shall be considered.


Duty cycle = $0.388 \text{ ms} / 0.627 \text{ ms} = 0.619$, Duty factor = $10 * \log(1/0.619) = 2.08$



Radio 1: Technology LE 2M (BT 5.0)

Duty cycle of test signal is < 98 %, duty factor shall be considered.


Duty cycle = $0.387 \text{ ms} / 0.632 \text{ ms} = 0.612$, Duty factor = $10 * \log(1/0.612) = 2.13$



Radio 2: Technology LE 1M (BT 4.2)

Duty cycle of test signal is < 98 %, duty factor shall be considered.

Duty cycle = $0.142 \text{ ms} / 0.382 \text{ ms} = 0.372$, Duty factor = $10 * \log(1/0.372) = 4.3$




3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	MicroSD Card	Transcend	NA	NA	NA	Provided by Lab
B.	SIM Card	R&S	CRT-Z3	NA	NA	Provided by Lab
C.	NFC Card	UGSI	NA	NA	NA	Supplied by client

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247)

KDB 558074 D01 15.247 Meas Guidance v05r02

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	July 12, 2018	July 11, 2019
Pre-Amplifier EMCI	EMC001340	980142	Jan. 25, 2019	Jan. 24, 2020
Loop Antenna Electro-Metrics	EM-6879	269	Sep. 07, 2018	Sep. 06, 2019
RF Cable	NA	LOOPCAB-001	Jan. 14, 2019	Jan. 13, 2020
RF Cable	NA	LOOPCAB-002	Jan. 14, 2019	Jan. 13, 2020
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 05, 2018	May 04, 2019
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Nov. 22, 2018	Nov. 21, 2019
RF Cable	8D	966-3-1	Mar. 18, 2019	Mar. 17, 2020
RF Cable	8D	966-3-2	Mar. 18, 2019	Mar. 17, 2020
RF Cable	8D	966-3-3	Mar. 18, 2019	Mar. 17, 2020
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Sep. 27, 2018	Sep. 26, 2019
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Nov. 25, 2018	Nov. 24, 2019
Pre-Amplifier EMCI	EMC12630SE	980384	Jan. 28, 2019	Jan. 27, 2020
RF Cable	EMC104-SM-SM-1200	160922	Jan. 28, 2019	Jan. 27, 2020
RF Cable	EMC104-SM-SM-2000	180601	June 12, 2018	June 11, 2019
RF Cable	EMC104-SM-SM-6000	180602	June 12, 2018	June 11, 2019
Spectrum Analyzer Keysight	N9030A	MY54490679	July 23, 2018	July 22, 2019
Pre-Amplifier EMCI	EMC184045SE	980387	Jan. 28, 2019	Jan. 27, 2020
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170519	Nov. 25, 2018	Nov. 24, 2019
RF Cable	EMC102-KM-KM-1200	160924	Jan. 28, 2019	Jan. 27, 2020
RF Cable	EMC102-KM-KM-1200	160925	Jan. 28, 2019	Jan. 27, 2020
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Spectrum Analyzer R&S	FSV40	100964	June 20, 2018	June 19, 2019
Power meter Anritsu	ML2495A	1014008	May 09, 2018	May 08, 2019
Power sensor Anritsu	MA2411B	0917122	May 09, 2018	May 08, 2019
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 15, 2019	Apr. 14, 2020

Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in 966 Chamber No. 3.
3. Loop antenna was used for all emissions below 30 MHz.
4. Tested Date: Apr. 18 to 29, 2019

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Controlling software (QRCT_V3.0.298.0) has been activated to set the EUT under transmission condition continuously.

4.1.7 Test Results (Mode 1)

Above 1GHz Data:

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.2 PK	74.0	-19.8	1.05 H	249	56.3	-2.1
2	2390.00	42.9 AV	54.0	-11.1	1.05 H	249	45.0	-2.1
3	*2402.00	96.2 PK			1.05 H	249	98.3	-2.1
4	*2402.00	94.9 AV			1.05 H	249	97.0	-2.1
5	4804.00	38.3 PK	74.0	-35.7	2.47 H	209	36.2	2.1
6	4804.00	30.2 AV	54.0	-23.8	2.47 H	209	28.1	2.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.8 PK	74.0	-21.2	2.76 V	318	54.9	-2.1
2	2390.00	41.7 AV	54.0	-12.3	2.76 V	318	43.8	-2.1
3	*2402.00	93.3 PK			2.76 V	318	95.4	-2.1
4	*2402.00	91.8 AV			2.76 V	318	93.9	-2.1
5	4804.00	39.6 PK	74.0	-34.4	1.25 V	134	37.5	2.1
6	4804.00	31.4 AV	54.0	-22.6	1.25 V	134	29.3	2.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	95.7 PK			1.08 H	232	98.0	-2.3
2	*2440.00	94.8 AV			1.08 H	232	97.1	-2.3
3	4880.00	38.5 PK	74.0	-35.5	2.53 H	216	36.4	2.1
4	4880.00	30.2 AV	54.0	-23.8	2.53 H	216	28.1	2.1
5	7320.00	43.0 PK	74.0	-31.0	1.59 H	183	35.0	8.0
6	7320.00	33.2 AV	54.0	-20.8	1.59 H	183	25.2	8.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	92.6 PK			2.74 V	343	94.9	-2.3
2	*2440.00	91.5 AV			2.74 V	343	93.8	-2.3
3	4880.00	39.3 PK	74.0	-34.7	1.22 V	153	37.2	2.1
4	4880.00	31.0 AV	54.0	-23.0	1.22 V	153	28.9	2.1
5	7320.00	46.0 PK	74.0	-28.0	2.26 V	152	38.0	8.0
6	7320.00	35.4 AV	54.0	-18.6	2.26 V	152	27.4	8.0

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	97.0 PK			1.01 H	237	99.4	-2.4
2	*2480.00	95.7 AV			1.01 H	237	98.1	-2.4
3	2483.50	54.0 PK	74.0	-20.0	1.01 H	237	56.4	-2.4
4	2483.50	42.4 AV	54.0	-11.6	1.01 H	237	44.8	-2.4
5	4960.00	38.8 PK	74.0	-35.2	2.36 H	206	36.5	2.3
6	4960.00	30.4 AV	54.0	-23.6	2.36 H	206	28.1	2.3
7	7440.00	43.5 PK	74.0	-30.5	1.52 H	198	35.2	8.3
8	7440.00	33.4 AV	54.0	-20.6	1.52 H	198	25.1	8.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.0 PK			2.80 V	343	95.4	-2.4
2	*2480.00	91.7 AV			2.80 V	343	94.1	-2.4
3	2483.50	52.7 PK	74.0	-21.3	2.80 V	343	55.1	-2.4
4	2483.50	41.4 AV	54.0	-12.6	2.80 V	343	43.8	-2.4
5	4960.00	39.2 PK	74.0	-34.8	1.37 V	159	36.9	2.3
6	4960.00	30.9 AV	54.0	-23.1	1.37 V	159	28.6	2.3
7	7440.00	45.6 PK	74.0	-28.4	2.29 V	171	37.3	8.3
8	7440.00	35.0 AV	54.0	-19.0	2.29 V	171	26.7	8.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.01	26.3 QP	40.0	-13.7	1.00 H	308	34.9	-8.6
2	140.15	23.4 QP	43.5	-20.1	1.50 H	302	31.6	-8.2
3	195.24	23.0 QP	43.5	-20.5	1.00 H	179	33.2	-10.2
4	345.19	25.3 QP	46.0	-20.7	1.50 H	246	31.0	-5.7
5	439.04	27.9 QP	46.0	-18.1	2.50 H	163	31.2	-3.3
6	543.78	28.4 QP	46.0	-17.6	1.00 H	115	29.5	-1.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 19	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.15	26.2 QP	40.0	-13.8	1.50 V	302	34.8	-8.6
2	137.38	23.4 QP	43.5	-20.1	2.24 V	165	31.9	-8.5
3	161.19	23.6 QP	43.5	-19.9	1.00 V	238	31.8	-8.2
4	194.95	22.1 QP	43.5	-21.4	1.50 V	204	32.2	-10.1
5	311.59	23.1 QP	46.0	-22.9	1.50 V	305	29.3	-6.2
6	465.70	27.9 QP	46.0	-18.1	1.50 V	174	30.6	-2.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.1.8 Test Results (Mode 2)

Above 1GHz Data:

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.8 PK	74.0	-19.2	1.02 H	247	56.9	-2.1
2	2390.00	43.3 AV	54.0	-10.7	1.02 H	247	45.4	-2.1
3	*2402.00	96.0 PK			1.02 H	247	98.1	-2.1
4	*2402.00	94.6 AV			1.02 H	247	96.7	-2.1
5	4804.00	38.2 PK	74.0	-35.8	2.47 H	216	36.1	2.1
6	4804.00	30.2 AV	54.0	-23.8	2.47 H	216	28.1	2.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	53.3 PK	74.0	-20.7	2.79 V	313	55.4	-2.1
2	2390.00	42.1 AV	54.0	-11.9	2.79 V	313	44.2	-2.1
3	*2402.00	92.9 PK			2.79 V	313	95.0	-2.1
4	*2402.00	91.3 AV			2.79 V	313	93.4	-2.1
5	4804.00	40.1 PK	74.0	-33.9	1.19 V	137	38.0	2.1
6	4804.00	31.7 AV	54.0	-22.3	1.19 V	137	29.6	2.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	95.1 PK			1.04 H	231	97.4	-2.3
2	*2440.00	94.5 AV			1.04 H	231	96.8	-2.3
3	4880.00	37.9 PK	74.0	-36.1	2.47 H	222	35.8	2.1
4	4880.00	29.7 AV	54.0	-24.3	2.47 H	222	27.6	2.1
5	7320.00	42.4 PK	74.0	-31.6	1.59 H	167	34.4	8.0
6	7320.00	32.9 AV	54.0	-21.1	1.59 H	167	24.9	8.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	93.2 PK			2.68 V	331	95.5	-2.3
2	*2440.00	91.8 AV			2.68 V	331	94.1	-2.3
3	4880.00	39.4 PK	74.0	-34.6	1.24 V	154	37.3	2.1
4	4880.00	31.3 AV	54.0	-22.7	1.24 V	154	29.2	2.1
5	7320.00	45.5 PK	74.0	-28.5	2.23 V	161	37.5	8.0
6	7320.00	34.9 AV	54.0	-19.1	2.23 V	161	26.9	8.0

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	97.0 PK			1.03 H	249	99.4	-2.4
2	*2480.00	95.5 AV			1.03 H	249	97.9	-2.4
3	2483.50	53.6 PK	74.0	-20.4	1.03 H	249	56.0	-2.4
4	2483.50	42.0 AV	54.0	-12.0	1.03 H	249	44.4	-2.4
5	4960.00	39.1 PK	74.0	-34.9	2.33 H	213	36.8	2.3
6	4960.00	30.7 AV	54.0	-23.3	2.33 H	213	28.4	2.3
7	7440.00	44.2 PK	74.0	-29.8	1.56 H	189	35.9	8.3
8	7440.00	33.9 AV	54.0	-20.1	1.56 H	189	25.6	8.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	93.4 PK			2.76 V	329	95.8	-2.4
2	*2480.00	91.9 AV			2.76 V	329	94.3	-2.4
3	2483.50	52.1 PK	74.0	-21.9	2.76 V	329	54.5	-2.4
4	2483.50	41.0 AV	54.0	-13.0	2.76 V	329	43.4	-2.4
5	4960.00	38.8 PK	74.0	-35.2	1.39 V	174	36.5	2.3
6	4960.00	30.5 AV	54.0	-23.5	1.39 V	174	28.2	2.3
7	7440.00	45.1 PK	74.0	-28.9	2.33 V	162	36.8	8.3
8	7440.00	34.7 AV	54.0	-19.3	2.33 V	162	26.4	8.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.20	25.7 QP	40.0	-14.3	1.50 H	263	34.3	-8.6
2	140.15	23.3 QP	43.5	-20.2	1.50 H	302	31.5	-8.2
3	195.20	23.4 QP	43.5	-20.1	1.50 H	163	33.6	-10.2
4	345.16	24.5 QP	46.0	-21.5	1.50 H	311	30.2	-5.7
5	439.10	28.6 QP	46.0	-17.4	1.00 H	281	31.9	-3.3
6	543.48	28.3 QP	46.0	-17.7	1.00 H	164	29.4	-1.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.15	25.9 QP	40.0	-14.1	1.50 V	241	34.5	-8.6
2	137.08	23.2 QP	43.5	-20.3	1.50 V	243	31.7	-8.5
3	161.21	23.1 QP	43.5	-20.4	1.50 V	169	31.3	-8.2
4	194.91	22.3 QP	43.5	-21.2	1.00 V	119	32.4	-10.1
5	311.89	22.7 QP	46.0	-23.3	2.00 V	163	28.9	-6.2
6	465.66	28.1 QP	46.0	-17.9	1.50 V	143	30.8	-2.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.1.9 Test Results (Mode 3)

Above 1GHz Data:

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.0 PK	74.0	-22.0	1.03 H	156	54.1	-2.1
2	2390.00	42.6 AV	54.0	-11.4	1.03 H	156	44.7	-2.1
3	*2402.00	93.2 PK			1.03 H	156	95.3	-2.1
4	*2402.00	91.9 AV			1.03 H	156	94.0	-2.1
5	4804.00	50.9 PK	74.0	-23.1	1.02 H	225	48.8	2.1
6	4804.00	47.0 AV	54.0	-7.0	1.02 H	225	44.9	2.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.5 PK	74.0	-19.5	1.22 V	72	56.6	-2.1
2	2390.00	44.1 AV	54.0	-9.9	1.22 V	72	46.2	-2.1
3	*2402.00	94.5 PK			1.22 V	72	96.6	-2.1
4	*2402.00	93.5 AV			1.22 V	72	95.6	-2.1
5	4804.00	48.5 PK	74.0	-25.5	1.33 V	165	46.4	2.1
6	4804.00	42.2 AV	54.0	-11.8	1.33 V	165	40.1	2.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	92.9 PK			1.00 H	184	95.2	-2.3
2	*2440.00	91.6 AV			1.00 H	184	93.9	-2.3
3	4880.00	51.5 PK	74.0	-22.5	1.04 H	215	49.4	2.1
4	4880.00	47.7 AV	54.0	-6.3	1.04 H	215	45.6	2.1
5	7320.00	47.3 PK	74.0	-26.7	1.51 H	231	39.3	8.0
6	7320.00	34.4 AV	54.0	-19.6	1.51 H	231	26.4	8.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2440.00	94.3 PK			1.20 V	76	96.6	-2.3
2	*2440.00	93.8 AV			1.20 V	76	96.1	-2.3
3	4880.00	48.9 PK	74.0	-25.1	1.41 V	162	46.8	2.1
4	4880.00	42.8 AV	54.0	-11.2	1.41 V	162	40.7	2.1
5	7320.00	47.6 PK	74.0	-26.4	1.03 V	252	39.6	8.0
6	7320.00	34.4 AV	54.0	-19.6	1.03 V	252	26.4	8.0

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	92.5 PK			1.04 H	182	94.9	-2.4
2	*2480.00	91.4 AV			1.04 H	182	93.8	-2.4
3	2483.50	62.1 PK	74.0	-11.9	1.04 H	182	64.5	-2.4
4	2483.50	43.9 AV	54.0	-10.1	1.04 H	182	46.3	-2.4
5	4960.00	52.6 PK	74.0	-21.4	1.00 H	221	50.3	2.3
6	4960.00	48.2 AV	54.0	-5.8	1.00 H	221	45.9	2.3
7	7440.00	47.8 PK	74.0	-26.2	1.53 H	213	39.5	8.3
8	7440.00	34.7 AV	54.0	-19.3	1.53 H	213	26.4	8.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	94.8 PK			1.14 V	89	97.2	-2.4
2	*2480.00	94.2 AV			1.14 V	89	96.6	-2.4
3	2483.50	63.4 PK	74.0	-10.6	1.14 V	89	65.8	-2.4
4	2483.50	44.0 AV	54.0	-10.0	1.14 V	89	46.4	-2.4
5	4960.00	48.6 PK	74.0	-25.4	1.31 V	168	46.3	2.3
6	4960.00	42.3 AV	54.0	-11.7	1.31 V	168	40.0	2.3
7	7440.00	47.8 PK	74.0	-26.2	1.03 V	225	39.5	8.3
8	7440.00	34.4 AV	54.0	-19.6	1.03 V	225	26.1	8.3

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency.


Below 1GHz Data:

CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.01	25.8 QP	40.0	-14.2	1.50 H	264	34.4	-8.6
2	140.15	22.8 QP	43.5	-20.7	2.00 H	243	31.0	-8.2
3	195.24	22.9 QP	43.5	-20.6	1.00 H	264	33.1	-10.2
4	345.19	24.6 QP	46.0	-21.4	1.50 H	304	30.3	-5.7
5	439.04	27.6 QP	46.0	-18.4	2.00 H	155	30.9	-3.3
6	543.78	27.8 QP	46.0	-18.2	1.00 H	263	28.9	-1.1

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	49.16	25.6 QP	40.0	-14.4	1.50 V	241	34.2	-8.6
2	137.36	23.2 QP	43.5	-20.3	2.00 V	295	31.7	-8.5
3	161.19	23.5 QP	43.5	-20.0	1.00 V	164	31.7	-8.2
4	194.95	22.0 QP	43.5	-21.5	1.50 V	263	32.1	-10.1
5	311.59	22.8 QP	46.0	-23.2	1.50 V	263	29.0	-6.2
6	465.70	27.5 QP	46.0	-18.5	1.50 V	255	30.2	-2.7

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30MHz~1000MHz.
5. The emission levels were very low against the limit of frequency range 9kHz~30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




4.2 6dB Bandwidth Measurement

4.2.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.2.2 Test Setup



4.2.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.2.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.2.5 Deviation from Test Standard


No deviation.

4.2.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.


4.2.7 Test Results (Mode 1)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.67	0.5	Pass
19	2440	0.68	0.5	Pass
39	2480	0.68	0.5	Pass



4.2.8 Test Results (Mode 2)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	1.14	0.5	Pass
19	2440	1.16	0.5	Pass
39	2480	1.15	0.5	Pass




4.2.9 Test Results (Mode 3)

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
0	2402	0.68	0.5	Pass
19	2440	0.71	0.5	Pass
39	2480	0.69	0.5	Pass

Spectrum Plot of Worst Value

CH 0




4.3 Conducted Output Power Measurement

4.3.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedures

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

Same as Item 4.2.6.

4.3.7 Test Results (Mode 1)

FOR PEAK POWER

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	1.072	0.30	30	Pass
19	2440	1.297	1.13	30	Pass
39	2480	1.091	0.38	30	Pass

FOR AVERAGE POWER

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	1.023	0.10
19	2440	0.9376	-0.28
39	2480	1.059	0.25

4.3.8 Test Results (Mode 2)

FOR PEAK POWER

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	1.758	2.45	30	Pass
19	2440	1.507	1.78	30	Pass
39	2480	1.901	2.79	30	Pass

FOR AVERAGE POWER

Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	1.596	2.03
19	2440	1.324	1.22
39	2480	1.718	2.35

4.3.9 Test Results (Mode 3)

FOR PEAK POWER

Channel	Frequency (MHz)	Peak Power (mW)	Peak Power (dBm)	Limit (dBm)	Pass/Fail
0	2402	2.239	3.50	30	Pass
19	2440	2.307	3.63	30	Pass
39	2480	2.382	3.77	30	Pass

FOR AVERAGE POWER


Channel	Frequency (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.208	3.44
19	2440	2.27	3.56
39	2480	2.333	3.68

4.4 Power Spectral Density Measurement

4.4.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm in any 3 kHz.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

4.4.5 Deviation from Test Standard


No deviation.

4.4.6 EUT Operating Condition

Same as Item 4.2.6.


4.4.7 Test Results (Mode 1)

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	-13.41	8	Pass
19	2440	-14.56	8	Pass
39	2480	-13.49	8	Pass



4.4.8 Test Results (Mode 2)

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	-16.24	8	Pass
19	2440	-17.17	8	Pass
39	2480	-16.02	8	Pass




4.4.9 Test Results (Mode 3)

Channel	Freq. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	Pass /Fail
0	2402	-10.48	8	Pass
19	2440	-9.92	8	Pass
39	2480	-9.52	8	Pass

Spectrum Plot of Worst Value

CH 39




4.5 Conducted Out of Band Emission Measurement

4.5.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

4.5.5 Deviation from Test Standard

No deviation.


4.5.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest and highest channel frequencies individually.


4.5.7 Test Results (Mode 1)

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.


CH 0




CH 19




CH 39



CH 0 Band edge




CH 39 Band edge




4.5.8 Test Results (Mode 2)

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.


CH 0




CH 19




CH 39



CH 0 Band edge




CH 39 Band edge




4.5.9 Test Results (Mode 3)

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.


CH 0




CH 19




CH 39



CH 0 Band edge



CH 39 Band edge



5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---