



REPORT No.: SZ22080354W01

TEST REPORT

APPLICANT : FJ Dynamics Co.,Ltd.

PRODUCT NAME : Satellite Navigation Base Station

MODEL NAME : FJ-RTK P9000A

BRAND NAME : FJDynamics

FCC ID : 2A2LL-FJ-RTKP9000A

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2022-09-06

TEST DATE : 2022-09-15 to 2023-04-30

ISSUE DATE : 2023-06-16

Edited by:

Su Xiaoxian

Su Xiaoxian(Rapporteur)

Approved by:

Shen Junsheng

Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1. Applicant and Manufacturer Information	3
1.2. Equipment Under Test (EUT) Description	3
1.3. Modulation Type and Data Rate of EUT	4
1.4. The Channel Number and Frequency	5
1.5. Test Standards and Results	6
1.6. Environmental Conditions	7
2. 47 CFR Part 15C Requirements	8
2.1. Antenna Requirement	8
2.2. Duty Cycle of Test Signal	9
2.3. Maximum Peak and Average Conducted Output Power	13
2.4. Bandwidth	16
2.5. Conducted Spurious Emissions and Band Edge	25
2.6. Power Spectral Density	38
2.7. Conducted Emission	47
2.8. Restricted Frequency Bands	51
2.9. Radiated Emission	64
Annex A Test Uncertainty	80
Annex B Testing Laboratory Information	81

Change History		
Version	Date	Reason for change
1.0	2023-06-16	First edition



1. Technical Information

Note: Provide by applicant.

1.1. Applicant and Manufacturer Information

Applicant:	FJ Dynamics Co.,Ltd.
Applicant Address:	1709, WeiXing Building, 61 GaoXin South 9th Rd, Nanshan District, Shenzhen, China
Manufacturer:	FJ Dynamics Co.,Ltd.
Manufacturer Address:	1709, WeiXing Building, 61 GaoXin South 9th Rd, Nanshan District, Shenzhen, China

1.2. Equipment Under Test (EUT) Description

Product Name:	Satellite Navigation Base Station	
Sample No.:	17#	
Hardware Version:	Q0039009	
Software Version:	R2013NewBase_v1.0.1.5.dfu	
Modulation Technology:	DSSS, OFDM	
Modulation Type:	Refer to section1.3	
Operating Frequency Range:	802.11b/g/ n (HT20): 2412MHz–2462MHz 802.11n (HT40): 2422MHz–2452MHz	
Antenna Type:	PCB Antenna	
Antenna Gain:	3.10dBi	
Accessory Information:	Battery	
	Brand Name:	N/A
	Model No.:	NP-F750/F770
	Serial No.:	N/A
	Capacity:	2*5200mAh
	Rated Voltage:	7.4V
	Charge Limit:	8.4V
	Manufacturer:	Dongguan King Power Digital Technology Co., Ltd

Note 1: We use the dedicated software to control the EUT continuous transmission.

Note 2: For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.3. Modulation Type and Data Rate of EUT

Modulation technology	Modulation Type	Data Rate (Mbps) Note1
DSSS (802.11b)	DBPSK	1
	DQPSK	2
	CCK	5.5/ 11
OFDM (802.11g)	BPSK	6 / 9
	QPSK	12 / 18
	16QAM	24 / 36
	64QAM	48 / 54
OFDM (802.11n (HT20))	BPSK	6.5
	QPSK	13/19.5
	16QAM	26/39
	64QAM	52/58.5/65
OFDM (802.11n (HT40))	BPSK	13.5
	QPSK	27/40.5
	16QAM	54/81/108
	64QAM	121.5/135

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.



1.4. The Channel Number and Frequency

Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11b/g/ n (HT20)	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432		
	6	2437		
	7	2442		
Test Mode	Channel	Frequency (MHz)	Channel	Frequency (MHz)
802.11n (HT40)	3	2422	8	2447
	4	2427	9	2452
	5	2432		
	6	2437		
	7	2442		

Note 1: The black bold channels were selected for test.



1.5. Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart C for the EUT FCC ID Certification:

No.	Identity	Document Title
1	47 CFR Part 15	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Test Date	Test Engineer	Result	Method Determination /Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	No deviation
2	N/A	Duty Cycle Of Test Signal	Sep 15, 2022	Zhong Yanshan	PASS	No deviation
3	15.247(b)	Maximum Peak and Average Conducted Output Power	Sep 15, 2022	Zhong Yanshan	PASS	No deviation
4	15.247(a)	Bandwidth	Sep 16, 2022	Zhong Yanshan	PASS	No deviation
5	15.247(d)	Conducted Spurious Emission and Band Edge	Sep 16, 2022	Zhong Yanshan	PASS	No deviation
6	15.247(e)	Power Spectral Density	Sep 16, 2022	Zhong Yanshan	PASS	No deviation
7	15.207	Conducted Emission	Sep 16, 2022	Zhong Yanshan	PASS	No deviation
8	15.247(d)	Restricted Frequency Bands	Aug 22, 2022	Wu Zhaoling	PASS	No deviation
9	15.209, 15.247(d)	Radiated Emission	Feb 30, 2023	Su Zhan	PASS	No deviation

Note 1: The tests were performed according to the method of measurements prescribed in ANSIC63.10-2013, KDB558074 D01 v05r02.



Note 2: The path loss during the RF test is calibrated to correct the results by the offset setting in the test equipments. The ref offset 11.5dB contains two parts that cable loss 1.5dB and Attenuator 10dB.

Note 3: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.

Note 4: When the test result is a critical value, we will use the measurement uncertainty give the judgment result based on the 95% confidence intervals.

1.6. Environmental Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106



2. 47 CFR Part 15C Requirements

2.1. Antenna Requirement

2.1.1. Applicable Standard

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1.2. Result:

The EUT has a internal PCB antenna coupled with the I-PEX connector. Please refer to the EUT photos.

2.2. Duty Cycle of Test Signal


2.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this subclause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be nonconstant.

2.2.2. Test Description

Test Setup:



ANSI C63.10 2013 Clause 11.6 was used in order to prove compliance.




2.2.3. Test Result


A. Test Verdict:

Test Mode	Duty Cycle (%) (D)	Duty Factor (10*lg[1/D])
802.11b	9.09	10.41
802.11g	8.68	10.61
802.11n (HT20)	8.33	10.79
802.11n (HT40)	8.68	10.61


B. Test Plot:




(Channel 1, 802.11b)



(Channel 1, 802.11g)



(Channel 1, 802.11n (HT20))



(Channel 3, 802.11n (HT40))

2.3. Maximum Peak and Average Conducted Output Power


2.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum peak conducted output power of the intentional radiator shall not exceed 1 Watt.

2.3.2. Test Description

The measured output power was calculated by the reading of the USB Wideband Power Sensor and calibration.

Test Setup:



The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.



2.3.3. Test Result

Maximum Peak Conducted Output Power

802.11b Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	23.15	0.207	30	1	PASS
6	2437	23.67	0.233			PASS
11	2462	23.62	0.230			PASS

802.11g Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	24.00	0.251	30	1	PASS
6	2437	24.36	0.273			PASS
11	2462	24.57	0.286			PASS

802.11n (HT20) Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
1	2412	24.17	0.261	30	1	PASS
6	2437	24.45	0.279			PASS
11	2462	24.68	0.294			PASS

802.11n (HT40) Mode

Channel	Frequency (MHz)	Measured Output Peak Power		Limit		Verdict
		dBm	W	dBm	W	
3	2422	24.04	0.254	30	1	PASS
6	2437	24.24	0.265			PASS
9	2452	24.35	0.272			PASS

**Maximum Average Conducted Output Power****802.11b Mode**

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	10.95	10.41	21.36	0.137	30	1	PASS
6	2437	9.85		20.26	0.106			PASS
11	2462	8.80		19.21	0.083			PASS

802.11g Mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	9.15	10.61	19.76	0.095	30	1	PASS
6	2437	8.08		18.69	0.074			PASS
11	2462	6.74		17.35	0.054			PASS

802.11n (HT20) Mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated				
		dBm		dBm	W	dBm	W	
1	2412	9.09	10.79	19.88	0.097	30	1	PASS
6	2437	7.78		18.57	0.072			PASS
11	2462	6.54		17.33	0.054			PASS

802.11n (HT40) Mode

Channel	Frequency (MHz)	Average Power				Limit		Verdict
		Measured	Duty Factor	Duty Factor Calculated				
		dBm		dBm	W	dBm	W	
3	2422	8.84	10.61	19.45	0.088	30	1	PASS
6	2437	8.04		18.65	0.073			PASS
9	2452	7.30		17.91	0.062			PASS


2.4. Bandwidth

2.4.1. Requirement

According to FCC section 15.247(a) (2), Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

2.4.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ω; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.4.3. Test Procedure

KDB 558074 Section 8.2 was used in order to prove compliance.



2.4.4. Test Result

802.11b Mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	10.03	≥500	PASS
6	2437	8.085	≥500	PASS
11	2462	9.827	≥500	PASS

B. Test Plot:



(Channel 1, 802.11b)



(Channel 6, 802.11b)



(Channel 11, 802.11b)



802.11g Mode

A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	16.36	≥500	PASS
6	2437	16.35	≥500	PASS
11	2462	16.38	≥500	PASS

B. Test Plot:



(Channel 1, 802.11g)



(Channel 6, 802.11g)



(Channel 11, 802.11g)

**802.11n (HT20) Mode****A. Test Verdict:**

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
1	2412	17.55	≥500	PASS
6	2437	17.57	≥500	PASS
11	2462	17.56	≥500	PASS

B. Test Plot:

(Channel 1, 802.11n (HT20))



(Channel 6, 802.11n (HT20))



(Channel 11, 802.11n (HT20))



802.11n (HT40) Mode


A. Test Verdict:

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limits(kHz)	Result
3	2422	36.40	≥500	PASS
6	2437	36.35	≥500	PASS
9	2452	36.42	≥500	PASS

B. Test Plot:



(Channel 3, 802.11n (HT40))



(Channel 6, 802.11n (HT40))



(Channel 9, 802.11n (HT40))


2.5. Conducted Spurious Emissions and Band Edge

2.5.1. Requirement

According to FCC section 15.247(c), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

2.5.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. In order to make an accurate measurement, set the span greater than RBW.

2.5.3. Test Procedure

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.




2.5.4. Test Result

802.11b Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-44.31	1.43	-18.57	PASS
6	2437	-38.22	2.38	-17.62	PASS
11	2462	-34.06	2.36	-17.64	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 1, 802.11b)



(Band Edge, Channel 1, 802.11b)



(30MHz to 25GHz, Channel 6, 802.11b)



(30MHz to 25GHz, Channel 11, 802.11b)



(Band Edge, Channel 11, 802.11b)




802.11g Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-39.72	-1.50	-21.5	PASS
6	2437	-40.01	1.22	-18.78	PASS
11	2462	-40.30	-0.44	-20.44	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 1, 802.11g)



(Band Edge, Channel 1, 802.11g)



(30MHz to 25GHz, Channel 6, 802.11g)



(30MHz to 25GHz, Channel 11, 802.11g)



(Band Edge, Channel 11, 802.11g)




802.11n (HT20) Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
1	2412	-40.20	1.21	-18.79	PASS
6	2437	-39.79	-1.49	-21.49	PASS
11	2462	-39.91	-3.56	-23.56	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 1, 802.11n (HT20))



(Band Edge, Channel 1, 802.11n (HT20))



(30MHz to 25GHz, Channel 6, 802.11n (HT20))



(30MHz to 25GHz, Channel 11, 802.11n (HT20))



(Band Edge, Channel 11, 802.11n (HT20))




802.11n (HT40) Mode

A. Test Verdict:

Channel	Frequency (MHz)	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
			Carrier Level	Calculated -20dBc Limit	
3	2422	-40.27	-3.18	-23.18	PASS
6	2437	-40.66	-3.57	-23.57	PASS
9	2452	-39.72	-2.82	-22.82	PASS


B. Test Plot:




(30MHz to 25GHz, Channel 3, 802.11n (HT40))



(Band Edge, Channel 3, 802.11n (HT40))



(30MHz to 25GHz, Channel 6, 802.11n (HT40))



(30MHz to 25GHz, Channel 9, 802.11n (HT40))



(Band Edge, Channel 9, 802.11n (HT40))


2.6. Power Spectral Density

2.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

2.6.2. Test Description

Test Setup:



The EUT is coupled to the Spectrum Analyzer; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

2.6.3. Test Procedure

KDB 558074 Section 8.4 was used in order to prove compliance.



2.6.4. Test Result

802.11b Mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-10.28	8	PASS
6	2437	-10.74	8	PASS
11	2462	-11.04	8	PASS

B. Test Plot:



(Channel 1, 802.11b)



(Channel 6, 802.11b)



(Channel 11, 802.11b)



A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-12.80	8	PASS
6	2437	-14.17	8	PASS
11	2462	-14.56	8	PASS

Agilent Spectrum Analyzer - Swept SA

00 RF SO G AC SENSE:INT ALIGN: AUTO 01:27:54 PM Sep 16, 2022

Marker 1 2.418270000000 GHz

PNO: Fast IF Gain: Low Trig: Free Run Atten: 20 dB

Avg Type: Log-Pwr Avg/Hold: >10/10

TRACE 1 2 3 4 5 TYPE M H A A A A A A A A DET P N N N N N N N

Ref Offset 11.5 dB Ref 20.00 dBm

10 dB/div Log

Mkr1 2.418 27 GHz -12.800 dBm

Center 2.41200 GHz Span 30.00 MHz

#Res BW 3.0 kHz #VBW 10 kHz Sweep 3.163 s (1001 pts)

MSG STATUS

Peak Search

Next Peak

Next Pk Right

Next Pk Left


Marker Delta

Mkr→CF

Mkr→Ref Lvl

More 1 of 2

(Channel 1, 802.11g)



(Channel 6, 802.11g)



(Channel 11, 802.11g)



802.11n (HT20) Mode

A. Test Verdict:

Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
1	2412	-13.97	8	PASS
6	2437	-13.68	8	PASS
11	2462	-14.20	8	PASS

B. Test Plot:



(Channel 1, 802.11n (HT20))




(Channel 6, 802.11n (HT20))



(Channel 11, 802.11n (HT20))

**802.11n (HT40) Mode****A. Test Verdict:**


Spectral power density (dBm/3kHz)				
Channel	Frequency (MHz)	Measured PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
3	2422	-16.20	8	PASS
6	2437	-16.23	8	PASS
9	2452	-17.02	8	PASS

B. Test Plot:

(Channel 3, 802.11n (HT40))



(Channel 6, 802.11n (HT40))



(Channel 9, 802.11n (HT40))

2.7. Conducted Emission

2.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).


Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

2.7.2. Test Description

Test Setup:



The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10 2013.



2.7.3. Test Result

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+PC+PC Adapter+WIFI TX

Test Voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss}} \text{ [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1987	53.10	29.98	63.66	53.66	Line	PASS
2	0.2728	48.66	26.38	61.03	51.03		PASS
3	0.2971	46.77	25.84	60.32	50.32		PASS
4	0.3959	43.75	23.83	57.94	47.94		PASS
5	0.4894	40.08	27.59	56.18	46.18		PASS
6	0.9676	33.64	21.82	56.00	46.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1548	43.72	29.44	65.74	55.74	Neutral	PASS
2	0.1903	38.64	27.12	64.03	54.03		PASS
3	0.2410	34.44	26.09	62.06	52.06		PASS
4	0.3340	29.68	23.80	59.35	49.35		PASS
5	0.4027	28.39	23.16	57.80	47.80		PASS
6	0.5339	27.72	22.31	56.00	46.00		PASS


2.8. Restricted Frequency Bands

2.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

2.8.2. Test Description

Test Setup



The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.



2.8.3. Test Procedure

KDB 558074 Section 8.6 and 8.7 was used in order to prove compliance.

2.8.4. Test Result

The lowest and highest channels are tested to verify Restricted Frequency Bands.

The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V/m]} = U_R + A_T + A_{\text{Factor}} \text{ [dB]}; A_T = L_{\text{Cable loss}} \text{ [dB]} - G_{\text{preamp}} \text{ [dB]}$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

Note: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition (vertical) was recorded in this test report.


802.11b Mode

A. Test Verdict:


Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2369.66	PK	23.85	6.74	27.20	57.79	74	PASS
1	2386.35	AV	11.03	6.74	27.20	44.97	54	PASS
11	2496.01	PK	24.27	6.74	27.20	58.21	74	PASS
11	2487.31	AV	10.60	6.74	27.20	44.54	54	PASS




B. Test Plot:



(PEAK, Channel 1, 802.11b)



(AVERAGE, Channel 1, 802.11b)



(PEAK, Channel 11, 802.11b)



(AVERAGE, Channel 11, 802.11b)




802.11g Mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2387.02	PK	24.13	6.74	27.20	58.07	74	PASS
1	2390.00	AV	11.90	6.74	27.20	45.84	54	PASS
11	2484.12	PK	23.61	6.74	27.20	57.55	74	PASS
11	2483.50	AV	11.50	6.74	27.20	45.44	54	PASS


B. Test Plot:




(PEAK, Channel 1, 802.11g)



(AVERAGE, Channel 1, 802.11g)



(PEAK, Channel 11, 802.11g)






802.11n (HT20) Mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dB μ V)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dB μ V/m)	Limit (dB μ V/m)	Verdict
		PK/ AV						
1	2374.82	PK	24.02	6.74	27.20	57.96	74	PASS
1	2390.00	AV	11.89	6.74	27.20	45.83	54	PASS
11	2484.42	PK	25.06	6.74	27.20	59.00	74	PASS
11	2483.50	AV	11.61	6.74	27.20	45.55	54	PASS


B. Test Plot:




(PEAK, Channel 1, 802.11n (HT20))



(AVERAGE, Channel 1, 802.11n (HT20))



(PEAK, Channel 11, 802.11n (HT20))



(AVERAGE, Channel 11, 802.11n (HT20))




802.11n (HT40) Mode


A. Test Verdict:

Channel	Frequency (MHz)	Detector	Receiver Reading U_R (dBμV)	A_T (dB)	A_{Factor} (dB@3m)	Max. Emission E (dBμV/m)	Limit (dBμV/m)	Verdict
		PK/ AV						
3	2388.08	PK	24.65	6.74	27.20	58.59	74	PASS
3	2390.00	AV	12.04	6.74	27.20	45.98	54	PASS
9	2488.43	PK	24.04	6.74	27.20	57.98	74	PASS
9	2483.92	AV	11.85	6.74	27.20	45.79	54	PASS


B. Test Plot:




(PEAK, Channel 3, 802.11n (HT40))



(AVERAGE, Channel 3, 802.11n (HT40))



(PEAK, Channel 9, 802.11n (HT40))



(AVERAGE, Channel 9, 802.11n (HT40))

2.9. Radiated Emission

2.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3


Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).


2.9.2. Test Description

Test Setup:


- 1) For radiated emissions from 9kHz to 30MHz



- 2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz



The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.



2.9.3. Test Result

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.


Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note2: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note3: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.


**802.11b Mode**

Plot for Channel 1



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
103.720	31.99	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1119.467	47.36	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1943.467	47.96	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4823.900	53.69	N/A	51.11	74.00	N/A	54.00	Horizontal	PASS
8430.440	46.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12138.760	47.26	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
105.660	32.23	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1108.800	46.41	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2420.267	47.28	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4824.100	56.75	N/A	52.61	74.00	N/A	54.00	Vertical	PASS
8455.080	46.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12520.680	47.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	32.37	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1210.133	46.05	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1596.800	46.92	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4873.040	49.56	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8415.040	47.08	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12197.280	47.55	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	32.27	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1109.867	46.85	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1942.933	46.25	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4873.900	54.57	N/A	51.36	74.00	N/A	54.00	Vertical	PASS
8981.760	47.42	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12317.400	47.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 11



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	32.75	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1110.400	47.12	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2410.133	47.02	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4922.320	49.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
8455.080	47.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12160.320	47.35	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
106.630	31.47	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1429.333	46.00	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1968.533	46.59	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4923.900	52.09	N/A	48.12	74.00	N/A	54.00	Vertical	PASS
7940.720	46.00	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12579.200	47.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**802.11g Mode**

Plot for Channel 1



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	32.04	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1145.600	46.04	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1699.200	46.64	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4824.300	53.69	N/A	43.92	74.00	N/A	54.00	Horizontal	PASS
7934.560	46.68	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12184.960	47.24	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	32.52	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1682.667	46.86	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1951.467	47.27	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4824.800	58.60	N/A	50.11	74.00	N/A	54.00	Vertical	PASS
8390.400	46.71	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12188.040	47.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
100.810	32.13	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1704.533	46.56	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2450.667	47.06	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4869.700	51.21	N/A	42.41	74.00	N/A	54.00	Horizontal	PASS
8910.920	46.60	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12671.600	48.04	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS


(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	32.28	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1305.067	45.20	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
2453.333	47.26	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4876.200	54.67	N/A	46.36	74.00	N/A	54.00	Vertical	PASS
8448.920	46.23	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12533.000	47.78	N/A	N/A	74.00	N/A	54.00	Vertical	PASS


(Antenna Vertical, 30MHz to 18GHz)

Plot for Channel 11



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
107.600	31.79	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1114.667	45.42	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1577.600	47.00	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4924.700	53.83	N/A	44.97	74.00	N/A	54.00	Horizontal	PASS
8467.400	46.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12505.280	47.02	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	33.17	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1116.800	45.71	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1965.867	46.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4924.600	57.59	N/A	47.46	74.00	N/A	54.00	Vertical	PASS
8415.040	46.86	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12148.000	47.55	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)

**802.11n (HT20) Mode**

Plot for Channel 1



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
112.450	32.49	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1109.867	46.18	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1946.667	46.54	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4817.600	58.08	N/A	49.13	74.00	N/A	54.00	Horizontal	PASS
8430.440	46.61	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12674.680	48.44	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	32.52	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1117.333	47.33	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1652.267	47.24	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4821.800	59.56	N/A	50.29	74.00	N/A	54.00	Vertical	PASS
7999.240	47.22	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12123.360	47.98	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
101.780	33.14	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1118.400	46.24	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1614.400	46.76	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4874.700	54.94	N/A	45.81	74.00	N/A	54.00	Horizontal	PASS
8485.880	46.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12144.920	47.43	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	32.63	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1246.400	45.94	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1685.333	47.38	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4874.500	55.65	N/A	46.41	74.00	N/A	54.00	Vertical	PASS
9046.440	47.34	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12594.600	47.67	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 11



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
95.960	32.78	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1206.933	45.56	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1848.533	47.19	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4922.000	53.50	N/A	44.16	74.00	N/A	54.00	Horizontal	PASS
8350.360	46.98	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12184.960	47.91	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
97.900	32.55	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1116.800	45.96	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1973.333	46.60	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4927.000	55.01	N/A	46.14	74.00	N/A	54.00	Vertical	PASS
8926.320	47.77	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12126.440	49.53	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)


**802.11n (HT40) Mode**

Plot for Channel 3



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
102.750	32.64	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1371.733	46.79	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
2388.267	46.51	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4832.200	54.40	N/A	44.32	74.00	N/A	54.00	Horizontal	PASS
8954.040	46.76	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12157.240	48.34	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)




Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
103.720	33.74	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1116.267	45.64	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1635.733	46.48	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4830.800	53.50	N/A	44.43	74.00	N/A	54.00	Vertical	PASS
8461.240	46.65	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12188.040	48.15	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 6



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
104.690	33.65	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1120.533	48.52	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1912.000	46.80	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4876.100	51.50	N/A	42.62	74.00	N/A	54.00	Horizontal	PASS
8448.920	47.29	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12671.600	48.31	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
98.870	33.07	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1206.400	45.86	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1895.467	46.69	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4874.000	51.76	N/A	44.89	74.00	N/A	54.00	Vertical	PASS
8411.960	46.61	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12554.560	47.72	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)




Plot for Channel 9



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
103.720	32.30	N/A	N/A	N/A	43.50	N/A	Horizontal	PASS
1371.200	45.76	N/A	N/A	N/A	46.00	N/A	Horizontal	PASS
1825.600	46.83	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
4904.500	51.95	N/A	43.36	74.00	N/A	54.00	Horizontal	PASS
8433.520	47.65	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS
12606.920	47.36	N/A	N/A	74.00	N/A	54.00	Horizontal	PASS

(Antenna Horizontal, 30MHz to 18GHz)



Fre. (MHz)	PK (dBμV/m)	QP (dBμV/m)	AV (dBμV/m)	Limit-PK (dBμV/m)	Limit-QP (dBμV/m)	Limit-AV (dBμV/m)	Antenna	Verdict
99.840	33.05	N/A	N/A	N/A	43.50	N/A	Vertical	PASS
1120.000	47.27	N/A	N/A	N/A	46.00	N/A	Vertical	PASS
1789.867	46.21	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
4905.800	52.87	N/A	44.86	74.00	N/A	54.00	Vertical	PASS
8427.360	46.70	N/A	N/A	74.00	N/A	54.00	Vertical	PASS
12181.880	46.85	N/A	N/A	74.00	N/A	54.00	Vertical	PASS

(Antenna Vertical, 30MHz to 18GHz)



Annex A Test Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for test performed on the EUT as specified in CISPR 16-1-2:

Test Items	Uncertainty
Peak Output Power	$\pm 2.22\text{dB}$
Power Spectral Density	$\pm 2.22\text{dB}$
Bandwidth	$\pm 5\%$
Conducted Spurious Emission	$\pm 2.77\text{dB}$
Restricted Frequency Bands	$\pm 5\%$
Radiated Emission	$\pm 2.95\text{dB}$
Conducted Emission	$\pm 2.44\text{dB}$

This uncertainty represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



Annex B Testing Laboratory Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

All measurement facilities used to collect the measurement data are located at FL.3, Building A, FeiYang Science Park, Block 67, BaoAn District, Shenzhen, 518101 P. R. China. The test site is constructed in conformance with the requirements of ANSI C63.10-2013 and CISPR Publication 22; the FCC designation number is CN1192, the test firm registration number is 226174.



4. Test Equipments Utilized

4.1 Conducted Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Attenuator 1	N/A	10dB	Resent	N/A	N/A
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2022.03.01	2023.02.28
				2023.02.27	2024.02.26
USB Wideband Power Sensor	MY54180008	U2021XA	Agilent	2021.10.21	2022.10.20
				2022.10.11	2023.10.10
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
Coaxial Cable	CB02	RF02	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A
Computer	T430i	Think Pad	Lenovo	N/A	N/A

4.2 Conducted Emission Test Equipments

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY56400093	N9038A	KEYSIGHT	2022.03.03	2023.03.02
				2023.02.09	2024.02.08
LISN	812744	NSLK 8127	Schwarzbeck	2022.03.03	2023.03.02
				2023.02.21	2024.02.20
Pulse Limiter (10dB)	VTSD 9561 F-B #206	VTSD 9561-F	Schwarzbeck	2022.07.06	2023.07.05
Coaxial Cable(BNC) (30MHz-26GHz)	CB01	EMC01	Morlab	N/A	N/A
Notebook	20210357	P144G	DELL	N/A	N/A
Notebook Adapter	N/A	HA65NM1 90	DELL	N/A	N/A

4.3 List of Software Used

Description	Manufacturer	Software Version
Test System	Townsend	V2.5.77.0418
MORLAB EMCR V1.2	MORLAB	V1.0
TS+ -[JS32-CE]	Tonscend	V2.5.0.0

**4.4 Radiated Test Equipments**

Equipment Name	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	MY54130016	N9038A	Agilent	2022.07.06	2023.07.05
Test Antenna - Bi-Log	9163-519	VULB 9163	Schwarzbeck	2022.05.25	2025.05.24
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2022.02.11	2025.02.10
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2022.07.13	2025.07.12
Test Antenna – Horn	BBHA9170#773	BBHA 9170	Schwarzbeck	2022.07.14	2025.07.13
Coaxial Cable (N male) (9KHz-30MHz)	CB04	EMC04	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-26GHz)	CB02	EMC02	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-26GHz)	CB03	EMC03	Morlab	N/A	N/A
Coaxial Cable (N male) (30MHz-40GHz)	CB05	EMC05	Morlab	N/A	N/A
1-18GHz pre-Amplifier	61171/61172	S020180L3203	Tonscend	2022.07.08	2023.07.07
18-26.5GHz pre-Amplifier	46732	S10M100L3802	Tonscend	2022.07.08	2023.07.07
26-40GHz pre-Amplifier	56774	S40M400L4002	Tonscend	2022.07.08	2023.07.07
Notch Filter	N/A	WRCG-2400-2483.5-60SS	Wainwright	2022.07.08	2023.07.07
Anechoic Chamber	N/A	9m*6m*6m	CRT	2020.05.22	2025.05.21

_____ END OF REPORT _____