

# FCC SAR Exclusion Report

Report No. : SFBHQC-WTW-P22070414A

Applicant : HON HAI PRECISION IND. CO., LTD.

Address : 5F-1, 5 Hsin-An Road Hsinchu, Science-Based Industrial Park Taiwan, R.O.C.

Product : NFC module

Brand : FOXCONN

FCC ID : MCLT77H747

Model No. : T77H747

FCC Rule Part : CFR §2.1093

Standards : IEEE Std 1528:2013  
KDB 865664 D01 v01r04, KDB 865664 D02 v01r02,  
KDB 447498 D01\_v06\_2015.10.23\_General RF Exposure Guidance

Sample Received Date : Jul. 12, 2023


Date of Evaluation : Jul. 31, 2023

Lab Address : No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location : No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City, Taiwan

**CERTIFICATION:** The above equipment have been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch – Lin Kou Laboratories**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by TAF or any government agencies.

Prepared By :

  
Lena Wang / Specialist

Approved By :

  
Gordon Lin / Manager



FCC Accredited No.: TW0003

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

## Table of Contents

Release Control Record .....	3
1. Summary of Maximum SAR Value .....	4
2. Description of Equipment Under Test .....	5
3. SAR Measurement Evaluation.....	6
3.1 Maximum Output Power.....	6
3.2 SAR Testing Exclusions .....	7
4. Information on the Testing Laboratories.....	8



## Release Control Record

Issue No.	Reason for Change	Date Issued
SFBHQC-WTW-P22070414A	Initial release	Aug. 10, 2023

## FCC SAR Exclusion Report

### 1. Summary of Maximum SAR Value

Equipment Class	Mode	Highest Reported SAR <sub>1g</sub> (W/kg)
DXX	NFC	Not Required

**Note:**

1. The SAR limit (**Head & Body: SAR<sub>1g</sub> 1.6 W/kg**) for general population / uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992.

## FCC SAR Exclusion Report

### 2. Description of Equipment Under Test

EUT Type	NFC module
Brand Name	FOXCONN
FCC ID	MCLT77H747
Model Name	T77H747
Tx Frequency Bands (Unit: MHz)	13.56
Uplink Modulations	NFC : ASK
Maximum Tune-up Conducted Power (Unit: dBm)	Please refer to section 3.1 of this report
Antenna Type	Refer to Note
EUT Stage	Engineering Sample

#### Note:

- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.
- The antennas provided to the EUT, please refer to the following table:

Antenna No.	Brand	Model	Antenna Gain(dBi)	Frequency range (MHz)	Antenna Type
1	SAA	LX8416-12-000-C	NA	13.56	PCB
2	Dexerials	ANT-M041A	NA	13.56	PCB
3	Dexerials	ANT-M043A	NA	13.56	PCB
4	Dexerials	ANT-M047A	NA	13.56	PCB
5	SAA	LX7828-12-000-C	NA	13.56	PCB
6	Murata	FLANBPA-0715	NA	13.56	PCB

### 3. SAR Measurement Evaluation

#### 3.1 Maximum Output Power

The maximum Tune Up power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	Frequency	Ant. 0 Max Tune-up
NFC	13.56	-34.5

## FCC SAR Exclusion Report

### 3.2 SAR Testing Exclusions

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

A. For the test separation distance  $\leq 50$  mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0$$

- When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

• For the test separation distance  $> 50$  mm, and the frequency at 100 MHz to 1500 MHz

$$\left[ (\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left( \frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

• For the test separation distance  $> 50$  mm, and the frequency at  $> 1500$  MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

B. For 100 MHz to 6 GHz and test separation distances  $> 50$  mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following.

- $\{[\text{Power allowed at numeric threshold for 50 mm in step A}] + [(\text{test separation distance} - 50 \text{ mm}) \cdot (f(\text{MHz})/150)]\}$  mW, for 100 MHz to 1500 MHz
- $\{[\text{Power allowed at numeric threshold for 50 mm in step A}] + [(\text{test separation distance} - 50 \text{ mm}) \times 10]\}$  mW, for  $> 1500$  MHz and  $\leq 6$  GHz

C. For frequencies below 100 MHz, the following may be considered for SAR test exclusion.

- For test separation distances  $> 50$  mm and  $< 200$  mm, the power threshold at the corresponding test separation distance at 100 MHz in step B) is multiplied by  $[1 + \log(100/f(\text{MHz}))]$
- For test separation distances  $\leq 50$  mm, the power threshold determined by the equation in C.(1) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$
- SAR measurement procedures are not established below 100 MHz.

Mode	Frequency (GHz)	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	Exclusion (mW)	Require SAR Testing?
NFC	13.56	-34.5	0.000355	237.17	No

#### Note:

- When the device output power is less than the power threshold shown in above table, the SAR testing exclusion is applied.

#### Summary:

Since the SAR assess for all device orientations apply SAR test exclusion per KDB 447498, SAR testing for this device is not required.

### **4. Information on the Testing Laboratories**

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Taiwan Huaya Lab:**

Add: No. 19, Huaya 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan  
Tel: +886-(0)3-318-3232  
Fax: +886-(0)3-211-5834

**Taiwan Linkou Lab:**

Add: No. 47-2, Baodoucuokeng, Linkou Dist., New Taipei City 244, Taiwan  
Tel: +886-(0)2-2605-2180  
Fax: +886-(0)2-2605-2943

**Taiwan Hsinchu Lab1:**

Add: E-2, No. 1, Lixing 1st Rd., East Dist., Hsinchu City 300, Taiwan  
Tel: +886-(0)3-666-8565  
Fax: +886-(0)3-666-8323

**Taiwan Hsinchu Lab2:**

Add: No. 49, Ln. 206, Wende Rd., Qionglin Township, Hsinchu County 307, Taiwan  
Tel: +886-(0)3-512-0595  
Fax: +886-(0)3-512-0568

**Taiwan Xindian Lab:**

Add: B2F., No. 215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan  
Tel: +886-(0)2-8914-5882  
Fax: +886-(0)2-8914-5840

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** <https://ee.bureauveritas.com.tw/BVInternet/Default>

The road map of all our labs can be found in our web site also.

---END---