

RF Exposure Evaluation Report

1 RF EXPOSURE

Product Name wireless mouse
 Model No. E703
 FCC ID 2ANBU-E703B

1.1 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusio

1.2 EUT RF EXPOSURE EVALUATION

Operational Mode: GFSK							
Channel (MHz)	Maximum Peak Conducted Output Power (dBuV/m)	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Limit
				(dBm)	(mW)		
2480	88.54	-6.66	± 1	-5.66	0.272	0.084	3.0
Conclusion: the calculated value ≤ 1.0 , SAR is exempted.							

Calculated value 0.084 < 3.0, So there is no require SAR test

dBm=dBuV/m-95.2