

TEST REPORT

of

FCC Part 15 Subpart C §15.209 and §15.231
IC RSS-210 Issue 10 and RSS-Gen Issue 5

FCC ID: TQ8-FOB-4F87M54
IC Certification: 5074A-FOB4F87M54

Equipment Under Test : FOB Smart Key
Model Name : FOB-4F87M54
Variant Model Name(s) : FOB-4F88M53
FCC Applicant : HYUNDAI MOBIS CO., LTD.
IC Applicant : Hyundai MOBIS Co., Ltd
Manufacturer : Hyundai Mobis Co., Ltd.
Date of Receipt : 2023.06.20
Date of Test(s) : 2023.06.21 ~ 2023.07.13
Date of Issue : 2023.07.13

In the configuration tested, the EUT complied with the standards specified above. This test report does not assure KOLAS accreditation.


- 1) The results of this test report are effective only to the items tested.
- 2) The SGS Korea is not responsible for the sampling, the results of this test report apply to the sample as received.
- 3) This test report cannot be reproduced, except in full, without prior written permission of the Company.
- 4) The data marked ※ in this report was provided by the customer and may affect the validity of the test results.

We are responsible for all the information of this test report except for the data(※) provided by the customer.

Tested by:


Murphy Kim

Technical
Manager:


Jinhyoung Cho

SGS Korea Co., Ltd. Gunpo Laboratory

INDEX

| <u>Table of Contents</u> | Page |
|---|------|
| 1. General Information ----- | 3 |
| 2. Field Strength of Fundamental and Spurious Emission----- | 7 |
| 3. Bandwidth of Operation Frequency----- | 16 |
| 4. Occupied Bandwidth----- | 18 |
| 5. Transmission Time----- | 20 |
| 6. Duty Cycle Correction Factor----- | 22 |
| 7. Antenna Requirement----- | 24 |

1. General Information

1.1. Testing Laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807
- Designation number: KR0150

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 688 0901

FAX : +82 31 688 0921

1.2. Details of Applicant

FCC Applicant : HYUNDAI MOBIS CO., LTD.

FCC Address : 203, Teheran-ro, Gangnam-gu, Seoul, South Korea, 135-977

IC Applicant : Hyundai MOBIS Co., Ltd

IC Address : 203, Teheran-ro, Gangnam-gu, Seoul, 135-977, Korea (Republic Of)

Contact Person : Choe, Seung-hoon

Phone No. : +82 31 260 0098

1.3. Details of Manufacturer

Company : Hyundai Mobis Co., Ltd.

Address : 203, Teheran-ro, Gangnam-gu, Seoul, Republic of Korea, 06141

1.4. Description of EUT

| | |
|---------------------------|--------------------------------|
| Kind of Product | FOB Smart Key |
| Model Name | FOB-4F87M54 |
| Variant Model Name | FOB-4F88M53 |
| Serial Number | Conducted: 001, Radiated: 002 |
| Power Supply | DC 3.0 V |
| Frequency Range | Tx: 433.92 MHz, Rx: 125.00 kHz |
| Modulation Type | FSK |
| Number of Channel | 1 |
| Antenna Type | PCB Pattern Antenna |
| Antenna Gain* | -11.61 dBi |
| H/W Version | 1.00 |
| S/W Version | 1.00 |
| FVIN | N/A |

1.5. Test Equipment List

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Interval | Cal. Due |
|--------------------------|-----------------------------|--------------------------------------|------------------------|---------------|---------------|---------------|
| Signal Generator | R&S | SMA100B | 106887 | Oct. 13, 2022 | Annual | Oct. 13, 2023 |
| Spectrum Analyzer | R&S | FSV30 | 103210 | Dec. 07, 2022 | Annual | Dec. 07, 2023 |
| Spectrum Analyzer | Agilent | N9020A | MY53421758 | Aug. 26, 2022 | Annual | Aug. 26, 2023 |
| DC Power Supply | R&S | HMP2020 | 019922876 | Apr. 27, 2023 | Annual | Apr. 27, 2024 |
| Attenuator | AEROFLEX | 40AH2W-10 | 40G-1 | Jun. 14, 2023 | Annual | Jun. 14, 2024 |
| Preamplifier | H.P. | 8447F | 2944A03909 | Aug. 04, 2022 | Annual | Aug. 04, 2023 |
| Signal Conditioning Unit | R&S | SCU-18 | 10117 | Jun. 15, 2023 | Annual | Jun. 15, 2024 |
| High Pass Filter | Wainwright Instrument GmbH | WHKX10-900-1000-18000-40SS | 7 | Mar. 02, 2023 | Annual | Mar. 02, 2024 |
| Loop Antenna | Schwarzbeck Mess-Elektronik | FMZB 1519 | 1519-039 | Aug. 23, 2021 | Biennial | Aug. 23, 2023 |
| Bilog Antenna | Schwarzbeck Mess-Elektronik | VULB 9163 | 01126 | Feb. 09, 2023 | Annual | Feb. 09, 2024 |
| Horn Antenna | R&S | HF906 | 100326 | Feb. 28, 2023 | Annual | Feb. 28, 2024 |
| Test Receiver | R&S | ESU26 | 100109 | Jan. 18, 2023 | Annual | Jan. 18, 2024 |
| Turn Table | Innco systems GmbH | DS 1200 S | N/A | N.C.R. | N/A | N.C.R. |
| Controller | Innco systems GmbH | CONTROLLER CO3000-4P | CO3000/963/38 330516/L | N.C.R. | N/A | N.C.R. |
| Antenna Mast | Innco systems GmbH | MA4640-XP-ET | MA4640/536/38 330516/L | N.C.R. | N/A | N.C.R. |
| Anechoic Chamber | SY Corporation | L × W × H (9.6 m × 6.4 m × 6.6 m) | N/A | N.C.R. | N/A | N.C.R. |
| Coaxial Cable | RFONE | MWX221-NMSNMS (4 m) | J1023142 | Apr. 04, 2023 | Semi-Annual | Oct. 04, 2023 |
| Coaxial Cable | Qualwave Inc. | QA500-18-NN-10 (10 m) | 22200114 | Apr. 04, 2023 | Semi-Annual | Oct. 04, 2023 |
| Coaxial Cable | RFONE | PL360P-292M292M-1.5M-A | 20200324002 | Apr. 14, 2023 | Semi-Annual | Oct. 14, 2023 |

Note;

- Operating software of EUT has integrated test interface. No additional software was used.
- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.

1.6. Summary of Test Results

The EUT has been tested according to the following specifications:

| APPLIED STANDARD: FCC Part 15 Subpart C, IC RSS-210 Issue 10 and RSS-Gen Issue 5 | | | |
|--|---|--|-------------------|
| Section in FCC | Section in IC | Test Item(s) | Result |
| 15.209(a) 15.231(b) | RSS-210 Issue 10 A.1, Table A1 RSS-Gen Issue 5 8.9 | Radiated emission, Spurious Emission and Field Strength of Fundamental | Complied |
| 15.231(c) | - | Bandwidth of Operation Frequency | Complied |
| - | RSS-210 Issue 10 A.1.3 RSS-Gen Issue 5 6.7 | Occupied Bandwidth | Complied |
| 15.231(a) | RSS-210 Issue 10 A.1.1 | Transmission Time | Complied |
| 15.207 | RSS-Gen Issue 5 8.8 | AC Power Line Conducted Emission | N/A ¹⁾ |

Note;

1) The AC power line test was not performed because the EUT use battery power for operation and which do not operate from the AC power lines.

1.7. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter | Uncertainty | |
|------------------------------------|-------------|---------|
| Occupied Bandwidth | 1.08 kHz | |
| Bandwidth of Operating Frequency | 1.13 kHz | |
| Transmission Time | 1.61 ms | |
| Radiated Emission, 9 kHz to 30 MHz | H | 3.40 dB |
| | V | 3.40 dB |
| Radiated Emission, below 1 GHz | H | 4.50 dB |
| | V | 5.10 dB |
| Radiated Emission, above 1 GHz | H | 3.70 dB |
| | V | 3.90 dB |

All measurement uncertainty values are shown with a coverage factor of $k=2$ to indicate a 95 % level of confidence.

1.8. Test Report Revision

| Revision | Report Number | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0 | F690501-RF-RTL004248 | 2023.07.13 | Initial |

1.9. Description of Variant Models

| Model name | | Description |
|---------------|-------------|--|
| Basic model | FOB-4F87M54 | - Basic model |
| Variant model | FOB-4F88M53 | - Same as basic model, but the difference in the number of external buttons of the product |


Note;

- The all test items performed with basic model


2. Field Strength of Fundamental and Spurious Emission

2.1. Test Setup


The diagram below shows the test setup that is utilized to make the measurements for emission below 30 MHz.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz.



The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



2.2. Limit

2.2.1. FCC

2.2.1.1. Radiated Emission Limits; general requirements.

According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meter) |
|-----------------|-----------------------------------|------------------------------|
| 0.009-0.490 | 2 400/F(kHz) | 300 |
| 0.490-1.705 | 24 000/F(kHz) | 30 |
| 1.705-30.0 | 30 | 30 |
| 30-88 | 100** | 3 |
| 88-216 | 150** | 3 |
| 216-960 | 200** | 3 |
| Above 960 | 500 | 3 |

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§15.231 and 15.241.

2.2.1.2. Periodic Operation in the band 40.66-40.70 MHz and above 70 MHz.

According to §15.231(b), in addition to the provisions of Section §15.205, the field strength of emissions from intentional radiators operated under this Section shall not exceed the following:

| Fundamental Frequency (MHz) | Field Strength of Fundamental (microvolts/meter) | Field Strength of Spurious Emissions (microvolts/meter) |
|-----------------------------|--|---|
| 40.66-40.70 | 2,250 | 225 |
| 70-130 | 1,250 | 125 |
| 130-174 | ¹ 1,250 to 3,750 | ¹ 125 to 375 |
| 174-260 | 3,750 | 375 |
| 260-470 | ¹ 3,750 to 12,500 | ¹ 375 to 1,250 |
| Above 470 | 12,500 | 1,250 |

¹linear interpolations

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu V/m$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu V/m$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

2.2.2. IC

2.2.2.1. Transmitter Emission Limits

According to RSS-Gen Issue 5, 8.9.

Except where otherwise indicated in the applicable RSS, radiated emissions shall comply with the field strength limits shown in table 5 and table 6. Additionally, the level of any transmitter unwanted emission shall not exceed the level of the transmitter's fundamental emission.

Table 5 - General field strength limits at frequencies above 30 MHz

| Frequency (MHz) | Field Strength ($\mu V/m$ at 3 m) |
|-----------------|------------------------------------|
| 30-88 | 100 |
| 88-216 | 150 |
| 216-960 | 200 |
| Above 960 | 500 |

Table 6 - General field strength limits at frequencies below 30 MHz

| Frequency | Magnetic Field Strength (H-Field) ($\mu A/m$) | Measurement Distance (m) |
|------------------------|---|--------------------------|
| 9-490 kHz ¹ | 6.37/F (F in kHz) | 300 |
| 490-1 705 kHz | 63.7/F (F in kHz) | 30 |
| 1.705-30 MHz | 0.08 | 30 |

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

2.2.2.2. Momentarily Operated Devices

According to A.1 of RSS-210 Issue 10.

The operation of momentarily operated devices is permitted in the bands specified in tables A1 and A2 of this annex, but is prohibited in the restricted frequency bands listed in RSS-Gen.

The frequency bands and field strength limits in tables A1 and A2 are reserved exclusively for the transmission of a control signal, such as those used with alarm systems, door openers, remote switches, etc. Data may be sent with a control signal. Radio control of toys or model aircraft, as well as continuous transmissions (such as voice or video), are not permitted, except as provided in section A.1.4 below.

Table A1 - Permissible Field Strength Limits for Momentarily Operated Devices

| Fundamental Frequency (MHz), Excluding Restricted Frequency Bands Specified in RSS-Gen | Field Strength of the Fundamental Emissions ($\mu\text{V/m}$ at 3 m) |
|--|---|
| 70-130 | 1,250 |
| 130-174 | 1,250 to 3,750* |
| 174-260** | 3,750 |
| 260-470** | 3,750 to 12,500* |
| Above 470 | 12,500 |

* Linear interpolation with frequency, f , in MHz:

For 130-174 MHz: Field Strength ($\mu\text{V/m}$) = $(56.82 \times f) - 6136$

For 260-470 MHz: Field Strength ($\mu\text{V/m}$) = $(41.67 \times f) - 7083$

** Frequency bands 225-328.6 MHz and 335.4-399.9 MHz are designated for the exclusive use of the Government of Canada. Manufacturers should be aware of possible harmful interference and degradation of their licence-exempt radio equipment in these frequency bands.

2.3. Test Procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.10-2013.

2.3.1. Test Procedures for emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
- c. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- d. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

2.3.2. Test Procedures for emission from 30 MHz to 1 000 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurements below 1 GHz resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

2.3.3. Test Procedures for emission above 1 GHz

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection at frequency above 1 GHz.

2.4. Test Result

Ambient temperature : (23 ± 1) °C
Relative humidity : 47 % R.H.

2.4.1. Field Strength of Fundamental


All emissions tested both horizontal and vertical. The following table shows the highest levels of radiated emissions on the worst polarization.

| Frequency (MHz) | Reading (dBμV) | Detect Mode | Ant. Pol. | AF (dB/m) | CL (dB) | DF (dB) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
|-----------------|----------------|-------------|-----------|-----------|---------|---------|-----------------|----------------|-------------|
| 433.96 | 62.12 | Peak | V | 22.10 | 2.57 | - | 86.79 | 100.83 | 14.04 |
| 433.96 | - | Average | V | - | - | 12.77 | 74.02 | 80.83 | 6.81 |

Remark;

- To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z). Worst orthogonal plan of EUT is **Z – axis**.
Definition of DUT for three orthogonal planes is described in the test setup photos.
- 3 m Limit (dBμV/m) = $20\log [41.67(F_{MHz}) - 7083] = 80.83$
- Peak Result = Reading + Antenna Factor + Cable Loss
- Average Result = Peak Result + DF
- DF (Duty Cycle Correction Factor): $20\log (T_{on} / 100 \text{ ms}) = 20\log (23 / 100) = -12.77$
- $T_{on} = 23.0 \text{ ms}$.
- $T_{on+off} = 100 \text{ ms}$ (pulse train is 100 ms instead of 147 ms).

- Test plot



2.4.2. Radiated Spurious Emission


The following table shows the highest levels of radiated emissions.
The frequency spectrum from 9 kHz to 4 000 MHz was investigated.

| Radiated Emissions | | | Ant. | Correction Factors | | | Total | Limit | |
|--------------------|----------------|-------------|-----------|--------------------|-------------|---------|-----------------|----------------|-------------|
| Frequency (MHz) | Reading (dBμV) | Detect Mode | Ant. Pol. | AF (dB/m) | AMP+CL (dB) | DF (dB) | Result (dBμV/m) | Limit (dBμV/m) | Margin (dB) |
| 867.96 | 36.30 | Peak | H | 27.30 | -24.80 | - | 38.80 | 60.83 | 22.03 |
| *1 301.61 | 65.84 | Peak | H | 25.00 | -40.57 | - | 50.27 | 74.00 | 23.73 |
| *3 905.60 | 49.37 | Peak | V | 32.29 | -37.15 | - | 44.51 | 74.00 | 29.49 |
| Above 4 000.00 | Not detected | - | - | - | - | - | - | - | - |


Remark;

- To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z).
Definition of DUT for three orthogonal planes is described in the test setup photos.
- 3 m Limit (dBμV/m) = $20\log [41.67(F_{\text{MHz}}) - 7083] - 20$ dBμV/m = 60.83 dBμV/m.
- Correction Factors = AF + AMP + CL.
- Peak Result = Reading + Correction Factors.
- Average Result = Peak Result + DF.
- DF (Duty Cycle Correction Factor): $20\log (T_{\text{on}} / 100 \text{ ms}) = 20\log (23 / 100) = -12.77$
- $T_{\text{on}} = 23.0 \text{ ms}$.
- $T_{\text{on+off}} = 100 \text{ ms}$ (pulse train is 100 ms instead of 147 ms).
- "**" means the restricted band.
- Test from 30 MHz to 1 000 MHz was performed using the software of EP5RE(V5.3.70) from TOYO.
- According to § 15.31(o), Emission levels are not reported much lower than the limits by over 20 dB.
- The maximized peak measured value complies with the average limit, to perform an average measurement is unnecessary.


- Test plots



3rd harmonic




9th harmonic



3. Bandwidth of Operation Frequency

3.1. Test Setup



3.2. Limit

According to §15.231(c), the bandwidth of the emission shall be no wider than 0.25 % of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5 % of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

3.3. Test Procedure


1. The transmitter output is connected to the spectrum analyzer.
2. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3 x RBW.
3. The bandwidth of fundamental frequency was measured and recorded.

3.4. Test Result

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.


| Frequency (MHz) | Bandwidth of Operation Frequency (kHz) | Limit (kHz) | Remark |
|-----------------|--|-------------|---|
| 433.92 | 110.89 | 1 084.80 | The point 20 dB down from the modulated carrier |

- Test plot



4. Occupied Bandwidth

4.1. Test Setup



4.2. Limit

According to A.1.3 of RSS-210 Issue 10, the occupied bandwidth of momentarily operated devices shall be less than or equal to 0.25 % of the centre frequency for devices operating between 70 MHz and 900 MHz. For devices operating above 900 MHz, the occupied bandwidth shall be less than or equal to 0.5 % of the centre frequency.

4.3. Test Procedure


1. The transmitter output is connected to the spectrum analyzer.
2. The resolution bandwidth (RBW) shall be in the range of 1 % to 5 % of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3 x RBW.
3. The bandwidth of fundamental frequency was measured and recorded.

4.4. Test Result

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.


| Frequency (MHz) | Occupied Bandwidth (kHz) | Limit (kHz) | Remark |
|--------------------|-----------------------------|----------------|-------------------------|
| 433.92 | 108.54 | 1 084.80 | 99 % Occupied bandwidth |

- Test plot



5. Transmission Time

5.1. Test Setup



5.2. Limit

5.2.1. FCC

According to §15.231(a)(1), a manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

5.2.2. IC

According to A.1.1(a) of RSS-210 Issue 10, a manually operated transmitter shall be equipped with a push-to-operate switch and be under manual control at all times during transmission. When released, the transmitter shall cease transmission within no more than 5 seconds of being released.

5.3. Test Procedure


1. The transmitter output is connected to the spectrum analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW = 1 MHz, VBW = 1 MHz, Span = 0 Hz, Sweep Time = 10 sec.
3. The bandwidth of fundamental frequency was measured and recorded.

5.4. Test Result

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.


| Frequency (MHz) | Transmission Time (sec) | Limit (sec) | Remark |
|-----------------|-------------------------|---------------------|--------|
| 433.92 | 0.30 | Same or less than 5 | Pass |

- Test plot



6. Duty Cycle Correction Factor

6.1. Test Setup



6.2. Limit

None (No dedicated Limit specified in the Rules).

6.3. Test Procedure

1. The transmitter output is connected to the spectrum analyzer.
2. Set center frequency of spectrum analyzer = operating frequency.
3. Set the spectrum analyzer as RBW = 1 MHz, VBW = 1 MHz, Span = 0 Hz, Sweep Time = 500 msec.

6.4. Test Result

Ambient temperature : (23 ± 1) °C
 Relative humidity : 47 % R.H.

CALCULATION:

Average Reading = Peak Reading (dBμV/m) + 20log (Duty Cycle).

In order to determine possible Maximum Modulation percentage, alternations are made to the EUT.
 We measured;

| T_{on+off} | T_{on} | $M \% = (T_{on} / T_{on+off}) * 100 \%$ | Duty Correction Factor |
|--------------|----------|---|------------------------|
| 100 ms | 23 ms | 23 | -12.77 dB |

$T_{on+off} = 100$ ms.


$T_{on} = 23.0$ ms.

Duty Cycle = $20\log (T_{on} / T_{on+off}) = 20\log (0.23) = -12.77$ dB.

Remark;

- $T_{on+off} = 100$ ms (pulse train is 100 ms instead of 147 ms).

- Test plot



7. Antenna Requirement

7.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

7.2. Antenna Connected Construction

Antenna used in this product is PCB Pattern Antenna with gain of -11.61 dB i.

- End of the Test Report -