

TEST REPORT

Reference No...... : WTX21X05051789W-1
FCC ID : 2AGA6-OONTZA3SH
Applicant : Shenzhen AngSi Technology Co., Ltd
Address : 6/F, Block B, Ding Xin Science Park, Hong Lang North No.2 Road, Bao An District, ShenZhen PRC
Product Name : Bluetooth speaker
Test Model. : OontZ Angle 3 Shower
Standards : FCC Part 15.247
Date of Receipt sample : Aug. 24, 2018
Date of Test..... : Aug. 24, 2018 to Sep. 03, 2018, Jun. 16, 2021
Date of Issue : Jun. 17, 2021
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308

Fax.: +86-755-33663309

Tested by:

Reviewed By:

Approved & Authorized By:

Jack Huang

Lion Cai

Silin Chen

Jack Huang/ Project Engineer

Lion Cai / RF Manager

Silin Chen / Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 TEST STANDARDS	5
1.3 TEST METHODOLOGY	5
1.4 TEST FACILITY	5
1.5 EUT SETUP AND TEST MODE	6
1.6 MEASUREMENT UNCERTAINTY	7
1.7 TEST EQUIPMENT LIST AND DETAILS	8
2. SUMMARY OF TEST RESULTS	9
3. RF EXPOSURE	10
3.1 STANDARD APPLICABLE	10
3.2 TEST RESULT	10
4. ANTENNA REQUIREMENT	11
4.1 STANDARD APPLICABLE	11
4.2 EVALUATION INFORMATION	11
5. FREQUENCY HOPPING SYSTEM REQUIREMENTS	12
5.1 STANDARD APPLICABLE	12
5.2 FREQUENCY HOPPING SYSTEM	12
5.3 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	13
6. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION	14
6.1 STANDARD APPLICABLE	14
6.2 TEST PROCEDURE	14
6.3 SUMMARY OF TEST RESULTS/PLOTS	14
7. DWELL TIME OF HOPPING CHANNEL	18
7.1 STANDARD APPLICABLE	18
7.2 TEST PROCEDURE	18
7.3 SUMMARY OF TEST RESULTS/PLOTS	18
8. 20DB BANDWIDTH	26
8.1 STANDARD APPLICABLE	26
8.2 TEST PROCEDURE	26
8.3 SUMMARY OF TEST RESULTS/PLOTS	27
9. RF OUTPUT POWER	30
9.1 STANDARD APPLICABLE	30
9.2 TEST PROCEDURE	30
9.3 SUMMARY OF TEST RESULTS/PLOTS	30
10. FIELD STRENGTH OF SPURIOUS EMISSIONS	35
10.1 STANDARD APPLICABLE	35
10.2 TEST PROCEDURE	35
10.3 CORRECTED AMPLITUDE & MARGIN CALCULATION	36
10.4 SUMMARY OF TEST RESULTS/PLOTS	36
11. OUT OF BAND EMISSIONS	44
11.1 STANDARD APPLICABLE	44
11.2 TEST PROCEDURE	44
11.3 SUMMARY OF TEST RESULTS/PLOTS	45
12. CONDUCTED EMISSIONS	51
12.1 TEST PROCEDURE	51
12.2 BASIC TEST SETUP BLOCK DIAGRAM	51
12.3 TEST RECEIVER SETUP	51
12.5 SUMMARY OF TEST RESULTS/PLOTS	51

Report version

Version No.	Date of issue	Description
Rev.00	2018-09-03	Original report STR18088270I-1.
Rev.01	Jun. 17, 2021	Refer to the old report STR18088270I-1, update the appearance photos of EUT, change the applicant & manufacturer's address, but the circuit and electronic structure have not changed, the manufacturer declares. Except for the updated conducted emissions test data due to the change of the USB port, the rest of the test data from the original report.

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant: Shenzhen AngSi Technology Co., Ltd
Address of applicant: 6/F, Block B, Ding Xin Science Park, Hong Lang North No.2 Road, Bao An District, ShenZhen PRC

Manufacturer: Shenzhen AngSi Technology Co., Ltd
Address of manufacturer: 6/F, Block B, Ding Xin Science Park, Hong Lang North No.2 Road, Bao An District, ShenZhen PRC

General Description of EUT	
Product Name:	Bluetooth speaker
Brand Name:	OontZ
Model No.:	OontZ Angle 3 Shower
Adding Model(s):	/
Rated Voltage:	DC 3.6V
Battery Capacity:	2500mAh
Power Adapter:	/
Note: The test data is gathered from a production sample, provided by the manufacturer.	

Technical Characteristics of EUT	
Bluetooth Version:	V4.2 (BDR/EDR mode)
Frequency Range:	2402-2480MHz
RF Output Power:	2.455dBm (Conducted)
Data Rate:	1Mbps, 2Mbps, 3Mbps
Modulation:	GFSK, Pi/4 QDPSK, 8DPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	4.1dBi
Lowest Internal Frequency of EUT:	26MHz

1.2 Test Standards

The tests were performed according to following standards:

FCC Rules Part 15.247: Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

ANSI C63.10-2013: American National Standard for Testing Unlicensed Wireless Devices.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, The equipment under test (EUT) was configured to measure its highest possible emission level. The test modes were adapted accordingly in reference to the Operating Instructions.

1.4 Test Facility

Address of the test laboratory

Laboratory: Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road, Block 70 Bao'an District, Shenzhen, Guangdong, China

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2441MHz
TM3	High Channel	2480MHz
TM4	Hopping	2402-2480MHz

Modulation Configure			
Modulation	Packet	Packet Type	Packet Size
GFSK	DH1	4	27
	DH3	11	183
	DH5	15	339
Pi/4 DQPSK	2DH1	20	54
	2DH3	26	367
	2DH5	30	679
8DPSK	3DH1	24	83
	3DH3	27	552
	3DH5	31	1021
Normal mode: the Bluetooth has been tested on the modulation of GFSK, (Pi/4)DQPSK and 8DPSK, compliance test and record the worst case.			

Test Conditions	
Temperature:	22~25 °C
Relative humidity	50~55 %.
ATM Pressure:	1019 mbar

EUT Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Special Cable List and Details			
Cable Description	Length (m)	Shielded/Unshielded	With / Without Ferrite
/	/	/	/

Auxiliary Equipment List and Details			
Description	Manufacturer	Model	Serial Number
iPhone6 Plus	Apple	MGAJ2ZP/A	FK1PQ4JBG5QW
Adapter	Dell Inc.	PSAI10R-050Q	/
USB CABLE	UGREEN	10836	/
AUX Line	PHILIPS	SWA5511/93A	/

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	$\pm 0.42\text{dB}$
Occupied Bandwidth	Conducted	$\pm 1.5\%$
Conducted Spurious Emission	Conducted	$\pm 2.17\text{dB}$
Conducted Emissions	Conducted	9-150kHz $\pm 3.74\text{dB}$
		0.15-30MHz $\pm 3.34\text{dB}$
Transmitter Spurious Emissions	Radiated	30-200MHz $\pm 4.52\text{dB}$
		0.2-1GHz $\pm 5.56\text{dB}$
		1-6GHz $\pm 3.84\text{dB}$
		6-18GHz $\pm 3.92\text{dB}$

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2021-04-12	2022-04-11
SEMT-1336	L.I.S.N	Rohde & Schwarz	ENV216	100097	2021-04-12	2022-04-11
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21
SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209(a)	Radiated Spurious Emissions	Compliant
§ 15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	RF Power Output	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§ 15.247(a)(1)	Frequency Hopping Sequence	Compliant
§ 15.247(g), (h)	Frequency Hopping System	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has an integral antenna, fulfill the requirement of this section.

5. Frequency Hopping System Requirements

5.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

5.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

5.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:

Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6. Quantity of Hopping Channels and Channel Separation

6.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

6.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.3, the number of hopping frequencies test method as follows.


- a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
- b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
- c) VBW \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.

According to ANSI C63.10-2013 section 7.8.2, the EUT shall have its hopping function enabled, the Carrier frequency separation test method as follows:

- a) Span: Wide enough to capture the peaks of two adjacent channels.
- b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
- c) Video (or average) bandwidth (VBW) \geq RBW.
- d) Sweep: Auto.
- e) Detector function: Peak.
- f) Trace: Max hold.
- g) Allow the trace to stabilize.




Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.3 Summary of Test Results/Plots



Mode	Channel	Carrier Frequencies Separation (kHz)	Result
GFSK	Low	997.5	Pass
	Middle	997.5	Pass
	High	982.5	Pass
8DPSK	Low	997.5	Pass
	Middle	1005	Pass
	High	1012.5	Pass

<p>Channel Separation-GFSK</p>	<div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm #Atten 25 dB</div><div>Mkr1 Δ -997.5 kHz 0.557 dB</div><div>Peak Search</div><div>Meas Tools ▸</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div><div><div>Log 10 dB/Offset 1.5 dB</div><div>M1 S2 S3 FC AA</div><div>Marker Δ -997.500 kHz 0.557 dB</div><div>Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts) Span 3 MHz</div></div></div>
<p>Middle Channel</p>	<div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm #Atten 25 dB</div><div>Mkr1 Δ 997.5 kHz -0.093 dB</div><div>Peak Search</div><div>Meas Tools ▸</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div><div><div>Log 10 dB/Offset 1.5 dB</div><div>M1 S2 S3 FC AA</div><div>Marker Δ 997.500 kHz -0.093 dB</div><div>Center 2.442 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts) Span 3 MHz</div></div></div>
<p>High Channel</p>	<div><div><div>Agilent</div><div>R T</div><div>Ref 15 dBm #Atten 25 dB</div><div>Mkr1 Δ -982.5 kHz -0.761 dB</div><div>Peak Search</div><div>Meas Tools ▸</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div><div><div>Log 10 dB/Offset 1.5 dB</div><div>M1 S2 S3 FC AA</div><div>Marker Δ -982.500 kHz -0.761 dB</div><div>Center 2.479 GHz #Res BW 30 kHz #VBW 100 kHz Sweep 5 ms (401 pts) Span 3 MHz</div></div></div>

Channel Separation-8DPSK	
Low Channel	
Middle Channel	
High Channel	

7. Dwell Time of Hopping Channel

7.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.4, the dwell time of a hopping channel test method as follows.

- a) Span: Zero span, centered on a hopping channel.
- b) RBW shall be \leq channel spacing and where possible RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
- c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
- d) Detector function: Peak.
- e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.

Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:

$$\begin{aligned} &(\text{Number of hops in the period specified in the requirements}) = \\ &(\text{number of hops on spectrum analyzer}) \times (\text{period specified in the requirements} / \text{analyzer sweep time}) \end{aligned}$$

The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation. The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

7.3 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length).
Test data is corrected with the worse case, which the packet length is DH1, DH3, and DH5.

The test period: $T = 0.4 \text{ Second} * 79 \text{ Channel} = 31.6 \text{ s}$
Waltek Testing Group (Shenzhen) Co., Ltd.
[Http://www.waltek.com.cn](http://www.waltek.com.cn)


Dwell time = time slot length * (Hopping rate / Number of hopping channels) * Period

Modulation	Test Channel	Packet	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
GFSK	Low	DH1	0.43	134.400	400
		DH3	1.68	268.800	400
		DH5	2.96	312.533	400
	Middle	DH1	0.42	134.400	400
		DH3	1.68	268.800	400
		DH5	2.96	311.467	400
	High	DH1	0.42	134.400	400
		DH3	1.68	268.800	400
		DH5	2.96	311.467	400
8DPSK	Low	3DH1	0.44	137.600	400
		3DH3	1.69	268.800	400
		3DH5	2.96	312.533	400
	Middle	3DH1	0.44	140.800	400
		3DH3	1.69	268.800	400
		3DH5	2.96	313.600	400
	High	3DH1	0.44	140.800	400
		3DH3	1.69	268.800	400
		3DH5	2.95	313.600	400


Please refer to the test plots as below:

DH1


Low Channel






Middle Channel




High Channel




DH3	
Low Channel	
Middle Channel	
High Channel	

DH5


Low Channel




Middle Channel



High Channel



Low Channel



Agilent

Ref 15 dBm #Atten 25 dB

Peak Log 10 dB/Offst 1.5 dB

Mkr1 Δ 440 μs 1.767 dB

Center 2.44100000 GHz

Center 2.441 GHz Res BW 1 MHz #VBW 3 MHz Span 0 Hz Sweep 4 ms (401 pts)

Center Freq 2.44100000 GHz

Start Freq 2.44100000 GHz

Stop Freq 2.44100000 GHz

CF Step 1.00000000 MHz Auto Ma

Freq Offset 0.00000000 Hz

Signal Track On Off

Scale Type Log Lin

Agilent R T

Ref 15 dBm #Atten 25 dB Mkr1 Δ 440 μ s 0.207 dB


Peak Log 10 dB/Offset 1.5 dB

Center 2.48000000 GHz

Center 2.48 GHz Res BW 1 MHz #VBW 3 MHz Span 0 Hz Sweep 4 ms (401 pts)

Center Freq 2.48000000 GHz Start Freq 2.48000000 GHz Stop Freq 2.48000000 GHz CF Step 1.00000000 MHz Auto Ma Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

Low Channel



Agilent

Ref 15 dBm #Atten 25 dB

Peak Log 10 dB/Offset 1.5 dB

Mkr1 Δ 2.96 ms 1.18 dB

Center 2.441000000 GHz

W1 S2 S3 VS AA

Center 2.441000000 GHz

Res BW 1 MHz #VBW 3 MHz Span 0 Hz

Center Freq 2.44100000 GHz

Start Freq 2.44100000 GHz

Stop Freq 2.44100000 GHz

CF Step 1.00000000 MHz Auto Man

Freq Offset 0.00000000 Hz

Signal Track On Off

Scale Type Log Lin

Unable to save file

Agilent R T

Ref 15 dBm #Atten 25 dB

Peak Log 10 dB/Offset 1.5 dB

Mkr1 Δ 2.95 ms 0.183 dB

Center 2.48000000 GHz

W1 S2 S3 VS AA

Center 2.48 GHz Res BW 1 MHz #VBW 3 MHz Span 0 Hz Res BW 1 MHz Sweep 4 ms (401 pts)

Freq/Channel Center Freq 2.48000000 GHz Start Freq 2.48000000 GHz Stop Freq 2.48000000 GHz CF Step 1.00000000 MHz Auto Mar Freq Offset 0.00000000 Hz Signal Track On Off Scale Type Log Lin

Unable to save file

8. 20dB Bandwidth

8.1 Standard Applicable

According to 15.247(a) and 15.215(c), 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.2 Test Procedure

According to ANSI C63.10-2013 section 6.9.2, the 20dB bandwidth test method as follows.

- a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW}/\text{RBW})]$ below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using $[(\text{reference value}) - \text{xx}]$. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-xx dB down amplitude” determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “-xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.3 Summary of Test Results/Plots

Test Mode	Test Channel MHz	20 dB Bandwidth kHz	Result
GFSK	2402	1029	Pass
	2441	1028	Pass
	2480	1028	Pass
8DPSK	2402	1311	Pass
	2441	1312	Pass
	2480	1315	Pass

Waltek Testing Group (Shenzhen) Co., Ltd.
Http://www.waltek.com.cn

<div>8DPSK</div>	<div> <div>Agilent</div> <div> <div>Ch Freq 2.402 GHz</div> <div>Occupied Bandwidth</div> <div>Center 2.40200000 GHz</div> </div> <div> <div>Ref 15 dBm #Peak Log 10 dB/ Offst 1.5 dB</div> <div>#Atten 25 dB</div> <div>Center 2.402 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 5 ms (401 pts)</div> <div> <div>Occupied Bandwidth</div> <div>1.1855 MHz</div> <div>Transmit Freq Error 9.333 kHz x dB Bandwidth 1.311 MHz</div> </div> </div> <div> <div>Freq/Channel</div> <div>Center Freq 2.40200000 GHz</div> <div>Start Freq 2.40050000 GHz</div> <div>Stop Freq 2.40350000 GHz</div> <div>CF Step 300.000000 kHz Auto Man</div> <div>Freq Offset 0.00000000 Hz</div> <div>Signal Track On Off</div> <div>Scale Type Log Lin</div> </div> </div>
<div>Middle Channel</div>	<div> <div>Agilent</div> <div> <div>Ch Freq 2.441 GHz</div> <div>Occupied Bandwidth</div> <div>Center 2.44100000 GHz</div> </div> <div> <div>Ref 15 dBm #Peak Log 10 dB/ Offst 1.5 dB</div> <div>#Atten 25 dB</div> <div>Center 2.441 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 5 ms (401 pts)</div> <div> <div>Occupied Bandwidth</div> <div>1.1839 MHz</div> <div>Transmit Freq Error 9.847 kHz x dB Bandwidth 1.312 MHz</div> </div> </div> <div> <div>Freq/Channel</div> <div>Center Freq 2.44100000 GHz</div> <div>Start Freq 2.43950000 GHz</div> <div>Stop Freq 2.44250000 GHz</div> <div>CF Step 300.000000 kHz Auto Man</div> <div>Freq Offset 0.00000000 Hz</div> <div>Signal Track On Off</div> <div>Scale Type Log Lin</div> </div> </div>
<div>High Channel</div>	<div> <div>Agilent</div> <div> <div>Ch Freq 2.48 GHz</div> <div>Occupied Bandwidth</div> <div>Center 2.48000000 GHz</div> </div> <div> <div>Ref 15 dBm #Peak Log 10 dB/ Offst 1.5 dB</div> <div>#Atten 25 dB</div> <div>Center 2.48 GHz #Res BW 30 kHz #VBW 100 kHz Span 3 MHz Sweep 5 ms (401 pts)</div> <div> <div>Occupied Bandwidth</div> <div>1.1834 MHz</div> <div>Transmit Freq Error 10.245 kHz x dB Bandwidth 1.315 MHz</div> </div> </div> <div> <div>Freq/Channel</div> <div>Center Freq 2.48000000 GHz</div> <div>Start Freq 2.47850000 GHz</div> <div>Stop Freq 2.48150000 GHz</div> <div>CF Step 300.000000 kHz Auto Man</div> <div>Freq Offset 0.00000000 Hz</div> <div>Signal Track On Off</div> <div>Scale Type Log Lin</div> </div> </div>

9. RF Output Power

9.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

9.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.5, the output power test method as follows.

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.

This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:

- 1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
- 2) RBW > 20 dB bandwidth of the emission being measured.
- 3) VBW \geq RBW.
- 4) Sweep: Auto.
- 5) Detector function: Peak.
- 6) Trace: Max hold.

b) Allow trace to stabilize.

c) Use the marker-to-peak function to set the marker to the peak of the emission.

d) The indicated level is the peak output power, after any corrections for external attenuators and cables.

e) A plot of the test results and setup description shall be included in the test report.

9.3 Summary of Test Results/Plots

Modulation type	Channel	Output power (dBm)	Output power (mW)	Limit (mW)	Result
GFSK	Low	-1.694	0.677	1000	Pass
	Middle	-0.435	0.905		
	High	0.976	1.252		
$\pi/4$ DQPSK	Low	-0.378	0.917	125	Pass
	Middle	0.912	1.234		
	High	2.248	1.678		
8DPSK	Low	-0.127	0.971	125	Pass
	Middle	1.197	1.317		
	High	2.455	1.760		

GFSK

Low Channel

Agilent R T

Ref 15 dBm #Atten 25 dB Mkr1 2.4021500 GHz -1.694 dBm

Peak Search Meas Tools ▶

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

More 1 of 2

Marker 2.402150000 GHz -1.694 dBm

Center 2.402 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 5 ms (401 pts)

Middle Channel

Agilent R T

Ref 15 dBm #Atten 25 dB Mkr1 2.4408375 GHz -0.435 dBm

Peak Search Meas Tools ▶

Next Peak

Next Pk Right

Next Pk Left

Min Search

Pk-Pk Search

More 1 of 2

Marker 2.440837500 GHz -0.435 dBm

Center 2.441 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 5 ms (401 pts)

High Channel

Agilent R T

Ref 15 dBm #Atten 25 dB Mkr1 2.4801125 GHz 0.976 dBm

Peak Search Meas Tools ▶

Next Peak

Next Pk Right

Next Pk Left

Min Search


Pk-Pk Search

More 1 of 2

Marker 2.480112500 GHz 0.976 dBm

Center 2.48 GHz Span 5 MHz #Res BW 1 MHz #VBW 3 MHz Sweep 5 ms (401 pts)

Pi/4 QDPSK	
Low Channel	<div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 15 dBm</div><div>#Atten 25 dB</div><div>Mkr1 2.401975 GHz</div><div>-0.378 dBm</div></div><div><div>Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1.5</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.401975000 GHz</div><div>-0.378 dBm</div></div><div><div>Center 2.402 GHz</div><div>#Res BW 3 MHz</div><div>#VBW 3 MHz</div><div>Sweep 4 ms (401 pts)</div><div>Span 10 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div>
Middle Channel	<div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 15 dBm</div><div>#Atten 25 dB</div><div>Mkr1 2.440900 GHz</div><div>0.912 dBm</div></div><div><div>Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1.5</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.440900000 GHz</div><div>0.912 dBm</div></div><div><div>Center 2.441 GHz</div><div>#Res BW 3 MHz</div><div>#VBW 3 MHz</div><div>Sweep 4 ms (401 pts)</div><div>Span 10 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div>
High Channel	<div><div><div><div>Agilent</div><div>R T</div></div><div><div>Ref 15 dBm</div><div>#Atten 25 dB</div><div>Mkr1 2.479950 GHz</div><div>2.248 dBm</div></div><div><div>Peak</div><div>Log</div><div>10</div><div>dB/</div><div>Offset</div><div>1.5</div><div>dB</div></div><div><div>M1 S2</div><div>S3 FC</div><div>AA</div></div><div><div>Marker</div><div>2.479950000 GHz</div><div>2.248 dBm</div></div><div><div>Center 2.48 GHz</div><div>#Res BW 3 MHz</div><div>#VBW 3 MHz</div><div>Sweep 4 ms (401 pts)</div><div>Span 10 MHz</div></div></div><div><div>Peak Search</div><div>Meas Tools</div><div>Next Peak</div><div>Next Pk Right</div><div>Next Pk Left</div><div>Min Search</div><div>Pk-Pk Search</div><div>More 1 of 2</div></div></div>



10. Field Strength of Spurious Emissions

10.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).


The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.


10.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

10.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Ant. Factor + Cable Loss – Ampl. Gain

The “Margin” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:


Margin = Corr. Ampl. – FCC Part 15 Limit

10.4 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.
All test modes (different data rate and different modulation) are performed, but only the worst case (8DPSK) is recorded in this report.


➤ Spurious Emissions Below 1GHz

Test Channel	Low	Polarity:	Horizontal
--------------	-----	-----------	------------




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	52.2079	34.93	-12.82	22.11	40.00	-17.89	318	100	peak
2	101.2885	33.67	-14.35	19.32	43.50	-24.18	199	100	peak
3	340.7817	32.52	-6.51	26.01	46.00	-19.99	68	100	peak
4	1000.0000	29.22	4.04	33.26	54.00	-20.74	145	100	peak

Test Channel	Low	Polarity:	Vertical
--------------	-----	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.9420	34.41	-12.87	21.54	40.00	-18.46	81	100	peak
2	107.5101	35.13	-13.97	21.16	43.50	-22.34	119	100	peak
3	357.9287	31.81	-6.73	25.08	46.00	-20.92	76	100	peak
4	996.4996	30.45	3.98	34.43	54.00	-19.57	102	100	peak

Test Channel	Middle	Polarity:	Horizontal
--------------	--------	-----------	------------




No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	42.0066	34.83	-13.29	21.54	40.00	-18.46	127	100	peak
2	106.3850	33.58	-14.00	19.58	43.50	-23.92	155	100	peak
3	352.9433	31.86	-6.57	25.29	46.00	-20.71	54	100	peak
4	1000.0000	29.51	4.04	33.55	54.00	-20.45	90	100	peak

Test Channel	Middle	Polarity:	Vertical
--------------	--------	-----------	----------




No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	50.9420	34.53	-12.87	21.66	40.00	-18.34	115	100	peak
2	108.2667	33.70	-13.96	19.74	43.50	-23.76	91	100	peak
3	414.7223	31.38	-6.20	25.18	46.00	-20.82	98	100	peak
4	996.4996	30.17	3.98	34.15	54.00	-19.85	157	100	peak

Test Channel	High	Polarity:	Horizontal
--------------	------	-----------	------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct dB/m	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Degree ()	Height (cm)	Remark
1	45.8553	34.69	-12.92	21.77	40.00	-18.23	265	100	peak
2	109.0286	33.00	-13.94	19.06	43.50	-24.44	236	100	peak
3	341.9786	31.30	-6.51	24.79	46.00	-21.21	79	100	peak
4	952.0937	31.39	2.91	34.30	46.00	-11.70	166	100	peak

Test Channel	High	Polarity:	Vertical
--------------	------	-----------	----------



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	()	(cm)	
1	52.9453	35.07	-12.88	22.19	40.00	-17.81	53	100	peak
2	100.9339	33.71	-14.38	19.33	43.50	-24.17	170	100	peak
3	346.8092	31.33	-6.49	24.84	46.00	-21.16	67	100	peak
4	972.3374	30.69	3.38	34.07	54.00	-19.93	121	100	peak

➤ Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804.00	60.94	-3.87	57.07	74.00	-16.93	H	PK
4804.00	47.45	-3.87	43.58	54.00	-10.42	H	AV
7206.00	55.80	1.14	56.94	74.00	-17.06	H	PK
7206.00	41.46	1.19	42.65	54.00	-11.35	H	AV
4804.00	59.54	-3.86	55.68	74.00	-18.32	V	PK
4804.00	45.80	-3.86	41.94	54.00	-12.06	V	AV
7206.00	56.17	1.10	57.27	74.00	-16.73	V	PK
7206.00	42.72	1.10	43.82	54.00	-10.18	V	AV
Middle Channel-2441MHz							
4882.00	60.90	-3.74	57.16	74.00	-16.84	H	PK
4882.00	46.39	-3.74	42.65	54.00	-11.35	H	AV
7323.00	55.31	1.47	56.78	74.00	-17.22	H	PK
7323.00	42.10	1.47	43.57	54.00	-10.43	H	AV
4882.00	61.37	-3.74	57.63	74.00	-16.37	V	PK
4882.00	45.27	-3.74	41.53	54.00	-12.47	V	AV
7323.00	55.17	1.47	56.64	74.00	-17.36	V	PK
7323.00	40.42	1.47	41.89	54.00	-12.11	V	AV
High Channel-2480MHz							
4960.00	60.74	-3.59	57.15	74.00	-16.85	H	PK
4960.00	46.75	-3.59	43.16	54.00	-10.84	H	AV
7440.00	55.19	1.79	56.98	74.00	-17.02	H	PK
7440.00	40.86	1.79	42.65	54.00	-11.35	H	AV
4960.00	60.80	-3.59	57.21	74.00	-16.79	V	PK
4960.00	46.65	-3.59	43.06	54.00	-10.94	V	AV
7440.00	55.38	1.79	57.17	74.00	-16.83	V	PK
7440.00	40.96	1.79	42.75	54.00	-11.25	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

11. Out of Band Emissions

11.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

11.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.6, the Band-edge measurements for RF conducted emissions test method as follows.

- a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e) (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).
- b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
- c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3.
- d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6, and orient the EUT and measurement antenna positions to produce the highest emission level.
- e) Perform the test as follows:
 - 1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
 - 2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than $[10 \log (\text{OBW/RBW})]$ below the reference level. Specific guidance is given in 4.1.5.2.
 - 3) Attenuation: Auto (at least 10 dB preferred).
 - 4) Sweep time: Coupled.
 - 5) Resolution bandwidth: 100 kHz.
 - 6) Video bandwidth: 300 kHz.
 - 7) Detector: Peak.
 - 8) Trace: Max hold.
- f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.
- g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if

this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak function to move the marker to the peak of the in-band emission.

h) Repeat step c) through step e) for every applicable modulation.

i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).

j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Restricted-band band-edge test method please refers to ANSI C63.10-2013 section 6.10.5. The emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band-edge measurements.

According to ANSI C63.10-2013 section 7.8.8, Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers.


Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

11.3 Summary of Test Results/Plots

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported.


All test modes (different data rate and different modulation) are performed, but only the worst case (8DPSK) is recorded in this report.

Test Channel	Low	Polarity:	Vertical(worst case 8DPSK)
--------------	-----	-----------	----------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2310.000	41.72	-7.78	33.94	54.00	-20.06	Average Detector
	2310.000	61.45	-7.78	53.67	74.00	-20.33	Peak Detector
2	2390.000	41.70	-7.32	34.38	54.00	-19.62	Average Detector
	2390.000	63.52	-7.32	56.20	74.00	-17.80	Peak Detector
3	2401.945	99.83	-7.25	92.58	/	/	Average Detector
	2402.047	108.68	-7.25	101.43	/	/	Peak Detector




Test Channel	High	Polarity:	Vertical(worst case 8DPSK)
--------------	------	-----------	----------------------------



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2480.005	103.07	-6.79	96.28	/	/	Average Detector
	2479.830	103.74	-6.79	96.95	/	/	Peak Detector
2	2483.500	57.72	-6.77	50.95	54.00	-3.05	Average Detector
	2483.500	66.03	-6.77	59.26	74.00	-14.74	Peak Detector
3	2500.000	41.89	-6.67	35.22	54.00	-18.78	Average Detector
	2500.000	53.59	-6.67	46.92	74.00	-27.08	Peak Detector



Worst mode 3DH1

Low channel






Worst mode 3DH1

Middle channel



Worst mode 3DH1

High channel




12. Conducted Emissions

12.1 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 Limit.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle. The spacing between the peripherals was 10 cm.

12.2 Basic Test Setup Block Diagram




12.3 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:


Start Frequency	150 kHz
Stop Frequency	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	10 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

12.5 Summary of Test Results/Plots

Test Mode	Communication	AC120V 60Hz	Polarity:	Neutral
-----------	---------------	-------------	-----------	---------



No.	Frequency	Limit dBuV	Level dBuV	Delta dB	Reading dBuV	Factor dB	Detector	Phase
1	150.000kHz	66.0	52.4	-13.6	42.0	10.4	QP	N
2	202.000kHz	63.5	50.0	-13.5	39.7	10.3	QP	N
3	254.000kHz	61.6	47.8	-13.8	37.5	10.3	QP	N
4	298.000kHz	60.3	41.1	-19.2	30.9	10.2	QP	N
5	354.000kHz	58.9	42.4	-16.5	32.2	10.2	QP	N
6	11.842MHz	60.0	42.9	-17.1	32.6	10.3	QP	N
7	150.000kHz	56.0	45.6	-10.4	35.2	10.4	CAV	N
8	202.000kHz	53.5	35.1	-18.4	24.8	10.3	CAV	N
9	258.000kHz	51.5	29.6	-21.9	19.3	10.3	CAV	N
10	290.000kHz	50.5	36.1	-14.4	25.9	10.2	CAV	N
11	866.000kHz	46.0	34.7	-11.3	24.8	9.9	CAV	N
12	4.990MHz	46.0	24.3	-21.7	14.3	10.0	CAV	N



***** END OF REPORT *****