

RF EXPOSURE REPORT

REPORT NO.: SA950210H01A
MODEL NO.: VNT6656G6A40
FCC ID: NCI-VNT6656G6A4X

ACCORDING: FCC Guidelines for Human Exposure
IEEE C95.1

APPLICANT: VIA Technologies, Inc.

ADDRESS: 8F, 533, Chung-Cheng Rd. Hsin-Tien, Taipei 231

ISSUED BY: Advance Data Technology Corporation

LAB LOCATION: No. 81-1, Lu Liao Keng, 9 Ling, Wu Lung
Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien,
Taiwan, R.O.C.

RF Exposure Measurement

1. Introduction

In this document, we try to prove the safety of radiation harmfulness to the human body for our product. The limit for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 is followed. The Gain of the antenna used in this product is measured in a Fully Anechoic Chamber (FAC) calibrated for antenna measurement in ADT, and also the maximum total power input to the antenna is measured. Through the Friis transmission formula and the maximum gain of the antenna, we can calculate the distance, away from the product, where the limit of MPE is reached.

Although the Friis transmission formula is a far field assumption, the calculated result of that is an over-prediction for near field power density. We will take that as the worst case to specify the safety range.

2. RF Exposure Limit

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
300-1500	F/300	6
1500-100,000	5	6
(B)Limits For General Population / Uncontrolled Exposure				
300-1500	F/1500	6
1500-100,000	1.0	30

F = Frequency in MHz

3. Friis Formula

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

where

P_d = power density in mW/cm^2

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, $1 mW/cm^2$. If we know the maximum Gain of the antenna and the total power input to the antenna, through the calculation, we will know the MPE value at distance 20cm.

Ref. : David K. Cheng, *Field and Wave Electromagnetics*, Second Edition,
Page 640, Eq. (11-133).

4. EUT Operating condition

The software provided by Manufacturer enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

5. Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. Warning statement to the user for keeping at least 20cm or more separation distance with the antenna should be included in users manual. So, this device is classified as **Mobile Device**

6. Test Results

6.1 Antenna Gain

The antennas used in this product are as following:

No.	Brand Name	Model No.	Gain (dBi)	Antenna Type	Antenna Connector
1	High-tek	T700(PEN)	0.05	PIFA	I-PEX
2	ARISTOTLE	PCB013	1	PCB	I-PEX
3	ARISTOTLE	C2H Series	2.5	Monopole	I-PEX
4	Own design	MN003	1.29	PCB	I-PEX

Note:

1. From above antennas, the different type of antennas was chosen for final test and its data were recorded in this report.
2. Antenna 2 and 4 are the same type of antenna. The antenna 5 was selected as representative antenna for the test.

6.2 Output Power Into Antenna & RF Exposure value at distance 20cm:

For Part 802.11b:

Antenna 1 : PIFA antenna (Gain : 0.05dBi)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	63.241	0.013	1.0
6	2437	64.863	0.013	1.0
11	2462	64.565	0.013	1.0

Antenna 3 : Monopole antenna (Gain : 2.5dBi)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	63.241	0.022	1.0
6	2437	64.863	0.023	1.0
11	2462	64.565	0.023	1.0

Antenna 4 : PCB antenna (Gain : 1.29dBi)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	63.241	0.017	1.0
6	2437	64.863	0.017	1.0
11	2462	64.565	0.017	1.0

For Part 802.11g:

Antenna 1 : PIFA antenna (Gain : 0.05dBi)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	64.863	0.013	1.0
6	2437	66.681	0.013	1.0
11	2462	67.608	0.014	1.0

Antenna 3 : Monopole antenna (Gain : 2.5dBi)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	64.863	0.023	1.0
6	2437	66.681	0.024	1.0
11	2462	67.608	0.024	1.0

Antenna 4 : PCB antenna (Gain : 1.29dBi)

Channel	Channel Frequency (MHz)	Output Power to Antenna (mW)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
1	2412	64.863	0.017	1.0
6	2437	66.681	0.018	1.0
11	2462	67.608	0.018	1.0