

CCSEM-TRF-001 Rev. 02 Sep 01, 2023 Report No.: KSCR240900186802

Page: 1 of 7

1 Cover Page

RF Exposure Evaluation Report

Application No.: KSCR2409001868AT **FCC ID:** OJFE62-X3RU-25

Name of Testing Laboratory

preparing the Report:

Compliance Certification Services (Kunshan) Inc.

Address of Testing Laboratory

preparing the Report:

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan

City, Jiangsu, China.

Applicant: Corning Optical Communications LLC

Address of Applicant: 840 N McCarthy Blvd, Milpitas, California, United States

Manufacturer: Corning Optical Communications LLC

Address of Manufacturer: 840 N McCarthy Blvd, Milpitas, California, United States

Equipment Under Test (EUT):

EUT Name: Remote Unit
Model No.: E62-X3RU
Trade mark: CORNING

Standard(s): FCC Rules 47 CFR §2.1091

KDB447498 D01 General RF Exposure Guidance v06

Date of Receipt: 2024-09-18

Date of Test: 2024-10-24 to 2024-10-26

Date of Issue: 2024-10-30

Test Result: Pass*

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

^{*} In the configuration tested, the EUT complied with the standards specified above.



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240900186802

Page: 2 of 7

| Revision Record | | | | | |
|-----------------|-------------|------------|--------|--|--|
| Version | Description | Date | Remark | | |
| 00 | Original | 2024-10-30 | / | | |
| | | | | | |
| | | | | | |

| Authorized for issue by: | | |
|--------------------------|---------------------------|--|
| Tested By | Kass_Gao/Project Engineer | |
| Approved By | Terry Hou /Reviewer | |



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240900186802

Page: 3 of 7

2 Contents

| | | | Page |
|---|------------|---|--------|
| 1 | Cov | er Page | 1 |
| _ | 0 | A surface | • |
| 2 | Con | tents | 3 |
| 3 | Gen | eral Information | 4 |
| | 3.1 | General Description of E.U.T. | 4 |
| | 3.2 | Technical Specifications | 4 |
| | 3.3 | Test Location | 5 |
| | 3.4 | Test Facility | 5 |
| 4 | Test | Standards and Limits | |
| • | | | _ |
| | 4.1 | FCC Radiofrequency radiation exposure limits: | 6 |
| 5 | Mea | surement and Calculation | 7 |
| | 5.1 5.2 | Maximum transmit powerMPE Calculation | 7 7 |



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240900186802

Page: 4 of 7

3 General Information

3.1 General Description of E.U.T.

| Power supply: AC 120V/60Hz or DC 48V | Power supply: | AC 120V/60Hz or DC 48V |
|--------------------------------------|---------------|------------------------|
|--------------------------------------|---------------|------------------------|

3.2 Technical Specifications

| Product Name: | Remote Unit |
|-----------------------|--|
| Device type: | Booster |
| Model No.: | E62-X3RU |
| Frequency Band: | NR Band n41 |
| Frequency Range: | 2496MHz-2690MHz |
| Antenna Type: | External Antenna |
| Antenna Gain: | 11 dBi for 2496MHz to 2690MHz (Provided by manufacturer) |
| Modulation Type: | QPSK,16QAM,64QAM,256QAM |
| Antenna Delivery: | 4T4R MIMO,2T2R MIMO,SISO |
| Nominal Output Power: | 46dBm |
| Nominal gain: | 46dB |

Note:

The antenna gain value is provided by the customer. The test lab will not be responsible for wrong test result due to incorrect information about antenna gain values.



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240900186802

Page: 5 of 7

3.3 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc.

No.10 Weiye Rd, Innovation park, Eco&Tec, Development Zone, Kunshan City, Jiangsu, China.

Tel: +86 512 5735 5888 Fax: +86 512 5737 0818

No tests were sub-contracted.

Note:

- 1.SGS is not responsible for wrong test results due to incorrect information (e.g., max. internal working frequency, antenna gain, cable loss, etc) is provided by the applicant. (If applicable).
- 2.SGS is not responsible for the authenticity, integrity and the validity of the conclusion based on results of the data provided by applicant. (If applicable).
- 3. Sample source: sent by customer.

3.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA

Compliance Certification Services (Kunshan) Inc. is accredited by the American Association for Laboratory Accreditation (A2LA). Certificate No. 2541.01.

• FCC

Compliance Certification Services (Kunshan) Inc. has been recognized as an accredited testing laboratory. Designation Number: CN1172.

• ISED

Compliance Certification Services (Kunshan) Inc. has been recognized by Innovation, Science and Economic Development Canada (ISED) as an accredited testing laboratory. Company Number: 2324E

VCCI

The 3m and 10m Semi-anechoic chamber and Shielded Room of Compliance Certification Services (Kunshan) Inc. has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-20134, R-11600, C-11707, T-11499, G-10216 respectively.



CCSEM-TRF-001 Rev. 02 Sep 01, 2023

Report No.: KSCR240900186802

Page: 6 of 7

4 Test Standards and Limits

4.1 FCC Radiofrequency radiation exposure limits:

According to §1.1310, the limit for general population/uncontrolled exposures

| Frequency range (MHz) | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm²) | Averaging time (minutes) | | |
|---|-------------------------------|-------------------------------|---------------------------|--------------------------|--|--|
| Limits for General Population/Uncontrolled Exposure | | | | | | |
| 0.3-1.34 | 614 | 1.63 | *(100) | 30 | | |
| 1.34-30 | 824/f | 2.19/f | *(180/f2) | 30 | | |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 | | |
| 300-1500 | / | / | f/1500 | 30 | | |
| 1500-100,000 | / | / | 1.0 | 30 | | |

Note: 5G N41 is 1mW/cm².



CCSEM-TRF-001 Rev. 02 Sep 01, 2023 Report No.: KSCR240900186802

Page: 7 of 7

5 Measurement and Calculation

5.1 Maximum transmit power

The Power Data is based on the RF Test Report KSCR240900186801.

5.2 MPE Calculation

According to the formula S=P/4 π R², we can calculate S which is MPE. Note:

1)P (mW)

2) R = distance to the center of radiation of antenna (in centimeter)

3) MPE limit = 1mW/cm²

| Test Mode | Frequency Band (MHz) | Maximum E.I.R.P (dBm) | Power Density (mW/cm2) | Limit of Power Density S(mW/cm2) | Safety Distance (cm) |
|-------------|-------------------------|-----------------------------|---------------------------|--|----------------------------|
| NR Band n41 | 2496~ 2690 | 62.80 | 0.972 | 1 | 395.0 |

According to the KDB447498 section 7.2 determine the device is exclusion from SAR test.

--End of the Report--