

SAR Compliance Test Report

Test report no.:	Salo_SAR_0627_02	Date of report:	2006-07-03
Template version:	5	Number of pages:	49
Testing laboratory:	TCC Nokia Salo Laboratory P.O.Box 86 Joensuunkatu 7H / Kiila 1B FIN-24101 SALO, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 45220	Client:	Nokia Corporation P.O. Box 68 Sinitaival 5 FIN-33721 TAMPERE, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 46880
Responsible test engineer:	Virpi Tuominen	Product contact person:	Timo Seppälä
Measurements made by:	Janne Hirsimäki, Ari Orte, Virpi Tuominen		
Tested devices:	RM-170, RM-171		
FCC IDs:	PDNRM-170, PDNRM-171	ICs:	661R-RM170, 661R-RM171
Supplement reports:	-		
Testing has been carried out in accordance with:	47CFR §2.1093 Radiofrequency Radiation Exposure Evaluation: Portable Devices FCC OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01) Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields RSS-102 Evaluation Procedure for Mobile and Portable Radio Transmitters with Respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields IEEE 1528 - 2003 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques		
Documentation:	The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test results:	The tested device complies with the requirements in respect of all parameters subject to the test. The test results and statements relate only to the items tested. The test report shall not be reproduced except in full, without written approval of the laboratory.		
Date and signatures:			
For the contents:			

CONTENTS

1. SUMMARY OF SAR TEST REPORT.....	3
1.1 TEST DETAILS.....	3
1.2 MAXIMUM RESULTS.....	3
1.2.1 Head Configuration.....	3
1.2.2 Body Worn Configuration	4
1.2.3 Maximum Drift	4
1.2.4 Measurement Uncertainty	4
2. DESCRIPTION OF THE DEVICE UNDER TEST.....	4
2.1 PICTURE OF THE DEVICE.....	5
2.2 DESCRIPTION OF THE ANTENNA	5
3. TEST CONDITIONS	5
3.1 TEMPERATURE AND HUMIDITY	5
3.2 TEST SIGNAL, FREQUENCIES AND OUTPUT POWER	5
4. DESCRIPTION OF THE TEST EQUIPMENT	6
4.1 MEASUREMENT SYSTEM AND COMPONENTS	6
4.1.1 Isotropic E-field Probe Type ET3DV6	7
4.2 PHANTOMS	7
4.3 TISSUE SIMULANTS	7
4.3.1 Tissue Simulant Recipes	8
4.3.2 System Checking	8
4.3.3 Tissue Simulants used in the Measurements.....	9
5. DESCRIPTION OF THE TEST PROCEDURE	10
5.1 DEVICE HOLDER.....	10
5.2 TEST POSITIONS.....	11
5.2.1 Against Phantom Head.....	11
5.2.2 Body Worn Configuration	11
5.3 SCAN PROCEDURES	12
5.4 SAR AVERAGING METHODS.....	12
6. MEASUREMENT UNCERTAINTY	13
7. RESULTS	14
APPENDIX A: SYSTEM CHECKING SCANS	18
APPENDIX B: MEASUREMENT SCANS.....	25
APPENDIX C: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)	48
APPENDIX D: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)	49

1. SUMMARY OF SAR TEST REPORT

1.1 Test Details

Period of test	2006-05-15 to 2006-05-23
SN, HW and SW numbers of tested device	SN: RM-170, 004400/81/171360/9, HW: 5002, SW: V06.12(02), DUT: 11186 SN: RM-171, 004400/81/173857/2, HW: 5006, SW: V06.12(02), DUT: 11273
Batteries used in testing	BL-5C, DUT: 11188, 11189
Headsets used in testing	HS-6, DUT: 11019
Other accessories used in testing	Memory Card, Type: MU-26, DUT: 11190
State of sample	Prototype unit
Notes	-

1.2 Maximum Results

The maximum measured SAR values for Head configuration and Body Worn configuration are given in section 1.2.1 and 1.2.2 respectively. The device conforms to the requirements of the standard(s) when the maximum measured SAR value is less than or equal to the limit.

1.2.1 Head Configuration

Type	Mode	Ch / f (MHz)	Radiated power	Position	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
RM-170	2-slot GPRS850	190 / 836.6	32.0dBm ERP	Right, Cheek	0.643W/kg	0.72W/kg	1.6 W/kg	PASSED
	2-slot GPRS1900	512 / 1850.2	31.0dBm EIRP	Right, Tilt	0.790W/kg	0.88W/kg	1.6 W/kg	PASSED
RM-171	2-slot GPRS850	251 / 848.8	31.7dBm ERP	Right, Cheek	0.827W/kg	0.93W/kg	1.6 W/kg	PASSED
	2-slot GPRS1900	512 / 1850.2	31.9dBm EIRP	Right, Tilt	0.858W/kg	0.96W/kg	1.6 W/kg	PASSED

1.2.2 Body Worn Configuration

Type	Mode	Ch / f (MHz)	Radiated power	Separation distance	Measured SAR value (1g avg)	Scaled* SAR value (1g avg)	SAR limit (1g avg)	Result
RM-170	2-slot GPRS850	190 / 836.6	28.3dBm ERP	1.5cm	1.03W/kg	1.15W/kg	1.6 W/kg	PASSED
	2-slot GPRS1900	661 / 1880.0	31.9dBm EIRP	1.5cm	0.941W/kg	1.05W/kg	1.6 W/kg	PASSED
RM-171	2-slot GPRS850	190 / 836.6	31.2dBm ERP	1.5cm	1.19W/kg	1.33W/kg	1.6 W/kg	PASSED
	2-slot GPRS1900	661 / 1880.0	32.7dBm EIRP	1.5cm	1.07W/kg	1.20W/kg	1.6 W/kg	PASSED

*SAR values are scaled up by 12% to cover measurement drift.

1.2.3 Maximum Drift

Maximum drift covered by 12% scaling up of the SAR values	Maximum drift during measurements
0.5dB	0.34dB

1.2.4 Measurement Uncertainty

Expanded Uncertainty (k=2) 95%	± 25.8%
--------------------------------	---------

2. DESCRIPTION OF THE DEVICE UNDER TEST

Device category	Portable
Exposure environment	General population / uncontrolled

Modes and Bands of Operation	GSM	GPRS	EGPRS	BT
	850 / 1900	850 / 1900	850 / 1900	
Modulation Mode	GMSK	GMSK	GMSK / 8PSK	GFSK
Duty Cycle	1/8	1/8 to 2/8	1/8 to 2/8	
Transmitter Frequency Range (MHz)	824 - 849 1850 - 1910	824 - 849 1850 - 1910	824 - 849 1850 - 1910	2402-2480

Outside of USA and Canada, the transmitter of the device is capable of operating also in 900 / 1800 MHz bands, which are not part of this filing.

This device has Dual Transfer Mode capability for use at the ear. Therefore, SAR for multi slot GPRS mode was evaluated against the head profile of the phantom.

2.1 Picture of the Device



RM-170, RM-171

2.2 Description of the Antenna

The device has an internal patch antenna.

3. TEST CONDITIONS

3.1 Temperature and Humidity

Ambient temperature (°C):	21.9 to 22.9
Ambient humidity (RH %):	27 to 33

3.2 Test Signal, Frequencies and Output Power

The device was put into operation by using a call tester. Communication between the device and the call tester was established by air link.

The device output power was set to maximum power level for all tests; a fully charged battery was used for every test sequence.

In all operating bands the measurements were performed on lowest, Middle and highest channels.

The radiated output power of the devices were measured by a separate test laboratory on the same unit(s) as used for SAR testing.

The difference between the two tested device types is that RM-170 has a camera and RM-171 does not. Due to similar RF performance of these two device types, testing of RM-171 was minimised based on the results from RM-170.

4. DESCRIPTION OF THE TEST EQUIPMENT

4.1 Measurement System and Components

The measurements were performed using an automated near-field scanning system, DASY4, manufactured by Schmid & Partner Engineering AG (SPEAG) in Switzerland. The SAR extrapolation algorithm used in all measurements was the 'advanced extrapolation' algorithm.

The following table lists calibration dates of SPEAG components:

Test Equipment	Serial Number	Calibration interval	Calibration expiry
DAE 3	388	12 months	2007-01
E-field Probe ET3DV6	1395	12 months	2006-09
Dipole Validation Kit, D835V2	462	24 months	2006-07
Dipole Validation Kit, D1900V2	5d030	24 months	2006-07
DASY4 software	Version 4.6	-	-

Additional test equipment used in testing:

Test Equipment	Model	Serial Number	Calibration interval	Calibration expiry
Signal Generator	HP 8657B	3630U08114	12 months	2007-01
Amplifier	AR 5S1G4	306024	12 months	2006-07
Power Meter	Agilent E4416A	GB41291465	12 months	2007-01
Power Sensor	Agilent E9323A	US40411045	12 months	2007-01
Call Tester	CMU 200	101111	-	-
Call Tester	CMU 200	104983	-	-
Vector Network Analyzer	8753E	US38432928	12 months	2006-10
Dielectric Probe Kit	85070B	US33020420	-	-

4.1.1 Isotropic E-field Probe Type ET3DV6

Construction	Symmetrical design with triangular core Built-in optical fiber for surface detection system Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., butyl diglycol)
Calibration	Calibration certificate in Appendix C
Frequency	10 MHz to 3 GHz (dosimetry); Linearity: ± 0.2 dB (30 MHz to 3 GHz)
Optical Surface Detection	± 0.2 mm repeatability in air and clear liquids over diffuse reflecting surfaces
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.4 dB in HSL (rotation normal to probe axis)
Dynamic Range	5 μ W/g to > 100 mW/g; Linearity: ± 0.2 dB
Dimensions	Overall length: 330 mm Tip length: 16 mm Body diameter: 12 mm Tip diameter: 6.8 mm Distance from probe tip to dipole centers: 2.7 mm
Application	General dosimetry up to 3 GHz Compliance tests of mobile phones Fast automatic scanning in arbitrary phantoms

4.2 Phantoms

The phantom used for all tests i.e. for both system checks and device testing, was the twin-headed "SAM Phantom", manufactured by SPEAG. The phantom conforms to the requirements of IEEE 1528 - 2003.

System checking was performed using the flat section, whilst Head SAR tests used the left and right head profile sections. Body SAR testing also used the flat section between the head profiles.

The SPEAG device holder (see Section 5.1) was used to position the device in all tests whilst a tripod was used to position the validation dipoles against the flat section of phantom.

4.3 Tissue Simulants

Recommended values for the dielectric parameters of the tissue simulants are given in IEEE 1528 - 2003 and FCC Supplement C to OET Bulletin 65. All tests were carried out using simulants

whose dielectric parameters were within $\pm 5\%$ of the recommended values. All tests were carried out within 24 hours of measuring the dielectric parameters.

The depth of the tissue simulant was 15.0 ± 0.5 cm measured from the ear reference point during system checking and device measurements.

4.3.1 Tissue Simulant Recipes

The following recipes were used for Head and Body tissue simulants:

800MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	39.74	55.97
HEC	0.25	1.21
Sugar	58.31	41.76
Preservative	0.15	0.27
Salt	1.55	0.79

1900MHz band

Ingredient	Head (% by weight)	Body (% by weight)
Deionised Water	54.50	70.25
Tween 20	45.23	29.41
Salt	0.27	0.34

4.3.2 System Checking

The manufacturer calibrates the probes annually. Dielectric parameters of the tissue simulants were measured every day using the dielectric probe kit and the network analyser. A system check measurement was made following the determination of the dielectric parameters of the simulant, using the dipole validation kit. A power level of 250 mW was supplied to the dipole antenna, which was placed under the flat section of the twin SAM phantom. The system checking results (dielectric parameters and SAR values) are given in the table below.

System checking, head tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.45	41.8	0.92	
	$\pm 10\%$ window	2.20 – 2.70			
	2006-05-15	2.57	41.6	0.90	22.8
	2006-05-23	2.58	41.5	0.90	22.6
1900	Reference result	9.76	39.5	1.46	
	$\pm 10\%$ window	8.78 – 10.74			
	2006-05-19	10.4	38.8	1.40	22.1
	2006-05-22	10.5	38.9	1.39	22.5

System checking, body tissue simulant

f [MHz]	Description	SAR [W/kg], 1g	Dielectric Parameters		Temp [°C]
			ϵ_r	σ [S/m]	
835	Reference result	2.45	54.6	0.99	
	$\pm 10\%$ window	2.20 – 2.70			
	2006-05-17	2.55	54.9	0.96	21.3
1900	Reference result	9.94	52.2	1.57	
	$\pm 10\%$ window	8.95 – 10.93			
	2006-05-20	10.8	52.7	1.53	22.4

Plots of the system checking scans are given in Appendix A.

4.3.3 Tissue Simulants used in the Measurements

Head tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	41.5	0.90	
	$\pm 5\%$ window	39.4 – 43.6	0.86 – 0.95	
	2006-05-15	41.6	0.90	21.0
	2006-05-23	41.5	0.90	21.0
1880	Recommended value	40.0	1.40	
	$\pm 5\%$ window	38.0 – 42.0	1.33 – 1.47	
	2006-05-19	38.9	1.39	21.0
	2006-05-22	39.0	1.37	21.0

Body tissue simulant measurements

f [MHz]	Description	Dielectric Parameters		Temp [°C]
		ϵ_r	σ [S/m]	
836	Recommended value	55.2	0.97	
	$\pm 5\%$ window	52.4 – 58.0	0.92 – 1.02	
	2006-05-17	54.9	0.96	21.0
	2006-05-23	55.1	0.97	21.0
1880	Recommended value	53.3	1.52	
	$\pm 5\%$ window	50.6 – 56.0	1.44 – 1.60	
	2006-05-19	52.9	1.51	21.0
	2006-05-20	52.8	1.52	21.0

5. DESCRIPTION OF THE TEST PROCEDURE

5.1 Device Holder

The device was placed in the device holder (illustrated below) that is supplied by SPEAG as an integral part of the Dasy system.



Device holder supplied by SPEAG

A Nokia designed spacer (illustrated below) was used to position the device within the SPEAG holder. The spacer positions the device so that the holder has minimal effect on the test results but still holds the device securely. The spacer was removed before the tests.



Nokia spacer

5.2 Test Positions

5.2.1 Against Phantom Head

Measurements were made in “cheek” and “tilt” positions on both the left hand and right hand sides of the phantom.

The positions used in the measurements were according to IEEE 1528 - 2003 "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques".



Photo of the device in “cheek” position



Photo of the device in “tilt” position

5.2.2 Body Worn Configuration

The device was placed in the SPEAG holder using the Nokia spacer and placed below the flat section of the phantom. The distance between the device and the phantom was kept at the separation distance indicated in the photo below using a separate flat spacer that was removed before the start of the measurements. The device was oriented with its antenna facing the phantom since this orientation gives higher results.



Photo of the device positioned for Body SAR measurement.
The spacer was removed for the tests

5.3 Scan Procedures

First, area scans were used for determination of the field distribution. Next, a zoom scan, a minimum of 5x5x7 points covering a volume of at least 30x30x30mm, was performed around the highest E-field value to determine the averaged SAR value. Drift was determined by measuring the same point at the start of the area scan and again at the end of the zoom scan.

5.4 SAR Averaging Methods

The maximum SAR value was averaged over a cube of tissue using interpolation and extrapolation.

The interpolation, extrapolation and maximum search routines within Dasy4 are all based on the modified Quadratic Shepard's method (Robert J. Renka, "Multivariate Interpolation Of Large Sets Of Scattered Data", University of North Texas ACM Transactions on Mathematical Software, vol. 14, no. 2, June 1988, pp. 139-148).

The interpolation scheme combines a least-square fitted function method with a weighted average method. A trivariate 3-D / bivariate 2-D quadratic function is computed for each measurement point and fitted to neighbouring points by a least-square method. For the zoom scan, inverse distance weighting is incorporated to fit distant points more accurately. The interpolating function is finally calculated as a weighted average of the quadratics.

In the zoom scan, the interpolation function is used to extrapolate the Peak SAR from the deepest measurement points to the inner surface of the phantom.

6. MEASUREMENT UNCERTAINTY

Table 6.1 – Measurement uncertainty evaluation

Uncertainty Component	Section in IEEE 1528	Tol. (%)	Prob Dist	Div	G_i	$G_i \cdot u_i$ (%)	ν_i
Measurement System							
Probe Calibration	E2.1	±5.9	N	1	1	±5.9	∞
Axial Isotropy	E2.2	±4.7	R	√3	$(1-c_p)^{1/2}$	±1.9	∞
Hemispherical Isotropy	E2.2	±9.6	R	√3	$(c_p)^{1/2}$	±3.9	∞
Boundary Effect	E2.3	±1.0	R	√3	1	±0.6	∞
Linearity	E2.4	±4.7	R	√3	1	±2.7	∞
System Detection Limits	E2.5	±1.0	R	√3	1	±0.6	∞
Readout Electronics	E2.6	±1.0	N	1	1	±1.0	∞
Response Time	E2.7	±0.8	R	√3	1	±0.5	∞
Integration Time	E2.8	±2.6	R	√3	1	±1.5	∞
RF Ambient Conditions - Noise	E6.1	±3.0	R	√3	1	±1.7	∞
RF Ambient Conditions - Reflections	E6.1	±3.0	R	√3	1	±1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	±0.4	R	√3	1	±0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	±2.9	R	√3	1	±1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5	±3.9	R	√3	1	±2.3	∞
Test sample Related							
Test Sample Positioning	E4.2	±6.0	N	1	1	±6.0	11
Device Holder Uncertainty	E4.1	±5.0	N	1	1	±5.0	7
Output Power Variation - SAR drift measurement	6.6.3	±0.0	R	√3	1	±0.0	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	±4.0	R	√3	1	±2.3	∞
Conductivity Target - tolerance	E3.2	±5.0	R	√3	0.64	±1.8	∞
Conductivity - measurement uncertainty	E3.3	±5.5	N	1	0.64	±3.5	5
Permittivity Target - tolerance	E3.2	±5.0	R	√3	0.6	±1.7	∞
Permittivity - measurement uncertainty	E3.3	±2.9	N	1	0.6	±1.7	5
Combined Standard Uncertainty			RSS			±12.9	116
Coverage Factor for 95%			k=2				
Expanded Uncertainty						±25.8	

7. RESULTS

The measured Head SAR values for the test device are tabulated below:

850MHz, Head SAR results

Type designation	Memory Card	Test configuration		SAR, averaged over 1g (W/kg)		
				Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
GSM		Power		34.5 dBm	34.5 dBm	33.7 dBm
RM-170	Without MC	Right	Cheek	-	0.476	-
2-slot GPRS		Power		32.3 dBm	32.0 dBm	31.0 dBm
RM-170	Without MC	Left	Cheek	-	0.608	-
			Tilt	-	0.459	-
		Right	Cheek	0.614	0.643	0.610
			Tilt	-	0.521	-
RM-170	With MC	Right Cheek		-	0.582	-
RM-170	Without MC	Right Cheek with BT active		-	0.589	-
2-slot EGPRS		Power		29.9 dBm	29.2 dBm	28.8 dBm
RM-170	Without MC	Right Cheek		-	0.210	-
2-slot GPRS		Power		32.3 dBm	32.4 dBm	31.7 dBm
RM-171	Without MC	Left	Cheek	-	-	-
			Tilt	-	-	-
		Right	Cheek	0.562	0.665	0.827
			Tilt	-	-	-
RM-171	With MC	Right Cheek		-	-	0.745
RM-171	Without MC	Right Cheek with BT active		-	-	0.766

1900MHz, Head SAR results

Type designation	Memory Card	Test configuration		SAR, averaged over 1g (W/kg)		
				Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
GSM		Power		32.0 dBm	32.6 dBm	31.7 dBm
RM-170	Without MC	Left	Cheek	-	0.302	-
2-slot GPRS		Power		31.1 dBm	31.6 dBm	30.2 dBm
RM-170	Without MC	Left	Cheek	-	0.418	-
			Tilt	-	0.500	-
		Right	Cheek	-	0.575	-
			Tilt	0.790	0.674	0.594
RM-170	With MC	Right Tilt		0.606	-	-
RM-170	Without MC	Right Tilt with BT active		0.772	-	-
2-slot EGPRS		Power		28.5 dBm	28.7 dBm	26.6 dBm
RM-170	Without MC	Right Tilt		0.371	-	-
2-slot GPRS		Power		31.9 dBm	32.6 dBm	31.8 dBm
RM-171	Without MC	Left	Cheek	-	-	-
			Tilt	-	-	-
		Right	Cheek	-	-	-
			Tilt	0.787	0.685	0.604
RM-171	With MC	Right Tilt		0.858	-	-
RM-171	With MC	Right Tilt with BT active		0.787	-	-

The measured Body SAR values for the test device are tabulated below:

850MHz, Body SAR results

Type designation	Memory Card	Test configuration	SAR, averaged over 1g (W/kg)		
			Ch 128 824.2 MHz	Ch 190 836.6 MHz	Ch 251 848.8 MHz
2-slot GPRS		Power	26.9 dBm	28.3 dBm	28.7 dBm
RM-170	Without MC	Without headset	0.954	1.03	0.981
		Headset HS-6	0.705	0.778	0.760
RM-170	With MC	Without headset	-	1.01	-
RM-170	Without MC	Without headset, with BT active	-	0.993	-
2-slot GPRS		Power	31.6 dBm	31.2 dBm	30.6 dBm
RM-171	Without MC	Without headset	1.09	1.19	1.11
		Headset HS-6	-	-	-
RM-171	With MC	Without headset	-	1.18	-
RM-171	Without MC	Without headset, with BT active	-	1.19	-

1900MHz, Body SAR results

Type designation	Memory Card	Test configuration	SAR, averaged over 1g (W/kg)		
			Ch 512 1850.2 MHz	Ch 661 1880.0 MHz	Ch 810 1909.8 MHz
2-slot GPRS		Power	31.9 dBm	31.9 dBm	30.6 dBm
RM-170	Without MC	Without headset	0.912	0.941	0.892
		Headset HS-6	0.840	0.842	0.728
RM-170	With MC	Without headset	-	0.884	-
RM-170	Without MC	Without headset, with BT active	-	0.888	-
2-slot GPRS		Power	31.9 dBm	32.7 dBm	32.9 dBm
RM-171	Without MC	Without headset	0.912	1.04	0.880
		Headset HS-6	-	-	-
RM-171	With MC	Without headset	-	1.07	-
RM-171	With MC	Without headset, with BT active	-	0.939	-

Plots of the Measurement scans are given in Appendix B.

APPENDIX A: SYSTEM CHECKING SCANS

Date/Time: 2006-05-15 11:47:45
Test Laboratory: TCC Nokia, Salo Laboratory
Type: D835V2; Serial: D835V2 - SN: 462


Communication System: CW
Frequency: 835 MHz; Duty Cycle: 1:1
Medium: HSL835; Medium Notes: t=22.8 C
Medium parameters used: f = 835 MHz; $\sigma = 0.9$ mho/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

A) d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 2.77 mW/g

A) d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 57.7 V/m; Power Drift = -0.061 dB
Peak SAR (extrapolated) = 3.86 W/kg
SAR(1 g) = 2.57 mW/g; SAR(10 g) = 1.68 mW/g
Maximum value of SAR (measured) = 2.76 mW/g



Date/Time: 2006-05-23 06:59:00
Test Laboratory: TCC Nokia, Salo Laboratory
Type: D835V2; Serial: D835V2 - SN: 462


Communication System: CW
Frequency: 835 MHz; Duty Cycle: 1:1
Medium: HSL835; Medium Notes: t=22.6 C
Medium parameters used: f = 835 MHz; σ = 0.903 mho/m; ϵ_r = 41.5; ρ = 1000 kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

A) d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 2.77 mW/g

A) d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 57.5 V/m; Power Drift = -0.011 dB
Peak SAR (extrapolated) = 3.91 W/kg
SAR(1 g) = 2.58 mW/g; SAR(10 g) = 1.68 mW/g
Maximum value of SAR (measured) = 2.81 mW/g



Date/Time: 2006-05-19 08:14:30
Test Laboratory: TCC Nokia, Salo Laboratory
Type: D1900V2; Serial: D1900V2 - SN: 5d030


Communication System: CW
Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: HSL1900; Medium Notes: 22.1C
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.4$ mho/m; $\epsilon_r = 38.8$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 12.3 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 93.5 V/m; Power Drift = -0.170 dB
Peak SAR (extrapolated) = 18.0 W/kg
SAR(1 g) = 10.4 mW/g; SAR(10 g) = 5.51 mW/g
Maximum value of SAR (measured) = 11.9 mW/g



Date/Time: 2006-05-22 10:25:22
Test Laboratory: TCC Nokia, Salo Laboratory
Type: D1900V2; Serial: D1900V2 - SN: 5d030


Communication System: CW
Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: HSL1900; Medium Notes: 22.5C
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 13.0 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 97.7 V/m; Power Drift = -0.046 dB
Peak SAR (extrapolated) = 18.1 W/kg
SAR(1 g) = 10.5 mW/g; SAR(10 g) = 5.56 mW/g
Maximum value of SAR (measured) = 11.9 mW/g



Date/Time: 2006-05-17 16:50:03
Test Laboratory: TCC Nokia, Salo Laboratory
Type: D835V2; Serial: D835V2 - SN: 462


Communication System: CW
Frequency: 835 MHz; Duty Cycle: 1:1
Medium: M835; Medium Notes: 21.3 C
Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.961 \text{ mho/m}$; $\epsilon_r = 54.9$; $\rho = 1000 \text{ kg/m}^3$
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.91, 5.91, 5.91); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

A) $d=15\text{mm}$, $\text{Pin}=250\text{mW}$ /Area Scan (61x81x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 2.75 mW/g

A) $d=15\text{mm}$, $\text{Pin}=250\text{mW}$ /Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$
Reference Value = 55.5 V/m ; Power Drift = -0.022 dB
Peak SAR (extrapolated) = 3.68 W/kg
SAR(1 g) = 2.55 mW/g ; SAR(10 g) = 1.69 mW/g
Maximum value of SAR (measured) = 2.74 mW/g



Date/Time: 2006-05-20 14:46:04
Test Laboratory: TCC Nokia, Salo Laboratory
Type: D1900V2; Serial: D1900V2 - SN: 5d030


Communication System: CW
Frequency: 1900 MHz; Duty Cycle: 1:1
Medium: M1900; Medium Notes: 22.4C
Medium parameters used: $f = 1900$ MHz; $\sigma = 1.53$ mho/m; $\epsilon_r = 52.7$; $\rho = 1000$ kg/m³
Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.19, 4.19, 4.19); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

d=15mm, Pin=250mW/Area Scan (61x81x1): Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (interpolated) = 13.7 mW/g

d=15mm, Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 94.2 V/m; Power Drift = -0.034 dB
Peak SAR (extrapolated) = 18.8 W/kg
SAR(1 g) = 10.8 mW/g; SAR(10 g) = 5.77 mW/g
Maximum value of SAR (measured) = 12.3 mW/g



APPENDIX B: MEASUREMENT SCANS

Date/Time: 2006-05-15 17:52:54

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: GSM850

Frequency: 836.6 MHz; Duty Cycle: 1:8.3

Medium: HSL835; Medium Notes: t=21.6 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.903$ mho/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.545 mW/g


Cheek position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.8 V/m; Power Drift = -0.071 dB

Peak SAR (extrapolated) = 0.881 W/kg

SAR(1 g) = 0.476 mW/g; SAR(10 g) = 0.278 mW/g

Maximum value of SAR (measured) = 0.524 mW/g



Date/Time: 2006-05-15 13:10:28

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: HSL835; Medium Notes: t=22.8 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.903$ mho/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 03.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 19.01.2006
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 170

Cheek position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.699 mW/g


Cheek position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.5 V/m; Power Drift = -0.169 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.608 mW/g; SAR(10 g) = 0.376 mW/g

Maximum value of SAR (measured) = 0.679 mW/g



Date/Time: 2006-05-15 13:42:57

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: HSL835; Medium Notes: t=22.8 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.903$ mho/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 03.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 19.01.2006
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 170

Tilt position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.504 mW/g

Tilt position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 22.9 V/m; Power Drift = -0.118 dB

Peak SAR (extrapolated) = 0.782 W/kg

SAR(1 g) = 0.459 mW/g; SAR(10 g) = 0.284 mW/g

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.505 mW/g



Date/Time: 2006-05-15 14:37:41

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: HSL835; Medium Notes: t=22.2 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.903$ mho/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 03.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 19.01.2006
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 170

Cheek position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.781 mW/g

Cheek position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.1 V/m; Power Drift = -0.318 dB

Peak SAR (extrapolated) = 1.19 W/kg

SAR(1 g) = 0.643 mW/g; SAR(10 g) = 0.381 mW/g

Maximum value of SAR (measured) = 0.749 mW/g

Cheek position, Middle /Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.1 V/m; Power Drift = -0.318 dB

Peak SAR (extrapolated) = 1.07 W/kg

SAR(1 g) = 0.579 mW/g; SAR(10 g) = 0.345 mW/g

Maximum value of SAR (measured) = 0.644 mW/g



Cheek position, Middle /Zoom Scan (5x5x7)/Cube 2: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.1 V/m; Power Drift = -0.318 dB

Peak SAR (extrapolated) = 0.959 W/kg

SAR(1 g) = 0.438 mW/g; SAR(10 g) = 0.262 mW/g

Maximum value of SAR (measured) = 0.531 mW/g



Date/Time: 2006-05-15 15:11:59

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: HSL835; Medium Notes: t=22.2 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.903$ mho/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 03.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 19.01.2006
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 170

Tilt position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.607 mW/g


Tilt position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.1 V/m; Power Drift = -0.285 dB

Peak SAR (extrapolated) = 0.910 W/kg

SAR(1 g) = 0.521 mW/g; SAR(10 g) = 0.310 mW/g

Maximum value of SAR (measured) = 0.569 mW/g



Date/Time: 2006-05-15 17:33:13

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot EGPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: HSL835; Medium Notes: t=21.6 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.903$ mho/m; $\epsilon_r = 41.6$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 03.09.2005
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 19.01.2006
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 170

Cheek position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.241 mW/g


Cheek position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 14.4 V/m; Power Drift = -0.238 dB

Peak SAR (extrapolated) = 0.364 W/kg

SAR(1 g) = 0.210 mW/g; SAR(10 g) = 0.124 mW/g

Maximum value of SAR (measured) = 0.226 mW/g



Date/Time: 2006-05-23 08:02:32

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-171; Serial: 004400/81/173857/2

Communication System: 2-slot GPRS850

Frequency: 848.8 MHz; Duty Cycle: 1:4.2

Medium: HSL835; Medium Notes: t=22.6 C

Medium parameters used: $f = 849$ MHz; $\sigma = 0.916$ mho/m; $\epsilon_r = 41.3$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.96, 5.96, 5.96); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek position, High /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.05 mW/g

Cheek position, High /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.2 V/m; Power Drift = -0.242 dB

Peak SAR (extrapolated) = 2.12 W/kg

SAR(1 g) = 0.827 mW/g; SAR(10 g) = 0.380 mW/g

Maximum value of SAR (measured) = 1.01 mW/g

Cheek position, High /Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm



Reference Value = 24.2 V/m; Power Drift = -0.242 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.671 mW/g; SAR(10 g) = 0.370 mW/g

Warning: Maximum averaged SAR over 10 g is located on the boundary of the measurement cube. This cube might not incorporate the absolute averaged SAR. Please consider a refinement of the Area Scan measurement.

Maximum value of SAR (measured) = 0.743 mW/g



Date/Time: 2006-05-19 08:59:00
Test Laboratory: TCC Nokia, Salo Laboratory
Type: RM-170; Serial: 004400/81/171366/6

Communication System: GSM1900
Frequency: 1880 MHz; Duty Cycle: 1:8.3
Medium: HSL1900; Medium Notes: 22.1C
Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³
Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.343 mW/g


Cheek position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 13.3 V/m; Power Drift = -0.147 dB

Peak SAR (extrapolated) = 0.443 W/kg

SAR(1 g) = 0.302 mW/g; SAR(10 g) = 0.182 mW/g

Maximum value of SAR (measured) = 0.327 mW/g



Date/Time: 2006-05-19 12:59:17

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 22.1C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.475 mW/g


Cheek position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.2 V/m; Power Drift = -0.116 dB

Peak SAR (extrapolated) = 0.601 W/kg

SAR(1 g) = 0.418 mW/g; SAR(10 g) = 0.251 mW/g

Maximum value of SAR (measured) = 0.456 mW/g



Date/Time: 2006-05-19 13:24:33

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 22.1C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Tilt position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.552 mW/g


Tilt position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 19.0 V/m; Power Drift = -0.335 dB

Peak SAR (extrapolated) = 0.811 W/kg

SAR(1 g) = 0.500 mW/g; SAR(10 g) = 0.283 mW/g

Maximum value of SAR (measured) = 0.567 mW/g



Date/Time: 2006-05-19 12:29:35

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 21.3 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.39$ mho/m; $\epsilon_r = 38.9$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Cheek position, Middle /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.696 mW/g


Cheek position, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 18.2 V/m; Power Drift = -0.152 dB

Peak SAR (extrapolated) = 1.05 W/kg

SAR(1 g) = 0.575 mW/g; SAR(10 g) = 0.308 mW/g

Maximum value of SAR (measured) = 0.670 mW/g



Date/Time: 2006-05-19 14:10:18

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 21.3 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.36$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Tilt position, Low /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.971 mW/g


Tilt position, Low /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 21.5 V/m; Power Drift = -0.153 dB

Peak SAR (extrapolated) = 1.41 W/kg

SAR(1 g) = 0.790 mW/g; SAR(10 g) = 0.424 mW/g

Maximum value of SAR (measured) = 0.887 mW/g



Date/Time: 2006-05-19 15:25:11

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot EGPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 21.3 C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.36$ mho/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1275
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Tilt position, Low/Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.440 mW/g

Tilt position, Low/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 14.7 V/m; Power Drift = -0.292 dB

Peak SAR (extrapolated) = 0.674 W/kg

SAR(1 g) = 0.371 mW/g; SAR(10 g) = 0.197 mW/g

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (measured) = 0.419 mW/g



Date/Time: 2006-05-22 11:17:32

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-171; Serial: 004400/81/173857/2

Communication System: 2-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 22.3C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.35$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Tilt position, Low /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

[Info: Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.833 mW/g


Tilt position, Low /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 23.3 V/m; Power Drift = -0.167 dB

Peak SAR (extrapolated) = 1.37 W/kg

SAR(1 g) = 0.787 mW/g; SAR(10 g) = 0.432 mW/g

Maximum value of SAR (measured) = 0.888 mW/g



Date/Time: 2006-05-22 12:09:05

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-171; Serial: 004400/81/173857/2

Communication System: 2-slot GPRS1900

Frequency: 1850.2 MHz; Duty Cycle: 1:4.2

Medium: HSL1900; Medium Notes: 22.3C

Medium parameters used (interpolated): $f = 1850.2$ MHz; $\sigma = 1.35$ mho/m; $\epsilon_r = 39.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.73, 4.73, 4.73); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 161

Tilt position, Low, MC /Area Scan (41x81x1): Measurement grid: dx=15mm, dy=15mm

Info: [Interpolated medium parameters used for SAR evaluation.](#)

Maximum value of SAR (interpolated) = 0.896 mW/g


Tilt position, Low, MC /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.1 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 1.55 W/kg

SAR(1 g) = 0.858 mW/g; SAR(10 g) = 0.462 mW/g

Maximum value of SAR (measured) = 0.976 mW/g



Date/Time: 2006-05-17 17:17:26

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: M835; Medium Notes: 21.0 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.963$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.91, 5.91, 5.91); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Measurement,Middle /Area Scan (41x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.12 mW/g


Body Measurement,Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 17.8 V/m; Power Drift = -0.268 dB

Peak SAR (extrapolated) = 1.35 W/kg

SAR(1 g) = 1.03 mW/g; SAR(10 g) = 0.745 mW/g

Maximum value of SAR (measured) = 1.09 mW/g



Date/Time: 2006-05-17 17:31:31

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: M835; Medium Notes: 21.0 C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.963$ mho/m; $\epsilon_r = 54.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DSY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.91, 5.91, 5.91); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Measurement,Middle, HS-6 /Area Scan (41x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.845 mW/g


Body Measurement,Middle, HS-6 /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 15.4 V/m; Power Drift = -0.254 dB

Peak SAR (extrapolated) = 1.02 W/kg

SAR(1 g) = 0.778 mW/g; SAR(10 g) = 0.560 mW/g

Maximum value of SAR (measured) = 0.824 mW/g



Date/Time: 2006-05-23 22:28:33

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-171; Serial: 004400/81/173857/2

Communication System: 2-slot GPRS850

Frequency: 836.6 MHz; Duty Cycle: 1:4.2

Medium: M850; Medium Notes: 22.2C

Medium parameters used: $f = 837$ MHz; $\sigma = 0.968$ mho/m; $\epsilon_r = 55.1$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(5.91, 5.91, 5.91); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 3; Type: SAM 4.0; Serial: 1272
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Measurement, Middle /Area Scan (41x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.28 mW/g


Body Measurement, Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 18.7 V/m; Power Drift = -0.272 dB

Peak SAR (extrapolated) = 1.56 W/kg

SAR(1 g) = 1.19 mW/g; SAR(10 g) = 0.853 mW/g

Maximum value of SAR (measured) = 1.26 mW/g



Date/Time: 2006-05-19 16:25:20

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: M1900; Medium Notes: 22.2 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 52.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.19, 4.19, 4.19); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Measurement,Middle /Area Scan (41x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.10 mW/g

Body Measurement,Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.9 V/m; Power Drift = -0.187 dB

Peak SAR (extrapolated) = 1.43 W/kg

SAR(1 g) = 0.941 mW/g; SAR(10 g) = 0.567 mW/g

Maximum value of SAR (measured) = 1.03 mW/g


Body Measurement,Middle /Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 25.9 V/m; Power Drift = -0.187 dB

Peak SAR (extrapolated) = 1.01 W/kg

SAR(1 g) = 0.701 mW/g; SAR(10 g) = 0.460 mW/g

Maximum value of SAR (measured) = 0.744 mW/g



Date/Time: 2006-05-19 16:45:57

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-170; Serial: 004400/81/171366/6

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: M1900; Medium Notes: 22.2 C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.51$ mho/m; $\epsilon_r = 52.9$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.19, 4.19, 4.19); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Measurement,Middle, HS-6 /Area Scan (41x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 0.956 mW/g

Body Measurement,Middle, HS-6 /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.5 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 1.30 W/kg

SAR(1 g) = 0.842 mW/g; SAR(10 g) = 0.498 mW/g

Maximum value of SAR (measured) = 0.935 mW/g


Body Measurement,Middle, HS-6 /Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 24.5 V/m; Power Drift = -0.107 dB

Peak SAR (extrapolated) = 0.850 W/kg

SAR(1 g) = 0.586 mW/g; SAR(10 g) = 0.385 mW/g

Maximum value of SAR (measured) = 0.631 mW/g



Date/Time: 2006-05-20 16:19:14

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-171; Serial: 004400/81/173857/2

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: M1900; Medium Notes: 22.1C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.19, 4.19, 4.19); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Measurement,Middle /Area Scan (41x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.15 mW/g

Body Measurement,Middle /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 27.6 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 1.59 W/kg

SAR(1 g) = 1.04 mW/g; SAR(10 g) = 0.630 mW/g

Maximum value of SAR (measured) = 1.12 mW/g


Body Measurement,Middle /Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 27.6 V/m; Power Drift = -0.142 dB

Peak SAR (extrapolated) = 1.19 W/kg

SAR(1 g) = 0.826 mW/g; SAR(10 g) = 0.541 mW/g

Maximum value of SAR (measured) = 0.883 mW/g



Date/Time: 2006-05-20 17:06:30

Test Laboratory: TCC Nokia, Salo Laboratory

Type: RM-171; Serial: 004400/81/173857/2

Communication System: 2-slot GPRS1900

Frequency: 1880 MHz; Duty Cycle: 1:4.2

Medium: M1900; Medium Notes: 22.1C

Medium parameters used: $f = 1880$ MHz; $\sigma = 1.52$ mho/m; $\epsilon_r = 52.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1395; Probe Notes: Advanced extrapolation
- ConvF(4.19, 4.19, 4.19); Calibrated: 2005-09-03
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn388; Calibrated: 2006-01-19
- Phantom: SAM 1; Type: Twin SAM 040 CA; Serial: TP-1179
- Measurement SW: DASY4, V4.6 Build 21; Postprocessing SW: SEMCAD, V1.8 Build 161

Body Measurement,Middle, MC /Area Scan (41x91x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 1.17 mW/g

Body Measurement,Middle, MC /Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 28.8 V/m; Power Drift = -0.164 dB

Peak SAR (extrapolated) = 1.63 W/kg

SAR(1 g) = 1.07 mW/g; SAR(10 g) = 0.641 mW/g

Maximum value of SAR (measured) = 1.18 mW/g


Body Measurement,Middle, MC /Zoom Scan (5x5x7)/Cube 1: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm

Reference Value = 28.8 V/m; Power Drift = -0.164 dB

Peak SAR (extrapolated) = 1.22 W/kg

SAR(1 g) = 0.845 mW/g; SAR(10 g) = 0.553 mW/g

Maximum value of SAR (measured) = 0.901 mW/g



APPENDIX C: RELEVANT PAGES FROM PROBE CALIBRATION REPORT(S)

E-field probe, SN: 1395
See the next three pages.



Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client **Nokia Salo TCC**

Certificate No: **ET3-1395_Sep05**

CALIBRATION CERTIFICATE

Object	ET3DV6 - SN:1395
Calibration procedure(s)	QA CAL-01.v5 and QA CAL-12.v4 Calibration procedure for dosimetric E-field probes
Calibration date:	September 3, 2005
Condition of the calibrated item	In Tolerance

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	3-May-05 (METAS, No. 251-00466)	May-06
Power sensor E4412A	MY41495277	3-May-05 (METAS, No. 251-00466)	May-06
Power sensor E4412A	MY41498087	3-May-05 (METAS, No. 251-00466)	May-06
Reference 3 dB Attenuator	SN: S5054 (3c)	11-Aug-05 (METAS, No. 251-00499)	Aug-06
Reference 20 dB Attenuator	SN: S5086 (20b)	3-May-05 (METAS, No. 251-00467)	May-06
Reference 30 dB Attenuator	SN: S5129 (30b)	11-Aug-05 (METAS, No. 251-00500)	Aug-06
Reference Probe ES3DV2	SN: 3013	7-Jan-05 (SPEAG, No. ES3-3013_Jan05)	Jan-06
DAE4	SN: 654	29-Nov-04 (SPEAG, No. DAE4-654_Nov04)	Nov-05
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Dec-03)	In house check: Dec-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-04)	In house check: Nov 05

	Name	Function	Signature
Calibrated by:	Nico Vetterli	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	

Issued: September 5, 2005

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

DASY - Parameters of Probe: ET3DV6 SN:1395

Sensitivity in Free Space ^A			Diode Compression ^B	
NormX	1.86 ± 10.1%	μV/(V/m) ²	DCP X	91 mV
NormY	1.82 ± 10.1%	μV/(V/m) ²	DCP Y	91 mV
NormZ	1.82 ± 10.1%	μV/(V/m) ²	DCP Z	91 mV

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL	900 MHz	Typical SAR gradient: 5 % per mm		
Sensor Center to Phantom Surface Distance		3.7 mm	4.7 mm	
SAR _{be} [%]	Without Correction Algorithm	9.6	5.0	
SAR _{be} [%]	With Correction Algorithm	0.0	0.2	
TSL	1750 MHz	Typical SAR gradient: 10 % per mm		
Sensor Center to Phantom Surface Distance		3.7 mm	4.7 mm	
SAR _{be} [%]	Without Correction Algorithm	13.4	8.8	
SAR _{be} [%]	With Correction Algorithm	1.1	0.1	


Sensor Offset

Probe Tip to Sensor Center	2.7 mm
----------------------------	--------

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of NormX,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 8).
^B Numerical linearization parameter; uncertainty not required.

Conversion Factor Assessment



f [MHz]	Validity [MHz] ^c	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF	Uncertainty
450	± 50 / ± 100	Head	43.5 ± 5%	0.87 ± 5%	0.05	1.80	6.78	± 13.3% (k=2)
835	± 50 / ± 100	Head	41.5 ± 5%	0.90 ± 5%	0.77	1.66	5.96	± 11.0% (k=2)
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.71	1.77	5.88	± 11.0% (k=2)
1750	± 50 / ± 100	Head	40.1 ± 5%	1.37 ± 5%	0.74	2.11	4.87	± 11.0% (k=2)
1900	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.67	2.33	4.73	± 11.0% (k=2)
1950	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.67	2.32	4.54	± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.87	1.91	4.30	± 11.8% (k=2)
450	± 50 / ± 100	Body	56.7 ± 5%	0.94 ± 5%	0.03	1.95	6.92	± 13.3% (k=2)
835	± 50 / ± 100	Body	55.2 ± 5%	0.97 ± 5%	0.63	1.87	5.91	± 11.0% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.62	1.93	5.71	± 11.0% (k=2)
1750	± 50 / ± 100	Body	53.4 ± 5%	1.49 ± 5%	0.62	2.73	4.22	± 11.0% (k=2)
1900	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.67	2.46	4.19	± 11.0% (k=2)
1950	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.68	2.37	4.09	± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.95	1.69	4.04	± 11.8% (k=2)

^c The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

APPENDIX D: RELEVANT PAGES FROM DIPOLE VALIDATION KIT REPORT(S)

Dipole D835V2, SN: 462
Dipole D1900V2, SN: 5d030
See the next six pages.

Client

Nokia Salo TCC

CALIBRATION CERTIFICATE

Object(s) **D835V2 - SN:462**

Calibration procedure(s) **QA CAL-05.v2
Calibration procedure for dipole validation kits**

Calibration date: **July 14, 2004**


Condition of the calibrated item **In Tolerance (according to the specific calibration document)**

This calibration statement documents traceability of M&TE used in the calibration procedures and conformity of the procedures with the ISO/IEC 17025 international standard.

All calibrations have been conducted in the closed laboratory facility: environment temperature 22 +/- 2 degrees Celsius and humidity < 75%.

Calibration Equipment used (M&TE critical for calibration)

Model Type	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter EPM E442	GB37480704	6-Nov-03 (METAS, No. 252-0254)	Nov-04
Power sensor HP 8481A	US37292783	6-Nov-03 (METAS, No. 252-0254)	Nov-04
Power sensor HP 8481A	MY41092317	18-Oct-02 (Agilent, No. 20021018)	Oct-04
RF generator R&S SML-03	100698	27-Mar-2002 (R&S, No. 20-92389)	In house check: Mar-05
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-03)	In house check: Oct 05

	Name	Function	Signature
Calibrated by:	Judith Mueller	Technician	
Approved by:	Katja Pokovic	Laboratory Director	

Date issued: July 15, 2004

This calibration certificate is issued as an intermediate solution until the accreditation process (based on ISO/IEC 17025 International Standard) for Calibration Laboratory of Schmid & Partner Engineering AG is completed.

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN462

Communication System: CW-835; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL 835 MHz;

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.92 \text{ mho/m}$; $\epsilon_r = 41.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ET3DV6 - SN1507; ConvF(6.3, 6.3, 6.3); Calibrated: 1/23/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn903; Calibrated: 2/19/2004
- Phantom: Flat Phantom half size; Type: QD000P49AA; Serial: SN:1001;
- Measurement SW: DASY4, V4.3 Build 8; Postprocessing SW: SEMCAD, V1.8 Build 117

Pin = 250 mW; d = 15 mm/Area Scan (81x81x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 2.62 mW/g


Pin = 250 mW; d = 15 mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 55.1 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 3.72 W/kg

SAR(1 g) = 2.45 mW/g; SAR(10 g) = 1.59 mW/g

Maximum value of SAR (measured) = 2.65 mW/g



Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN462

Communication System: CW-835; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: Muscle 835 MHz;

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 54.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ET3DV6 - SN1507; ConvF(6.13, 6.13, 6.13); Calibrated: 1/23/2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn903; Calibrated: 2/19/2004
- Phantom: Flat Phantom half size; Type: QD000P49AA; Serial: SN:1001;
- Measurement SW: DASY4, V4.3 Build 8; Postprocessing SW: SEMCAD, V1.8 Build 117

Pin = 250 mW; d = 15 mm/Area Scan (81x81x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$
Maximum value of SAR (interpolated) = 2.64 mW/g


Pin = 250 mW; d = 15 mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5\text{mm}$, $dy=5\text{mm}$, $dz=5\text{mm}$

Reference Value = 53.6 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.59 W/kg

SAR(1 g) = 2.45 mW/g; SAR(10 g) = 1.61 mW/g

Maximum value of SAR (measured) = 2.66 mW/g





Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

Client **Nokia Oulu 2**

Certificate No: **D1900V2-5d030_Feb05**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d030**

Calibration procedure(s) **QA CAL-05.v6
Calibration procedure for dipole validation kits**

Calibration date: **February 18, 2005**

Condition of the calibrated item **In Tolerance**


This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.


All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter EPM E442	GB37480704	12-Oct-04 (METAS, No. 251-00412)	Oct-05
Power sensor HP 8481A	US37292783	12-Oct-04 (METAS, No. 251-00412)	Oct-05
Reference 20 dB Attenuator	SN: 5086 (20g)	10-Aug-04 (METAS, No 251-00402)	Aug-05
Reference 10 dB Attenuator	SN: 5047.2 (10r)	10-Aug-04 (METAS, No 251-00402)	Aug-05
Reference Probe ET3DV6	SN 1507	26-Oct-04 (SPEAG, No. ET3-1507_Oct04)	Oct-05
DAE4	SN 601	07-Jan-05 (SPEAG, No. DAE4-601_Jan05)	Jan-06

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Power sensor HP 8481A	MY41092317	18-Oct-02 (SPEAG, in house check Oct-03)	In house check: Oct-05
RF generator R&S SML-03	100698	27-Mar-02 (SPEAG, in house check Dec-03)	In house check: Dec-05
Network Analyzer HP 8753E	US37390585 S4206	18-Oct-01 (SPEAG, in house check Nov-04)	In house check: Nov 05

Calibrated by:	Name Mike Meili	Function Laboratory Technician	Signature 
----------------	---------------------------	--	--

Approved by:	Katja Pokovic	Technical Manager	
--------------	----------------------	--------------------------	---

Issued: February 25, 2005

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d030

Communication System: CW-1900; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL 1800 MHz;

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.46$ mho/m; $\epsilon_r = 39.5$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ET3DV6 - SN1507; ConvF(4.96, 4.96, 4.96); Calibrated: 26.10.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.01.2005
- Phantom: Flat Phantom 5.0; Type: QD000P50AA; Serial: 1001;
- Measurement SW: DASY4, V4.5 Build 11; Postprocessing SW: SEMCAD, V1.8 Build 144

Pin = 250 mW; d = 10 mm/Area Scan (81x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 11.2 mW/g


Pin = 250 mW; d = 10 mm/Zoom Scan 2 (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 88.4 V/m; Power Drift = 0.020 dB

Peak SAR (extrapolated) = 17.1 W/kg

SAR(1 g) = 9.76 mW/g; SAR(10 g) = 5.09 mW/g

Maximum value of SAR (measured) = 11.1 mW/g



0 dB = 11.1 mW/g

Test Laboratory: SPEAG, Zurich, Switzerland

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:5d030

Communication System: CW-1900; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: Muscle 1800 MHz;

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.57$ mho/m; $\epsilon_r = 52.2$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

Measurement Standard: DASY4 (High Precision Assessment)

DASY4 Configuration:

- Probe: ET3DV6 - SN1507; ConvF(4.43, 4.43, 4.43); Calibrated: 26.10.2004
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.01.2005
- Phantom: Flat Phantom 5.0; Type: QD000P50AA; Serial: 1001;
- Measurement SW: DASY4, V4.5 Build 13; Postprocessing SW: SEMCAD, V1.8 Build 142

Pin = 250 mW; d = 10 mm/Area Scan (81x81x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 11.5 mW/g



Pin = 250 mW; d = 10 mm/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 89.4 V/m; Power Drift = 0.0 dB

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 9.94 mW/g; SAR(10 g) = 5.3 mW/g

Maximum value of SAR (measured) = 11.2 mW/g



0 dB = 11.2 mW/g