

SPECIFICATION



深圳市大显科技有限公司

Shenzhen Daxian Technology Co., Ltd.

国光 Maverick-15 寸- BT 天线组件GGEC Maverick-15 inch BT Antenna assembly

产 品 规 格 书

Product Specification

客 户 connection	国光 GGEC	频 段 frequency range	2400 ~ 2500MHz
项目名称 entry name	Maverick-15 inch	版 本 edition	V2.0
物料编号 Material No	1M-AVK15-053	颜 色 Color	黑色 Black
客户料号 Customer Item Number	EAN0042401		
R F 设计 R F Design	沈 川 Chuan.Shen	结构设计 Structural Design	周锐斌 Ruibin.Zhou
品质经理 Quality Manager	胡子寅 ZiYin.Hu	技术总监 Technical Director	张 磊 Lei.Zhang
日 期 Date	2024-12-19		

客户确认:

Customer confirmation:

装配是否符合贵司要求: ☐OK ☐NGWhether the assembly meets your company's requirements: ☐OK ☐NG

深圳市大显科技有限公司

Shenzhen DaXian Technology Co., Ltd.

深圳市龙岗区布吉镇吉华路 513 号上水径村(国防培训基地
对面) 达成工业园综合楼 7 楼

TEL:0755-28576002

FAX:0755-84276383

上海分部: 上海市张江高科技园区集成电路产业区龙东大道
3000 号 8 号楼 201 室

TEL:021-61630552

FAX:755-84276383

Buji Town, Longgang District, Shenzhen, China Jihua Road 513,
Shangshuijing Village (opposite the national defense
training base) Dacheng Industrial Park, Building 7.

TEL:0755-28576002

FAX:0755-84276383

Room201, Building8, LongDongRoad3000#, Semiconductor Industry
Park, ZhangJiang Hitech Zone, ShangHai

TEL:021-61630552

FAX:755-84276383

变更履历

Revision history

[illegible]

索引 Indexes

一、项目说明 Project Description.....	4
二、 BT 天线 antenna.....	4
1、 规格 specifications.....	4
1.1 电气规格标准 Electrical specifications and standards.....	5
1.1.1 电性能指标 Electrical performance index.....	5
1.1.2 天线位置布局 Antenna Location Layout.....	5
1.2 结构规格标准 Structural specifications and standards.....	6
1.2.1 天线组成 Antenna composition..	6
2、测试环境 testing environment.....	6
3、测试 test.	7
3.1 驻波(VSWR)的测试 Test of standing wave (VSWR).....	7
3.1.1 测试连接 Test connection.....	7
3.2 效率、功率 (TRP)、灵敏度 (TIS) 的测试 Testing of efficiency, power (TRP), sensitivity (TIS).....	7
3.2.1 测试的场地 Test site.....	7
3.2.2 测试的仪表 Tested Instruments.....	7
3.2.3 测试数据 test data.....	7-8
4、VSWR 参数图 Parameter diagram.....	9
5、无源场型图 Passive field pattern diagram.....	10
6、有源效率场型图 Active efficiency field pattern diagram.....	11
7、户外拉距测试 Outdoor Pull distance test.....	12
8、结论 conclusion.....	12
三、工程图 schedule drawing.....	13

www.Topant.com.cn

一 项目说明 Project Description


客户名: Customer Name:	国光 GGEC
整机类型: Type of complete machine:	音箱 loudspeaker box
天线频段: Antenna band:	2400 ~ 2500MHz
天线形式: Antenna form:	FPC+同轴线+线材海绵 FPC+coaxial line+wire sponge
馈电形式: Feed form:	焊接 weld
硬件版本: Hardware version:	/

二 BT 天线组件 Antenna assembly

1 规格 specifications

本报告主要提供 Maverick-15 寸项目天线的各项电气和结构性能参数的测试状况。下图为大显设计的天线图片。

This report mainly provides the testing status of various electrical and structural performance parameters of the antenna for the Maverick-15 inch project. The following image shows an antenna with a large display design.



天线外观图

antenna appearing diagram

www.Topant.com.cn

1.1 电气规格标准 Electrical specifications and standards


1.1.1 电性能指标 Electrical performance index

天线工作频段在 **2400 ~ 2500 MHz**。下表是大显设计和量产天线的电性能的指标。

The operating frequency band of the antenna is between 2400 and 2500 MHz. The following table shows the electrical performance indicators of large display design and mass production antennas.

Frequency Range	Frequency (MHz)	VSWR
BT	2400 ~ 2500	≤ 2

1.1.3 天线位置布局 Antenna Location Layout



1.2 结构规格标准 Structural specifications and standards

1.2.1 天线组成 Antenna composition

天线主要是由 FPC+同轴线+线材海绵 组成。

The antenna is mainly composed of FPC+coaxial line+wire sponge.

www.Topant.com.cn

2、测试设备 The Equipment of Active Test

Satimo 3D Chamber $6\times 4\times 4$ (m)

Agilent 8960 E5515c

Network analyzer-R&S ZVL



图 2

Figure 2

3 测试 test

3.1 驻波(VSWR)的测试 Test of standing wave (VSWR)

3.1.1 测试连接: VSWR 测试装置依次的连接为: R&S ZVL 网络分析仪 → 测试线 → 测试治

Test connection: The VSWR test device is sequentially connected as follows: R&S ZVL network analyzer → test line → test fixture

实测(附图)Actual measurement (attached drawing)

3.2 增益及效率、功率 (TRP)、灵敏度 (TIS) 的测试

Gain and efficiency, power (TRP), sensitivity (TIS) testing

3.2.1 测试的场地 Test site:

大显微波暗室。测试频率范围为 400MHz—6GHz, 静区范围为 50cm 圆周, 反射率小于-50 dB。

Large display microwave anechoic chamber. The test frequency range is 400MHz - 6GHz, the static zone range is 50cm circumferential, and the reflectivity is less than - 50dB.

3.2.2 测试的仪表 Tested Instruments:

R&S ZVL 网络分析仪、Agilent8960 E5515C、标准喇叭天线、法国 SATIMO-SG24SYSTEM 系统、打印机等。

R&S ZVL network analyzer, Agilent 8960 E5515C, standard horn antenna, French SATIMO-SG24SYSTEM system, printer, etc.

3.2.3 测试数据 : 在微波暗室中, 测试的功率和灵敏度相关的数值如下表

Test data: In a microwave anechoic chamber, the values related to the power and sensitivity tested are shown in the table bel

OTA 有源测试 OTA active testing

BAND	CH	TRP (dBm)	TIS (dBm)
BT	0	0.09	-82.28
	39	-1.18	-83.38
	78	-2.04	-83.14

BT 传导数据 BT conduction data:

BAND	CH	TX (dBm)	RX (dBm)
BT	0	2.5	-86
	39	1.37	-86
	78	0.36	-86

无源效率&增益 Passive efficiency&gain:


Freq (MHz)	Gain (dBi)	Effi (dB)	Effi (%)
2400	2.08	-3.04	49.61
2410	2.09	-3.04	49.62
2420	2.12	-3.01	49.98
2430	2.33	-2.95	50.75
2440	2.37	-2.94	50.85
2450	2.43	-3.01	51.3
2460	2.12	-2.90	49.96
2470	2.11	-3.03	49.82
2480	2.09	-3.03	49.74
2490	2.08	-3.04	49.64
2500	2.04	-3.07	49.34

www.Topant.com.cn

4、VSWR 参数图 VSWR parameter diagram





5、无源效率场型图 Passive efficiency field pattern diagram






www.Topant.com.cn

6、有源效率场型图 Active efficiency field pattern diagram

Polar: Total



Polar: Total



www.Topant.com.cn

7、户外拉距测试 Outdoor Pull distance test

拉距测试 (Pull distance test) :
测试时间 (Testing time) : 2024/12/18
测试场地 (test site) : 深圳烟草公司附近 (Near Shenzhen Tobacco Company)
测试手机 (Test Cell Phones) : Iphone 14 Pro

测试方向 Test direction	前 ahead	后 empress	左 left	右 right
	测试距离Test Distance			
BT	75M	75M	70M	75M

8、结论 conclusion

此天线是在客户提供样机基础上设计，电参数和结构性能已达到技术要求，请确认！

This antenna is designed based on the prototype provided by the customer. The electrical parameters and structural performance have met the technical requirements, please confirm!

