Instructions of Remote Control

1. Please pull out the insulation tape from the remote control, before starting to use it.

2. Press the button to select functions. The functions are :

ON : turn on the lights OFF : turn off the lights TIMER : start or cancel timing (6 hours "on",18 hours "off") STEADY WARMWHITE : steady warm white STEADY MULTI : steady multicolor SLO-GOL : fading warm white & multicolor TWINKLE/FLASH : twinkle / flash warm white & multicolor DIM - : decrease the brightness DIM + : increase the brightness

Instructions of 2 button control

- Press **RUSH** button , select lighting functions below cycle. Function 1: steady warm white. Function 2: steady multicolor. Function 3: fading warm white & multicolor. Function 4: twinkle / flash warm white & multicolor.
- 2. Press **ON/OFF** button , turn on or turn off the lights.

FCC Caution

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Any Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or

more of the following measures:

-Reorient or relocate the receiving antenna.

-Increase the separation between the equipment and receiver.

-Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.

-Consult the dealer or an experienced radio/TV technician for help.