

Report No. : AG013161-001 Date : 2006 June 13

Application No. : LG211856(1)

Applicant : Mattel Asia Pacific Sourcing Limited

13/F., South Tower, World Finance Centre,

Harbour City, Tsim Sha Tsui,

Kowloon, Hong Kong

Sample Description : One(1) submitted sample(s) stated to be N. S. E. C. T

of Model No. J9863

Rating : 1 x 9V size battery No. of submitted sample : Two (2) piece(s) ***

Date Received : 2006 June 01

Test Period : 2006 June 01 – 2006 June 07

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)

ANSI C63.4 - 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15

Subpart C.

For and on behalf of

CMA Industrial Development Foundation Limited

Deputy Manager - EL. Division

Page 1 of 11



Report No. : AG013161-001 Date : 2006 June 13

Table of Contents

1	Gen	eral Information	3
	1.1	General Description	3
	1.2	Location of the test site	4
	1.3	List of measuring equipment.	5
2	Desc	cription of the radiated emission test	
	2.1	Test Procedure	6
	2.2	Test Result	6
	2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test		8
	3.1	Test Procedure	8
	3.2	Test Result	8
	3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Phot	ograph	9
	4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
	4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document		10
	5.1	Bandwidth	10
	5.2	Duty cycle	10
	5.3	Transmission time	10
6	App	endices	11



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for N.S.E.C.T. Operating at 49.860MHz which is controlled by a crystal. The EUT is powered 1 X 9V size battery and it has five control trigger in the front of EUT. When forward, backward, turn left, turn right and Raise / Lower gun button is pressed once, it will transmit corresponding signal to receiver unit

The brief circuit description is listed as follows:

- U1 and associated circuit act as encoder.
- Y1, Q2 and associated circuit act as oscillator.
- Q3 and associated circuit act as RF amplify.

Page 3 of 11



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at:

Ground Floor, Yan Hing Centre, 9 – 13 Wong Chuk Yeung Street, Fo Tan, Shatin, New Territories, Hong Kong.

Page 4 of 11

FCC ID: PIYJ9863-06A4T



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
EMI Test Receiver	R&S	ESCI	100152
Broadband Antenna	Schaffner	CBL6112B	2692



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 - 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

Peak Detector data was measured unless otherwise stated.

The harmonic emissions meeting the requirement of section 15.209 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

It was found that the EUT meet the FCC requirement.

Page 6 of 11



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m	Antenna and Cable factor	Average Factor	Field Strength	Limit at 3m (dBµV/m)	Margin (dB)
		(dBµV/m)	(dB)	(dB)	(dBµV/m)		
49.860	V	70.0	10.3	-5.9	74.4	80.0	-5.6
99.722	V	16.1	9.2	-	25.3	43.5	-18.2
149.860	Н	11.0	11.9	-	22.9	43.5	-20.6
199.421	Н	13.9	9.2	-	23.1	43.5	-20.4
*249.305	Н	17.3	9.7	-	27.0	46.0	-19.0
299.162	Н	20.6	13.9	ı	34.5	46.0	-11.5
349.026	Н	14.2	14.9	-	29.1	46.0	-16.9
398.894	Н	17.6	14.9	1	32.5	46.0	-13.5
448.749	Н	11.6	17.7	ı	29.3	46.0	-16.7
498.610	Н	12.7	17.7	-	30.4	46.0	-15.6

Page 7 of 11 FCC ID: PIYJ9863-06A4T



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 - 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable

Page 8 of 11



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho2.jpg and InPho1.jpg to InPho4.jpg.

Page 9 of 11

FCC ID: PIYJ9863-06A4T



Report No. : AG013161-001 Date : 2006 June 13

Test Result :

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

The plot on saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. The field strength of any emission appearing between the band edges and up to 10 kHz above and below the band edges (49.81 and 49.91 MHz) is at least 26dB below the carrier level. It meets the requirement of Section 15.235(b).

5.2 Duty cycle

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 10.84ms

Effective period of the cycle = (0.34×6) ms + (0.68×5) ms

= 5.44 ms

Duty Cycle = (5.44 / 10.84)ms

= 0.502

Therefore, the average factor is found by $20 \log_{10} 0.502 = -5.9 dB$

5.3 Transmission time

N/A



Report No. : AG013161-001 Date : 2006 June 13

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	2	pages
A4.	ID Label/Location	1	page
A5.	Bandwidth Plot	1	page
A6.	Average Factor	2	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	1	page
A9.	User Manual	4	pages
A10.	Operation Description	1	page

***** End of Report *****

Page 11 of 11 FCC ID: PIYJ9863-06A4T