




FCC RADIO TEST REPORT

FCC ID : HLZA24003
Equipment : Tablet PC
Brand Name : acer
Model Name : A24003
Marketing Name : Acer Iconia Tab A10, A10-21
Applicant : Acer Incorporated
8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist.,
New Taipei City 22181, Taiwan (R.O.C)
Manufacturer : Acer Incorporated
8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist.,
New Taipei City 22181, Taiwan (R.O.C)
Standard : FCC Part 15 Subpart E §15.407

The product was received on May 28, 2024 and testing was performed from Jun. 03, 2024 to Jun. 26, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 Support Unit used in test configuration and system	9
2.5 EUT Operation Test Setup	10
2.6 Measurement Results Explanation Example.....	10
3 Test Result	11
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	11
3.2 Maximum Conducted Output Power Measurement	12
3.3 Power Spectral Density Measurement	13
3.4 Unwanted Emissions Measurement.....	14
3.5 AC Conducted Emission Measurement.....	19
3.6 Antenna Requirements.....	21
4 List of Measuring Equipment.....	22
5 Measurement Uncertainty	24
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR452713E	01	Initial issue of report	Jul. 02, 2024
FR452713E	02	Revise List of Measuring Equipment and Appendix D This report is an updated version, replacing the report issued on Jul. 02, 2024.	Jul. 05, 2024

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403(i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	4.49 dB under the limit at 5645.85 MHz
3.5	15.207	AC Conducted Emission	Pass	7.41 dB under the limit at 0.16 MHz
3.6	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Danny Lee

Report Producer: Wilda Wei

1 General Description

1.1 Product Feature of Equipment Under Test

Product Specification subjective to this standard				
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax, Wi-Fi 5GHz 802.11a/n/ac/ax and GNSS.				
Antenna Type WLAN: PIFA Antenna Bluetooth: PIFA Antenna GPS / BDS: PIFA Antenna				
Antenna information				
5725 MHz ~ 5850 MHz		Peak Gain (dBi)	5.04	
SKU List				
	SKU1_4G+64G	SKU2_4G+64G	SKU3_4G+128G	SKU4_4G+128G
Memory	Shenzhen Gcai Electronic Technology Co., /4GB/GD84D32MJ0-42C2	Rayson/4GB/RS1G32LF4 D2BDS-53BT	Shenzhen Gcai Electronic Technology Co., /4GB/GD84D32MJ0-42C2	Rayson/4GB/RS1G32LO4D 2BDS-53BT
eMMC	Rayson/64GB/RS70B64G 4S16G	Shenzhen Techwinsemi Technology Co., Ltd./64GB/UEMCGS63S0	Rayson/128GB/RS70BT7 G4S09F	Shenzhen Techwinsemi Technology Co., Ltd./128GB/UEMDGS63S0

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH21-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155 [#]	5775	165	5825

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "[#]" are 802.11ac VHT80 and 802.11ax HE80.

2.2 Test Mode

The power for 802.11n and 802.11ac mode is smaller than 802.11ax mode, so all other conducted and radiated test is covered by 802.11ax mode.

The final test modes include the worst data rates for each modulation shown in the table below.

Single Mode


Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by HE20)	MCS0
802.11n HT40 (Covered by HE40)	MCS0
802.11ac VHT20 (Covered by HE20)	MCS0
802.11ac VHT40 (Covered by HE40)	MCS0
802.11ac VHT80 (Covered by HE80)	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN (2.4GHz) Link + H-Pattern + Earphone + SD Card + USB Cable (Charging from Adapter) for SKU4 Mode 2 : Bluetooth Link + WLAN (5GHz) Link + MPEG4 (Color Bar) + Earphone + SD Card + USB Cable (Charging from Adapter) for SKU4 Mode 3 : Bluetooth Link + WLAN (2.4GHz) Idle + Camera (Front) + Earphone + SD Card + USB Cable (Data Link with Notebook) (Read) for SKU4 Mode 4 : Bluetooth Link + WLAN (5GHz) Idle + Camera (Rear) + Earphone + SD Card + USB Cable (Data Link with Notebook)(Write) for SKU4 Mode 5 : Bluetooth Link + WLAN (2.4GHz) Link + GPS RX + Earphone + SD Card + USB Cable (Data Link with Notebook) (Read) for SKU4
Remark: - The worst case of Conducted Emission is mode 3; only the test data of it was reported. - For Radiated Test Cases, the tests were performed with SKU3.	

Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11ax HE20	802.11ax HE40	802.11ax HE80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	SBH20	PY7-RD0010	N/A	N/A
2.	GPS Emulator	Spectracom	GSG-6	N/A	N/A	N/A
3.	Earphone + Mic	Samsung	Ecouteur	N/A	Unshielded, 1.8m	N/A
4.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
5.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
6.	iPod	Apple	A1199	FCC DoC	Shielded, 1.0m	N/A
7.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A



2.5 EUT Operation Test Setup

The RF test items, utility “ADB commend” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.2.3 Test Procedures

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.


Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300kHz.
 - Set VBW ≥ 1 MHz.
 - Add $10 \log(500 \text{ kHz}/\text{RBW})$ to the measured result, whereas RBW ($< 500 \text{ kHz}$) is the reduced resolution bandwidth of the spectrum analyzer set during measurement
 - Number of points in sweep $\geq 2 \text{ Span} / \text{RBW}$.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6 \text{ dB}$ if the duty cycle is 25 percent.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

- (2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

- (3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
Section G) Unwanted emissions measurement.
(1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW $\geq$ 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
(3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading.
When there is no suspected emission found and the emission level is with at least 6 dB margin


against QP limit line, the position is marked as “-”.

7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies.


When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.

3.4.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Jun. 04, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 04, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz~200MHz	Oct. 20, 2023	Jun. 04, 2024	Oct. 19, 2024	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 14, 2024	Jun. 04, 2024	Mar. 13, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	Jun. 04, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	Jun. 04, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	Jun. 04, 2024	Sep. 19, 2024	Conduction (CO07-HY)
LOOP Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 12, 2023	Jun. 12, 2024~ Jun. 26, 2024	Sep. 11, 2024	Radiation (03CH21-HY)
Bilog Antenna	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63303 & 001	30MHz~1GHz	Oct. 15, 2023	Jun. 12, 2024~ Jun. 26, 2024	Oct. 14, 2024	Radiation (03CH21-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C03A18EN	1GHz~18GHz	Jul. 12, 2023	Jun. 12, 2024~ Jun. 26, 2024	Jul. 11, 2024	Radiation (03CH21-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1223	18GHz~40GHz	Jul. 10, 2023	Jun. 12, 2024~ Jun. 26, 2024	Jul. 09, 2024	Radiation (03CH21-HY)
Amplifier	SONOMA	310N	421580	30MHz~1GHz	Jul. 15, 2023	Jun. 12, 2024~ Jun. 26, 2024	Jul. 14, 2024	Radiation (03CH21-HY)
Amplifier	EMEC	EM01G18GA	060876	1GHz~18GHz	Sep. 28, 2023	Jun. 12, 2024~ Jun. 26, 2024	Sep. 27, 2024	Radiation (03CH21-HY)
Preamplifier	EMEC	EM18G40G	060871	18GHz~40GHz	Aug. 30, 2023	Jun. 12, 2024~ Jun. 26, 2024	Aug. 29, 2024	Radiation (03CH21-HY)
Spectrum Analyzer	Keysight	N9010B	MY62170358	10Hz~44GHz	Aug. 28, 2023	Jun. 12, 2024~ Jun. 26, 2024	Aug. 27, 2024	Radiation (03CH21-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	Jun. 12, 2024~ Jun. 26, 2024	Mar. 05, 2025	Radiation (03CH21-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804397/2,804612/2,804614/2	30MHz~40GHz	Oct. 24, 2023	Jun. 12, 2024~ Jun. 26, 2024	Oct. 23, 2024	Radiation (03CH21-HY)
Hygrometer	TECPEL	DTM-303A	TP211568	N/A	Oct. 30, 2023	Jun. 12, 2024~ Jun. 26, 2024	Oct. 14, 2024	Radiation (03CH21-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Jun. 12, 2024~ Jun. 26, 2024	N/A	Radiation (03CH21-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Jun. 12, 2024~ Jun. 26, 2024	N/A	Radiation (03CH21-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jun. 12, 2024~ Jun. 26, 2024	N/A	Radiation (03CH21-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Jun. 12, 2024~ Jun. 26, 2024	N/A	Radiation (03CH21-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	Jun. 03, 2024~ Jun. 25, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 35 (NO:109)	10MHz~6GHz	Jan. 15, 2024	Jun. 03, 2024~ Jun. 25, 2024	Jan. 14, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Jan. 24, 2024	Jun. 03, 2024~ Jun. 25, 2024	Jan. 23, 2025	Conducted (TH05-HY)
Power Divider	Woken	2Way SMA	DCMD38W1E 2	N/A	N/A	Jun. 03, 2024~ Jun. 25, 2024	N/A	Conducted (TH05-HY)
Software1	Sporton	BTWIFI_Final_v ersion:1.0(2024- 04-11)	N/A	Conducted Items	N/A	Jun. 03, 2024~ Jun. 25, 2024	N/A	Conducted (TH05-HY)
Software2	Raditeq	RadiMation 2021.1.8	N/A	Conducted Power	N/A	Jun. 03, 2024~ Jun. 25, 2024	N/A	Conducted (TH05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.44 dB
--	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.40 dB
--	---------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.60 dB
--	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.60 dB
--	---------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.50 dB
--	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Wei Shun	Temperature:	21~25	°C
Test Date:	2024/06/03~2024/06/25	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
11a	6Mbps	1	149	5745	17.49	-	26.79	-	16.36	-	0.5	Pass
11a	6Mbps	1	157	5785	17.54	-	28.10	-	16.37	-	0.5	Pass
11a	6Mbps	1	165	5825	17.55	-	27.06	-	16.37	-	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna											
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)		FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	13.06	-	30.00	-	5.04	-	Pass
11a	6Mbps	1	157	5785	13.31	-	30.00	-	5.04	-	Pass
11a	6Mbps	1	165	5825	13.21	-	30.00	-	5.04	-	Pass
HT20	MCS0	1	149	5745	13.26	-	30.00	-	5.04	-	Pass
HT20	MCS0	1	157	5785	13.16	-	30.00	-	5.04	-	Pass
HT20	MCS0	1	165	5825	13.09	-	30.00	-	5.04	-	Pass
HT40	MCS0	1	151	5755	13.28	-	30.00	-	5.04	-	Pass
HT40	MCS0	1	159	5795	13.19	-	30.00	-	5.04	-	Pass
VHT20	MCS0	1	149	5745	13.36	-	30.00	-	5.04	-	Pass
VHT20	MCS0	1	157	5785	13.26	-	30.00	-	5.04	-	Pass
VHT20	MCS0	1	165	5825	13.19	-	30.00	-	5.04	-	Pass
VHT40	MCS0	1	151	5755	13.38	-	30.00	-	5.04	-	Pass
VHT40	MCS0	1	159	5795	13.29	-	30.00	-	5.04	-	Pass
VHT80	MCS0	1	155	5775	13.23	-	30.00	-	5.04	-	Pass

TEST RESULTS DATA
Power Spectral Density

U-NII-3 single antenna															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)		Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11a	6Mbps	1	149	5745	0.14		2.22	-	-2.07	-	30.00	-	5.04	-	Pass
11a	6Mbps	1	157	5785	0.14		2.22	-	-1.80	-	30.00	-	5.04	-	Pass
11a	6Mbps	1	165	5825	0.14		2.22	-	-1.83	-	30.00	-	5.04	-	Pass

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

U-NII-3 single antenna													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2		
HE20	MCS0	1	149	5745	Full	19.49	-	26.82	-	19.00	-	0.5	Pass
HE20	MCS0	1	157	5785	Full	19.56	-	27.11	-	19.02	-	0.5	Pass
HE20	MCS0	1	165	5825	Full	19.53	-	27.75	-	19.04	-	0.5	Pass
HE40	MCS0	1	151	5755	Full	38.86	-	48.45	-	38.10	-	0.5	Pass
HE40	MCS0	1	159	5795	Full	38.89	-	49.66	-	38.11	-	0.5	Pass
HE80	MCS0	1	155	5775	Full	77.87	-	88.00	-	78.03	-	0.5	Pass

TEST RESULTS DATA
Average Power Table

U-NII-3 single antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)		FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
HE20	MCS0	1	149	5745	Full	13.46	-	30.00	-	5.04	-	Pass
HE20	MCS0	1	157	5785	Full	13.36	-	30.00	-	5.04	-	Pass
HE20	MCS0	1	165	5825	Full	13.29	-	30.00	-	5.04	-	Pass
HE40	MCS0	1	151	5755	Full	13.48	-	30.00	-	5.04	-	Pass
HE40	MCS0	1	159	5795	Full	13.39	-	30.00	-	5.04	-	Pass
HE80	MCS0	1	155	5775	Full	13.33	-	30.00	-	5.04	-	Pass




TEST RESULTS DATA
Power Spectral Density

U-NII-3 single antenna																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)		Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
HE20	MCS0	1	149	5745	Full	0.13	-	2.22	-	-1.85	-	30.00	-	5.04	-	Pass
HE20	MCS0	1	157	5785	Full	0.13	-	2.22	-	-2.49	-	30.00	-	5.04	-	Pass
HE20	MCS0	1	165	5825	Full	0.13	-	2.22	-	-2.56	-	30.00	-	5.04	-	Pass
HE40	MCS0	1	151	5755	Full	0.07	-	2.22	-	-4.94	-	30.00	-	5.04	-	Pass
HE40	MCS0	1	159	5795	Full	0.07	-	2.22	-	-5.44	-	30.00	-	5.04	-	Pass
HE80	MCS0	1	155	5775	Full	0.16	-	2.22	-	-8.37	-	30.00	-	5.04	-	Pass


**Test Result of 6dB and 26dB and 99% Occupied Bandwidth**

<Ant. 1>

<802.11a>

6dB Bandwidth**26dB Bandwidth****99% Occupied Bandwidth**


N/A






<802.11ax HE40>


6dB Bandwidth



26dB Bandwidth



99% Occupied Bandwidth




N/A




<802.11ax HE80>


6dB Bandwidth



26dB Bandwidth



99% Occupied Bandwidth




N/A




Test Result of Power Spectral Density

<802.11a>




<802.11ax HE20>






<802.11ax HE40>



<802.11ax HE80>






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	22.8~24.6°C
		Relative Humidity :	53.4~61.2%

EUT Information

Report NO : 452713
Test Mode : Mode 3
Test Voltage : Power from system
Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.173310	---	42.09	54.80	12.71	L1	OFF	19.9
0.173310	57.06	---	64.80	7.74	L1	OFF	19.9
0.183750	---	34.82	54.31	19.49	L1	OFF	19.9
0.183750	52.52	---	64.31	11.79	L1	OFF	19.9
0.206250	---	20.43	53.36	32.93	L1	OFF	19.9
0.206250	46.63	---	63.36	16.73	L1	OFF	19.9
0.228750	---	31.65	52.50	20.85	L1	OFF	19.9
0.228750	47.46	---	62.50	15.04	L1	OFF	19.9
0.253500	---	19.59	51.64	32.05	L1	OFF	19.9
0.253500	40.00	---	61.64	21.64	L1	OFF	19.9
0.319740	---	18.08	49.71	31.63	L1	OFF	19.9
0.319740	32.66	---	59.71	27.05	L1	OFF	19.9
3.679350	---	28.72	46.00	17.28	L1	OFF	20.0
3.679350	35.62	---	56.00	20.38	L1	OFF	20.0
4.026750	---	26.80	46.00	19.20	L1	OFF	20.0
4.026750	34.21	---	56.00	21.79	L1	OFF	20.0
4.569900	---	23.15	46.00	22.85	L1	OFF	20.0
4.569900	31.07	---	56.00	24.93	L1	OFF	20.0
17.697030	---	27.74	50.00	22.26	L1	OFF	20.1

17.697030	33.55	---	60.00	26.45	L1	OFF	20.1
-----------	-------	-----	-------	-------	----	-----	------

EUT Information

Report NO : 452713
Test Mode : Mode 3
Test Voltage : Power from system
Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.164670	---	43.34	55.23	11.89	N	OFF	19.9
0.164670	57.82	---	65.23	7.41	N	OFF	19.9
0.192750	---	21.66	53.92	32.26	N	OFF	19.9
0.192750	43.46	---	63.92	20.46	N	OFF	19.9
0.206250	---	25.92	53.36	27.44	N	OFF	19.9
0.206250	44.43	---	63.36	18.93	N	OFF	19.9
0.249450	---	18.94	51.78	32.84	N	OFF	19.9
0.249450	40.02	---	61.78	21.76	N	OFF	19.9
0.314250	---	17.50	49.86	32.36	N	OFF	19.9
0.314250	31.65	---	59.86	28.21	N	OFF	19.9
3.728040	---	28.26	46.00	17.74	N	OFF	20.0
3.728040	35.05	---	56.00	20.95	N	OFF	20.0
4.236000	---	23.88	46.00	22.12	N	OFF	20.0
4.236000	31.95	---	56.00	24.05	N	OFF	20.0
17.508840	---	27.10	50.00	22.90	N	OFF	20.2
17.508840	33.05	---	60.00	26.95	N	OFF	20.2



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Jack Cheng, Ray Lung and Sky Chang	Temperature :	18~26°C
		Relative Humidity :	50~70 %




C1. Radiated Spurious Emission Test Modes

Mode	Band	Band (GHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 31	U-NII-3	5.725-5.85	1	802.11a	149	5745	6Mbps	-	-
Mode 32	U-NII-3	5.725-5.85	1	802.11a	157	5785	6Mbps	-	-
Mode 33	U-NII-3	5.725-5.85	1	802.11a	165	5825	6Mbps	-	-
Mode 34	U-NII-3	5.725-5.85	1	802.11ax HE20	149	5745	MCS0	Full RU	-
Mode 35	U-NII-3	5.725-5.85	1	802.11ax HE20	157	5785	MCS0	Full RU	-
Mode 36	U-NII-3	5.725-5.85	1	802.11ax HE20	165	5825	MCS0	Full RU	-
Mode 37	U-NII-3	5.725-5.85	1	802.11ax HE40	151	5755	MCS0	Full RU	-
Mode 38	U-NII-3	5.725-5.85	1	802.11ax HE40	159	5795	MCS0	Full RU	-
Mode 39	U-NII-3	5.725-5.85	1	802.11ax HE80	155	5775	MCS0	Full RU	-
Mode 40	U-NII-3	5.725-5.85	1	802.11ax HE80	155	5775	MCS0	Full RU	SHF
Mode 41	U-NII-3	5.725-5.85	1	802.11ax HE80	155	5775	MCS0	Full RU	LF




**C2. Summary of each worse mode**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
31	802.11a	149	5608.99	49.73	68.20	-18.47	H	Peak	Pass	-	Band Edge
	802.11a	149	11490.00	40.47	54.00	-13.53	H	Avg.	Pass	-	Harmonic
32	802.11a	157	5617.58	49.57	68.20	-18.63	H	Peak	Pass	-	Band Edge
	802.11a	157	11570.00	40.08	54.00	-13.92	H	Avg.	Pass	-	Harmonic
33	802.11a	165	5930.00	49.76	68.20	-18.44	H	Peak	Pass	-	Band Edge
	802.11a	165	11650.00	39.97	54.00	-14.03	V	Avg.	Pass	-	Harmonic
34	802.11ax HE20	149	5650.17	51.59	68.33	-16.74	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	149	11490.00	40.51	54.00	-13.49	V	Avg.	Pass	Full RU	Harmonic
35	802.11ax HE20	157	5621.83	50.24	68.20	-17.96	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	157	11570.00	40.14	54.00	-13.86	V	Avg.	Pass	Full RU	Harmonic
36	802.11ax HE20	165	5948.13	49.66	68.20	-18.54	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE20	165	11650.00	40.00	54.00	-14.00	V	Avg.	Pass	Full RU	Harmonic
37	802.11ax HE40	151	5649.14	62.88	68.20	-5.32	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	151	11510.00	40.43	54.00	-13.57	V	Avg.	Pass	Full RU	Harmonic
38	802.11ax HE40	159	5923.19	53.20	69.54	-16.34	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE40	159	11590.00	40.32	54.00	-13.68	V	Avg.	Pass	Full RU	Harmonic
39	802.11ax HE80	155	5645.85	63.71	68.20	-4.49	H	Peak	Pass	Full RU	Band Edge
	802.11ax HE80	155	11550.00	40.91	54.00	-13.09	H	Avg.	Pass	Full RU	Harmonic
40	SHF	155	39505.22	40.28	54.00	-13.72	H	Avg.	Pass	-	SHF
41	LF	155	72.68	32.53	40.00	-7.47	V	QP	Pass	-	LF





Mode	31																																																																																																																																									
	Band Edge																																																																																																																																									
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5608.99</td><td>49.73</td><td>68.20</td><td>-18.47</td><td>38.53</td><td>33.05</td><td>13.07</td><td>34.92</td><td>0.00</td><td>140</td><td>106</td><td>PEAK</td></tr><tr><td>2</td><td>5651.77</td><td>50.81</td><td>69.51</td><td>-18.70</td><td>39.32</td><td>33.31</td><td>13.14</td><td>34.96</td><td>0.00</td><td>140</td><td>106</td><td>PEAK</td></tr><tr><td>3</td><td>5715.13</td><td>71.69</td><td>109.44</td><td>-37.75</td><td>59.82</td><td>33.66</td><td>13.23</td><td>35.02</td><td>0.00</td><td>140</td><td>106</td><td>PEAK</td></tr><tr><td>4</td><td>5728.79</td><td>75.08</td><td>112.59</td><td>-37.51</td><td>63.18</td><td>33.68</td><td>13.24</td><td>35.02</td><td>0.00</td><td>140</td><td>106</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5608.99	49.73	68.20	-18.47	38.53	33.05	13.07	34.92	0.00	140	106	PEAK	2	5651.77	50.81	69.51	-18.70	39.32	33.31	13.14	34.96	0.00	140	106	PEAK	3	5715.13	71.69	109.44	-37.75	59.82	33.66	13.23	35.02	0.00	140	106	PEAK	4	5728.79	75.08	112.59	-37.51	63.18	33.68	13.24	35.02	0.00	140	106	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>110.73</td><td>-----</td><td>-----</td><td>98.72</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00</td><td>140</td><td>106</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	110.73	-----	-----	98.72	33.78	13.27	35.04	0.00	140	106
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5608.99	49.73	68.20	-18.47	38.53	33.05	13.07	34.92	0.00	140	106	PEAK																																																																																																																														
2	5651.77	50.81	69.51	-18.70	39.32	33.31	13.14	34.96	0.00	140	106	PEAK																																																																																																																														
3	5715.13	71.69	109.44	-37.75	59.82	33.66	13.23	35.02	0.00	140	106	PEAK																																																																																																																														
4	5728.79	75.08	112.59	-37.51	63.18	33.68	13.24	35.02	0.00	140	106	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5745.00	110.73	-----	-----	98.72	33.78	13.27	35.04	0.00	140	106	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBN:0.200kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>103.23</td><td>-----</td><td>-----</td><td>91.25</td><td>33.76</td><td>13.26</td><td>35.04</td><td>0.00</td><td>140</td><td>106</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	103.23	-----	-----	91.25	33.76	13.26	35.04	0.00	140	106	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5745.00	103.23	-----	-----	91.25	33.76	13.26	35.04	0.00	140	106	AVERAGE																																																																																																																														





Mode	31																																																																																																																																									
	Band Edge																																																																																																																																									
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5637.41</td><td>49.65</td><td>68.20</td><td>-18.55</td><td>38.27</td><td>33.22</td><td>13.11</td><td>34.95</td><td>0.00</td><td>300</td><td>252</td><td>PEAK</td></tr><tr><td>2</td><td>5651.77</td><td>49.92</td><td>69.51</td><td>-19.59</td><td>38.43</td><td>33.31</td><td>13.14</td><td>34.96</td><td>0.00</td><td>300</td><td>252</td><td>PEAK</td></tr><tr><td>3</td><td>5711.36</td><td>72.81</td><td>108.38</td><td>-35.57</td><td>60.95</td><td>33.65</td><td>13.22</td><td>35.01</td><td>0.00</td><td>300</td><td>252</td><td>PEAK</td></tr><tr><td>4</td><td>5728.21</td><td>75.17</td><td>111.27</td><td>-36.10</td><td>63.28</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00</td><td>300</td><td>252</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5637.41	49.65	68.20	-18.55	38.27	33.22	13.11	34.95	0.00	300	252	PEAK	2	5651.77	49.92	69.51	-19.59	38.43	33.31	13.14	34.96	0.00	300	252	PEAK	3	5711.36	72.81	108.38	-35.57	60.95	33.65	13.22	35.01	0.00	300	252	PEAK	4	5728.21	75.17	111.27	-36.10	63.28	33.68	13.23	35.02	0.00	300	252	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>110.27</td><td>-----</td><td>-----</td><td>98.26</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00</td><td>300</td><td>252</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	110.27	-----	-----	98.26	33.78	13.27	35.04	0.00	300	252
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5637.41	49.65	68.20	-18.55	38.27	33.22	13.11	34.95	0.00	300	252	PEAK																																																																																																																														
2	5651.77	49.92	69.51	-19.59	38.43	33.31	13.14	34.96	0.00	300	252	PEAK																																																																																																																														
3	5711.36	72.81	108.38	-35.57	60.95	33.65	13.22	35.01	0.00	300	252	PEAK																																																																																																																														
4	5728.21	75.17	111.27	-36.10	63.28	33.68	13.23	35.02	0.00	300	252	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5745.00	110.27	-----	-----	98.26	33.78	13.27	35.04	0.00	300	252	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.200kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>102.78</td><td>-----</td><td>-----</td><td>98.08</td><td>33.76</td><td>13.26</td><td>35.04</td><td>0.00</td><td>300</td><td>252</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5745.00	102.78	-----	-----	98.08	33.76	13.26	35.04	0.00	300	252	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5745.00	102.78	-----	-----	98.08	33.76	13.26	35.04	0.00	300	252	AVERAGE																																																																																																																														






Mode	31																																																																																																																																															
	Harmonic																																																																																																																																															
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz																																																																																																																																															
ANT	1																																																																																																																																															
Pol.	Horizontal						Vertical																																																																																																																																									
Peak Avg																																																																																																																																																
	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL						Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL																																																																																																																																									
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11490.00</td><td>50.19</td><td>74.00</td><td>-23.81</td><td>32.60</td><td>38.70</td><td>19.06</td><td>40.61</td><td>0.44</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 11490.00</td><td>40.47</td><td>54.00</td><td>-13.53</td><td>22.88</td><td>38.70</td><td>19.06</td><td>40.61</td><td>0.44</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3 17235.00</td><td>51.71</td><td>68.20</td><td>-16.49</td><td>34.76</td><td>40.04</td><td>23.62</td><td>47.17</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11490.00	50.19	74.00	-23.81	32.60	38.70	19.06	40.61	0.44	--	--	PEAK	2 11490.00	40.47	54.00	-13.53	22.88	38.70	19.06	40.61	0.44	--	--	AVERAGE	3 17235.00	51.71	68.20	-16.49	34.76	40.04	23.62	47.17	0.46	--	--	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11490.00</td><td>50.97</td><td>74.00</td><td>-23.03</td><td>33.38</td><td>38.70</td><td>19.06</td><td>40.61</td><td>0.44</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 11490.00</td><td>40.40</td><td>54.00</td><td>-13.60</td><td>22.81</td><td>38.70</td><td>19.06</td><td>40.61</td><td>0.44</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3 17235.00</td><td>52.53</td><td>68.20</td><td>-15.67</td><td>35.58</td><td>40.04</td><td>23.62</td><td>47.17</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11490.00	50.97	74.00	-23.03	33.38	38.70	19.06	40.61	0.44	--	--	PEAK	2 11490.00	40.40	54.00	-13.60	22.81	38.70	19.06	40.61	0.44	--	--	AVERAGE	3 17235.00	52.53	68.20	-15.67	35.58	40.04	23.62	47.17	0.46	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																						
1 11490.00	50.19	74.00	-23.81	32.60	38.70	19.06	40.61	0.44	--	--	PEAK																																																																																																																																					
2 11490.00	40.47	54.00	-13.53	22.88	38.70	19.06	40.61	0.44	--	--	AVERAGE																																																																																																																																					
3 17235.00	51.71	68.20	-16.49	34.76	40.04	23.62	47.17	0.46	--	--	PEAK																																																																																																																																					
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																						
1 11490.00	50.97	74.00	-23.03	33.38	38.70	19.06	40.61	0.44	--	--	PEAK																																																																																																																																					
2 11490.00	40.40	54.00	-13.60	22.81	38.70	19.06	40.61	0.44	--	--	AVERAGE																																																																																																																																					
3 17235.00	52.53	68.20	-15.67	35.58	40.04	23.62	47.17	0.46	--	--	PEAK																																																																																																																																					




Mode	31	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH149_5745MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL






Mode	32																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5617.50</td><td>49.57</td><td>68.20</td><td>-18.63</td><td>38.30</td><td>33.11</td><td>13.09</td><td>34.93</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr><tr><td>2</td><td>5650.14</td><td>47.80</td><td>68.30</td><td>-20.50</td><td>36.33</td><td>33.30</td><td>13.13</td><td>34.96</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr><tr><td>3</td><td>5705.82</td><td>59.55</td><td>106.83</td><td>-47.28</td><td>47.73</td><td>33.62</td><td>13.21</td><td>35.01</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr><tr><td>4</td><td>5721.18</td><td>62.06</td><td>113.48</td><td>-51.42</td><td>50.16</td><td>33.68</td><td>13.24</td><td>35.02</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5617.50	49.57	68.20	-18.63	38.30	33.11	13.09	34.93	0.00	107	101	PEAK	2	5650.14	47.80	68.30	-20.50	36.33	33.30	13.13	34.96	0.00	107	101	PEAK	3	5705.82	59.55	106.83	-47.28	47.73	33.62	13.21	35.01	0.00	107	101	PEAK	4	5721.18	62.06	113.48	-51.42	50.16	33.68	13.24	35.02	0.00	107	101	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>111.87</td><td>-----</td><td>-----</td><td>99.76</td><td>33.86</td><td>13.32</td><td>35.07</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	111.87	-----	-----	99.76	33.86	13.32	35.07	0.00	107	101
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5617.50	49.57	68.20	-18.63	38.30	33.11	13.09	34.93	0.00	107	101	PEAK																																																																																																																														
2	5650.14	47.80	68.30	-20.50	36.33	33.30	13.13	34.96	0.00	107	101	PEAK																																																																																																																														
3	5705.82	59.55	106.83	-47.28	47.73	33.62	13.21	35.01	0.00	107	101	PEAK																																																																																																																														
4	5721.18	62.06	113.48	-51.42	50.16	33.68	13.24	35.02	0.00	107	101	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	111.87	-----	-----	99.76	33.86	13.32	35.07	0.00	107	101	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:0.200kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>104.15</td><td>-----</td><td>-----</td><td>92.04</td><td>33.86</td><td>13.32</td><td>35.07</td><td>0.00</td><td>107</td><td>101</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	104.15	-----	-----	92.04	33.86	13.32	35.07	0.00	107	101	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	104.15	-----	-----	92.04	33.86	13.32	35.07	0.00	107	101	AVERAGE																																																																																																																														




Mode	32																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																				
ANT	1																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5852.65</td><td>63.78</td><td>116.16</td><td>-52.38</td><td>51.70</td><td>33.00</td><td>13.41</td><td>35.13</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr><tr><td>2</td><td>5858.26</td><td>61.00</td><td>109.89</td><td>-48.89</td><td>48.92</td><td>33.00</td><td>13.42</td><td>35.14</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr><tr><td>3</td><td>5924.92</td><td>47.53</td><td>68.26</td><td>-20.73</td><td>35.43</td><td>33.00</td><td>13.50</td><td>35.20</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr><tr><td>4</td><td>5926.57</td><td>49.15</td><td>68.20</td><td>-19.05</td><td>37.05</td><td>33.00</td><td>13.50</td><td>35.20</td><td>0.00</td><td>107</td><td>101</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5852.65	63.78	116.16	-52.38	51.70	33.00	13.41	35.13	0.00	107	101	PEAK	2	5858.26	61.00	109.89	-48.89	48.92	33.00	13.42	35.14	0.00	107	101	PEAK	3	5924.92	47.53	68.26	-20.73	35.43	33.00	13.50	35.20	0.00	107	101	PEAK	4	5926.57	49.15	68.20	-19.05	37.05	33.00	13.50	35.20	0.00	107	101	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5852.65	63.78	116.16	-52.38	51.70	33.00	13.41	35.13	0.00	107	101	PEAK																																																																									
2	5858.26	61.00	109.89	-48.89	48.92	33.00	13.42	35.14	0.00	107	101	PEAK																																																																									
3	5924.92	47.53	68.26	-20.73	35.43	33.00	13.50	35.20	0.00	107	101	PEAK																																																																									
4	5926.57	49.15	68.20	-19.05	37.05	33.00	13.50	35.20	0.00	107	101	PEAK																																																																									





Mode	32																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5630.34</td><td>49.31</td><td>68.20</td><td>-18.89</td><td>37.97</td><td>33.18</td><td>13.10</td><td>34.94</td><td>0.00</td><td>300</td><td>256</td><td>PEAK</td></tr><tr><td>2</td><td>5650.32</td><td>48.85</td><td>68.44</td><td>-19.59</td><td>37.38</td><td>33.30</td><td>13.13</td><td>34.96</td><td>0.00</td><td>300</td><td>256</td><td>PEAK</td></tr><tr><td>3</td><td>5706.93</td><td>58.12</td><td>107.14</td><td>-49.02</td><td>46.28</td><td>33.63</td><td>13.22</td><td>35.01</td><td>0.00</td><td>300</td><td>256</td><td>PEAK</td></tr><tr><td>4</td><td>5721.18</td><td>60.17</td><td>113.48</td><td>-53.31</td><td>48.27</td><td>33.68</td><td>13.24</td><td>35.02</td><td>0.00</td><td>300</td><td>256</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5630.34	49.31	68.20	-18.89	37.97	33.18	13.10	34.94	0.00	300	256	PEAK	2	5650.32	48.85	68.44	-19.59	37.38	33.30	13.13	34.96	0.00	300	256	PEAK	3	5706.93	58.12	107.14	-49.02	46.28	33.63	13.22	35.01	0.00	300	256	PEAK	4	5721.18	60.17	113.48	-53.31	48.27	33.68	13.24	35.02	0.00	300	256	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>109.46</td><td>-----</td><td>-----</td><td>97.33</td><td>33.88</td><td>13.33</td><td>35.08</td><td>0.00</td><td>300</td><td>256</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	109.46	-----	-----	97.33	33.88	13.33	35.08	0.00	300	256
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5630.34	49.31	68.20	-18.89	37.97	33.18	13.10	34.94	0.00	300	256	PEAK																																																																																																																														
2	5650.32	48.85	68.44	-19.59	37.38	33.30	13.13	34.96	0.00	300	256	PEAK																																																																																																																														
3	5706.93	58.12	107.14	-49.02	46.28	33.63	13.22	35.01	0.00	300	256	PEAK																																																																																																																														
4	5721.18	60.17	113.48	-53.31	48.27	33.68	13.24	35.02	0.00	300	256	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	109.46	-----	-----	97.33	33.88	13.33	35.08	0.00	300	256	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.200kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>102.01</td><td>-----</td><td>-----</td><td>89.90</td><td>33.86</td><td>13.32</td><td>35.07</td><td>0.00</td><td>300</td><td>256</td><td>AVERAGE</td></tr></tbody></table>														Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	102.01	-----	-----	89.90	33.86	13.32	35.07	0.00	300	256	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	102.01	-----	-----	89.90	33.86	13.32	35.07	0.00	300	256	AVERAGE																																																																																																																														





Mode	32																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																							
ANT	1																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.47</td><td>59.64</td><td>112.02</td><td>-52.38</td><td>47.55</td><td>33.00</td><td>13.42</td><td>35.13</td><td>0.00</td><td>300 256 PEAK</td></tr><tr><td>2 5872.62</td><td>55.60</td><td>105.87</td><td>-50.27</td><td>43.51</td><td>33.00</td><td>13.44</td><td>35.15</td><td>0.00</td><td>300 256 PEAK</td></tr><tr><td>3 5924.92</td><td>48.05</td><td>68.26</td><td>-20.21</td><td>35.95</td><td>33.00</td><td>13.50</td><td>35.20</td><td>0.00</td><td>300 256 PEAK</td></tr><tr><td>4 5944.39</td><td>49.55</td><td>68.20</td><td>-18.65</td><td>37.44</td><td>33.00</td><td>13.52</td><td>35.21</td><td>0.00</td><td>300 256 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.47	59.64	112.02	-52.38	47.55	33.00	13.42	35.13	0.00	300 256 PEAK	2 5872.62	55.60	105.87	-50.27	43.51	33.00	13.44	35.15	0.00	300 256 PEAK	3 5924.92	48.05	68.26	-20.21	35.95	33.00	13.50	35.20	0.00	300 256 PEAK	4 5944.39	49.55	68.20	-18.65	37.44	33.00	13.52	35.21	0.00	300 256 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1 5854.47	59.64	112.02	-52.38	47.55	33.00	13.42	35.13	0.00	300 256 PEAK																																																															
2 5872.62	55.60	105.87	-50.27	43.51	33.00	13.44	35.15	0.00	300 256 PEAK																																																															
3 5924.92	48.05	68.26	-20.21	35.95	33.00	13.50	35.20	0.00	300 256 PEAK																																																															
4 5944.39	49.55	68.20	-18.65	37.44	33.00	13.52	35.21	0.00	300 256 PEAK																																																															






Mode	32																																																																																																																																							
	Harmonic																																																																																																																																							
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz																																																																																																																																							
ANT	1																																																																																																																																							
Pol.	Horizontal	Vertical																																																																																																																																						
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 11570.00</td><td>49.61</td><td>74.00</td><td>-24.39</td><td>32.21</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 11570.00</td><td>40.08</td><td>54.00</td><td>-13.92</td><td>22.68</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3 17355.00</td><td>50.96</td><td>68.20</td><td>-17.24</td><td>34.34</td><td>39.91</td><td>23.69</td><td>47.44</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11570.00	49.61	74.00	-24.39	32.21	38.56	19.13	40.72	0.43	--	--	PEAK	2 11570.00	40.08	54.00	-13.92	22.68	38.56	19.13	40.72	0.43	--	--	AVERAGE	3 17355.00	50.96	68.20	-17.24	34.34	39.91	23.69	47.44	0.46	--	--	PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1 11570.00</td><td>48.53</td><td>74.00</td><td>-25.47</td><td>31.13</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 11570.00</td><td>40.05</td><td>54.00</td><td>-13.95</td><td>22.65</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3 17355.00</td><td>51.03</td><td>68.20</td><td>-17.17</td><td>34.41</td><td>39.91</td><td>23.69</td><td>47.44</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11570.00	48.53	74.00	-25.47	31.13	38.56	19.13	40.72	0.43	--	--	PEAK	2 11570.00	40.05	54.00	-13.95	22.65	38.56	19.13	40.72	0.43	--	--	AVERAGE	3 17355.00	51.03	68.20	-17.17	34.41	39.91	23.69	47.44	0.46	--	--	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																														
1 11570.00	49.61	74.00	-24.39	32.21	38.56	19.13	40.72	0.43	--	--	PEAK																																																																																																																													
2 11570.00	40.08	54.00	-13.92	22.68	38.56	19.13	40.72	0.43	--	--	AVERAGE																																																																																																																													
3 17355.00	50.96	68.20	-17.24	34.34	39.91	23.69	47.44	0.46	--	--	PEAK																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																														
1 11570.00	48.53	74.00	-25.47	31.13	38.56	19.13	40.72	0.43	--	--	PEAK																																																																																																																													
2 11570.00	40.05	54.00	-13.95	22.65	38.56	19.13	40.72	0.43	--	--	AVERAGE																																																																																																																													
3 17355.00	51.03	68.20	-17.17	34.41	39.91	23.69	47.44	0.46	--	--	PEAK																																																																																																																													






Mode	32	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH157_5785MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL





Mode	33																																																																																																																																									
	Band Edge																																																																																																																																									
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5854.88</td><td>69.51</td><td>111.08</td><td>-41.57</td><td>57.43</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>100</td><td>94</td><td>PEAK</td></tr><tr><td>2</td><td>5858.50</td><td>73.05</td><td>109.82</td><td>-36.77</td><td>60.97</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>100</td><td>94</td><td>PEAK</td></tr><tr><td>3</td><td>5924.38</td><td>48.48</td><td>68.66</td><td>-20.18</td><td>36.37</td><td>33.80</td><td>13.50</td><td>35.19</td><td>0.00</td><td>100</td><td>94</td><td>PEAK</td></tr><tr><td>4</td><td>5930.00</td><td>49.76</td><td>68.20</td><td>-18.44</td><td>37.65</td><td>33.80</td><td>13.51</td><td>35.20</td><td>0.00</td><td>100</td><td>94</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.88	69.51	111.08	-41.57	57.43	33.80	13.42	35.14	0.00	100	94	PEAK	2	5858.50	73.05	109.82	-36.77	60.97	33.80	13.42	35.14	0.00	100	94	PEAK	3	5924.38	48.48	68.66	-20.18	36.37	33.80	13.50	35.19	0.00	100	94	PEAK	4	5930.00	49.76	68.20	-18.44	37.65	33.80	13.51	35.20	0.00	100	94	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>110.97</td><td>-----</td><td>-----</td><td>98.85</td><td>33.85</td><td>13.38</td><td>35.11</td><td>0.00</td><td>100</td><td>94</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	110.97	-----	-----	98.85	33.85	13.38	35.11	0.00	100	94
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5854.88	69.51	111.08	-41.57	57.43	33.80	13.42	35.14	0.00	100	94	PEAK																																																																																																																														
2	5858.50	73.05	109.82	-36.77	60.97	33.80	13.42	35.14	0.00	100	94	PEAK																																																																																																																														
3	5924.38	48.48	68.66	-20.18	36.37	33.80	13.50	35.19	0.00	100	94	PEAK																																																																																																																														
4	5930.00	49.76	68.20	-18.44	37.65	33.80	13.51	35.20	0.00	100	94	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5825.00	110.97	-----	-----	98.85	33.85	13.38	35.11	0.00	100	94	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
						Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:0.200kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>103.59</td><td>-----</td><td>-----</td><td>91.46</td><td>33.86</td><td>13.37</td><td>35.10</td><td>0.00</td><td>100</td><td>94</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	103.59	-----	-----	91.46	33.86	13.37	35.10	0.00	100	94	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5825.00	103.59	-----	-----	91.46	33.86	13.37	35.10	0.00	100	94	AVERAGE																																																																																																																														





Mode	33																																																																																																															
	Band Edge																																																																																																															
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz																																																																																																															
ANT	1																																																																																																															
Pol.	Vertical	Fundamental																																																																																																														
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5853.88</td><td>69.49</td><td>113.36</td><td>-43.87</td><td>57.41</td><td>33.80</td><td>13.41</td><td>35.13</td><td>0.00</td><td>319 256 PEAK</td></tr><tr><td>2 5868.75</td><td>66.16</td><td>106.95</td><td>-40.79</td><td>54.08</td><td>33.80</td><td>13.43</td><td>35.15</td><td>0.00</td><td>319 256 PEAK</td></tr><tr><td>3 5924.38</td><td>48.53</td><td>68.66</td><td>-20.13</td><td>36.42</td><td>33.80</td><td>13.50</td><td>35.19</td><td>0.00</td><td>319 256 PEAK</td></tr><tr><td>4 5937.50</td><td>49.16</td><td>68.20</td><td>-19.04</td><td>37.05</td><td>33.80</td><td>13.52</td><td>35.21</td><td>0.00</td><td>319 256 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5853.88	69.49	113.36	-43.87	57.41	33.80	13.41	35.13	0.00	319 256 PEAK	2 5868.75	66.16	106.95	-40.79	54.08	33.80	13.43	35.15	0.00	319 256 PEAK	3 5924.38	48.53	68.66	-20.13	36.42	33.80	13.50	35.19	0.00	319 256 PEAK	4 5937.50	49.16	68.20	-19.04	37.05	33.80	13.52	35.21	0.00	319 256 PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5825.00</td><td>109.38</td><td>-----</td><td>-----</td><td>97.26</td><td>33.84</td><td>13.39</td><td>35.11</td><td>0.00</td><td>319 256 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5825.00	109.38	-----	-----	97.26	33.84	13.39	35.11	0.00	319 256 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																						
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1 5853.88	69.49	113.36	-43.87	57.41	33.80	13.41	35.13	0.00	319 256 PEAK																																																																																																							
2 5868.75	66.16	106.95	-40.79	54.08	33.80	13.43	35.15	0.00	319 256 PEAK																																																																																																							
3 5924.38	48.53	68.66	-20.13	36.42	33.80	13.50	35.19	0.00	319 256 PEAK																																																																																																							
4 5937.50	49.16	68.20	-19.04	37.05	33.80	13.52	35.21	0.00	319 256 PEAK																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1 5825.00	109.38	-----	-----	97.26	33.84	13.39	35.11	0.00	319 256 PEAK																																																																																																							
Avg	Blank	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.200kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5825.00</td><td>101.95</td><td>-----</td><td>-----</td><td>89.83</td><td>33.85</td><td>13.38</td><td>35.11</td><td>0.00</td><td>319 256 AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5825.00	101.95	-----	-----	89.83	33.85	13.38	35.11	0.00	319 256 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1 5825.00	101.95	-----	-----	89.83	33.85	13.38	35.11	0.00	319 256 AVERAGE																																																																																																							






Mode	33																																																																																																																																																					
	Harmonic																																																																																																																																																					
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz																																																																																																																																																					
ANT	1																																																																																																																																																					
Pol.	Horizontal						Vertical																																																																																																																																															
Peak Avg																																																																																																																																																						
	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL						Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL																																																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11650.00</td><td>47.94</td><td>74.00</td><td>-26.06</td><td>30.55</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>11650.00</td><td>39.88</td><td>54.00</td><td>-14.12</td><td>22.49</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>3</td><td>17475.00</td><td>50.47</td><td>68.20</td><td>-17.73</td><td>33.95</td><td>40.00</td><td>23.77</td><td>47.71</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11650.00	47.94	74.00	-26.06	30.55	38.60	19.20	40.84	0.43	--	--	PEAK	2	11650.00	39.88	54.00	-14.12	22.49	38.60	19.20	40.84	0.43	--	--	Average	3	17475.00	50.47	68.20	-17.73	33.95	40.00	23.77	47.71	0.46	--	--	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11650.00</td><td>48.54</td><td>74.00</td><td>-25.46</td><td>31.15</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>11650.00</td><td>39.97</td><td>54.00</td><td>-14.03</td><td>22.58</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>17475.00</td><td>51.43</td><td>68.20</td><td>-16.77</td><td>34.91</td><td>40.00</td><td>23.77</td><td>47.71</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11650.00	48.54	74.00	-25.46	31.15	38.60	19.20	40.84	0.43	--	--	PEAK	2	11650.00	39.97	54.00	-14.03	22.58	38.60	19.20	40.84	0.43	--	--	AVERAGE	3	17475.00	51.43	68.20	-16.77	34.91	40.00	23.77	47.71	0.46	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	11650.00	47.94	74.00	-26.06	30.55	38.60	19.20	40.84	0.43	--	--	PEAK																																																																																																																																										
2	11650.00	39.88	54.00	-14.12	22.49	38.60	19.20	40.84	0.43	--	--	Average																																																																																																																																										
3	17475.00	50.47	68.20	-17.73	33.95	40.00	23.77	47.71	0.46	--	--	PEAK																																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	11650.00	48.54	74.00	-25.46	31.15	38.60	19.20	40.84	0.43	--	--	PEAK																																																																																																																																										
2	11650.00	39.97	54.00	-14.03	22.58	38.60	19.20	40.84	0.43	--	--	AVERAGE																																																																																																																																										
3	17475.00	51.43	68.20	-16.77	34.91	40.00	23.77	47.71	0.46	--	--	PEAK																																																																																																																																										






Mode	33	
	Harmonic	
	U-NII-3_5.725-5.85_802.11a_CH165_5825MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL





Mode	34																																																																																																																								
	Band Edge																																																																																																																								
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																																																																								
ANT	1																																																																																																																								
Pol.	Horizontal						Fundamental																																																																																																																		
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5646.11</td><td>51.18</td><td>68.20</td><td>-17.02</td><td>39.73</td><td>33.28</td><td>13.13</td><td>34.96</td><td>0.00 137 101 PEAK</td></tr><tr><td>2</td><td>5650.17</td><td>51.59</td><td>68.33</td><td>-16.74</td><td>40.12</td><td>33.30</td><td>13.13</td><td>34.96</td><td>0.00 137 101 PEAK</td></tr><tr><td>3</td><td>5718.90</td><td>77.09</td><td>110.49</td><td>-33.40</td><td>65.20</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00 137 101 PEAK</td></tr><tr><td>4</td><td>5720.79</td><td>76.47</td><td>112.59</td><td>-36.12</td><td>64.57</td><td>33.68</td><td>13.24</td><td>35.02</td><td>0.00 137 101 PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5646.11	51.18	68.20	-17.02	39.73	33.28	13.13	34.96	0.00 137 101 PEAK	2	5650.17	51.59	68.33	-16.74	40.12	33.30	13.13	34.96	0.00 137 101 PEAK	3	5718.90	77.09	110.49	-33.40	65.20	33.68	13.23	35.02	0.00 137 101 PEAK	4	5720.79	76.47	112.59	-36.12	64.57	33.68	13.24	35.02	0.00 137 101 PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5745.00</td><td>111.04</td><td>-----</td><td>-----</td><td>99.03</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00 137 101 PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5745.00	111.04	-----	-----	99.03	33.78	13.27	35.04	0.00 137 101 PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																
1	5646.11	51.18	68.20	-17.02	39.73	33.28	13.13	34.96	0.00 137 101 PEAK																																																																																																																
2	5650.17	51.59	68.33	-16.74	40.12	33.30	13.13	34.96	0.00 137 101 PEAK																																																																																																																
3	5718.90	77.09	110.49	-33.40	65.20	33.68	13.23	35.02	0.00 137 101 PEAK																																																																																																																
4	5720.79	76.47	112.59	-36.12	64.57	33.68	13.24	35.02	0.00 137 101 PEAK																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																
1	5745.00	111.04	-----	-----	99.03	33.78	13.27	35.04	0.00 137 101 PEAK																																																																																																																
Avg	Blank						 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:0.270kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5745.00</td><td>103.21</td><td>-----</td><td>-----</td><td>91.20</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00 137 101 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5745.00	103.21	-----	-----	91.20	33.78	13.27	35.04	0.00 137 101 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																
1	5745.00	103.21	-----	-----	91.20	33.78	13.27	35.04	0.00 137 101 AVERAGE																																																																																																																





Mode	34																																																																																																															
	Band Edge																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																																																															
ANT	1																																																																																																															
Pol.	Vertical	Fundamental																																																																																																														
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5646.11</td><td>50.09</td><td>68.20</td><td>-18.11</td><td>38.64</td><td>33.28</td><td>13.13</td><td>34.96</td><td>0.00 303 254 PEAK</td></tr><tr><td>2</td><td>5651.62</td><td>51.27</td><td>69.40</td><td>-18.13</td><td>39.79</td><td>33.31</td><td>13.13</td><td>34.96</td><td>0.00 303 254 PEAK</td></tr><tr><td>3</td><td>5719.48</td><td>80.54</td><td>110.65</td><td>-30.11</td><td>68.65</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00 303 254 PEAK</td></tr><tr><td>4</td><td>5728.93</td><td>76.87</td><td>112.92</td><td>-36.05</td><td>64.97</td><td>33.68</td><td>13.24</td><td>35.02</td><td>0.00 303 254 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5646.11	50.09	68.20	-18.11	38.64	33.28	13.13	34.96	0.00 303 254 PEAK	2	5651.62	51.27	69.40	-18.13	39.79	33.31	13.13	34.96	0.00 303 254 PEAK	3	5719.48	80.54	110.65	-30.11	68.65	33.68	13.23	35.02	0.00 303 254 PEAK	4	5728.93	76.87	112.92	-36.05	64.97	33.68	13.24	35.02	0.00 303 254 PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>108.98</td><td>-----</td><td>-----</td><td>96.97</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00 303 254 PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5745.00	108.98	-----	-----	96.97	33.78	13.27	35.04	0.00 303 254 PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1	5646.11	50.09	68.20	-18.11	38.64	33.28	13.13	34.96	0.00 303 254 PEAK																																																																																																							
2	5651.62	51.27	69.40	-18.13	39.79	33.31	13.13	34.96	0.00 303 254 PEAK																																																																																																							
3	5719.48	80.54	110.65	-30.11	68.65	33.68	13.23	35.02	0.00 303 254 PEAK																																																																																																							
4	5728.93	76.87	112.92	-36.05	64.97	33.68	13.24	35.02	0.00 303 254 PEAK																																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1	5745.00	108.98	-----	-----	96.97	33.78	13.27	35.04	0.00 303 254 PEAK																																																																																																							
Avg	Blank	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.270kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>5745.00</td><td>101.44</td><td>-----</td><td>-----</td><td>89.46</td><td>33.76</td><td>13.26</td><td>35.04</td><td>0.00 303 254 AVERAGE</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5745.00	101.44	-----	-----	89.46	33.76	13.26	35.04	0.00 303 254 AVERAGE																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																							
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																							
1	5745.00	101.44	-----	-----	89.46	33.76	13.26	35.04	0.00 303 254 AVERAGE																																																																																																							






Mode	34																																																																													
	Harmonic																																																																													
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz																																																																													
ANT	1																																																																													
Pol.	Horizontal						Vertical																																																																							
Peak Avg																																																																														
	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL						Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL																																																																							
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 11490.00</td><td>50.16</td><td>74.00</td><td>-23.84</td><td>32.57</td><td>38.70</td><td>19.06</td><td>40.61</td><td>0.44</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2 11490.00</td><td>40.49</td><td>54.00</td><td>-13.51</td><td>22.90</td><td>38.70</td><td>19.06</td><td>40.61</td><td>0.44</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3 17235.00</td><td>51.87</td><td>68.20</td><td>-16.33</td><td>34.92</td><td>40.04</td><td>23.62</td><td>47.17</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 11490.00	50.16	74.00	-23.84	32.57	38.70	19.06	40.61	0.44	--	--	PEAK	2 11490.00	40.49	54.00	-13.51	22.90	38.70	19.06	40.61	0.44	--	--	AVERAGE	3 17235.00	51.87	68.20	-16.33	34.92	40.04	23.62	47.17	0.46	--	--	PEAK
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																					
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																						
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																				
1 11490.00	50.16	74.00	-23.84	32.57	38.70	19.06	40.61	0.44	--	--	PEAK																																																																			
2 11490.00	40.49	54.00	-13.51	22.90	38.70	19.06	40.61	0.44	--	--	AVERAGE																																																																			
3 17235.00	51.87	68.20	-16.33	34.92	40.04	23.62	47.17	0.46	--	--	PEAK																																																																			




Mode	34	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH149_Full RU_5745MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL






Mode	35																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5621.83</td><td>50.24</td><td>68.20</td><td>-17.96</td><td>38.95</td><td>33.13</td><td>13.09</td><td>34.93</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr><tr><td>2</td><td>5650.88</td><td>49.95</td><td>68.85</td><td>-18.90</td><td>38.47</td><td>33.31</td><td>13.13</td><td>34.96</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr><tr><td>3</td><td>5714.33</td><td>66.29</td><td>109.21</td><td>-42.92</td><td>54.41</td><td>33.66</td><td>13.23</td><td>35.01</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr><tr><td>4</td><td>5728.07</td><td>62.62</td><td>110.95</td><td>-48.33</td><td>50.73</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5621.83	50.24	68.20	-17.96	38.95	33.13	13.09	34.93	0.00	100	101	PEAK	2	5650.88	49.95	68.85	-18.90	38.47	33.31	13.13	34.96	0.00	100	101	PEAK	3	5714.33	66.29	109.21	-42.92	54.41	33.66	13.23	35.01	0.00	100	101	PEAK	4	5728.07	62.62	110.95	-48.33	50.73	33.68	13.23	35.02	0.00	100	101	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>112.04</td><td>-----</td><td>-----</td><td>99.91</td><td>33.88</td><td>13.33</td><td>35.08</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	112.04	-----	-----	99.91	33.88	13.33	35.08	0.00	100	101
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5621.83	50.24	68.20	-17.96	38.95	33.13	13.09	34.93	0.00	100	101	PEAK																																																																																																																														
2	5650.88	49.95	68.85	-18.90	38.47	33.31	13.13	34.96	0.00	100	101	PEAK																																																																																																																														
3	5714.33	66.29	109.21	-42.92	54.41	33.66	13.23	35.01	0.00	100	101	PEAK																																																																																																																														
4	5728.07	62.62	110.95	-48.33	50.73	33.68	13.23	35.02	0.00	100	101	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	112.04	-----	-----	99.91	33.88	13.33	35.08	0.00	100	101	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:0.270kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>103.87</td><td>-----</td><td>-----</td><td>91.74</td><td>33.88</td><td>13.33</td><td>35.08</td><td>0.00</td><td>100</td><td>101</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	103.87	-----	-----	91.74	33.88	13.33	35.08	0.00	100	101	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	103.87	-----	-----	91.74	33.88	13.33	35.08	0.00	100	101	AVERAGE																																																																																																																														




Mode	35																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																				
ANT	1																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.96</td><td>59.83</td><td>110.89</td><td>-51.06</td><td>47.75</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr><tr><td>2</td><td>5861.07</td><td>60.87</td><td>109.10</td><td>-48.23</td><td>48.79</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr><tr><td>3</td><td>5924.43</td><td>47.76</td><td>68.62</td><td>-20.86</td><td>35.65</td><td>33.80</td><td>13.50</td><td>35.19</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr><tr><td>4</td><td>5937.30</td><td>48.93</td><td>68.20</td><td>-19.27</td><td>36.83</td><td>33.80</td><td>13.51</td><td>35.21</td><td>0.00</td><td>100</td><td>101</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.96	59.83	110.89	-51.06	47.75	33.80	13.42	35.14	0.00	100	101	PEAK	2	5861.07	60.87	109.10	-48.23	48.79	33.80	13.42	35.14	0.00	100	101	PEAK	3	5924.43	47.76	68.62	-20.86	35.65	33.80	13.50	35.19	0.00	100	101	PEAK	4	5937.30	48.93	68.20	-19.27	36.83	33.80	13.51	35.21	0.00	100	101	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.96	59.83	110.89	-51.06	47.75	33.80	13.42	35.14	0.00	100	101	PEAK																																																																									
2	5861.07	60.87	109.10	-48.23	48.79	33.80	13.42	35.14	0.00	100	101	PEAK																																																																									
3	5924.43	47.76	68.62	-20.86	35.65	33.80	13.50	35.19	0.00	100	101	PEAK																																																																									
4	5937.30	48.93	68.20	-19.27	36.83	33.80	13.51	35.21	0.00	100	101	PEAK																																																																									





Mode	35																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5645.88</td><td>49.14</td><td>68.20</td><td>-19.06</td><td>37.69</td><td>33.28</td><td>13.13</td><td>34.96</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr><tr><td>2</td><td>5651.80</td><td>48.21</td><td>69.54</td><td>-21.33</td><td>36.72</td><td>33.31</td><td>13.14</td><td>34.96</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr><tr><td>3</td><td>5718.59</td><td>54.78</td><td>110.40</td><td>-55.62</td><td>42.90</td><td>33.67</td><td>13.23</td><td>35.02</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr><tr><td>4</td><td>5720.07</td><td>50.28</td><td>110.95</td><td>-60.67</td><td>38.39</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5645.88	49.14	68.20	-19.06	37.69	33.28	13.13	34.96	0.00	307	156	PEAK	2	5651.80	48.21	69.54	-21.33	36.72	33.31	13.14	34.96	0.00	307	156	PEAK	3	5718.59	54.78	110.40	-55.62	42.90	33.67	13.23	35.02	0.00	307	156	PEAK	4	5720.07	50.28	110.95	-60.67	38.39	33.68	13.23	35.02	0.00	307	156	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>99.40</td><td>-----</td><td>-----</td><td>87.27</td><td>33.88</td><td>13.33</td><td>35.08</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	99.40	-----	-----	87.27	33.88	13.33	35.08	0.00	307	156
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5645.88	49.14	68.20	-19.06	37.69	33.28	13.13	34.96	0.00	307	156	PEAK																																																																																																																														
2	5651.80	48.21	69.54	-21.33	36.72	33.31	13.14	34.96	0.00	307	156	PEAK																																																																																																																														
3	5718.59	54.78	110.40	-55.62	42.90	33.67	13.23	35.02	0.00	307	156	PEAK																																																																																																																														
4	5720.07	50.28	110.95	-60.67	38.39	33.68	13.23	35.02	0.00	307	156	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	99.40	-----	-----	87.27	33.88	13.33	35.08	0.00	307	156	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.270kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5785.00</td><td>91.44</td><td>-----</td><td>-----</td><td>79.29</td><td>33.89</td><td>13.34</td><td>35.08</td><td>0.00</td><td>307</td><td>156</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5785.00	91.44	-----	-----	79.29	33.89	13.34	35.08	0.00	307	156	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5785.00	91.44	-----	-----	79.29	33.89	13.34	35.08	0.00	307	156	AVERAGE																																																																																																																														





Mode	35																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																				
ANT	1																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.96</td><td>47.49</td><td>110.89</td><td>-63.40</td><td>35.41</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr><tr><td>2</td><td>5872.95</td><td>49.63</td><td>105.77</td><td>-56.14</td><td>37.54</td><td>33.80</td><td>13.44</td><td>35.15</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr><tr><td>3</td><td>5924.43</td><td>47.98</td><td>68.62</td><td>-20.64</td><td>35.87</td><td>33.80</td><td>13.50</td><td>35.19</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr><tr><td>4</td><td>5931.19</td><td>49.64</td><td>68.20</td><td>-18.56</td><td>37.53</td><td>33.80</td><td>13.51</td><td>35.20</td><td>0.00</td><td>307</td><td>156</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.96	47.49	110.89	-63.40	35.41	33.80	13.42	35.14	0.00	307	156	PEAK	2	5872.95	49.63	105.77	-56.14	37.54	33.80	13.44	35.15	0.00	307	156	PEAK	3	5924.43	47.98	68.62	-20.64	35.87	33.80	13.50	35.19	0.00	307	156	PEAK	4	5931.19	49.64	68.20	-18.56	37.53	33.80	13.51	35.20	0.00	307	156	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.96	47.49	110.89	-63.40	35.41	33.80	13.42	35.14	0.00	307	156	PEAK																																																																									
2	5872.95	49.63	105.77	-56.14	37.54	33.80	13.44	35.15	0.00	307	156	PEAK																																																																									
3	5924.43	47.98	68.62	-20.64	35.87	33.80	13.50	35.19	0.00	307	156	PEAK																																																																									
4	5931.19	49.64	68.20	-18.56	37.53	33.80	13.51	35.20	0.00	307	156	PEAK																																																																									






Mode	35																																																																																																																									
	Harmonic																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz																																																																																																																									
ANT	1																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11570.00</td><td>49.89</td><td>74.00</td><td>-24.11</td><td>32.49</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>-- -- PEAK</td></tr><tr><td>2 11570.00</td><td>40.07</td><td>54.00</td><td>-13.93</td><td>22.67</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>-- -- AVERAGE</td></tr><tr><td>3 17355.00</td><td>52.01</td><td>68.20</td><td>-16.19</td><td>35.39</td><td>39.91</td><td>23.69</td><td>47.44</td><td>0.46</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11570.00	49.89	74.00	-24.11	32.49	38.56	19.13	40.72	0.43	-- -- PEAK	2 11570.00	40.07	54.00	-13.93	22.67	38.56	19.13	40.72	0.43	-- -- AVERAGE	3 17355.00	52.01	68.20	-16.19	35.39	39.91	23.69	47.44	0.46	-- -- PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11570.00</td><td>49.90</td><td>74.00</td><td>-24.10</td><td>32.50</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>-- -- PEAK</td></tr><tr><td>2 11570.00</td><td>40.14</td><td>54.00</td><td>-13.86</td><td>22.74</td><td>38.56</td><td>19.13</td><td>40.72</td><td>0.43</td><td>-- -- AVERAGE</td></tr><tr><td>3 17355.00</td><td>52.05</td><td>68.20</td><td>-16.15</td><td>35.43</td><td>39.91</td><td>23.69</td><td>47.44</td><td>0.46</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11570.00	49.90	74.00	-24.10	32.50	38.56	19.13	40.72	0.43	-- -- PEAK	2 11570.00	40.14	54.00	-13.86	22.74	38.56	19.13	40.72	0.43	-- -- AVERAGE	3 17355.00	52.05	68.20	-16.15	35.43	39.91	23.69	47.44	0.46	-- -- PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 11570.00	49.89	74.00	-24.11	32.49	38.56	19.13	40.72	0.43	-- -- PEAK																																																																																																																	
2 11570.00	40.07	54.00	-13.93	22.67	38.56	19.13	40.72	0.43	-- -- AVERAGE																																																																																																																	
3 17355.00	52.01	68.20	-16.19	35.39	39.91	23.69	47.44	0.46	-- -- PEAK																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 11570.00	49.90	74.00	-24.10	32.50	38.56	19.13	40.72	0.43	-- -- PEAK																																																																																																																	
2 11570.00	40.14	54.00	-13.86	22.74	38.56	19.13	40.72	0.43	-- -- AVERAGE																																																																																																																	
3 17355.00	52.05	68.20	-16.15	35.43	39.91	23.69	47.44	0.46	-- -- PEAK																																																																																																																	






Mode	35	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH157_Full RU_5785MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL





Mode	36																																																																																																																																									
	Band Edge																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5854.88</td><td>74.11</td><td>111.08</td><td>-36.97</td><td>62.03</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>100</td><td>96</td><td>PEAK</td></tr><tr><td>2</td><td>5856.38</td><td>73.72</td><td>110.41</td><td>-36.69</td><td>61.64</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>100</td><td>96</td><td>PEAK</td></tr><tr><td>3</td><td>5924.75</td><td>49.68</td><td>68.38</td><td>-18.70</td><td>37.58</td><td>33.80</td><td>13.50</td><td>35.20</td><td>0.00</td><td>100</td><td>96</td><td>PEAK</td></tr><tr><td>4</td><td>5948.13</td><td>49.66</td><td>68.20</td><td>-18.54</td><td>37.55</td><td>33.80</td><td>13.53</td><td>35.22</td><td>0.00</td><td>100</td><td>96</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.88	74.11	111.08	-36.97	62.03	33.80	13.42	35.14	0.00	100	96	PEAK	2	5856.38	73.72	110.41	-36.69	61.64	33.80	13.42	35.14	0.00	100	96	PEAK	3	5924.75	49.68	68.38	-18.70	37.58	33.80	13.50	35.20	0.00	100	96	PEAK	4	5948.13	49.66	68.20	-18.54	37.55	33.80	13.53	35.22	0.00	100	96	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>111.72</td><td>-----</td><td>-----</td><td>99.60</td><td>33.84</td><td>13.39</td><td>35.11</td><td>0.00</td><td>100</td><td>96</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	111.72	-----	-----	99.60	33.84	13.39	35.11	0.00	100	96
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5854.88	74.11	111.08	-36.97	62.03	33.80	13.42	35.14	0.00	100	96	PEAK																																																																																																																														
2	5856.38	73.72	110.41	-36.69	61.64	33.80	13.42	35.14	0.00	100	96	PEAK																																																																																																																														
3	5924.75	49.68	68.38	-18.70	37.58	33.80	13.50	35.20	0.00	100	96	PEAK																																																																																																																														
4	5948.13	49.66	68.20	-18.54	37.55	33.80	13.53	35.22	0.00	100	96	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5825.00	111.72	-----	-----	99.60	33.84	13.39	35.11	0.00	100	96	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
						Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:0.270kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>103.63</td><td>-----</td><td>-----</td><td>91.50</td><td>33.86</td><td>13.37</td><td>35.10</td><td>0.00</td><td>100</td><td>96</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	103.63	-----	-----	91.50	33.86	13.37	35.10	0.00	100	96	AVERAGE																																																																																			
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5825.00	103.63	-----	-----	91.50	33.86	13.37	35.10	0.00	100	96	AVERAGE																																																																																																																														





Mode	36																																																																																																																																									
	Band Edge																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak	 Level (dBuV/m) vs Frequency (MHz) for Vertical polarization. The plot shows a red limit line and a blue signal line. A peak is labeled PEAK_BE(B4)_16-24.						 Level (dBuV/m) vs Frequency (MHz) for Fundamental polarization. The plot shows a red limit line and a blue signal line. A peak is labeled PEAK(UNII).																																																																																																																																			
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5854.63</td><td>50.91</td><td>111.65</td><td>-60.74</td><td>38.82</td><td>33.80</td><td>13.42</td><td>35.13</td><td>0.00</td><td>100</td><td>153</td><td>PEAK</td></tr><tr><td>2</td><td>5874.38</td><td>49.09</td><td>105.37</td><td>-56.28</td><td>37.00</td><td>33.80</td><td>13.44</td><td>35.15</td><td>0.00</td><td>100</td><td>153</td><td>PEAK</td></tr><tr><td>3</td><td>5924.63</td><td>47.98</td><td>68.48</td><td>-20.50</td><td>35.88</td><td>33.80</td><td>13.50</td><td>35.20</td><td>0.00</td><td>100</td><td>153</td><td>PEAK</td></tr><tr><td>4</td><td>5949.38</td><td>49.46</td><td>68.20</td><td>-18.74</td><td>37.35</td><td>33.80</td><td>13.53</td><td>35.22</td><td>0.00</td><td>100</td><td>153</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.63	50.91	111.65	-60.74	38.82	33.80	13.42	35.13	0.00	100	153	PEAK	2	5874.38	49.09	105.37	-56.28	37.00	33.80	13.44	35.15	0.00	100	153	PEAK	3	5924.63	47.98	68.48	-20.50	35.88	33.80	13.50	35.20	0.00	100	153	PEAK	4	5949.38	49.46	68.20	-18.74	37.35	33.80	13.53	35.22	0.00	100	153	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>90.70</td><td>-----</td><td>-----</td><td>78.57</td><td>33.86</td><td>13.37</td><td>35.10</td><td>0.00</td><td>100</td><td>153</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	90.70	-----	-----	78.57	33.86	13.37	35.10	0.00	100	153
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5854.63	50.91	111.65	-60.74	38.82	33.80	13.42	35.13	0.00	100	153	PEAK																																																																																																																														
2	5874.38	49.09	105.37	-56.28	37.00	33.80	13.44	35.15	0.00	100	153	PEAK																																																																																																																														
3	5924.63	47.98	68.48	-20.50	35.88	33.80	13.50	35.20	0.00	100	153	PEAK																																																																																																																														
4	5949.38	49.46	68.20	-18.74	37.35	33.80	13.53	35.22	0.00	100	153	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5825.00	90.70	-----	-----	78.57	33.86	13.37	35.10	0.00	100	153	PEAK																																																																																																																														
Avg	Blank						 Level (dBuV/m) vs Frequency (MHz) for Fundamental polarization. The plot shows a red limit line and a blue signal line. A peak is labeled AVG_54.																																																																																																																																			
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.270kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>83.52</td><td>-----</td><td>-----</td><td>71.39</td><td>33.86</td><td>13.37</td><td>35.10</td><td>0.00</td><td>100</td><td>153</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	83.52	-----	-----	71.39	33.86	13.37	35.10	0.00	100	153	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5825.00	83.52	-----	-----	71.39	33.86	13.37	35.10	0.00	100	153	AVERAGE																																																																																																																														






Mode	36																																																																																																																									
	Harmonic																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz																																																																																																																									
ANT	1																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11650.00</td><td>49.10</td><td>74.00</td><td>-24.90</td><td>31.71</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>-- -- PEAK</td></tr><tr><td>2 11650.00</td><td>40.00</td><td>54.00</td><td>-14.00</td><td>22.61</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>-- -- AVERAGE</td></tr><tr><td>3 17475.00</td><td>51.35</td><td>68.20</td><td>-16.85</td><td>34.83</td><td>40.00</td><td>23.77</td><td>47.71</td><td>0.46</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11650.00	49.10	74.00	-24.90	31.71	38.60	19.20	40.84	0.43	-- -- PEAK	2 11650.00	40.00	54.00	-14.00	22.61	38.60	19.20	40.84	0.43	-- -- AVERAGE	3 17475.00	51.35	68.20	-16.85	34.83	40.00	23.77	47.71	0.46	-- -- PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 11650.00</td><td>48.47</td><td>74.00</td><td>-25.53</td><td>31.08</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>-- -- PEAK</td></tr><tr><td>2 11650.00</td><td>40.00</td><td>54.00</td><td>-14.00</td><td>22.61</td><td>38.60</td><td>19.20</td><td>40.84</td><td>0.43</td><td>-- -- AVERAGE</td></tr><tr><td>3 17475.00</td><td>50.79</td><td>68.20</td><td>-17.41</td><td>34.27</td><td>40.00</td><td>23.77</td><td>47.71</td><td>0.46</td><td>-- -- PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11650.00	48.47	74.00	-25.53	31.08	38.60	19.20	40.84	0.43	-- -- PEAK	2 11650.00	40.00	54.00	-14.00	22.61	38.60	19.20	40.84	0.43	-- -- AVERAGE	3 17475.00	50.79	68.20	-17.41	34.27	40.00	23.77	47.71	0.46	-- -- PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 11650.00	49.10	74.00	-24.90	31.71	38.60	19.20	40.84	0.43	-- -- PEAK																																																																																																																	
2 11650.00	40.00	54.00	-14.00	22.61	38.60	19.20	40.84	0.43	-- -- AVERAGE																																																																																																																	
3 17475.00	51.35	68.20	-16.85	34.83	40.00	23.77	47.71	0.46	-- -- PEAK																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 11650.00	48.47	74.00	-25.53	31.08	38.60	19.20	40.84	0.43	-- -- PEAK																																																																																																																	
2 11650.00	40.00	54.00	-14.00	22.61	38.60	19.20	40.84	0.43	-- -- AVERAGE																																																																																																																	
3 17475.00	50.79	68.20	-17.41	34.27	40.00	23.77	47.71	0.46	-- -- PEAK																																																																																																																	




Mode	36	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE20_CH165_Full RU_5825MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL






Mode	37																																																																																																																																																						
	Band Edge - L																																																																																																																																																						
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																																																																																						
ANT	1																																																																																																																																																						
Pol.	Horizontal						Fundamental																																																																																																																																																
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5649.14</td><td>62.88</td><td>68.20</td><td>-5.32</td><td>51.42</td><td>33.29</td><td>13.13</td><td>34.96</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr><tr><td>2</td><td>5655.34</td><td>65.62</td><td>72.16</td><td>-6.54</td><td>54.11</td><td>33.33</td><td>13.14</td><td>34.96</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr><tr><td>3</td><td>5707.73</td><td>78.31</td><td>107.37</td><td>-29.06</td><td>66.47</td><td>33.63</td><td>13.22</td><td>35.01</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr><tr><td>4</td><td>5728.44</td><td>80.10</td><td>111.79</td><td>-31.69</td><td>68.21</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5649.14	62.88	68.20	-5.32	51.42	33.29	13.13	34.96	0.00	114	103	PEAK	2	5655.34	65.62	72.16	-6.54	54.11	33.33	13.14	34.96	0.00	114	103	PEAK	3	5707.73	78.31	107.37	-29.06	66.47	33.63	13.22	35.01	0.00	114	103	PEAK	4	5728.44	80.10	111.79	-31.69	68.21	33.68	13.23	35.02	0.00	114	103	PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5755.00</td><td>109.52</td><td>-----</td><td>-----</td><td>97.54</td><td>33.76</td><td>13.26</td><td>35.04</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	109.52	-----	-----	97.54	33.76	13.26	35.04	0.00	114	103	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	5649.14	62.88	68.20	-5.32	51.42	33.29	13.13	34.96	0.00	114	103	PEAK																																																																																																																																											
2	5655.34	65.62	72.16	-6.54	54.11	33.33	13.14	34.96	0.00	114	103	PEAK																																																																																																																																											
3	5707.73	78.31	107.37	-29.06	66.47	33.63	13.22	35.01	0.00	114	103	PEAK																																																																																																																																											
4	5728.44	80.10	111.79	-31.69	68.21	33.68	13.23	35.02	0.00	114	103	PEAK																																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	5755.00	109.52	-----	-----	97.54	33.76	13.26	35.04	0.00	114	103	PEAK																																																																																																																																											
Avg	Blank												 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:0.560kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5755.00</td><td>100.93</td><td>-----</td><td>-----</td><td>88.95</td><td>33.76</td><td>13.26</td><td>35.04</td><td>0.00</td><td>114</td><td>103</td><td>AVERAGE</td></tr></tbody></table>													Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	100.93	-----	-----	88.95	33.76	13.26	35.04	0.00	114	103	AVERAGE																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																													
1	5755.00	100.93	-----	-----	88.95	33.76	13.26	35.04	0.00	114	103	AVERAGE																																																																																																																																											




Mode	37																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																				
ANT	1																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5853.28</td><td>64.04</td><td>114.72</td><td>-50.68</td><td>51.96</td><td>33.00</td><td>13.41</td><td>35.13</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr><tr><td>2</td><td>5866.74</td><td>58.93</td><td>107.51</td><td>-48.58</td><td>46.85</td><td>33.00</td><td>13.43</td><td>35.15</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr><tr><td>3</td><td>5922.12</td><td>49.80</td><td>70.33</td><td>-20.53</td><td>37.69</td><td>33.00</td><td>13.50</td><td>35.19</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr><tr><td>4</td><td>5926.60</td><td>50.98</td><td>68.20</td><td>-17.22</td><td>38.88</td><td>33.00</td><td>13.50</td><td>35.20</td><td>0.00</td><td>114</td><td>103</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5853.28	64.04	114.72	-50.68	51.96	33.00	13.41	35.13	0.00	114	103	PEAK	2	5866.74	58.93	107.51	-48.58	46.85	33.00	13.43	35.15	0.00	114	103	PEAK	3	5922.12	49.80	70.33	-20.53	37.69	33.00	13.50	35.19	0.00	114	103	PEAK	4	5926.60	50.98	68.20	-17.22	38.88	33.00	13.50	35.20	0.00	114	103	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																											
1	5853.28	64.04	114.72	-50.68	51.96	33.00	13.41	35.13	0.00	114	103	PEAK																																																																									
2	5866.74	58.93	107.51	-48.58	46.85	33.00	13.43	35.15	0.00	114	103	PEAK																																																																									
3	5922.12	49.80	70.33	-20.53	37.69	33.00	13.50	35.19	0.00	114	103	PEAK																																																																									
4	5926.60	50.98	68.20	-17.22	38.88	33.00	13.50	35.20	0.00	114	103	PEAK																																																																									





Mode	37																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5649.14</td><td>61.12</td><td>68.20</td><td>-7.08</td><td>49.66</td><td>33.29</td><td>13.13</td><td>34.96</td><td>0.00</td><td>300</td><td>248</td><td>PEAK</td></tr><tr><td>2</td><td>5663.40</td><td>69.41</td><td>78.14</td><td>-8.73</td><td>57.85</td><td>33.38</td><td>13.15</td><td>34.97</td><td>0.00</td><td>300</td><td>248</td><td>PEAK</td></tr><tr><td>3</td><td>5704.32</td><td>74.60</td><td>106.41</td><td>-31.81</td><td>62.78</td><td>33.62</td><td>13.21</td><td>35.01</td><td>0.00</td><td>300</td><td>248</td><td>PEAK</td></tr><tr><td>4</td><td>5728.13</td><td>76.61</td><td>111.09</td><td>-34.48</td><td>64.72</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00</td><td>300</td><td>248</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5649.14	61.12	68.20	-7.08	49.66	33.29	13.13	34.96	0.00	300	248	PEAK	2	5663.40	69.41	78.14	-8.73	57.85	33.38	13.15	34.97	0.00	300	248	PEAK	3	5704.32	74.60	106.41	-31.81	62.78	33.62	13.21	35.01	0.00	300	248	PEAK	4	5728.13	76.61	111.09	-34.48	64.72	33.68	13.23	35.02	0.00	300	248	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5755.00</td><td>107.79</td><td>-----</td><td>-----</td><td>95.78</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00</td><td>300</td><td>248</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	107.79	-----	-----	95.78	33.78	13.27	35.04	0.00	300	248
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5649.14	61.12	68.20	-7.08	49.66	33.29	13.13	34.96	0.00	300	248	PEAK																																																																																																																														
2	5663.40	69.41	78.14	-8.73	57.85	33.38	13.15	34.97	0.00	300	248	PEAK																																																																																																																														
3	5704.32	74.60	106.41	-31.81	62.78	33.62	13.21	35.01	0.00	300	248	PEAK																																																																																																																														
4	5728.13	76.61	111.09	-34.48	64.72	33.68	13.23	35.02	0.00	300	248	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5755.00	107.79	-----	-----	95.78	33.78	13.27	35.04	0.00	300	248	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:0.560kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5755.00</td><td>98.87</td><td>-----</td><td>-----</td><td>86.81</td><td>33.82</td><td>13.29</td><td>35.05</td><td>0.00</td><td>300</td><td>248</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	98.87	-----	-----	86.81	33.82	13.29	35.05	0.00	300	248	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor			Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5755.00	98.87	-----	-----	86.81	33.82	13.29	35.05	0.00	300	248	AVERAGE																																																																																																																														





Mode	37																																																																																						
	Band Edge - R																																																																																						
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz																																																																																						
ANT	1																																																																																						
Pol.	Vertical	Fundamental																																																																																					
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.45</td><td>56.24</td><td>112.05</td><td>-55.81</td><td>44.15</td><td>33.00</td><td>13.42</td><td>35.13</td><td>0.00</td><td>300</td><td>240</td><td>PEAK</td></tr><tr><td>2</td><td>5866.54</td><td>56.82</td><td>107.57</td><td>-50.75</td><td>44.74</td><td>33.00</td><td>13.43</td><td>35.15</td><td>0.00</td><td>300</td><td>240</td><td>PEAK</td></tr><tr><td>3</td><td>5924.65</td><td>48.07</td><td>68.46</td><td>-20.39</td><td>35.97</td><td>33.00</td><td>13.50</td><td>35.20</td><td>0.00</td><td>300</td><td>240</td><td>PEAK</td></tr><tr><td>4</td><td>5933.82</td><td>48.54</td><td>68.20</td><td>-19.66</td><td>36.43</td><td>33.00</td><td>13.51</td><td>35.20</td><td>0.00</td><td>300</td><td>240</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5854.45	56.24	112.05	-55.81	44.15	33.00	13.42	35.13	0.00	300	240	PEAK	2	5866.54	56.82	107.57	-50.75	44.74	33.00	13.43	35.15	0.00	300	240	PEAK	3	5924.65	48.07	68.46	-20.39	35.97	33.00	13.50	35.20	0.00	300	240	PEAK	4	5933.82	48.54	68.20	-19.66	36.43	33.00	13.51	35.20	0.00	300	240	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																												
1	5854.45	56.24	112.05	-55.81	44.15	33.00	13.42	35.13	0.00	300	240	PEAK																																																																											
2	5866.54	56.82	107.57	-50.75	44.74	33.00	13.43	35.15	0.00	300	240	PEAK																																																																											
3	5924.65	48.07	68.46	-20.39	35.97	33.00	13.50	35.20	0.00	300	240	PEAK																																																																											
4	5933.82	48.54	68.20	-19.66	36.43	33.00	13.51	35.20	0.00	300	240	PEAK																																																																											






Mode	37										
	Harmonic										
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz										
ANT	1										
Pol.	Horizontal						Vertical				
Peak Avg											
	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL						Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL				




Mode	37	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE40_CH151_Full RU_5755MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL






Mode	38																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Horizontal						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5636.27</td><td>50.79</td><td>68.20</td><td>-17.41</td><td>39.41</td><td>33.22</td><td>13.11</td><td>34.95</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr><tr><td>2</td><td>5650.12</td><td>49.98</td><td>68.29</td><td>-18.31</td><td>38.51</td><td>33.30</td><td>13.13</td><td>34.96</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr><tr><td>3</td><td>5701.21</td><td>64.36</td><td>105.54</td><td>-41.18</td><td>52.55</td><td>33.60</td><td>13.21</td><td>35.00</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr><tr><td>4</td><td>5720.32</td><td>65.28</td><td>111.52</td><td>-46.24</td><td>53.39</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5636.27	50.79	68.20	-17.41	39.41	33.22	13.11	34.95	0.00	100	293	PEAK	2	5650.12	49.98	68.29	-18.31	38.51	33.30	13.13	34.96	0.00	100	293	PEAK	3	5701.21	64.36	105.54	-41.18	52.55	33.60	13.21	35.00	0.00	100	293	PEAK	4	5720.32	65.28	111.52	-46.24	53.39	33.68	13.23	35.02	0.00	100	293	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>107.65</td><td>-----</td><td>-----</td><td>95.54</td><td>33.86</td><td>13.32</td><td>35.07</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	107.65	-----	-----	95.54	33.86	13.32	35.07	0.00	100	293
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5636.27	50.79	68.20	-17.41	39.41	33.22	13.11	34.95	0.00	100	293	PEAK																																																																																																																														
2	5650.12	49.98	68.29	-18.31	38.51	33.30	13.13	34.96	0.00	100	293	PEAK																																																																																																																														
3	5701.21	64.36	105.54	-41.18	52.55	33.60	13.21	35.00	0.00	100	293	PEAK																																																																																																																														
4	5720.32	65.28	111.52	-46.24	53.39	33.68	13.23	35.02	0.00	100	293	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	107.65	-----	-----	95.54	33.86	13.32	35.07	0.00	100	293	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBN:1.100kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>99.12</td><td>-----</td><td>-----</td><td>87.02</td><td>33.85</td><td>13.32</td><td>35.07</td><td>0.00</td><td>100</td><td>293</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Level	Factor	Loss	Factor	Factor		Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	99.12	-----	-----	87.02	33.85	13.32	35.07	0.00	100	293	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																																		
Freq	Level	Line	Level	Factor	Loss	Factor	Factor		Remark																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	99.12	-----	-----	87.02	33.85	13.32	35.07	0.00	100	293	AVERAGE																																																																																																																														




Mode	38																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																				
ANT	1																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.83</td><td>70.87</td><td>111.19</td><td>-40.32</td><td>58.79</td><td>33.80</td><td>13.42</td><td>35.14</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr><tr><td>2</td><td>5865.84</td><td>70.12</td><td>107.76</td><td>-37.64</td><td>58.03</td><td>33.80</td><td>13.43</td><td>35.14</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr><tr><td>3</td><td>5923.19</td><td>53.20</td><td>69.54</td><td>-16.34</td><td>41.09</td><td>33.80</td><td>13.50</td><td>35.19</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr><tr><td>4</td><td>5925.20</td><td>51.37</td><td>68.20</td><td>-16.83</td><td>39.27</td><td>33.80</td><td>13.50</td><td>35.20</td><td>0.00</td><td>100</td><td>293</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.83	70.87	111.19	-40.32	58.79	33.80	13.42	35.14	0.00	100	293	PEAK	2	5865.84	70.12	107.76	-37.64	58.03	33.80	13.43	35.14	0.00	100	293	PEAK	3	5923.19	53.20	69.54	-16.34	41.09	33.80	13.50	35.19	0.00	100	293	PEAK	4	5925.20	51.37	68.20	-16.83	39.27	33.80	13.50	35.20	0.00	100	293	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.83	70.87	111.19	-40.32	58.79	33.80	13.42	35.14	0.00	100	293	PEAK																																																																									
2	5865.84	70.12	107.76	-37.64	58.03	33.80	13.43	35.14	0.00	100	293	PEAK																																																																									
3	5923.19	53.20	69.54	-16.34	41.09	33.80	13.50	35.19	0.00	100	293	PEAK																																																																									
4	5925.20	51.37	68.20	-16.83	39.27	33.80	13.50	35.20	0.00	100	293	PEAK																																																																									





Mode	38																																																																																																																																									
	Band Edge - L																																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																																																																									
ANT	1																																																																																																																																									
Pol.	Vertical						Fundamental																																																																																																																																			
Peak																																																																																																																																										
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5638.81</td><td>50.57</td><td>68.20</td><td>-17.63</td><td>39.17</td><td>33.23</td><td>13.12</td><td>34.95</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr><tr><td>2</td><td>5651.87</td><td>52.44</td><td>69.59</td><td>-17.15</td><td>40.95</td><td>33.31</td><td>13.14</td><td>34.96</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr><tr><td>3</td><td>5703.55</td><td>65.82</td><td>106.19</td><td>-40.37</td><td>54.01</td><td>33.61</td><td>13.21</td><td>35.01</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr><tr><td>4</td><td>5720.32</td><td>64.99</td><td>111.52</td><td>-46.53</td><td>53.10</td><td>33.68</td><td>13.23</td><td>35.02</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5638.81	50.57	68.20	-17.63	39.17	33.23	13.12	34.95	0.00	307	257	PEAK	2	5651.87	52.44	69.59	-17.15	40.95	33.31	13.14	34.96	0.00	307	257	PEAK	3	5703.55	65.82	106.19	-40.37	54.01	33.61	13.21	35.01	0.00	307	257	PEAK	4	5720.32	64.99	111.52	-46.53	53.10	33.68	13.23	35.02	0.00	307	257	PEAK	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>108.67</td><td>-----</td><td>-----</td><td>96.53</td><td>33.88</td><td>13.36</td><td>35.10</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	108.67	-----	-----	96.53	33.88	13.36	35.10	0.00	307	257
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5638.81	50.57	68.20	-17.63	39.17	33.23	13.12	34.95	0.00	307	257	PEAK																																																																																																																														
2	5651.87	52.44	69.59	-17.15	40.95	33.31	13.14	34.96	0.00	307	257	PEAK																																																																																																																														
3	5703.55	65.82	106.19	-40.37	54.01	33.61	13.21	35.01	0.00	307	257	PEAK																																																																																																																														
4	5720.32	64.99	111.52	-46.53	53.10	33.68	13.23	35.02	0.00	307	257	PEAK																																																																																																																														
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	108.67	-----	-----	96.53	33.88	13.36	35.10	0.00	307	257	PEAK																																																																																																																														
Avg	Blank																																																																																																																																									
							Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:1.100kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>100.31</td><td>-----</td><td>-----</td><td>88.15</td><td>33.89</td><td>13.36</td><td>35.09</td><td>0.00</td><td>307</td><td>257</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	100.31	-----	-----	88.15	33.89	13.36	35.09	0.00	307	257	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																
1	5795.00	100.31	-----	-----	88.15	33.89	13.36	35.09	0.00	307	257	AVERAGE																																																																																																																														





Mode	38																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																				
ANT	1																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.21</td><td>72.00</td><td>112.60</td><td>-40.60</td><td>59.91</td><td>33.00</td><td>13.42</td><td>35.13</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr><tr><td>2</td><td>5857.47</td><td>75.65</td><td>110.11</td><td>-34.46</td><td>63.57</td><td>33.00</td><td>13.42</td><td>35.14</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr><tr><td>3</td><td>5924.74</td><td>48.41</td><td>68.40</td><td>-19.99</td><td>36.31</td><td>33.00</td><td>13.50</td><td>35.20</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr><tr><td>4</td><td>5944.27</td><td>49.82</td><td>68.20</td><td>-18.38</td><td>37.71</td><td>33.00</td><td>13.52</td><td>35.21</td><td>0.00</td><td>307</td><td>257</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.21	72.00	112.60	-40.60	59.91	33.00	13.42	35.13	0.00	307	257	PEAK	2	5857.47	75.65	110.11	-34.46	63.57	33.00	13.42	35.14	0.00	307	257	PEAK	3	5924.74	48.41	68.40	-19.99	36.31	33.00	13.50	35.20	0.00	307	257	PEAK	4	5944.27	49.82	68.20	-18.38	37.71	33.00	13.52	35.21	0.00	307	257	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.21	72.00	112.60	-40.60	59.91	33.00	13.42	35.13	0.00	307	257	PEAK																																																																									
2	5857.47	75.65	110.11	-34.46	63.57	33.00	13.42	35.14	0.00	307	257	PEAK																																																																									
3	5924.74	48.41	68.40	-19.99	36.31	33.00	13.50	35.20	0.00	307	257	PEAK																																																																									
4	5944.27	49.82	68.20	-18.38	37.71	33.00	13.52	35.21	0.00	307	257	PEAK																																																																									






Mode	38																																																																																																																									
	Harmonic																																																																																																																									
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz																																																																																																																									
ANT	1																																																																																																																									
Pol.	Horizontal	Vertical																																																																																																																								
Peak Avg	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 11590.00</td><td>50.54</td><td>74.00</td><td>-23.46</td><td>33.19</td><td>38.52</td><td>19.15</td><td>40.75</td><td>0.43</td><td>-- -- PEAK</td></tr><tr><td>2 11590.00</td><td>40.30</td><td>54.00</td><td>-13.70</td><td>22.95</td><td>38.52</td><td>19.15</td><td>40.75</td><td>0.43</td><td>-- -- AVERAGE</td></tr><tr><td>3 17385.00</td><td>51.40</td><td>68.20</td><td>-16.80</td><td>34.77</td><td>39.97</td><td>23.71</td><td>47.51</td><td>0.46</td><td>-- -- PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11590.00	50.54	74.00	-23.46	33.19	38.52	19.15	40.75	0.43	-- -- PEAK	2 11590.00	40.30	54.00	-13.70	22.95	38.52	19.15	40.75	0.43	-- -- AVERAGE	3 17385.00	51.40	68.20	-16.80	34.77	39.97	23.71	47.51	0.46	-- -- PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1 11590.00</td><td>49.78</td><td>74.00</td><td>-24.22</td><td>32.43</td><td>38.52</td><td>19.15</td><td>40.75</td><td>0.43</td><td>-- -- PEAK</td></tr><tr><td>2 11590.00</td><td>40.32</td><td>54.00</td><td>-13.68</td><td>22.97</td><td>38.52</td><td>19.15</td><td>40.75</td><td>0.43</td><td>-- -- AVERAGE</td></tr><tr><td>3 17385.00</td><td>51.81</td><td>68.20</td><td>-16.39</td><td>35.18</td><td>39.97</td><td>23.71</td><td>47.51</td><td>0.46</td><td>-- -- PEAK</td></tr></tbody></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 11590.00	49.78	74.00	-24.22	32.43	38.52	19.15	40.75	0.43	-- -- PEAK	2 11590.00	40.32	54.00	-13.68	22.97	38.52	19.15	40.75	0.43	-- -- AVERAGE	3 17385.00	51.81	68.20	-16.39	35.18	39.97	23.71	47.51	0.46	-- -- PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 11590.00	50.54	74.00	-23.46	33.19	38.52	19.15	40.75	0.43	-- -- PEAK																																																																																																																	
2 11590.00	40.30	54.00	-13.70	22.95	38.52	19.15	40.75	0.43	-- -- AVERAGE																																																																																																																	
3 17385.00	51.40	68.20	-16.80	34.77	39.97	23.71	47.51	0.46	-- -- PEAK																																																																																																																	
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																	
1 11590.00	49.78	74.00	-24.22	32.43	38.52	19.15	40.75	0.43	-- -- PEAK																																																																																																																	
2 11590.00	40.32	54.00	-13.68	22.97	38.52	19.15	40.75	0.43	-- -- AVERAGE																																																																																																																	
3 17385.00	51.81	68.20	-16.39	35.18	39.97	23.71	47.51	0.46	-- -- PEAK																																																																																																																	




Mode	38	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE40_CH159_Full RU_5795MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL






Mode	39																																																																																																																															
	Band Edge - L																																																																																																																															
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																															
ANT	1																																																																																																																															
Pol.	Horizontal	Fundamental																																																																																																																														
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5645.85</td><td>63.71</td><td>68.20</td><td>-4.49</td><td>52.26</td><td>33.28</td><td>13.13</td><td>34.96</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr><tr><td>2</td><td>5650.05</td><td>62.20</td><td>68.24</td><td>-6.04</td><td>50.73</td><td>33.30</td><td>13.13</td><td>34.96</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr><tr><td>3</td><td>5700.63</td><td>76.43</td><td>105.38</td><td>-28.95</td><td>64.62</td><td>33.60</td><td>13.21</td><td>35.00</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr><tr><td>4</td><td>5720.93</td><td>79.16</td><td>112.91</td><td>-33.75</td><td>67.26</td><td>33.68</td><td>13.24</td><td>35.02</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5645.85	63.71	68.20	-4.49	52.26	33.28	13.13	34.96	0.00	122	103	PEAK	2	5650.05	62.20	68.24	-6.04	50.73	33.30	13.13	34.96	0.00	122	103	PEAK	3	5700.63	76.43	105.38	-28.95	64.62	33.60	13.21	35.00	0.00	122	103	PEAK	4	5720.93	79.16	112.91	-33.75	67.26	33.68	13.24	35.02	0.00	122	103	PEAK	 Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>105.32</td><td>-----</td><td>-----</td><td>93.29</td><td>33.80</td><td>13.28</td><td>35.05</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5775.00	105.32	-----	-----	93.29	33.80	13.28	35.05	0.00	122	103	PEAK
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																						
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																							
1	5645.85	63.71	68.20	-4.49	52.26	33.28	13.13	34.96	0.00	122	103	PEAK																																																																																																																				
2	5650.05	62.20	68.24	-6.04	50.73	33.30	13.13	34.96	0.00	122	103	PEAK																																																																																																																				
3	5700.63	76.43	105.38	-28.95	64.62	33.60	13.21	35.00	0.00	122	103	PEAK																																																																																																																				
4	5720.93	79.16	112.91	-33.75	67.26	33.68	13.24	35.02	0.00	122	103	PEAK																																																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5775.00	105.32	-----	-----	93.29	33.80	13.28	35.05	0.00	122	103	PEAK																																																																																																																				
Avg	Blank	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:1.100kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>97.45</td><td>-----</td><td>-----</td><td>85.39</td><td>33.82</td><td>13.29</td><td>35.05</td><td>0.00</td><td>122</td><td>103</td><td>AVERAGE</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	5775.00	97.45	-----	-----	85.39	33.82	13.29	35.05	0.00	122	103	AVERAGE																																																																																		
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																							
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																						
1	5775.00	97.45	-----	-----	85.39	33.82	13.29	35.05	0.00	122	103	AVERAGE																																																																																																																				




Mode	39																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																				
ANT	1																																																																																				
Pol.	Horizontal	Fundamental																																																																																			
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.45</td><td>74.65</td><td>112.05</td><td>-37.40</td><td>62.56</td><td>33.80</td><td>13.42</td><td>35.13</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr><tr><td>2</td><td>5869.85</td><td>71.57</td><td>106.64</td><td>-35.07</td><td>59.49</td><td>33.80</td><td>13.43</td><td>35.15</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr><tr><td>3</td><td>5924.98</td><td>50.37</td><td>68.22</td><td>-17.85</td><td>38.27</td><td>33.80</td><td>13.50</td><td>35.20</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr><tr><td>4</td><td>5928.13</td><td>51.13</td><td>68.20</td><td>-17.07</td><td>39.03</td><td>33.80</td><td>13.50</td><td>35.20</td><td>0.00</td><td>122</td><td>103</td><td>PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.45	74.65	112.05	-37.40	62.56	33.80	13.42	35.13	0.00	122	103	PEAK	2	5869.85	71.57	106.64	-35.07	59.49	33.80	13.43	35.15	0.00	122	103	PEAK	3	5924.98	50.37	68.22	-17.85	38.27	33.80	13.50	35.20	0.00	122	103	PEAK	4	5928.13	51.13	68.20	-17.07	39.03	33.80	13.50	35.20	0.00	122	103	PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																												
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.45	74.65	112.05	-37.40	62.56	33.80	13.42	35.13	0.00	122	103	PEAK																																																																									
2	5869.85	71.57	106.64	-35.07	59.49	33.80	13.43	35.15	0.00	122	103	PEAK																																																																									
3	5924.98	50.37	68.22	-17.85	38.27	33.80	13.50	35.20	0.00	122	103	PEAK																																																																									
4	5928.13	51.13	68.20	-17.07	39.03	33.80	13.50	35.20	0.00	122	103	PEAK																																																																									





Mode	39																																																																																																																																							
	Band Edge - L																																																																																																																																							
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																							
ANT	1																																																																																																																																							
Pol.	Vertical						Fundamental																																																																																																																																	
Peak																																																																																																																																								
	Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto						Site : 03CH21-HY Condition: PEAK(UNI) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto																																																																																																																																	
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5641.48</td><td>62.69</td><td>68.20</td><td>-5.51</td><td>51.27</td><td>33.25</td><td>13.12</td><td>34.95</td><td>0.00</td><td>300</td><td>254</td><td>PEAK</td></tr><tr><td>2</td><td>5657.23</td><td>67.31</td><td>73.57</td><td>-6.26</td><td>55.80</td><td>33.34</td><td>13.14</td><td>34.97</td><td>0.00</td><td>300</td><td>254</td><td>PEAK</td></tr><tr><td>3</td><td>5701.68</td><td>75.55</td><td>105.67</td><td>-30.12</td><td>63.73</td><td>33.61</td><td>13.21</td><td>35.00</td><td>0.00</td><td>300</td><td>254</td><td>PEAK</td></tr><tr><td>4</td><td>5720.93</td><td>76.58</td><td>112.91</td><td>-36.33</td><td>64.68</td><td>33.68</td><td>13.24</td><td>35.02</td><td>0.00</td><td>300</td><td>254</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5641.48	62.69	68.20	-5.51	51.27	33.25	13.12	34.95	0.00	300	254	PEAK	2	5657.23	67.31	73.57	-6.26	55.80	33.34	13.14	34.97	0.00	300	254	PEAK	3	5701.68	75.55	105.67	-30.12	63.73	33.61	13.21	35.00	0.00	300	254	PEAK	4	5720.93	76.58	112.91	-36.33	64.68	33.68	13.24	35.02	0.00	300	254	PEAK	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>105.27</td><td>-----</td><td>-----</td><td>93.26</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00</td><td>300</td><td>254</td><td>PEAK</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	105.27	-----	-----	93.26	33.78	13.27	35.04	0.00	300	254
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																															
1	5641.48	62.69	68.20	-5.51	51.27	33.25	13.12	34.95	0.00	300	254	PEAK																																																																																																																												
2	5657.23	67.31	73.57	-6.26	55.80	33.34	13.14	34.97	0.00	300	254	PEAK																																																																																																																												
3	5701.68	75.55	105.67	-30.12	63.73	33.61	13.21	35.00	0.00	300	254	PEAK																																																																																																																												
4	5720.93	76.58	112.91	-36.33	64.68	33.68	13.24	35.02	0.00	300	254	PEAK																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																															
1	5775.00	105.27	-----	-----	93.26	33.78	13.27	35.04	0.00	300	254	PEAK																																																																																																																												
Avg	Blank																																																																																																																																							
	Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBN:1.100kHz SMT:Auto						Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBN:1.100kHz SMT:Auto																																																																																																																																	
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>95.93</td><td>-----</td><td>-----</td><td>83.92</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00</td><td>300</td><td>254</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	95.93	-----	-----	83.92	33.78	13.27	35.04	0.00	300	254	AVERAGE	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5775.00</td><td>95.93</td><td>-----</td><td>-----</td><td>83.92</td><td>33.78</td><td>13.27</td><td>35.04</td><td>0.00</td><td>300</td><td>254</td><td>AVERAGE</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	95.93	-----	-----	83.92	33.78	13.27	35.04	0.00	300	254	AVERAGE																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																															
1	5775.00	95.93	-----	-----	83.92	33.78	13.27	35.04	0.00	300	254	AVERAGE																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																															
1	5775.00	95.93	-----	-----	83.92	33.78	13.27	35.04	0.00	300	254	AVERAGE																																																																																																																												





Mode	39																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																							
ANT	1																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	 Site : 03CH21-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C03A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>5854.45</td><td>69.16</td><td>112.05</td><td>-42.89</td><td>57.07</td><td>33.00</td><td>13.42</td><td>35.13</td><td>0.00 300 254 PEAK</td></tr><tr><td>2</td><td>5866.70</td><td>71.68</td><td>107.52</td><td>-35.84</td><td>59.60</td><td>33.00</td><td>13.43</td><td>35.15</td><td>0.00 300 254 PEAK</td></tr><tr><td>3</td><td>5924.45</td><td>49.15</td><td>68.61</td><td>-19.46</td><td>37.05</td><td>33.00</td><td>13.50</td><td>35.20</td><td>0.00 300 254 PEAK</td></tr><tr><td>4</td><td>5937.23</td><td>49.23</td><td>68.20</td><td>-18.97</td><td>37.13</td><td>33.00</td><td>13.51</td><td>35.21</td><td>0.00 300 254 PEAK</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	5854.45	69.16	112.05	-42.89	57.07	33.00	13.42	35.13	0.00 300 254 PEAK	2	5866.70	71.68	107.52	-35.84	59.60	33.00	13.43	35.15	0.00 300 254 PEAK	3	5924.45	49.15	68.61	-19.46	37.05	33.00	13.50	35.20	0.00 300 254 PEAK	4	5937.23	49.23	68.20	-18.97	37.13	33.00	13.51	35.21	0.00 300 254 PEAK	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																															
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1	5854.45	69.16	112.05	-42.89	57.07	33.00	13.42	35.13	0.00 300 254 PEAK																																																															
2	5866.70	71.68	107.52	-35.84	59.60	33.00	13.43	35.15	0.00 300 254 PEAK																																																															
3	5924.45	49.15	68.61	-19.46	37.05	33.00	13.50	35.20	0.00 300 254 PEAK																																																															
4	5937.23	49.23	68.20	-18.97	37.13	33.00	13.51	35.21	0.00 300 254 PEAK																																																															





Mode	39																																																																																																																																																					
	Harmonic																																																																																																																																																					
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																																					
ANT	1																																																																																																																																																					
Pol.	Horizontal						Vertical																																																																																																																																															
Peak Avg																																																																																																																																																						
	Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL						Site : 03CH21-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C03A18EN_230712 VERTICAL																																																																																																																																															
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11550.00</td><td>50.63</td><td>74.00</td><td>-23.37</td><td>33.18</td><td>38.60</td><td>19.11</td><td>40.69</td><td>0.43</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>11550.00</td><td>40.91</td><td>54.00</td><td>-13.09</td><td>23.46</td><td>38.60</td><td>19.11</td><td>40.69</td><td>0.43</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>17325.00</td><td>51.88</td><td>68.20</td><td>-16.32</td><td>35.17</td><td>39.95</td><td>23.67</td><td>47.37</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11550.00	50.63	74.00	-23.37	33.18	38.60	19.11	40.69	0.43	--	--	PEAK	2	11550.00	40.91	54.00	-13.09	23.46	38.60	19.11	40.69	0.43	--	--	AVERAGE	3	17325.00	51.88	68.20	-16.32	35.17	39.95	23.67	47.37	0.46	--	--	PEAK	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>11550.00</td><td>49.99</td><td>74.00</td><td>-24.01</td><td>32.54</td><td>38.60</td><td>19.11</td><td>40.69</td><td>0.43</td><td>--</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>11550.00</td><td>40.86</td><td>54.00</td><td>-13.14</td><td>23.41</td><td>38.60</td><td>19.11</td><td>40.69</td><td>0.43</td><td>--</td><td>--</td><td>AVERAGE</td></tr><tr><td>3</td><td>17325.00</td><td>51.48</td><td>68.20</td><td>-16.72</td><td>34.77</td><td>39.95</td><td>23.67</td><td>47.37</td><td>0.46</td><td>--</td><td>--</td><td>PEAK</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	11550.00	49.99	74.00	-24.01	32.54	38.60	19.11	40.69	0.43	--	--	PEAK	2	11550.00	40.86	54.00	-13.14	23.41	38.60	19.11	40.69	0.43	--	--	AVERAGE	3	17325.00	51.48	68.20	-16.72	34.77	39.95	23.67	47.37	0.46	--	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	11550.00	50.63	74.00	-23.37	33.18	38.60	19.11	40.69	0.43	--	--	PEAK																																																																																																																																										
2	11550.00	40.91	54.00	-13.09	23.46	38.60	19.11	40.69	0.43	--	--	AVERAGE																																																																																																																																										
3	17325.00	51.88	68.20	-16.32	35.17	39.95	23.67	47.37	0.46	--	--	PEAK																																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																												
1	11550.00	49.99	74.00	-24.01	32.54	38.60	19.11	40.69	0.43	--	--	PEAK																																																																																																																																										
2	11550.00	40.86	54.00	-13.14	23.41	38.60	19.11	40.69	0.43	--	--	AVERAGE																																																																																																																																										
3	17325.00	51.48	68.20	-16.72	34.77	39.95	23.67	47.37	0.46	--	--	PEAK																																																																																																																																										





Mode	39	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 HORIZONTAL	 Site : 03CH21-HY Condition: AVG_54 3m DRH18-E_LE2C03A18EN_230712 VERTICAL



Mode	40																																																																																																																																
	SHF																																																																																																																																
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																
ANT	1																																																																																																																																
Pol.	Horizontal					Vertical																																																																																																																											
Peak																																																																																																																																	
	Site : 03CH21-HY Condition: PEAK_74 1m 88HA9170_1223_230710 HORIZONTAL					Site : 03CH21-HY Condition: PEAK_74 1m 88HA9170_1223_230710 VERTICAL																																																																																																																											
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 25242.21</td><td>40.47</td><td>74.00</td><td>-33.53</td><td>42.13</td><td>39.23</td><td>29.05</td><td>60.40</td><td>-9.54</td><td>-- -- PEAK</td></tr><tr><td>2 39505.22</td><td>50.39</td><td>74.00</td><td>-23.61</td><td>39.00</td><td>44.95</td><td>36.58</td><td>60.60</td><td>-9.54</td><td>188 256 PEAK</td></tr><tr><td>3 39505.22</td><td>40.28</td><td>54.00</td><td>-13.72</td><td>28.90</td><td>44.94</td><td>36.58</td><td>60.60</td><td>-9.54</td><td>188 256 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 25242.21	40.47	74.00	-33.53	42.13	39.23	29.05	60.40	-9.54	-- -- PEAK	2 39505.22	50.39	74.00	-23.61	39.00	44.95	36.58	60.60	-9.54	188 256 PEAK	3 39505.22	40.28	54.00	-13.72	28.90	44.94	36.58	60.60	-9.54	188 256 AVERAGE	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 19540.53</td><td>39.11</td><td>74.00</td><td>-34.89</td><td>40.36</td><td>38.19</td><td>25.25</td><td>63.15</td><td>-9.54</td><td>-- -- PEAK</td></tr><tr><td>2 39571.59</td><td>49.39</td><td>74.00</td><td>-24.61</td><td>37.96</td><td>44.97</td><td>36.59</td><td>60.59</td><td>-9.54</td><td>102 220 PEAK</td></tr><tr><td>3 39571.59</td><td>40.20</td><td>54.00</td><td>-13.80</td><td>28.76</td><td>44.98</td><td>36.59</td><td>60.59</td><td>-9.54</td><td>102 220 AVERAGE</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 19540.53	39.11	74.00	-34.89	40.36	38.19	25.25	63.15	-9.54	-- -- PEAK	2 39571.59	49.39	74.00	-24.61	37.96	44.97	36.59	60.59	-9.54	102 220 PEAK	3 39571.59	40.20	54.00	-13.80	28.76	44.98	36.59	60.59	-9.54
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																								
1 25242.21	40.47	74.00	-33.53	42.13	39.23	29.05	60.40	-9.54	-- -- PEAK																																																																																																																								
2 39505.22	50.39	74.00	-23.61	39.00	44.95	36.58	60.60	-9.54	188 256 PEAK																																																																																																																								
3 39505.22	40.28	54.00	-13.72	28.90	44.94	36.58	60.60	-9.54	188 256 AVERAGE																																																																																																																								
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	Remark																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																								
1 19540.53	39.11	74.00	-34.89	40.36	38.19	25.25	63.15	-9.54	-- -- PEAK																																																																																																																								
2 39571.59	49.39	74.00	-24.61	37.96	44.97	36.59	60.59	-9.54	102 220 PEAK																																																																																																																								
3 39571.59	40.20	54.00	-13.80	28.76	44.98	36.59	60.59	-9.54	102 220 AVERAGE																																																																																																																								





Mode	41																																																																																																																																																																																																		
	LF																																																																																																																																																																																																		
	U-NII-3_5.725-5.85_802.11ax HE80_CH155_Full RU_5775MHz																																																																																																																																																																																																		
ANT	1																																																																																																																																																																																																		
Pol.	Horizontal								Vertical																																																																																																																																																																																										
QP/ Peak																																																																																																																																																																																																			
	Site : 03CH21-HY Condition: QP 3m LF_633038001_231015 HORIZONTAL								Site : 03CH21-HY Condition: QP 3m LF_633038001_231015 VERTICAL																																																																																																																																																																																										
	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>72.68</td><td>33.90</td><td>40.00</td><td>-6.10</td><td>52.25</td><td>12.88</td><td>1.44</td><td>32.72</td><td>0.05 -- Peak</td></tr><tr><td>2</td><td>96.93</td><td>24.64</td><td>43.50</td><td>-18.86</td><td>39.72</td><td>15.86</td><td>1.69</td><td>32.69</td><td>0.06 100 86 QP</td></tr><tr><td>3</td><td>243.40</td><td>30.08</td><td>46.00</td><td>-15.92</td><td>42.46</td><td>17.58</td><td>2.67</td><td>32.74</td><td>0.11 -- Peak</td></tr><tr><td>4</td><td>284.14</td><td>31.64</td><td>46.00</td><td>-14.36</td><td>42.58</td><td>18.86</td><td>2.89</td><td>32.77</td><td>0.08 -- Peak</td></tr><tr><td>5</td><td>628.49</td><td>31.84</td><td>46.00</td><td>-14.16</td><td>34.14</td><td>26.31</td><td>4.30</td><td>33.02</td><td>0.11 -- Peak</td></tr><tr><td>6</td><td>816.67</td><td>33.24</td><td>46.00</td><td>-12.76</td><td>32.64</td><td>28.17</td><td>4.88</td><td>32.63</td><td>0.18 -- Peak</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	72.68	33.90	40.00	-6.10	52.25	12.88	1.44	32.72	0.05 -- Peak	2	96.93	24.64	43.50	-18.86	39.72	15.86	1.69	32.69	0.06 100 86 QP	3	243.40	30.08	46.00	-15.92	42.46	17.58	2.67	32.74	0.11 -- Peak	4	284.14	31.64	46.00	-14.36	42.58	18.86	2.89	32.77	0.08 -- Peak	5	628.49	31.84	46.00	-14.16	34.14	26.31	4.30	33.02	0.11 -- Peak	6	816.67	33.24	46.00	-12.76	32.64	28.17	4.88	32.63	0.18 -- Peak	<table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr></thead><tbody><tr><td>1</td><td>72.68</td><td>32.53</td><td>40.00</td><td>-7.47</td><td>50.88</td><td>12.88</td><td>1.44</td><td>32.72</td><td>0.05 100 334 QP</td></tr><tr><td>2</td><td>96.93</td><td>34.23</td><td>43.50</td><td>-9.27</td><td>49.31</td><td>15.86</td><td>1.69</td><td>32.69</td><td>0.06 100 114 QP</td></tr><tr><td>3</td><td>270.56</td><td>28.54</td><td>46.00</td><td>-17.46</td><td>39.33</td><td>19.05</td><td>2.82</td><td>32.76</td><td>0.10 -- Peak</td></tr><tr><td>4</td><td>276.38</td><td>29.41</td><td>46.00</td><td>-16.59</td><td>40.49</td><td>18.74</td><td>2.85</td><td>32.76</td><td>0.09 -- Peak</td></tr><tr><td>5</td><td>628.49</td><td>35.76</td><td>46.00</td><td>-10.24</td><td>38.06</td><td>26.31</td><td>4.30</td><td>33.02</td><td>0.11 -- Peak</td></tr><tr><td>6</td><td>950.53</td><td>35.01</td><td>46.00</td><td>-10.99</td><td>30.09</td><td>31.07</td><td>5.26</td><td>31.63</td><td>0.22 -- Peak</td></tr></tbody></table>									Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	72.68	32.53	40.00	-7.47	50.88	12.88	1.44	32.72	0.05 100 334 QP	2	96.93	34.23	43.50	-9.27	49.31	15.86	1.69	32.69	0.06 100 114 QP	3	270.56	28.54	46.00	-17.46	39.33	19.05	2.82	32.76	0.10 -- Peak	4	276.38	29.41	46.00	-16.59	40.49	18.74	2.85	32.76	0.09 -- Peak	5	628.49	35.76	46.00	-10.24	38.06	26.31	4.30	33.02	0.11 -- Peak	6	950.53	35.01	46.00	-10.99	30.09	31.07	5.26	31.63
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																										
1	72.68	33.90	40.00	-6.10	52.25	12.88	1.44	32.72	0.05 -- Peak																																																																																																																																																																																										
2	96.93	24.64	43.50	-18.86	39.72	15.86	1.69	32.69	0.06 100 86 QP																																																																																																																																																																																										
3	243.40	30.08	46.00	-15.92	42.46	17.58	2.67	32.74	0.11 -- Peak																																																																																																																																																																																										
4	284.14	31.64	46.00	-14.36	42.58	18.86	2.89	32.77	0.08 -- Peak																																																																																																																																																																																										
5	628.49	31.84	46.00	-14.16	34.14	26.31	4.30	33.02	0.11 -- Peak																																																																																																																																																																																										
6	816.67	33.24	46.00	-12.76	32.64	28.17	4.88	32.63	0.18 -- Peak																																																																																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																											
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																										
1	72.68	32.53	40.00	-7.47	50.88	12.88	1.44	32.72	0.05 100 334 QP																																																																																																																																																																																										
2	96.93	34.23	43.50	-9.27	49.31	15.86	1.69	32.69	0.06 100 114 QP																																																																																																																																																																																										
3	270.56	28.54	46.00	-17.46	39.33	19.05	2.82	32.76	0.10 -- Peak																																																																																																																																																																																										
4	276.38	29.41	46.00	-16.59	40.49	18.74	2.85	32.76	0.09 -- Peak																																																																																																																																																																																										
5	628.49	35.76	46.00	-10.24	38.06	26.31	4.30	33.02	0.11 -- Peak																																																																																																																																																																																										
6	950.53	35.01	46.00	-10.99	30.09	31.07	5.26	31.63	0.22 -- Peak																																																																																																																																																																																										



Appendix D. Duty Cycle Plots

<For Radiated Spurious Emission test>

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
1	802.11a	97.08	5490	0.18	200Hz
1	5GHz 802.11ax HE20 Full RU	91.52	3885	0.26	270Hz
1	5GHz 802.11ax HE40 Full RU	92.49	1970	0.51	560Hz
1	5GHz 802.11ax HE80 Full RU	72.66	970	1.03	1.1kHz





<For Conducted test>

Antenna	Band	Duty Cycle(%)	T(us)	Duty Factor(dB)
1	802.11a	96.82	5480	0.14
1	5GHz 802.11ax HE20	97.00	3880	0.13
1	5GHz 802.11ax HE40	98.48	-	0.07
1	5GHz 802.11ax HE80	96.35	3700	0.16

<Ant. 1>

